INCH-POUND
MIL-DTL-24640B
SUPPLEMENT 1
22 August 2002

DETAIL SPECIFICATION

CABLES, LIGHT-WEIGHT, ELECTRIC, LOW SMOKE, FOR SHIPBOARD USE, GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-DTL-24640B, dated 22 August 2002.

SPECIFICATION SHEETS

MIL-DTL-24640/1 - Cable, Electric, 600 Volts, Light-Weight, Two-Conductor, Low Power, Type DX.
MIL-DTL-24640/2 - Cable, Electrical, 600 Volts, Light-Weight, Three-Conductor, Low Power, Type TX.
MIL-DTL-24640/3 - Cable, Electric, 600 Volts, Light-Weight, Four-Conductor, Low Power, Type FX.
MIL-DTL-24640/4 - Cable, Electric, 600 Volts, Light-Weight, Multi-Pair, AWG 20, Type TTX.
MIL-DTL-24640/5 - Cable, Electric, 600 Volts, Light-Weight, Multi-Pair, AWG 20, Type TTXS (Including Variation Type TTXSO).
MIL-DTL-24640/6 - Cable, Electric, 600 Volts, Light-Weight, Multi-Pair, AWG 22, Type 2XAO.
MIL-DTL-24640/7 - Cable, Electric, 600 Volts, Light-Weight, Multi-Conductor, AWG 22, Type 1XMSO.
MIL-DTL-24640/8 - Cable, Electric, 600 Volts, Light-Weight, Multi-Conductor, AWG 20, Type MXO.
MIL-DTL-24640/9 - Cable, Electric, 600 Volts, Light-Weight, Multi-Pair, AWG 22, Type 2XS (Including Variation Type 2XSO).
MIL-DTL-24640/10 - Cable, Electric, 600 Volts, Light-Weight, Multi-Conductor, AWG 16, Type MXSO.
MIL-DTL-24640/11 - Cable, Electric, 600 Volts, Light-Weight, Multi-Triad, AWG 18, Type 3XS.
MIL-DTL-24640/12 - Cable, Electric, 600 Volts, Light-Weight, Multi-Pair AWG 26, Type 2X0.
MIL-DTL-24640/13 - Cable, Electric, 600 Volts, Light-Weight, Multi-Pair, AWG 26, Type 2XSX0.
MIL-DTL-24640/14 - Cable, Electric, 600 Volts, Light-Weight, Multi-Conductor, AWG 22, Type 1XSOW.
MIL-DTL-24640/15 - Cable, Electric, 600 volts, Light-Weight, Multi-Pair, AWG 22, Type 2XSAW (Including Variation Type 2XSAOW).
MIL-DTL-24640/16 - Cable, Electric, 600 Volts, Light-Weight, Multi-Pair, AWG 18, Type 2XSW (Including Variation Type 2XSOW).

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:39Z
Check the source to verify that this is the current version before use.

MIL-DTL-24640/17 - Cable, Electric, 600 Volts, Light-Weight, Multi-Pair, AWG 26, Type 2XOW.
MIL-DTL-24640/18 - Cable, Electric, 600 Volts, Light-Weight, Multi-Triad, AWG 18, Type 3XSW (Including Variation Type 3XSOW).
MIL-DTL-24640/19 - Cable, Electric, 600 Volts, Light-Weight, Two-Conductor, Power, Type DXW (Including Variation Type DXOW).
MIL-DTL-24640/20 - Cable, Electric, 600 Volts, Light-Weight, Three-Conductor, Low Power, Type TXW (Including Variation Type TXOW).
MIL-DTL-24640/21 - Cable, Electric, 600 Volts, Light-Weight, Four-Conductor, Low Power, Type FXW (Including Variation Type FXOW).
MIL-DTL-24640/22 - Cable, Electric, 600 Volts, Light-Weight, Seven-Conductor, Low Power, Type 7XW.
MIL-DTL-24640/23 - Cable, Electric, 600 Volts, Light-Weight, Multi-Conductor, AWG 18, Type MXCW (Including Variation Type MXCOW).
MIL-DTL-24640/24 - Cable, Electric, 600 Volts, Light-Weight, Multi-Pair, AWG 22, Type TTXW (Including Variation Type TTXOW).

Preparing activity:
Navy - SH

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:39Z
Check the source to verify that this is the current version before use.