MILITARY SPECIFICATION

ALTIMETER-ENCODER AAU-32/A

"This amendment forms a part of Military Specification MIL-A-81852A dated 20 February 1986, and is approved for use by all Departments and Agencies of the Department of Defense."

PAGE 1

1.2 Delete and substitute:

"1.2 Classification. Four types of altimeters are covered by this specification and are as follows:

I. Type AAU-32/A-1 Altimeter-Encoder (interchangeable with AAU-32/A) - incorporates "Aviation Red" lighting and "blue filtered" white lighting

II. Type AAU-32/A-2 Altimeter-Encoder (interchangeable with AAU-32A/A) - incorporates "Aviation Red" lighting and "instrument and panel" white lighting."

III. Type AAU-32/A-3 Altimeter-Encoder - incorporates Class A NVIS Green A "Night Vision Imaging System (NVIS) Compatible lighting."

IV. Type AAU-32/A-4 Altimeter-Encoder - incorporates "Class B NVIS Green A "Night Vision Imaging System (NVIS) Compatible lighting."

PAGE 2

"2.1.1 Add: "MIL-L-85762 Lighting, Aircraft Interior, Night Vision Imaging System (NVIS), compatible"

PAGE 13

3.7 Delete second sentence and substitute:

"The lighting colors shall be as specified in MIL-C-25050, MIL-L-85762 Class A or B NVIS Green A, and in 1.2."

AMSC - N/A FSC 6610

Distribution Statement A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:16Z
Check the source to verify that this is the current version before use.

3.7(a) Delete and substitute:

"a. Brightness for the "Aviation red", "instruments and panel" white and "NVIS" compatible lighting shall be as specified in MIL-L-25467 except for modification in (c). Applied voltage shall be as specified in MIL-L-25467."

PAGE 19

4.4.2 Delete: "Altimeter-Encoder AAU-32/A-1 (or AAU-32/A-2)" and replace with "Altimeter-Encoder AAU-32/A-1 (or AAU-32/A-2 or AAU-32/A-3 or AAU-32/A-4)."

PAGE 29

4.5.11 Delete and substitute:

"4.5.11 Lighting. The lighting system shall be excited with 5.0 ± 0.1v and examined to verify that all lamps function properly. Both the red and white lighting systems or the "NVIS" compatible lighting system when specified shall be checked."

PAGE 31

4.6.7 Add: "MIL-L-85762 test shall be used when "NVIS" compatible lighting is specified."

PAGE 34

4.7.9 At the end of the third sentence, Add: "or MIL-L-85762, as applicable."

PAGE 48

Figure 3 add: "Note 3. When "NVIS" compatible lighting Class A NVIS Green A is specified, it shall be powered by pins X and Z. Pin Y shall be open."

Note 4: When "NVIS" compatible lighting Class B NVIS Green A is specified, it shall be powered by pins Y and Z. Pin X shall be open."

Add reference to Notes 3 and 4 to Pins XY and Z.

Custodians:
Navy-AS
Army-AV

Preparing Activity:
Navy-AS
(Project No. 6610-0153)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:16Z
Check the source to verify that this is the current version before use.