MILITARY SPECIFICATION

GROUT MATERIAL, RAPID SETTING

This Amendment forms a part of MIL-G-81830A(AS), dated 28 November 1983, and is approved for use within the Naval Air Systems Command, Department of the Navy and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

4.4, delete and substitute:

"4.4 Quality conformance inspection. The quality conformance inspection of grout material shall consist of the tests for gel and set time (4.6.3) and compression test (4.6.5). Mixing properties are to be observed during the gel and set time tests. Additionally the supplier shall furnish certification that the material offered by inspection has been processed in the same manner and degree using the same base materials as the approved qualification sample."

4.4.2, delete and substitute"

"4.4.2 Sampling for quality conformance testing. The sample size for quality conformance testing shall consist of one 100 pound drum. The manufacturer shall be responsible for performance of all quality conformance tests (see 4.4) for each lot of material. Failure of the sample to comply with any of the quality conformance requirements shall be cause to reject the lot represented by the sample.

4.4.2.1 Verification testing. When requested by the acquiring activity, a 100 pound sample package as specified in Section 5 shall be forwarded to the Naval Air Engineering Center (see 4.3.1). A copy of the quality conformance test report shall accompany the sample."

Preparing Activity
Navy - AS
(Project 5610-N379)

AMSC N/A

DISTRIBUTION STATEMENT A, Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:15Z
Check the source to verify that this is the current version before use.