MILITARY SPECIFICATION

HEAT TRANSFER FLUID, FLUOROCHEMICAL

This amendment forms a part of Military Specification MIL-H-81829 dated 6 July 1971, and is approved for use by all Departments and Agencies of the Department of Defense.

Page 2

Paragraph 3.3, Table II, under "Limits" for Dielectric Strength: Delete "340 V/mil (min)" and substitute "34KV/.1 inch (2.54 mm)

Page 3

Paragraph 4.2.1: Delete and substitute:

"4.2.1 Sampling for examination of end item. A one quart sample shall be taken from each lot of transfer fluid for examination in accordance with 4.2.2.1."

Add paragraph: 4.2.1.1 Lot - A lot is defined as an indefinite number of unit containers offered for acceptance and filled with a homogeneous mixture of material from one isolated container or filled with a homogeneous mixture of material manufactured by a single plant run (not exceeding 24 hours) through the same processing equipment, with no change in ingredient materials.

Page 4

Paragraph 4.3, third sentence: Delete and substitute "The sample size shall be three pints taken after final filtration, while packaging from an agitated mixing tank."

FSC 6850

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:15Z
Check the source to verify that this is the current version before use.

Paragraph 6.3: Delete in its entirety.

Preparing activity:
NAVY - AS

(Project 6850-0599)

Custodians:
Army - MI
Navy - AS
Air Force - 68

User Activities:
Army - MU
DSA - GSA

☆U.S. GOVERNMENT PRINTING OFFICE: 1976—603-766/6719

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:15Z
Check the source to verify that this is the current version before use.