INCH-POUND

MIL-C-55365/4C
23 August 1990
SUPERSEDING
MIL-C-55365/4B
10 March 1987

MILITARY SPECIFICATION SHEET

CAPACITORS, CHIP, FIXED, TANTALUM, ESTABLISHED RELIABILITY, STYLES CWR06 AND CWR09

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-C-55365.




FIGURE 1. Style CWR06 - (conformally coated) capacitors.

© denotes changes

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.


Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:17Z
Check the source to verify that this is the current version before use.

Case size	L ±.015 (0.38)	W ±.015 (0.38)	H ±.015 (0.38)	P ±.005 (0.13)
A	.100 (2.54)	.050 (1.27)	.050 (1.27)	.030 (0.76)
B	.150 (3.81)	.050 (1.27)	.050 (1.27)	.030 (0.76)
C	.200 (5.08)	.050 (1.27)	.050 (1.27)	.030 (0.76)
D	.150 (3.81)	.100 (2.54)	.050 (1.27)	.030 (0.76)
E	.200 (5.08)	.100 (2.54)	.050 (1.27)	.030 (0.76)
F	.220 (5.59)	.135 (3.43)	.070 (1.78)	.030 (0.76)
G	.265 (6.73)	.110 (2.79)	.110 (2.79)	.050 (1.27)
H	.285 (7.24)	.150 (3.81)	.110 (2.79)	.050 (1.27)

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Metric equivalents are in parentheses.
4. These capacitors are designed for mounting by dip soldering, thermo-compression bonding, reflow soldering, or other conventional means.
5. Cathode terminal may be epoxy coated on one surface for polarity identification.
6. Ⓒ Solderable surfaces are only those surfaces designated as such.
7. Ⓒ Anode and cathode terminals may be two-sided, three-sided, or five-sided, and may not be the same on some designs, but will meet all specification requirements.
8. Ⓒ The anode terminal shall be identified by the riser wire connection, which may extend the case size .015 (0.38 mm) maximum. The riser wire weld area is not solderable. The riser wire connection shall have a continuous weld of a minimum of 25 percent of the contact surface.
9. Ⓒ When solder coated terminations are required, add .015 (0.38 mm) to termination dimension tolerances.

FIGURE 1. Style CWR06 - (conformally coated) capacitors - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:17Z
Check the source to verify that this is the current version before use.



Case size	L ±.015 (0.38)	W ±.015 (0.38)	H ±.015 (0.38)	P ±.005 (0.13)	W_2 ±.005 (0.13)	H_2 min
A	.100 (2.54)	.050 (1.27)	.050 (1.27)	.030 (0.76)	.050 (1.27)	.030 (0.76)
B	.150 (3.81)	.050 (1.27)	.050 (1.27)	.030 (0.76)	.050 (1.27)	.030 (0.76)
C	.200 (5.08)	.050 (1.27)	.050 (1.27)	.030 (0.76)	.050 (1.27)	.030 (0.76)
D	.150 (3.81)	.100 (2.54)	.050 (1.27)	.030 (0.76)	.095 (2.41)	.030 (0.76)
E	.200 (5.08)	.100 (2.54)	.050 (1.27)	.030 (0.76)	.095 (2.41)	.030 (0.76)
F	.220 (5.59)	.135 (3.43)	.070 (1.78)	.030 (0.76)	.130 (3.30)	.040 (1.02)
G	.265 (6.73)	.110 (2.79)	.110 (2.79)	.050 (1.27)	.105 (2.67)	.060 (1.52)
H	.285 (7.24)	.150 (3.81)	.110 (2.79)	.050 (1.27)	.145 (3.68)	.060 (1.52)

FIGURE 2. Style CWR09 molded chip.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:17Z
Check the source to verify that this is the current version before use.

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Metric equivalents are in parentheses.
4. These capacitors are designed for mounting by dip soldering, thermo-compression bonding, reflow soldering, or other conventional means.
(C) 5. The anode (+) terminal shall be identified by a marking on the case.
(C) 6. The termination width (W_2) shall be maintained to the top of the solderable area.
(C) 7. Solderable surfaces are only those surfaces designated as such. Termination edges are not considered solderable.
(C) 8. When solder coated terminations are required, add .015 (0.38 mm) to the termination dimension tolerances.

FIGURE 2. Style CWR09 molded chip - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:17Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Design and construction:

© Dimensions and configuration: See figures 1 and 2.

Case type: Chip.

Material: Sintered tantalum.

Leads: Unleaded.

© Termination finish: In accordance with termination finishes B, C, H, or K of MIL-C-55365.

DC rated voltage: See table I. Above +85°C, voltage derating is required (see MIL-C-55365).

Operating temperature range: -55°C to +125°C.

© Failure rate level: In accordance with MIL-C-55365.

DC leakage (DCL): See table I.

Capacitance (Cap.): See table I.

Cap. tolerance: ±5 percent (J), ±10 percent (K), or ±20 percent (M).

Dissipation factor (DF): See table I.

Resistance to soldering heat: In accordance with MIL-C-55365.

Stability at low and high temperatures: In accordance with MIL-C-55365.

Step 1 (+25°C):	DCL	-	See table I.
	Cap.	-	Shall not exceed tolerance of table I value.
	DF	-	See table I.
Step 2 (-55°C):	ΔCap.	-	Shall not exceed ±10 percent of initial measurement.
	DF	-	See table I.
Step 3 (+25°C):	DCL	-	See table I.
	ΔCap.	-	Shall not exceed ±5 percent of initial +25°C measurement.
	DF	-	See table I.
Step 4 (+85°C):	DCL	-	See table I.
	ΔCap.	-	Shall not exceed ±10 percent of initial +25°C measurement.
	DF	-	See table I.
Step 5 (+125°C):	DCL	-	See table I.
	ΔCap.	-	Shall not exceed ±15 percent of initial +25°C measurement.
	DF	-	See table I.
Step 6 (+25°C):	DCL	-	See table I.
	ΔCap.	-	Shall not exceed ±5 percent of initial +25°C measurement.
	DF	-	See table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:17Z
Check the source to verify that this is the current version before use.

Surge voltage: In accordance with MIL-C-55365.

DCL - See table I.
ΔCap. - Within ±5 percent of initial value.
DF - See table I.

Life: Method 108 of MIL-STD-202.

2,000 hours:

At 25°C: DCL - See table I.
ΔCap. - Shall not exceed ±5 percent of initial measured value.
DF - See table I.

At 85°C: DCL - See table I.

At 125°C: DCL - See table I.

10,000 hours:

At 25°C: DCL - 200 percent of initial requirement.
ΔCap. - Shall not exceed ±10 percent of initial measured value.
DF - See table I.

At 85°C: DCL - 200 percent of initial requirement.

At 125°C: DCL - 200 percent of initial requirement.

© TABLE I. Styles CWR06 and CWR09 characteristics.

PIN 1/	DC rated voltage (85°C)	Cap. (nom)	DC leakage (max)			Dissipation factor (max)			Case size
			+25°C	+85°C	+125°C	+25°C	+85°C +125°C	-55°C	
	Volts	μF	μA	μA	μA	%	%	%	
CWR0-C-225--	4	2.2	1.0	10	12	6	8	8	A
CWR0-C-475--	4	4.7	1.0	10	12	6	8	8	B
CWR0-C-685--	4	6.8	1.0	10	12	6	8	8	C
CWR0-C-106--	4	10.0	1.0	10	12	8	8	10	D
CWR0-C-156--	4	15.0	1.0	10	12	8	10	12	E
CWR0-C-336--	4	33.0	2.0	20	24	8	10	12	F
CWR0-C-686--	4	68.0	3.0	30	36	10	12	12	G
CWR0-C-107--	4	100.0	4.0	40	48	10	12	12	H
CWR0-D-155--	6	1.5	1.0	10	12	6	8	8	A
CWR0-D-335--	6	3.3	1.0	10	12	6	8	8	B
CWR0-D-475--	6	4.7	1.0	10	12	6	8	8	C
CWR0-D-685--	6	6.8	1.0	10	12	6	8	8	D
CWR0-D-106--	6	10.0	1.0	10	12	8	10	12	E
CWR0-D-226--	6	22.0	2.0	20	24	8	10	12	F
CWR0-D-476--	6	47.0	3.0	30	36	10	12	12	G
CWR0-D-686--	6	68.0	4.0	40	48	10	12	12	H
CWR0-F-105--	10	1.0	1.0	10	12	6	8	8	A
CWR0-F-225--	10	2.2	1.0	10	12	6	8	8	B
CWR0-F-335--	10	3.3	1.0	10	12	6	8	8	C
CWR0-F-475--	10	4.7	1.0	10	12	6	8	8	D
CWR0-F-685--	10	6.8	1.0	10	12	6	8	8	E

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:17Z
Check the source to verify that this is the current version before use.

© TABLE I. Styles CWR06 and CWR09 characteristics - Continued.

PIN 1/	DC rated voltage (85°C)	Cap. (nom)	DC leakage (max)			Dissipation factor (max)			Case size
			+25°C	+85°C	+125°C	+25°C	+85°C +125°C	-55°C	
	Volts	µF	µA	µA	µA	%	%	%	
CWR0-F-156--	10	15.0	2.0	20	24	8	8	10	F
CWR0-F-336--	10	33.0	3.0	30	36	10	12	12	G
CWR0-F-476--	10	47.0	5.0	50	60	10	12	12	H
CWR0-H-684--	15	.68	1.0	10	12	6	8	8	A
CWR0-H-155--	15	1.5	1.0	10	12	6	8	8	B
CWR0-H-225--	15	2.2	1.0	10	12	6	8	8	C
CWR0-H-335--	15	3.3	1.0	10	12	6	8	8	D
CWR0-H-475--	15	4.7	1.0	10	12	6	8	8	E
CWR0-H-106--	15	10.0	2.0	20	24	6	8	8	F
CWR0-H-226--	15	22.0	4.0	40	48	8	8	10	G
CWR0-H-336--	15	33.0	5.0	50	60	8	8	10	H
CWR0-J-474--	20	.47	1.0	10	12	6	8	8	A
CWR0-J-684--	20	.68	1.0	10	12	6	8	8	B
CWR0-J-105--	20	1.0	1.0	10	12	6	8	8	B
CWR0-J-155--	20	1.5	1.0	10	12	6	8	8	C
CWR0-J-225--	20	2.2	1.0	10	12	6	8	8	D
CWR0-J-335--	20	3.3	1.0	10	12	6	8	8	E
CWR0-J-685--	20	6.8	2.0	20	24	6	8	8	F
CWR0-J-156--	20	15.0	3.0	30	36	6	8	8	G
CWR0-J-226--	20	22.0	4.0	40	48	6	8	8	H
CWR0-K-334--	25	.33	1.0	10	12	6	8	8	A
CWR0-K-684--	25	.68	1.0	10	12	6	8	8	B
CWR0-K-105--	25	1.0	1.0	10	12	6	8	8	C
CWR0-K-155--	25	1.5	1.0	10	12	6	8	8	D
CWR0-K-225--	25	2.2	1.0	10	12	6	8	8	E
CWR0-K-475--	25	4.7	2.0	20	24	6	8	8	F
CWR0-K-685--	25	6.8	2.0	20	24	6	8	8	G
CWR0-K-106--	25	10.0	3.0	30	36	6	8	8	G
CWR0-K-156--	25	15.0	4.0	40	48	6	8	8	H
CWR0-M-224--	35	.22	1.0	10	12	6	8	8	A
CWR0-M-474--	35	.47	1.0	10	12	6	8	8	B
CWR0-M-684--	35	.68	1.0	10	12	6	8	8	C
CWR0-M-105--	35	1.0	1.0	10	12	6	8	8	D
CWR0-M-155--	35	1.5	1.0	10	12	6	8	8	E
CWR0-M-335--	35	3.3	1.0	10	12	6	8	8	F
CWR0-M-475--	35	4.7	2.0	20	24	6	8	8	G
CWR0-M-685--	35	6.8	3.0	30	36	6	8	8	H
CWR0-N-104--	50	.10	1.0	10	12	6	8	8	A
CWR0-N-154--	50	.15	1.0	10	12	6	8	8	A
CWR0-N-224--	50	.22	1.0	10	12	6	8	8	B
CWR0-N-334--	50	.33	1.0	10	12	6	8	8	B
CWR0-N-474--	50	.47	1.0	10	12	6	8	8	C
CWR0-N-684--	50	.68	1.0	10	12	6	8	8	D
CWR0-N-105--	50	1.0	1.0	10	12	6	8	8	E
CWR0-N-155--	50	1.5	1.0	10	12	6	8	8	F
CWR0-N-225--	50	2.2	2.0	20	24	6	8	8	F
CWR0-N-335--	50	3.3	2.0	20	24	6	8	8	G
CWR0-N-475--	50	4.7	3.0	30	36	6	8	8	H

1/ Complete PIN shall include additional symbols to indicate style, termination finish, capacitance tolerance, and failure rate level.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:17Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - MI
Navy - SH
Air Force - 17, 99
NASA - NA
DLA - ES

User activities:
Army - AR
Navy - AS, CG, MC, OS
Air Force - 19

Preparing activity:
Army - ER

Agent:
DLA - ES

(Project 5910-1638)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:17Z
Check the source to verify that this is the current version before use.