MIL-R-50658C (AR)
29 March 1991
SUPERSEDING
MIL-R-50658B (AR)
28 March 1990

# MILITARY SPECIFICATION

## REGULATOR, 15 VOLT, BOARD ASSEMBLY: 10548958

This specification is approved for use by the U. S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

## 1. SCOPE

1.1 Scope. This specification covers a 15-volt regulator board assembly, hereinafter referred to as a 15-volt regulator, used in the regulator assemblies of Power Supply PP-4812, part of Radar Set AN/VPS-2 and in Subassembly PP-6324, part of Radar Test Set AN/TPM-22 (see 6.1).

## 2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

MILITARY

MIL-F-13926 -" Fire Control Materiel, Manufacture and Inspection, General Specification for
MIL-I-45607 - Inspection Equipment, Acquisition, Maintenance and Disposition of

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army ARDEC, ATTN: SMCAR-BAC-S, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC n/a
DISTRIBUTION STATEMENT A.
FSC 1285

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:32Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-810 - Environmental Test Methods and Engineering Guidelines
MIL-STD-2000 - Standard Requirements for Soldering Electrical and Electronic Assemblies

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks *are* available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS (See 6.4)

u. s. ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

10S48823 - Inductor, Power
10548830 - Transformer, Saturable Core
10548958 - 15-Volt Regulator Board Assembly

PACKAGING DATA SHEET

PS10548958 - Packaging of 15-Volt Regulator

(Copies of drawings, publications and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 order of precedence. In the event of conflict between the text of this specification and the references cited herein the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:32Z
Check the source to verify that this is the current version before use.

## 3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings and specifications.

3.2 Components and assemblies. The components and assemblies shall comply with all requirements specified on Drawing 10548958, all associated drawings, and with all requirements specified @ applicable specifications and standards. Where applicable, the 15-volt regulator shall meet the requirements of MIL-F-13926 as follows:

a. Dimensions and tolerances.
b. Inorganic protective surface finishings.
c. Part identification and marking.
d. Workmanship.

3.3 Environmental service conditions.

3.3.1 Vibration. The 15-volt regulator shall not suffer damage and shall meet the requirements of 3.4 and 3.5 after exposure to sinusoidal vibrations, in each of three mutually perpendicular axes, as follows:

| Frequency Range | Amplitude |
|---|---|
| 10 to 15 hertz | 0.06 inches double amplitude |
| 15 to 25 hertz | 0.04 inches double amplitude |
| 25 to 40 hertz | 0.02 Inches double amplitude |

The frequency of vibration shall be swept logarithmically.
The cycling time shall be 120 minutes per axis.
The sweep rate shall be 3.75 minutes ± 10% per decade.
The 10-40-10 hertz sweep time is 2 minutes 30 seconds ± 10%.

3.3.2 Shock. The 15-volt regulator shall not suffer damage and shall meet the requirements of 3.4 and 3.5 after exposure to a total of 18 impulse shocks consisting of three shock impulses of 15 g's ~ 10%, 11 milliseconds ± 10%, half-sine wave applied in each direction of 3 mutually perpendicular axes.

3.3.3 Altitude.

3.3.3.1 Operating. The 15-volt regulator shall meet the requirements of 3.4 and 3.5 during and after exposure to barometric pressure encountered at 10,000 feet above sea level (20.6 inches of Hg).



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:32Z
Check the source to verify that this is the current version before use.

3.3.3.2 Non-operating. The 15-volt regulator shall meet the requirements of 3.4 and 3.5 after exposure for not less than 10 minutes to barometric pressure encountered at 40,000 feet above sea level (5.5 inches of Hg).

3.3.4 Temperature.

3.3.4.1 operating. The 15-volt regulator shall meet the requirements of 3.4 and 3.5 when stabilized thermally at any temperature between -40 deg. F and +155 deg. F.

3.3.4.2 Non-operating (storage). The 15-volt regulator shall not suffer permanent damage when subjected to the constant temperature extremes of -60 deg. F for a period of 24 hours and +160 deg. F for a period of 4 hours (after temperature stabilization ), and shall meet the requirements of 3.4 and 3.5 when returned to room ambient.

3.3.5 Humidity (non-operating) The 15-volt regulator shall meet the requirements of 3.4 and 3.; after exposure to an atmosphere with a relative humidity in excess of 95 percent for a period of 10 days.

3.4 Electrical. Each conductor shall be electrically continuous as specified on the schematic diagram of the 15-volt regulator board assembly.

3.5 Performance. The 15-volt regulator shall produce results as given in 3.5.1 when supplied with the input voltages specified in Table I (Input characteristics).

TABLE 1. Input characteristics.

| REQUIREMENT | CHARACTERISTIC |
|---|---|
| Input voltage 1/ | 19 to 29 Vdc; regulated to ± 0.5% |
| Input signal 1/ | 22 ± 1 KHz, 71.5 ± 12.5 V peak-to-peak square wave |

1/ Input voltages and signals are connected into the circuit using test fixture as specified In 4.6.2.3 and test setup as specified in 4.7.3.

3.5.1 Output terminals. The output terminals are E6 (+) and E7 (-).



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:32Z
Check the source to verify that this is the current version before use.

3.5.1.1 Output voltage level potentiometer R2. R2 shall control the output voltage between circuit board terminals E6 (+) and E7 (-). The nominal output voltage shall be 15.00 ~ 0.10 volts (V), with a load current of 1.0 + 0.2 ampere direct current (Adc).

3.5.1.2 Current limit potentiometer R17. R17 shall control the point at which the current limiting circuitry becomes effective. With a short applied between E6 and E7, maximum current drain shall be controlled by R17 and shall not exceed 1.6 A. The output shall automatically recover after removal of the short circuit.

3.5.1.3 Voltage regulation, line. The output voltage shall not vary more than ~0.15 volt direct current (Vdc) with an input voltage variation from 19 to 29 Vdc, and a constant load current of 1.0 A.

3.5.1.4 Voltage regulation, load. The output voltage shall not vary more than ~0.15 Vdc with the input voltage fixed at 24 ~ 5 Vdc when the output current varies from 0 to 1.0 A.

3.5.1.5 Output ripple. The ripple voltage shall not exceed 0.15 V peak-to-peak when the input voltage is 24 ~ 0.24 Vdc and the load current is 1.0 A. Exclude high-frequency spikes which occur at approximately 25 usec intervals.

3.6 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection In accordance with the technical provisions herein (see 4.3).

3.7 Soldering. All soldering shall be in accordance with the general requirements of MIL-STD-2000 in addition to detail requirement (task) F of paragraph 1.2 of MIL-STD-2000.

## 4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:32Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items shall meet all retirements of Sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall Inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material. either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 General Provisions. The component and subassembly inspection requirements of MIL-F-13926 form a part of the quality assurance provisions of this specification. Reference shall be made to MIL-STD-109 to define quality assurance terms used herein.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4 ) .
c. Special sampling inspection (see 4.5).

4.2.1 Inspection conditions. Unless otherwise specified, all examinations and tests shall be conducted at the following standard ambient conditions:

| | | |
|---|---|---|
| a. | Temperature | +50 deg. F to +90 deg. F |
| b. | Relative humidity | 90% RH max. |
| c. | Pressure | 28 to 32 inches of Hg |

4.3 First article inspection.

4.3.1 *First* article submission. The contractor shall submit a first article sample as designated by the contracting officer consisting of three (3) 15-volt regulators for inspection in accordance with 4.3.2.

4.3.2 Inspections to be performed. First article assemblies, components and test specimens may be subjected by the Government to any or all of the examinations and tests specified in Table II and Table III herein and to any or all requirements of the applicable drawings.

4.3.3 Relection. If any assembly, component or test specimen fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon failure of any assembly, component or test specimen to comply with any of the stated requirements.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:32Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. The term 'inspection lot" is defined as a homogeneous collection of units of product from which a representative sample is drawn or which is inspected 100 percent to determine conformance with applicable requirements. Units of product selected for inspection shall represent only the inspection lot from which they are drawn and shall not be construed to represent any prior *or* subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, using the same materials and methods, in accordance with the same drawings, same drawing revisions, same specifications and the same specification revisions. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein, regardless of the type of inspection procedure which is being applied to determine conformance with requirements.

4.4.2 Examination and tests.

4.4.2.1 Components, assemblies and subassemblies. ml components, assemblies, and subassemblies shall be insDected in accordance with the Inspection provisions contained in-this specification and the Quality Assurance Provisions (QAP) listed in the Technical Data Package (TDP). In the absence of QAPS, the applicable quality assurance provisions of MIL-F-13926 shall apply.

m

4.4.2.2 Final acceptance inspection. Subsequent to first article approval, examinations and tests related to Section 3 herein shall be performed in accordance with the sampling plans specified in 4.4.2.3 herein. Examination and test for packaging and marking shall be in accordance with Section 5 herein. The tabulated classification of defects in 4.4.2.3 shall constitute the minimum inspection to be performed by the contractor after first article approval and prior to Government acceptance or rejection by item or lot.

4.4.2.3 Functional tests. The tests in Table II shall be performed on a 100% basis.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:32Z
Check the source to verify that this is the current version before use.

TABLE II. Functional tests (100 percent inspection).

| CHARACTERISTIC | REQUIREMENT | TEST PROCEDURE |
|---|---|---|
| Critical: | None | N/A |
| Major: | | |
| 101. Electrical | 3.4 | 4.7.2 |
| 102. Performance | 3.5 | 4.7.3 |
| Minor: | None | N/A |

4.5 Special sampling. One 15-volt regulator out of the first 100 produced and one out of each 100 produced thereafter shall be selected at random. The sample shall-have met the requirements and tests of Table II (Functional tests) and shall then meet the requirements and tests in Table 111 (Special sampling). Unless otherwise specified in the contract, the items shall be returned to the lot upon successful completion of testing.

TABLE III. Special sampling.

| CHARACTERISTIC | REQUIREMENT | TEST PROCEDURE |
|---|---|---|
| Critical: | None | N/A |
| Major | | |
| 103. Vibration | 3.3.1 | 4.7.1.1 |
| 104. Shock | 3.3.2 | 4.7.1.2 |
| 105. Altitude | 3.3*3 | 4.7.1.3 |
| 106. Temperature | 3.3.4 | 4.7.1.4 |
| 107. Humidity | 3.3.5 | 4.7.1.5 |
| Minor: | None | N/A |

4.5.1 Failure of sample. Should any one item of a special sampling fail to meet any of the specified test requirements, acceptance of the product shall be suspended by the Government until necessary corrections to all production since the last test as well as to current production has been accomplished in accordance with the provisions of the contract.

4.6 Inspection equipment.

4.6.1 Government-furnished inspection equipment. Where the contract provides for Government-furnished test equipment, supply and maintenance of test equipment shall be in accordance with the applicable requirements of MIL-I-45607.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:32Z
Check the source to verify that this is the current version before use.

4.6.2 Contractor-furnished inspection equipment.

4.6.2.1 Government design. Unless otherwise specified In the contract, all inspection equipment identified by drawing number in specifications or QAPs forming a part of the contract shall be supplied by the contractor in accordance with design specified. The contractor may, however, propose alternatives to Government designs for approval in accordance with 6.3.

4.6.2.2 Contractor design. The contractor shall design and supply inspection equipment compatible with the 'Methods of Inspection" specified In 4.7 of this specification and with the component inspection procedures specified in 'Examination" and 'Test Facilities" *requirements* of MIL-F-13926 whenever Government designs are not specified (see 4.6.2.1). Since tolerance of test equipment is normally considered to be within 10 percent of the product tolerance for which it is intended, this inherent error in the test equipment design must be considered as part of the prescribed product tolerance limit. Thus, concept, construction, materials, dimensions, and tolerances used in the design of test equipment shall be so selected and controlled as to ensure that the test equipment will reliably indicate acceptability of a product which does not exceed 90 percent of the prescribed limit and permit positive rejection when nonconforming. Construction shall be such as to facilitate routine calibration of test equipment. Contractor inspection equipment designs shall be submitted for approval in accordance with 6.3.

4.6.2.3 Test equipment. In conjunction with 4.6.2.1 and 4.6.2.2, the standard test equipment listed in Table IV (Test equipment list) shall be used in the performance of the applicable test methods and procedures as specified in 4.7.

TABLE IV. Test equipment list.

| ITEM NUMBER | | DESCRIPTION |
|---|---|---|
| 1.. | Signal generator | Capable of producing a 22 ± 1 KHz, 71.5 ± 12.5 V peak-to-peak square wave. output impedance less than 20 ohms. |
| 2. | Power supply | DC 19 to 29 V, 2 A, regulated to 0.5%. |
| 3* | Voltmeter | DC, O to 30 V, 0.01% accuracy, 20,000 ohms/volt or greater. |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:32Z
Check the source to verify that this is the current version before use.

TABLE IV. Test equipment list (continued).

| ITEM NUMBER | | DESCRIPTION |
|---|---|---|
| 4. | Oscilloscope | Input sensitivity: 20 mV/CHt. Input impedance: 1 megohm. Vertical passband: DC! to 1 MHZ. Horizontal deflection: 5 us/cm. |
| 5. | Ammeter | DC, O to 2 A, 1% accuracy. |
| 6. | Test fixture | As specified in Figure 1. See Table V for fixture parts list. |

TABLE V. Test fixture Parts list.

| ITEM | NOMENCLATURE | DESCRIPTION |
|---|---|---|
| cl | Capacitor | 300 uF, 40 V |
| CRl | Diode | General purpose, JAN 1N645 |
| L1 | Inductor, power | 1.0 mH, 1.5 A, 10548823 |
| Q1 | Transistor, power | NPN, silicon, 2N3767 |
| R1 | Resistor | Fixed, 2.4 Kohms, 1/2 W, RC20GF242K |
| R2 | Resistor | Variable O to 20 ohms, 50 W |
| S1 | Switch | SPST, General purpose, 2 A rated |
| S2 | Switch | SPST, General purpose, 2 A rated |
| T1 | Transformer | Saturable core, 10548830 |


4.7 Methods of inspection.

4.7.1 Environmental. Environmental tests shall be conducted in accordance with the test conditions, general test performance guidance, and individual test methods of MIL-STD-810.-except as specified herein. Test facilities, chambers and apparatus-used in conducting the tests contained in this specification shall be capable of meeting the conditions required.

4.7.1.1 Vibration. The test shall be performed as specified in Method 514, Category 8, Procedure I, of MIL-STD-810 as modified by 3.3.1 herein. In Step 1 of procedure I only steps 4 through 8 of paragraph II-2.1 apply. The 15-volt regulator shall be attached to the vibration generator directly or with a fixture,



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:32Z
Check the source to verify that this is the current version before use.




* Refer to 4.6.2.3

FIGURE 1. Test fixture, regulator board.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:32Z
Check the source to verify that this is the current version before use.

and securely held by its normal means of attachment. After vibration, the 15-volt regulator shall be tested as specified In 4.7.2 and 4.7 3 herein to determine compliance with 3.3.1.

4.7.1.2 **Shock.** This test shall be performed as specified in Procedure I, section II of Method 516 of MIL-STD-810 except that:

a. The post test functional check (Step 5 of Procedure I) need not be conducted until completion of all shock impulses.

b. The shock pulses shall be 15 g's ± 10% amplitude and 11 ms ± 10% duration.

c. The maximum g shall occur at 5.5 milliseconds ± 10%.

d. The shock measuring system shall have a flat frequency response within ± 10% from 20 to 2,000 Hertz.

After the application of all the shock impulses, the 15-volt regulator shall be tested as specified in 4.7.2 and 4.7.3 to determine compliance with 3.3.2.

4.7.1.3 Altitude (operating and non-operating) This test shall be performed as specified in Procedures II and III, Method 500 of MIL-STD-810. The operational checkout shall be as specified in 4.7.2 and 4.7.3 for compliance with 3.3.3.

4.7.1.4 **Temperature.**

4.7.1.4.1 **High (operating and non-operating) .** This test shall be performed as specified in Procedures I and II, Method 501 of MIL-STD-810 with constant temperature extremes as specified in 3.3.4. The operational checkout shall be as specified in 4.7.2 and 4.7.3 for compliance with 3.3.4.

4.7.1.4.2 **Low (operating and non-operating)** This test shall be Performed as specified in Procedures I and 11; Method 502 of MIL-STD-810 with constant temperature extremes as specified in 3.3.4. The operational checkout shall be as specified in 4.7.2 and 4.7.3 for compliance with 3.3.4.

4.7.1.5 **Humidity (non-operating )** This test shall be performed in accordance with Procedure 1-1, Method 507 of MIL-STD-810 except that in Step 7, checkout shall be performed at the conclusion of the test only, with the item at standard ambient conditions. The operational checkout shall be as specified in 4.7.2 and 4.7.3 for compliance with 3.3.5.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:32Z
Check the source to verify that this is the current version before use.

4.7.2 **Electrical.** Continuity shall be inspected by standard measuring equipment and visual examination for compliance with 3.4.

4.7.3 **Performance.** The selected 15-volt regulators shall be tested as follows: All tests shall be Performed with the test equipment Connected to the 15-volt regulator as shown in Figure 2.

4.7.3.1 **Output voltage level potentiometer R2.** Using the signal generator (item 1, Table IV), apply a 22 ± 1 kilohertz (KHz) square wave to test fixture terminals Xl and X2 and adjust item 1 so that the amplitude of the input signal is 71.5 ± 12.5 V peak-to-peak. Using power supply, item 2, apply 24 ± 5 vdc between the (+) and (-) terminals on the test fixture. With switch S1 open and using the voltmeter, (item 3, Table IV) verify that the voltage between P4 (-) and P5 (+) on the test fixture can be adjusted to 15.00 ± 0.10 Vdc.

4.7.3.2 **Current limit potentiometer R17.** Perform the following steps in sequence:

a. Set up the conditions specified in 4.7.3.1.

b. Adjust R2 for a voltage indication of 15.00 ± 0.10 vdc.

c. Adjust R17 fully CCW.

d. Close load switch S1 (see Figure 1).

e. Close short switch S2 (see Figure 1).

f. Adjust R17 CW until output current equals 1.6 Adc.

g" Open S2.

h. Vary the resistive load (R2) to obtain a current indication of 1.0 Adc.

i. Record voltmeter indication on item 3.


j* Close S2 momentarily, then open.

k. Using the voltmeter (item 3, Table IV), verify that the output automatically returns to within ± 0.10 V of the level in 'i" above.

4.7.3.3 **Voltage regulation, line.** With R2 and R17 adjusted as in 4.7.3.2, adjust the resistive load (R2) to obtain 1.0 A. Vary the input voltage (item 2, Table IV) from 19 to 29 Vdc. Verify that the output voltage does not vary more than ± 0.15 Vdc.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:32Z
Check the source to verify that this is the current version before use.




* Refer to 4.6.2.3

FIGURE 2. Test harness setup.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:32Z
Check the source to verify that this is the current version before use.

4.7.3.4 Voltage regulation, load. Set the input voltage to 24 + 5 Vdc. With R2 and R17 adjusted as in 4.7.3.2, adjust the ~esistive load (R2) to maximum and open switch S1. Record the voltage indication using voltmeter (Item 3, Table IV). Close switch S1 and vary the resistive load to obtain 1.0 A. using voltmeter (item 3, Table IV), verify that the output voltage does not vary more than ± 0.ls Vdc.

4.7.3.5 Output ripple. With the input voltage set at 24 ± 0.24 Vdc and R2 and R17 adjusted as in 4.7.3.2, adjust the resistive load to 1.0 A. Using oscilloscope (item 4, Table IV), verify that the ripple does not exceed 0.1s V peak-to-peak. Exclude high-frequency spikes which occur at approximately 25 usec Intervals.

4.8 soldering. Soldering processes shall be inspected by certified inspectors to the requirements and acceptance criteria of MIL-STD-2000 as specified in 3.7.

## 5. PACKAGING

5.1 General. Preservation, packing and marking shall be in accordance with Packaging Data Sheet P10548958.

## 6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The 15-volt regulator is used in the regulator assembly part of Power Supply PP-4812, part of Radar Set AN/VPS-2 and is also used in Subassembly PP-6324, part of Radar Test Set AN/TPM-22. The 15-volt regulator is used to regulate the output voltage within the specified requirements for functional operation of Radar Set AN/VPS-2. In the test set it is used to check voltage regulator performance of the radar power supply.

6.2 Acquisition Requirements. Acquisition documents must specify the following:

a. Title, number and date of this specification.
b. Applicable stock number.
c. First article sample requirements.
d. Packaging requirements, if other than specified in Section 5.
e. Serialization requirements, if applicable.



Source: https://assist.dla.mil -- Downloaded: 2026t0-22T20:32Z
Check the source to verify that this is the currentversion before use.

f. Certificate of conformance for each lot or shipment of product.

g. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1).

6.3 Submission of contractor inspection equipment designs for approval. submit two copies of designs as required to: Commander, ~.S. Army ARDEC, Attn: AMSMC-QAF-1, Picatinny Arsenal, NJ 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract.

6.4 Drawings. Drawings listed in Section 2 of this specification under the heading U.S. Army Armament Research, Development and Engineering Center (ARDEC), may also include drawings prepared by, and identified as, U.S. Army Armament Research and Development Command (ARRADCW), Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under cognizance of ARDEC.

6.5 Key word listing.

Fire control system
Power Supply PP-4812/VPS-2
Radar Set AN/VPS-2
Radar Test Set AN/TPM-22
Subassembly PP-6324/TPM-22
Vulcan Air Defense System (VADS)

6.6 Changes from previous issue. Asterisks (or vertical lines) are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1285-A773)



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:32Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

**INSTRUCTIONS**

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

| I RECOMMEND A CHANGE: | 1. DOCUMENT NUMBER | 2. DOCUMENT DATE (YYMMDD) |
|---|---|---|
| | MIL-R-50658C (AR) | 29 March 1991 |

3. DOCUMENT TITLE: REGULATOR, 15 VOLT, BOARD ASSEMBLY: 10548958

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets if needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

| a. NAME (Last, First, Middle Initial) | b. ORGANIZATION | |
|---|---|---|
| c. ADDRESS (Include Zip Code) | d. TELEPHONE (Include Area Code)<br>(1) Commercial<br>(2) AUTOVON (If applicable) | 7. DATE SUBMITTED (YYMMDD) |

8. PREPARING ACTIVITY

| a. NAME | b. TELEPHONE (Include Area Code) | |
|---|---|---|
| US ARMY ARDEC<br>STANDARDIZATION OFFICE | (1) Commercial<br>(201) 724-6674 | (2) AUTOVON<br>880-6674 |
| c. ADDRESS (Include Zip Code)<br>ATTN: SMCAR-BAC-S<br>PICATINNY ARSENAL, NJ 07806-5000 | IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:<br>Defense Quality and Standardization Office<br>5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466<br>Telephone (703) 756-2340 AUTOVON 289-2340 | |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:32Z
Check the source to verify that this is the current version before use.