A-A-50218
15 December 1983

COMMERCIAL ITEM DESCRIPTION

RAILWAY MOTOR CARS, MAINTENANCE

8-MAN, 3000 LB LOAD CAPACITY, 56 1/2 INCH GAUGE

The General Services Administration has authorized the use of this commerical item description in preference to Military Specification MIL-R-10651.

This commercial item description covers the requirements for an 8-man railway maintenance motor car of 2000 pound load capacity meeting all applicable American Railway Engineering Association (AREA) requirements.

Salient Characteristics:

Standard commercial engine (gas or diesel) sized to meet performance requirements set forth under "intended use". Engine shall be enclosed with movable panels for ease of maintenance.
Transmission capable of transmitting the full power of the engine with equal speed in either direction of travel and with all gear lever positions clearly and durably labeled.
Electric starting.
Industrial strength battery.
Heavy-duty alternator.
Brakes applied at all four wheels.
Auxiliary parking brake inside cab.
Elastomer or spring-type suspension.
Heavy duty tapered roller bearings.
Flanged steel wheels meeting AREA or AAR requirements.
Cab enclosed by metal canopy top and flexible side curtains that can be secured either open or closed from both inside and out with quick-release fasteners.
Safety glass windshields front and rear.
Dual electric windshield wipers front and rear.
Upholstered seating for eight persons.
Interior cab light.
Sealed beam headlights and taillights front and rear.
Illuminated instrument panel equipped with standard operating controls, gages, and switches and with all position and functions clearly labeled.
Electric horn.
One 5 pound dry chemical fire extinguisher with location clearly stenciled.
Tool storage area.
Rail sweeps at all wheels.
Derail guards.
Turntable with pivot and set-off rails.
Drawheads at each end.
Self-closing hooks with safety catch at each end.
Four lifting lugs of sufficient capacity to lift motor car with location clearly indicated by stenciling "SLING HERE".

FSC 2230

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:41Z
Check the source to verify that this is the current version before use.

High-gloss enamel paint system in AREA standard yellow with black stenciling.
Permanent metal identification plate mounted in a conspicuous place and showing manufacturer's name, address, model, serial number, and date of manufacture.

Intended use. The motor car is intended to transport men and materials to work sites under its own power. It shall be capable of operating at a minimum of 10 mph when transporting a load of 2,000 pounds and towing five loaded 3-ton trailer cars simultaneously on straight and level track. The motor car shall be capable of negotiating a 100 foot radius curve.

Materials and workmanship. Materials shall meet ASTM and AREA specifications where applicable for the purpose intended. The 8-man railway maintenance motor car shall be fabricated from compatible materials, inherently corrosion resistant or treated to provide protection against the various forms of corrosion and deterioration that may be encountered in any of the applicable storage and operating environment to which the item may be exposed. Dissimilar metals, as defined in MIL-STD-889 shall be electrically insulated from one another to minimize or prevent galvanic corrosion. Workmanship in construction and finish shall be of high quality and consistent with industry standards.

Environmental condition. The motor car shall be capable of operation without malfunction or damage at ambient temperatures from -25° F to +125° F.

Essential safety features. All parts that rotate, reciprocate, or are subject to high operational temperatures and that are so located as to be a hazard to operating personnel, shall be guarded or insulated. All floors and steps shall have anti-skid surfaces. Fluid level indicators for engine, transmission, and other components shall be within easy and safe access of the operator or maintenance personnel. All controls shall be within convenient reach and vision of operator in his normal operating position. Noise levels shall meet OSHA requirements.

Standard commercial product. The above salient characteristics are set forth as minimum requirements. The motor car shall be in accordance with these minimum requirements and shall be the manufacturer's standard commercial product. Additional or better features which are not specifically prohibited by this specification but which are a part of the manufacturer's standard commercial product, shall be included in the motor car being furnished. A standard commercial product is a product which has been sold or is being currently offered for sale on the commercial market through advertisements, manufacturer's catalogs, or brochures, and represents the latest production model. It shall have been in production, marketed, and in use for a minimum of one year. The introduction of normal product improvements is acceptable. The car shall differ from the standard commercial product if serious differences exist between the standard commercial product and MIL-STD-1472.

Acceptance. Acceptance of these motor cars shall be based on visual inspection and demonstration of its performance capabilities. The first produced motor car shall be completely inspected to insure that all components have been provided.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:41Z
Check the source to verify that this is the current version before use.

The motor car shall be given a 1 hour continuous track run test combining forward and reverse directions at the highest speed practicable while operating all functional elements. No deviation in the remaining units shall be allowed without the approval of the contracting officer.

Packaging and marking. The items shall be preserved in accordance with the manufacturer's standard practice in a manner to prevent deterioration and damage. The motor car shall be prepared for shipment in a manner which will insure arrival at destination in a satisfactory condition. Preparation for delivery shall comply with applicable carrier rules and regulations.

Battery shall be shipped wet, in fully-charged condition, but with terminals disconnected. All systems shall be shipped with all fluid levels in normal operating ranges (except fuel). Antifreeze, if applicable, shall be added to provide protection for stated environmental conditions.

A metal, wood, or composition plate of sufficient size to contain the marking information shall be attached in a conspicuous location. The marking shall consist of the item nomenclature, stock number, contract number, consignees's complete address and additional markings as specified in the contract or order. Markings shall be applied in a legible manner, in contrasting color, of an appropriate size, and a waterproof material.

(Copies of specifications, standards, and drawings required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

Custodians:
Army - ME
Navy - YD
Air Force - 84

Preparing activity:
Army - ME

Project 2230-0066

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:41Z
Check the source to verify that this is the current version before use.