A-A-50221
12 May 1986

COMMERCIAL ITEM DESCRIPTION

TOOL, FORCED ENTRY AND RESCUE, 20,000 POUNDS

The General Services Administration has authorized the use of this commercial item description.

This description covers a gasoline engine powered, hydraulic operated forced entry and rescue tool.

Salient characteristics:

Design: The tool shall be designed for spreading and pulling by means of two arms acting in a scissors type action. The two arms acting together shall produce a minimum force of not less than 20,000 pounds when measured 1 inch from the tip of the arms and shall have an opening width of not less than 26 inches. The arms shall be designed for attachment of special accessory equipment used for tearing; chain attachment for pulling by fire departments during automotive and aircraft extrication of personnel. The tool shall be designed for one man operation and shall weigh not more than 46 pounds less the weight of the power pack and hoses and accessory equipment. Operating controls shall be of the dead man type, stopping all hydraulic action without further movement when released by the operator.

Power pack: The power pack shall be a hydraulic pump operated by a 4 cycle air cooled gasoline engine. The engine, hydraulic pump and oil reservoir shall be mounted in a carrying frame assembly as one unit. The unit shall weigh no more than 75 pounds including hydraulic hoses and valve arrangement necessary to operate the tool. Not less than 15 feet of properly sized hydraulic connecting hose with quick disconnect fitting shall be furnished with each pack. The tool shall operate on petroleum base hydraulic oil.

Hydraulic power pack: The tool shall be equipped with a hydraulic pump, oil reservoir, safety relief valves, lines, and fitting to operate as specified. Hydraulic lines shall be designed so that they cannot be connected incorrectly. Safety relief valves shall be set and sealed by the manufacturer to a pressure equal or below the maximum working pressure of all hydraulic operated components. The reservoir shall form the base mounting for the hydraulic pump and gasoline engine.

Engine: The rescue tool shall be powered by a 4 cycle air cooled, rope start, gasoline engine. The engine shall operate on fuel conforming to ASTM D 439. The engine shall be direct coupled to the hydraulic pump.

AMSC N/A FSC 4240

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:41Z
Check the source to verify that this is the current version before use.

Accessories: The rescue tool shall be equipped with the following accessories:

2 chains - 6 ft. minimum length with hooks.
2 chain adaptors.
1 set of replacement tips.
1 hydraulic operated metal cutting shears.

Certification of commercial item. The contractor shall certify that the product offered to the Government meets the salient characteristics of this description and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices and is the same product as the manufacturer's current product offered by the contractor in the commercial market place for at least one year preceding the solicitation. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Small business. A small business that cannot meet the certification-of-commercial-item requirement of this document, may make an offer under this solicitation; and, if such small business is the apparent successful offeror, the Government may require the small business to submit a sample forced entry and rescue tool. Any such tool may be evaluated for this solication if time to contract award permits. Such evaluation would be to determine conformance to all requirements of this commercial item description and to determine equivalency to forced entry and rescue tools available in the commercial marketplace in the areas of durability, human factors engineering and safety. It should be noted that bid samples are not required unless specifically requested by the contracting officer. Note. The Government may elect not to evaluate a bid sample from an apparent low bidder for award for this solicitation if a determination of urgency is made by the contracting officer. The bid sample would then be evaluated prior to future solicitation for comparable items.

Noise level requirement. The noise produced by the complete system shall not exceed 85dB(A) when operated under full load conditions. Permission to exceed the 85dB(A) requirement shall be requested of the procuring activity if it can be documented to the satisfaction of the procuring activity that noise reduction to 85dB(A) or below is clearly beyond the state-of-the-art or adversly impacts cost/system effectiveness, or both. Upon procuring activity approval of the analysis, hearing protection warning signs will be required to be affixed permanently to the equipment and shall state "CAUTION, HEARING PROTECTION REQUIRED WITHIN _____ FEET", giving the safe distance away from the equipment that 85dB(A) will always be met. Hearing protectors shall not be supplied with the equipment.

Noise test. Noise level measurements shall be recorded in dB(A) and in octave band widths of 63, 125, 250, 500, 1,000, 2,000, 4,000, and 8,000 Hz at each operator or crew position(s). In addition, distances shall be recorded at no

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:41Z
Check the source to verify that this is the current version before use.

fewer than 12 equal (horizontal) arc increments around the equipment that inscribe the 85dB(A) contour. Sound level meter shall conform with ANSI S1.4 and manufacturer plus background noise level during test shall be recorded. Failure to comply shall constitute failure of this test.

Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practical.

Human factors engineering. The unit shall conform to human factors engineering criteria of MIL-STD-1472, 5.5 (Labeling), 5.9 (Design for maintainability), and 5.13 (Hazards and safety).

Packaging and marking. Military packaging shall be specified when shipments are to overseas Department of Defense (DoD) consignees. Commercial packaging may be specified for shipments to DoD consignees within the continental United States and to non-DoD consignees worldwide. When a supplier's normal packaging will satisfy the requirements for military packaging, it may be used.

Military packaging. Each tool and its accessories shall be preserved and packed to protect against physical damage and deterioration in a logistic environment characterized by the following:

1. Multiple handling during transportation and intransit storage.
2. Shock, vibration and static loading forces during worldwide shipment by all transport modes.
3. Uncontrolled warehouse storage for extended periods.
4. Weather exposure during shipment and intransit transfers.
5. Stacking loads during shipment and storage.

The engine shall be internally preserved to protect combustion chamber and valves. Quantities of tools destined to a single address may be unitized into one or more unit loads.

Commercial. Each tool shall be packaged in accordance with the supplier's normal method for retail distribution. Tools shipped to a single destination may be unitized to permit handling as a single unit. Shipping containers shall comply with Uniform Freight Classification or National Motor Freight Classification rules.

Marking. Unit, intermediate (when provided), and exterior packs shall be marked with the item nomenclature, stock or part number, quantity per pack, and contract number as a minimum: additional marking shall be as specified in the contract or order. Exterior packs shall have, in addition, the complete consignee's address. Markings shall be applied in a legible manner, in a contrasting color, of an appropriate size, and of waterproof materials.

Quality assurance. The tools shall be examined for the following defects. Presence of one or more defects shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:41Z
Check the source to verify that this is the current version before use.

1. Engine not as specified.
2. Does not operate as specified.
3. Hydraulic oil not as specified.
4. Accessories not as specified.
5. Packaging and marking not as specified.

MILITARY INTEREST:

Custodians
Army - ME

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:
Army - ME

Project 4240-A816

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:41Z
Check the source to verify that this is the current version before use.