A-A-50311
June 30, 1992

COMMERCIAL ITEM DESCRIPTION

GUN, FLUSHING, RADIATOR, AND ENGINE BLOCK

The General Services Administration has authorized the use of this commercial item description (CID) as a replacement for Military Specification MIL-G-14562D

Abstract. This description covers one type of gun capable of flushing water, with air pressure, through the radiator or engine block. By regulation of the control valves, the gun shall be capable of mixing air and water in any proportion desired by the operator. The gun shall function efficiently when operating from an air source of 60 to 120 pounds per square inch (psig) and a water source of 15 to 45 psig with a rate of flow of no less than three gallons per minute.

Salient characteristics.

1. Body. The body shall be a corrosive-resistant metal casting. A hand grip shall be provided to afford a positive hold by the operator. With air and water valves in the OFF position, the gun shall be capable of withstanding 200 psig air pressure an 75 psig water pressure for no less than 60 seconds without leakage or damage to the gun.

2. Air and water connecting threads. The gun shall contain a standard 0.25 - 18 NPT female thread for air hose attachment and a standard 0.75 - 11 1/2 NH female thread for water hose attachment.

3. Radiator and block hose adapters. The radiator and block adapter, or adapters, shall be of the graduated or self-holding type and shall accommodate radiator and engine block hoses having an inside diameter of no more than 1.000 inch up to, and including, an inside diameter of no less than 2.000 inches. The adapters shall approximate a cone in shape and may be an integral part of the gun body or be detachable.

4. Heater hose adapter. Unless otherwise specified, a heater hose adapter shall be provided with the gun and may be an integral part of the gun body or be detachable.

Beneficial comments, recommendations, clarifications, additions, deletions, etc. and any data which may improve this document should be sent: Commander, US Army Armament Research, Development and Engineering Center, ATTN: SMCAR-EST-P, Rock Island, IL 61299-7300

AMSC N/A FSC 4910

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:41Z
Check the source to verify that this is the current version before use.

5. Air control valve. An air control valve shall be provided which can be operated independently of, or simultaneously with, the water control valve. The valve may be a button, trigger, or level type.

6. Water control valve. A water control valve shall be provided which can be operated independently of, or simultaneously with, the air control valve. The valve may be a button, trigger, or lever type.

7. Discharge hose assembly. Unless otherwise specified, a discharge hose assembly 30 inches ± one inch in length shall be provided to facilitate flushing when space is limited or hose connections which are not readily accessible are encountered. The hose shall have a connection on one end to fit the gun discharge outlet or adapters, and a means for attaching to the radiator, engine block or heater on the other end.

Contractor certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards and quality assurance practices. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent.

Packaging. The preservation, packaging, packing, and marking shall be as specified in the contract or order.

Note.

Ordering data. Acquisition documents should specify the following:

a. Title, CID number, and date of this document.
b. If heater hose adapter is not required (see 4.)
c. If discharge hose is not required (see 7.)

As the result of a market acceptability survey, the following companies have shown to be manufacturers of an acceptable product described within this Commercial Item Description. This list does not limit or exclude the selection of other manufacturers who have an acceptable product provided that they meet the market acceptability criteria, as verified by the CID developer, that has been established for the CID. Other manufacturers' products will be considered for a current procurement if the following market acceptability criteria can be met before the specified date of contract award.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:41Z
Check the source to verify that this is the current version before use.

Market acceptability criteria:

1. Must have a commercial distribution system.
2. Must have repair support (spare parts) system.
3. Must produce and sell at least 100 flushing guns per year to commercial customers.
4. Must have been in business producing commercial flushing guns for no less than one year.

Therm Processes, Inc.
1609 E. 8th St.
Dallas, TX 75203
Model 1348-00

Barbee Co.
418 E. Breckinridge
P. O. 323
Louisville, KY 40201
Model 175-C

MILITARY INTERESTS:

Military Coordinating Activity

Custodian

Army - AL
Navy - YD
Air Force - 99

Review activity

DLA-CS
Air Force - 82

User activity

Navy - MC

CIVIL AGENCY COORDINATING ACTIVITIES:

GSA - FSS

PREPARING ACTIVITY:

Army - AL

Project 4910-0748

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:41Z
Check the source to verify that this is the current version before use.