The documentation and process conversion measures necessary to comply with this document shall be completed by 3 May 2025.

INCH-POUND

MIL-PRF-19500/526J
w/AMENDMENT 1
3 February 2025
SUPERSEDING
MIL-PRF-19500/526J
26 May 2019

PERFORMANCE SPECIFICATION SHEET

TRANSISTOR, NPN, SILICON, POWER,
TYPE 2N3879, QUALITY LEVELS JAN, JANTX, AND JANTXV

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-19500.

1. SCOPE

1.1 Scope. This specification covers the performance requirements for NPN, silicon, power transistors. Three levels of product assurance (JAN, JANTX, and JANTXV) are provided for each device type as specified in MIL-PRF-19500.

1.2 Package outline. The device package outline is a modified TO-213AA (similar to a TO-66) in accordance with figure 1.

1.3 Maximum ratings. Unless otherwise specified, T_A = +25°C.

P_T (1) T_C = +25°C	$R_{\theta JC}$	V_{CBO}	V_{CEO}	V_{EBO}	I_B	IC	T_J and T_{STG}
W	°C/W	V dc	V dc	V dc	A dc	A dc	°C
35	5	120	75	7	5	7	-65 to +200

(1) Derate linearly 200 mW/°C for T_C > +25°C.

1.4 Primary electrical characteristics.

	h_{FE1} (1) V_{CE} = 5.0 V dc I_C = 0.5 A dc	h_{FE2} (1) V_{CE} = 5.0 V dc I_C = 4.0 A dc	$V_{BE(SAT)1}$ I_C = 4.0 A dc I_B = 0.4 A dc	$V_{CE(SAT)1}$ I_C = 4.0 A dc I_B = 0.4 A dc	C_{obo} V_{CB} = 10 V dc I_E = 0 0.1 MHz ≤ f ≤ 1 MHz	$\lvert h_{fe} \rvert$ V_{CE} = 10 V dc I_C = 500 mA dc f = 10 MHz	Switching (see table I and figure 2 herein)	
							t_{on}	t_{off}
			V dc	V dc	pF		µs	µs
Min	40	20				4		
Max		80	2.0	1.2	175	20	0.44	1.2

(1) Pulsed (see 4.5.1).

Comments, suggestions, or questions on this document should be addressed to DLA Land and Maritime, ATTN: VAC, P.O. Box 3990, Columbus, OH 43218-3990, or emailed to Semiconductor@dla.mil . Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

FSC 5961

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:47Z
Check the source to verify that this is the current version before use.

1.5 Part or Identifying Number (PIN). The PIN is in accordance with MIL-PRF-19500, and as specified herein. See 6.4 for PIN construction example and 6.5 for a list of available PINs.

1.5.1 JAN certification mark and quality level. The quality level designators for encapsulated devices that are applicable for this specification sheet from the lowest to the highest level are as follows: "JAN", "JANTX", and "JANTXV".

1.5.2 Device type. The designation system for the devices covered by this specification sheet is as follows.

1.5.2.1 First number and first letter symbols. The devices of this specification sheet use the first number and letter symbols "2N".

1.5.2.2 Second number symbols. The second number symbols for the devices covered by this specification sheet is "3879".

1.5.3 Lead finish. The lead finishes applicable to this specification sheet are listed on QPDSIS-19500.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-PRF-19500 – Semiconductor Devices, General Specification for.

DEPARTMENT OF DEFENSE STANDARDS


MIL-STD-750 – Test Methods For Semiconductor Devices.

(Copies of these documents are available online at https://quicksearch.dla.mil.)

2.3 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:47Z
Check the source to verify that this is the current version before use.

Symbol	Dimensions				Notes
	Inches		Millimeters		
	Min	Max	Min	Max	
CD	.470	.500	11.94	12.70	4
CH	.250	.340	6.35	8.64	
HR		.350		8.89	5
HR_1	.115	.145	2.92	3.68	5
HT	.050	.075	1.27	1.91	7
LD	.028	.034	0.71	0.86	8, 9
LL	.360	.500	9.14	12.70	8, 9
L_1		.050		1.27	8, 9
MHD	.142	.152	3.61	3.86	6
MHS	.958	.962	24.33	24.43	
PS	.190	.210	4.83	5.33	10
PS_1	.093	.107	2.36	2.72	10
S	.570	.590	14.48	14.99	



NOTES:
1. Dimensions are in inches. Millimeters are given for general information only.
2. Pin 1 is the emitter and pin 2 is the base. The collector shall be electrically connected to the case.
3. The seating plane of the header shall be flat within .001 inch (0.03 mm) concave to .004 inch (0.10 mm) convex inside a .520 inch (13.20 mm) diameter circle on the center of the header and flat within .001 inch (0.03 mm) concave to .006 inch (0.15 mm) convex overall.
4. Body contour is optional within zone defined by dimension CD.
5. The radius applies to two places, at both sides (dimension HR) or ends (dimension HR_1) of the package.
6. Applies to two holes, at both ends.
7. Dimension HT does not include sealing flanges.
8. Applies to both terminals.
9. Dimension LD applies between dimensions L_1 and LL. Lead diameter shall not exceed twice dimension LD within dimension L_1.
10. These dimensions should be measured at points .050 inch (1.27 mm) +.055 inch (1.40 mm) -0 inch below seating plane. When gauge is not used, measurement will be made at the seating plane.

FIGURE 1. Physical dimensions for a modified TO-213-AA (similar to TO-66).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:47Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 General. The individual item requirements shall be as specified in MIL-PRF-19500 and as modified herein.

3.2 Qualification. Devices furnished under this specification shall be products that are manufactured by a manufacturer authorized by the qualifying activity for listing on the applicable qualified manufacturers list before contract award (see 4.2 and 6.3).

3.3 Abbreviations, symbols, and definitions. Abbreviations, symbols, and definitions used herein shall be as specified in MIL-PRF-19500.

3.4 Interface and physical dimensions. Interface and physical dimensions shall be as specified in MIL-PRF-19500, and on figure 1.

3.4.1 Lead finish. Lead finish shall be solderable in accordance with MIL-PRF-19500, MIL-STD-750, and herein. Where a choice of lead finish is desired, it shall be specified in the acquisition document (see 6.2).

3.4.2 Pin-out. The pin-out of the encapsulated devices shall be as shown on figure 1.

3.5 Marking. Marking shall be in accordance with MIL-PRF-19500.

3.6 Electrical performance characteristics. Unless otherwise specified, the electrical performance characteristics are as specified in 1.3, 1.4, and table I herein.

3.7 Electrical test requirements. The electrical test requirements shall be as specified in table I.

3.8 Workmanship. Semiconductor devices shall be processed in such a manner as to be uniform in quality and shall be free from other defects that will affect life, serviceability, or appearance.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Screening (see 4.3).

c. Conformance inspection (see 4.4 and tables I and II).

4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL-PRF-19500.

4.2.1 Group E qualification. Group E inspection shall be performed for qualification or re-qualification only. In case qualification was awarded to a prior revision of the specification sheet that did not request the performance of table II tests, the tests specified in table II herein that were not performed in the prior revision shall be performed on the first inspection lot of this revision to maintain qualification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:47Z
Check the source to verify that this is the current version before use.

* 4.3 Screening (JANTX and JANTXV levels only). Screening shall be in accordance with table E-IV of MIL-PRF-19500 and as specified herein. The following measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Screen	Measurements for JANTX and JANTXV levels
(1) 3c	Thermal impedance (see 4.3.2).
9	I_{CEX1}.
11	h_{FE2}; I_{CEX1}; ΔI_{CEX1} = 100 percent of initial value or 2 µA dc, whichever is greater.
12	See 4.3.1.
13	Subgroup 2 of table I herein. ΔI_{CEX1} = 100 percent of initial value or 2 µA dc, whichever is greater. Δh_{FE2} = ±25 percent of initial value.

(1) Shall be performed anytime after temperature cycling, screen 3a; and does not need to be repeated in screening requirements.

4.3.1 Power burn-in. Power burn-in conditions shall be as follows: T_J = +187.5°C, ±12.5°C; V_{CB} = 10 - 30 V dc; T_A = room ambient as defined in the general requirements of 4.5 of MIL-STD-750. With approval of the qualifying activity and preparing activity, alternate burn-in criteria (hours, bias conditions, T_J, and mounting conditions) shall be used. A justification demonstrating equivalence is required. In addition, the manufacturing site's burn-in data and performance history will be essential criteria for burn-in modification approval.

4.3.2 Thermal impedance. The thermal impedance measurements shall be performed in accordance with method 3131 of MIL-STD-750 using the guidelines in that method for determining I_M, I_H, t_H, t_{MD}, t_{SW}, (and V_H where appropriate). See table II, subgroup 4 herein.

4.4 Conformance inspection. Conformance inspection shall be in accordance with MIL-PRF-19500 and as specified herein.

4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with MIL-PRF-19500 and table I herein. End-point electrical measurements shall be in accordance with table I, subgroup 2 herein.

4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the tests and conditions specified for subgroup testing in table E-VIC (small die flow) of MIL-PRF-19500 and herein.

Step	Method	Condition
1	1026	Steady-state life: Test condition B, 1,000 hours minimum, V_{CB} = 10 V dc, power shall be applied to the device to achieve T_J = +150°C minimum; n = 45, c = 0.
2	1048	Blocking life, T_A = +150°C, V_{CB} = 80 percent of rated voltage, 48 hours minimum. n = 45, c = 0.
3	1032	High-temperature life (non-operating), T_A = +200°C, t = 340 hours, n = 22, c = 0.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:47Z
Check the source to verify that this is the current version before use.

4.4.2.1 Sample selection. Samples selected for small die flow group B inspection shall be in accordance with all of the following requirements:

a. Samples shall be chosen from an inspection lot that has been submitted to and passed table I, subgroup 2, conformance inspection.

b. When the final lead finish is solder, or any plating prone to oxidation at high temperature, the samples for life test may be selected prior to the application of final lead finish.

c. Separate samples may be used for each step.

4.4.2.2 Failures. In the event of a lot failure, the resubmission requirements of MIL-PRF-19500 shall apply. In addition, all catastrophic failures during small die flow group B inspection shall be analyzed to the extent possible to identify root cause and corrective action. Whenever a failure is identified as wafer lot and wafer processing related, the entire wafer lot and related devices assembled from the wafer lot shall be rejected unless an appropriate corrective action to eliminate the failure mode has been implemented and the devices from the wafer lot are screened to eliminate the failure mode.

4.4.3 Group C inspection. Group C inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-VII of MIL-PRF-19500.

Subgroup	Method	Condition
C2	2036	Test condition A; weight = 10 pounds (4.5.4 kg); t = 15 s.
C5	3131	See 4.3.2, $R_{\theta JC}$ = 5°C/W.
C6		Not applicable.

4.4.3.1 Group C sample selection. Samples for subgroups in group C shall be chosen at random from any lot containing the intended package type and lead finish procured to the same specification which is submitted to and passes table I tests herein for conformance inspection. When the final lead finish is solder, or any plating prone to oxidation at high temperature, the samples for C6 life test may be selected prior to the application of final lead finish. Testing of a subgroup using a single device type enclosed in the intended package type shall be considered as complying with the requirements for that subgroup.

4.4.4 Group E inspection. Group E inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-IX of MIL-PRF-19500 and as specified in table II herein. Electrical measurements (end-points) shall be in accordance with table I, subgroup 2 herein.

4.5 Methods of inspection. Methods of inspection shall be as specified in the appropriate tables and as follows.

4.5.1 Pulse measurements. Conditions for pulse measurements shall be as specified in section 4 of MIL-STD-750.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:47Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection.

Inspection 1/	MIL-STD-750		Symbol	Limits	Limits	Unit
	Method	Conditions		Min	Max	
Subgroup 1 2/						
Visual and mechanical examination	2071					
Solderability 3/	2026					
Resistance to solvent 3/ 4/	1022					
Temp cycling 3/	1051	Test condition C, 25 cycles				
Hermetic seal Fine leak Gross leak	1071					
Electrical measurements		Table I, subgroup 2				
Bond strength 3/	2037	Pre-condition T_A = +250°C at t = 24 hours or T_A = +300°C at t = 2 hours, n = 11 wires, c = 0				
Decap internal visual	2075	n = 4, c = 0				
Subgroup 2						
Thermal impedance 5/	3131	See 4.3.2	$Z_{\theta JX}$			°C/W
Breakdown voltage, collector to emitter	3011	Bias condition D; I_C = 200 mA dc; pulsed (see 4.5.1)	$V_{(BR)CEO}$	75		V dc
Collector to emitter cutoff current	3041	Bias condition D; V_{CE} = 50 V dc	I_{CEO}		5	mA dc
Collector to emitter cutoff current	3041	Bias condition A; V_{CE} = 100 V dc; V_{BE} = 1.5 V dc	I_{CEX1}		10	µA dc
Emitter to base cutoff current	3061	Bias condition D; V_{EB} = 7 V dc	I_{EBO}		10	mA dc
Collector to base cutoff current	3036	Bias condition D; V_{CB} = 120 V dc	I_{CBO}		10	µA dc
Base emitter voltage (nonsaturated)	3066	Test condition B; I_C = 4.0 A dc; V_{CE} = 2.0 V dc; pulsed (see 4.5.1)	V_{BE}		1.8	V dc

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:47Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limits	Limits	Unit
	Method	Conditions		Min	Max	
Subgroup 2 - continued						
Base emitter voltage (saturated)	3066	Test condition A; I_C = 4.0 A dc; I_B = 0.4 A dc; pulsed (see 4.5.1)	$V_{BE(SAT)}$		2.0	V dc
Collector to emitter saturated voltage	3071	I_C = 4.0 A dc; I_B = 0.4 A dc; pulsed (see 4.5.1)	$V_{CE(SAT)}$		1.2	V dc
Forward-current transfer ratio	3076	V_{CE} = 5.0 V dc; I_C = 0.5 A dc; pulsed (see 4.5.1)	h_{FE1}	40		
Forward-current transfer ratio	3076	V_{CE} = 5.0 V dc; I_C = 4.0 A dc; pulsed (see 4.5.1)	h_{FE2}	20	80	
Forward-current transfer ratio	3076	V_{CE} = 2.0 V dc; IC = 4.0 A dc; pulsed (see 4.5.1)	h_{FE3}	12	100	
Subgroup 3						
High temperature operation:		T_A = +150°C				
Collector to emitter cutoff current	3041	Bias condition A; V_{CE} = 100 V dc; V_{BE} = 1.5 V dc	I_{CEX2}		750	µA dc
Low temperature operation:		T_A = -55°C				
Forward-current transfer ratio	3076	V_{CE} = 5.0 V dc; I_C = 0.5 A dc; pulsed (see 4.5.1)	h_{FE4}	10		
Subgroup 4						
Pulse response	3251	Test condition A except test circuit and pulse requirements in accordance with figure 2 herein.				
Turn-on time		V_{CC} = 30 V dc; I_C = 4.0 A dc; I_B = 0.4 A dc	$t_{(on)}$		0.44	µs
Turn-off time		V_{CC} = 30 V dc; I_C = 4.0 A dc; I_B = -I_B = 0.4 A dc	$t_{(off)}$		1.2	µs
Magnitude of common emitter small-signal short-circuit forward-current transfer ratio	3306	V_{CE} = 10 V dc; I_C = 500 mA dc; f = 10 MHz	$\|h_{fe}\|$	4	20	
Open circuit output capacitance	3236	V_{CB} = 10 V dc; I_E = 0; 0.1 MHz ≤ f ≤ 1.0 MHz	C_{obo}		175	pF

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:47Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limits	Limits	Unit
	Method	Conditions		Min	Max	
Subgroup 5						
Safe operating area (continuous dc)	3051	T_C = +25°C; t = 1 s, 1 cycle; (see figure 3)				
Test 1		V_{CE} = 5 V dc; I_C = 7 A dc				
Test 2		V_{CE} = 28 V dc; I_C = 1.25 A dc				
Test 3		V_{CE} = 40 V dc; I_C = 500 mA dc				
Test 4		V_{CE} = 75 V dc; I_C = 100 mA dc				
End-point electrical measurements		Table I, subgroup 2				
Safe operating area (switching)	3053	Load condition C, (unclamped inductive load) (see figure 4) T_C = +25°C; duty cycle ≤ 5 percent; R_S = 0.1 ohm; $t_r = t_f \leq 2$ µs				
Test 1		$t_p \approx 50$ µs (vary to obtain I_C); R_{BB1} = 5.0 ohms; V_{BB1} = 10 V dc; R_{BB2} = 50 ohms; V_{BB2} = 4 V dc; I_C = 4 A dc; L = 125 µH; V_{CC} = 10 V dc; R of inductor = 0.1 ohm				
Test 2		tp ≈ 25 µs (vary to obtain I_C); R_{BB1} = 5.0 ohms; V_{BB1} = 10 V dc; R_{BB2} = 50 ohms; V_{BB2} = 1.5 V dc; I_C = 1 A dc; L = 250 µH; V_{CC} = 10 V dc; R of inductor = 0.1 ohm				
End-point electrical measurements		Table I, subgroup 2				
Safe operating area (switching)	3053	Load condition B; T_A = +25°C; I_C = 7 A dc; V_{CC} = 45 V dc; clamped voltage = 75 V dc, duty cycle ≤ 5 percent; R_{BB1} = 5.0 ohms; V_{BB1} = 10 V dc; R_{BB2} = 50 ohms; V_{BB2} = -4 V dc; L = 250 µH; R of inductor = 0.1 ohm; R_L = as required to limit I_C				

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:47Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limits	Limits	Unit
	Method	Conditions		Min	Max	
Subgroups 6 and 7 Not applicable						


1/ For sampling plan, see MIL-PRF-19500.
2/ For resubmission of failed subgroup 1, double the sample size of the failed test or sequence of tests.
3/ Separate samples may be used.
4/ Not required for laser marked devices.
5/ This test required for the following end-point electrical measurements only:
Group B, steps 2 and 3.
Group C, subgroup 2.
Group E, subgroup 1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:47Z
Check the source to verify that this is the current version before use.


TABLE II. Group E inspection (all quality levels) for qualification and re-qualification only.

Inspection	MIL-STD-750		Sample plan
	Method	Conditions	
Subgroup 1			45 devices c = 0
Temperature cycling	1051	500 cycles.	
Hermetic seal Fine leak Gross leak	1071		
Electrical measurements		See table I, subgroup 2.	
Subgroup 2			45 devices c = 0
Blocking life	1048	Test temperature = +125°C; V_{CB} = 80 percent of rated; t = 1,000 hours.	
Electrical measurements		See table I, subgroup 2.	
Subgroup 4			Sample size N/A
Thermal impedance curves		See MIL-PRF-19500.	
Subgroup 8			45 devices c = 0
Reverse stability	1033	Condition B.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:47Z
Check the source to verify that this is the current version before use.



TURN-ON (t_{on}) TIME TEST CIRCUIT



TURN-OFF (t_{off}) TIME TEST CIRCUIT

$t_s + t_f = t_{off}$

FIGURE 2. Switching time test circuits.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:47Z
Check the source to verify that this is the current version before use.




FIGURE 3. Maximum safe operating graph (continuous dc).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:47Z
Check the source to verify that this is the current version before use.




FIGURE 4. Safe operating area for switching between saturation and cutoff (unclamped load).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:47Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the Military Service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory. The notes specified in MIL-PRF-19500 are applicable to this specification.)

6.1 Intended use. Semiconductors conforming to this specification are intended for original equipment design applications and logistic support of existing equipment.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.


b. Packaging requirements (see 5.1).

c. Lead finish (see 3.4.1).

d. The complete PIN, see 1.5 and 6.4.

6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Manufacturers List (QML-19500) whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from DLA Land and Maritime, ATTN: VQE, P.O. Box 3990, Columbus, OH 43218-3990 or e-mail vqe.chief@dla.mil. An online listing of products qualified to this specification may be found in the Qualified Products Database (QPD) at https://qpldocs.dla.mil.

6.4 PIN construction example. The PINs for devices are constructed using the following form.



6.5 List of PINs. The list of all possible PINs for the devices available on this specification sheet are JAN2N3879, JANTX2N3879, and JANTXV2N3879.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:47Z
Check the source to verify that this is the current version before use.

* 6.6 Request for new types and configurations. Requests for new device types or configurations for inclusions in this specification sheet should be submitted to: DLA Land and Maritime, ATTN: VAC, Post Office Box 3990, Columbus, OH 43218-3990 or by electronic mail at Semiconductor@dla.mil.

* 6.7 Amendment notations. The margins of this specification are marked with asterisks to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Custodians:
Army - CR
* Navy - SH
Air Force - 85
NASA - NA
DLA - CC

Review activity:
Army - AV
Air Force - 19

Preparing activity:
DLA - CC

(Project 5961-2024-079)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:47Z
Check the source to verify that this is the current version before use.