MIL-C-14892 (AR)
AMENDMENT 3
30 November 1983
SUPERSEDING
AMENDMENT 2
21 February 1975

MILITARY SPECIFICATION

CASE, CARTRIDGE, 105MM, M150B1

This amendment forms a part of Military Specification MIL-C-14892 (MU) dated 1 November 1973, and is approved for use by the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1:

Delete: "IEL-10521648 - Inspection Equipment List for Case, Cartridge, 105MM, M150B1".

Add: "F8645291 - Gage, chamber".

PAGE 4

4.2.1, Delete in its entirety and substitute:

"4.2.1 Initial production sample. At the beginning of regular production, a sample shall be submitted in accordance with contract requirements and shall consist of 274 cartridge cases as follows:

254 Cartridge Cases - Coated
20 Cartridge Cases - Uncoated

250 of the above coated cartridge cases shall be forwarded to a designated proving ground for ballistic testing. The sample shall be manufactured using the same materials, equipment, processes and procedures as used in regular production. All parts and materials, including packaging and packing, shall be the same as used in regular production and shall be obtained from the same source of supply. A

FSC 1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:03Z
Check the source to verify that this is the current version before use.

first article sample or portion thereof as directed by the procuring agency shall also be submitted whenever there is a lapse in production for a period in excess of 90 days or whenever a change occurs in manufacturing processes, material used, drawing specifications or source of supply, such as to significantly affect product uniformity as determined by the responsible technical agency."

PAGE 5

4.3.2.2, Delete: Major defect "113".

PAGE 6

4.3.2.3, Under "Critical", delete line 1 in its entirety and substitute: "None defined".

PAGE 7

Add:

"4.3.3.a Metal defects. Prior to coating and after coating each cartridge case shall be visually examined for metal defects. Failure of any cartridge case to comply with the requirements of 3.9.1 or established visual standards shall be cause for rejection of the cartridge case."

PAGE 10

* 4.3.7, Delete in its entirety.

4.4.2.1, Delete in its entirety and substitute:

"4.4.2.1 Hardness. This test shall be performed on the locations specified by the applicable drawing in accordance with the procedures prescribed for Rockwell Hardness Testing by ASTM Method E-18."

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:03Z
Check the source to verify that this is the current version before use.

4.4.6, Delete in its entirety and substitute:

"4.4.6 Macro examination. The cartridge case shall be cut in a 90 degree section along the axis through the primer hole. The specimen shall be etched in accordance with the procedures prescribed for this test by ASTM Method A-317."

The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army-AR

Preparing activity
Army-AR

(Project 1315-A593)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:03Z
Check the source to verify that this is the current version before use.