MILITARY SPECIFICATION

INITIATOR, CARTRIDGE ACTUATED: DELAY M114 ASSEMBLY

1. SCOPE

1.1 This specification covers Initiator, Cartridge Actuated, Delay, XM114, Assembly, loaded with Cartridge Delay, M231, for use with other propellant actuated devices in aircrew emergency escape systems.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

Military

MIL-A-2550	Ammunition and Special Weapons, General Specification For

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	Quality Assurance Terms and Definitions
MIL-STD-414	Sampling Procedures and Tables for Inspection by Variables for Percent Defective
MS-28741	hose Assembly, Detachable End Fitting, Medium Pressure

DRAWINGS

Munitions Command

F11726503	Initiator, Cartridge Actuated, Delay, XM114, Assembly
F8798142	Box, Packing, Ammunition for Initiator, Delay, M10 in Fiber Container M398
F8798143	Container, Fiber, Ammunition, M398 for Initiator, Delay, Cartridge Actuated, M10, M30, M31, M32, M42, M43, M72 or XM114.
IEL11726503	Inspection Equipment List for Initiator, Cartridge Actuated, Delay, XM114, Assembly

Source: https://assist.dla.mil -- Downloaded: 202610-18T05:02Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 General.- Materials, parts and assemblies shall comply with the requirements specified on the applicable drawings and referenced specifications.

3.2 Breakaway torque.- The chamber and cap of the assembled initiator shall withstand a breakaway torque application of 400 inch-pounds without loosening or deformation.

3.3 Residual magnetism.- The initiator shall not deflect the indicator of the compass more than 3 degrees in either direction when passed in front of the compass at a distance of 6 inches.

3.4 Functional.

3.4.1 Ballistics.- Initiators loaded with accepted cartridges and temperature conditioned shall produce pressure values specified in Table I Pressure values shall be recorded at the end of 15 feet of aircraft hose, size No. 4, in accordance with MS28741.

TABLE I

Temperature	Pressure (psi) Min	Max	Ignition Delay (See 6.3)
-65°F to -70°F	500	1300	0.92 sec max
65°F to 75°F	500	1650	0.72 ± 0.12
200°F to 205°F	1000	1750	0.55 min

3.4.1.1 Initiator.- The initiator shall be fired by a source delivering an output equal to that of an M3A1 Initiator at the end of 15 feet of aircraft hose, size No. 4, in accordance with MS28741, at 70° ± 5°F.

3.4.2 The Initiator shall not fail to fire.

3.4.3 The Initiator shall function without mechanical failure (See 6.2).

3.5 Workmanship.- The requirements for workmanship are as specified on the applicable drawings, referenced specifications and the following.

3.5.1 Metal defects.- The part shall be free from cracks, splits, cold shuts, inclusions, porosity or other metal defects.

3.5.2 Burr.- The part shall not have a burr which might interfere with the assembly or function of the item, or which might be injurious to personnel handling the item.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:02Z
Check the source to verify that this is the current version before use.

3.5.3 Foreign matter.- The part or assembly shall not contain chips, dirt, grease, rust, corrosion or other foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality Assurance terms and definitions.- Reference shall be made to MIL-STD-109 to define quality assurance terms used.

4.1.2 Inspection.- Inspection shall be in accordance with MIL-A-2550.

4.2 Inspection provisions.

4.2.1 Lot.

4.2.1.1 Submission of product.- The product shall be submitted in accordance with MIL-STD-105.

4.2.1.2 Size of lot.- A lot shall consist of an identifiable group of assembled units containing metal parts assemblies produce by a homogeneous process and loaded with acceptable cartridges.

4.2.2 Examination.- One hundred percent examination shall be performed for all critical defects. Examination for major and minor defects shall be performed on a defect basis in accordance with the classification of defects using the sampling plan and associated criteria in Table II. All nonconforming material shall be rejected. The total number of allowable defects per class for either the major or minor classification shall not exceed the acceptance number of Table II. Four power magnification may be used for inspection of such defects as burr and foreign matter.

TABLE II

		Major		Minor	
Lot Size	Sample Size	Accept	Reject	Accept	Reject
1-300	100%	-	-	-	-
301-800	50	0	1	1	2
801-1800	90	1	2	2	3

Source: https://assist.dla.mil -- Downloaded: 20260-18T05:02Z
Check the source to verify that this is the current version before use.

4.2.2.1 Cartridge, Delay, Drawing D10536005, covering a detail of Drawing F11726503.

	Method of Inspection
Critical	
1. Mixed cartridges	visual
2. Metal defective	visual
3. O-ring missing	visual
4. Sealing disc missing, damaged or improperly secured	visual
Major	
101. O-ring split, cut or cracked	visual
102. Foreign matter	visual
Minor	
201. Case scratched, wrinkled, bulged or dented	visual
202. Varnish missing or inadequate	visual

4.2.2.2 Assembly, Drawing F11726503, less Drawings B8359536, B8593298, D8594856, D8594857, D8594860 and D10521632.

Critical	
1. Set screw missing	visual
Major	
101. Thread damaged	visual
102. Burr	visual
103. Foreign matter	visual
Minor	
201. Case scratched, wrinkled, bulged or dented	visual
202. Varnish missing or inadequate	visual

4.2.2.3 Assembly, Drawing F11726503, less Drawings B8359536, B85939536, B8593298, D8594857, D8594860 and D10521632.

Critical	
1. Screw missing	visual

Source: https://assist.dla.mil -- Downloaded: 202610-18T05:02Z
Check the source to verify that this is the currentversion before use.

4.2.2.3 (cont'd)

Defect	Method of Inspection
101. Thread damaged	visual
102. Burr	visual
103. Foreign matter	visual

Minor

None defined

4.2.2.4 Assembly, Drawing F11726503, less Drawings B8359536, B8593298 and D8594857.

Critical

1. Cartridge loose	Manual and visual
2. Cartridge retainer loose	Manual and visual
3. Metering groove of cartridge retainer missing	visual
4. Elongated hole of cartridge retainer missing	visual

Major

None defined

Minor

None defined

4.2.2.5 Assembly, Drawing F11726503, less Drawings B8359536 and B8593298.

Critical

1. Location of cartridge retainer	gage
2. Shear pin not engaged in firing pin	gage
3. Any part missing	visual
4. Improper assembly	visual
5. Foreign matter in gas port	visual

Major

101. Length from firing pin housing boss face to gas port face, max.	gage

Source: https://assist.dla.mil -- Downloaded: 202610-18T05:02Z
Check the source to verify that this is the current version before use.

4.2.2.5 (cont'd)

Defect	Method of Inspection
Minor	
201. Varnish missing or inadequate	visual
202. Location of label incorrect	visual
203. Barrier material missing from set screw	visual

4.2.2.6 Assembly, Drawing F11726503.

Critical	
1. Marking missing, incorrect or illegible	visual
Major	
101. Height of cap, max.	gage
102. Cap set screw missing, loose or above flush	visual
Minor	
201. Total length, max.	gage
202. Location of marking incorrect	visual
203. Shipping cap or plug missing	visual
204. Protective finish inadequate or defective	visual

4.2.2.7 Container Fiber, Drawing C8798143.

Critical: None defined	
Major: None defined	
Minor	
201. Gap between body and cover, max.	manual
202. Contents loose	manual
203. Metal ends loose or distorted	manual
204. Cut or damaged through all unpregnated layers	visual
205. Marking missing, incorrect or illegible	visual
206. Tape incomplete or badly wrinkled	visual
207. Length of tear tab, min.	visual
208. Color of tape incorrect	visual

4.2.2.8 Box, Packing, Drawing C8798142.

Source: https://assist.dla.mil -- Downloaded: 202610-18T05:02Z
Check the source to verify that this is the currenversion before use.

4.2.2.8 (Cont'd)

Defect	Method of Inspection
Critical: None defined	
Major: None defined:	
Minor	
201. Contents loose	manual
202. Hardware missing, loose, broken or improperly engaged	Manual and visual
203. Strapping missing, loose, broken or improperly assembled improperly assembled	Manual and visual
204. Contents of box exposed	visual
205. Box damaged	visual
206. Marking missing, incorrect or illegible	visual
207. Number of units incorrect	visual
208. Car seal missing, unsealed or improperly positioned	visual

4.2.3 Inspection testing.- The following tests shall be performed in accordance with 4.3.

4.2.3.1 Breakaway torque.- Each initiator shall be subjected to a breakaway torque application. Failure of any initiator to comply with the requirements of 3.2 shall be cause for rejection of the assembly.

4.2.3.2 Residual magnetism.- Each assembly shall be subjected to the test for excessive residual magnetism. Failure of any assembly to comply with the requirements of 3.3 shall be cause for rejection of the assembly.

4.2.3.3 Functional.- The following test shall be performed by the Government.

4.2.3.3.1 Ballistics.- Twenty one units shall be tested to determine compliance with requirements of 3.4.1, 3.4.2 and 3.4.3. The units shall be temperature conditioned as provided in Table III and 4.3.3.1.1. The variables sampling plan of MIL-STD-414, example C-2 or C-3, as applicable for the AQL listed in table shall be used for each sample of 7 units. Failure of any unit to comply with the requirements of 3.4.1, 3.4.2 and 3.4.3, or failure of a sample to meet the criteria of the variables sampling plan shall be cause for rejection of the lot.

TABLE III

Temperature	Sample Size	AQL
-65° to -70°F	7	0.65%
65° to 75°F	7	0.65%
200° to 205°	7	0.65%

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:02Z
Check the source to verify that this is the current version before use.

4.2.4 Inspection equipment.- The examination and tests shall be made using equipment listed on IEL11726503.

4.3 Test Methods and Procedures.

4.3.1 Breakaway torque.- A torque wrench set at the torque requirement specified in 3.2 shall be used in conjunction with the fixture to determine the adequacy of the joint. The torque shall be applied to the cap.

4.3.2 Residual magnetism.- The initiator shall be tested for excessive residual magnetism in an area free of local magnetic effects by placing the initiator six inches from and at the same height as the compass in a north-south horizontal position (cap end at south) with the compass set in an east-west heading. The initiator shall be moved slowly past the compass in a longitudinal direction for its entire length, rotated 90 degrees in the horizontal position about its longitudinal axis and moved slowly back past the compass. This procedure shall be repeated for each 90 degree rotation of the initiator.

4.3.3 Functional.

4.3.3.1 Ballistic.- The test sample shall be rigidly supported in the fixture. The sample shall be tested within 5 minutes after removal from the conditioning chamber. When this time limit is exceeded the sample unit shall be reconditioned in accordance with 4.3.3.1.1.

4.3.3.1.1 Temperature conditioning.- A standard M114 initiator, loaded with a dummy M231 cartridge, containing a temperature sensitive element, shall be placed in the conditioning chamber at the same time as the samples. The conditioning time shall be a minimum of 1 hour longer than the time necessary to bring the element contained in the dummy cartridge to the required temperature.

5. PREPARATION FOR DELIVERY

5.1 Packing and marking.- Packing and marking shall be in accordance with Drawings C8798142 and C8798143.

6. NOTES

6.1 Ordering data.- Procurement documents should specify the title number and date of this specification.

6.2 A mechanical failure is defined as any deformation or breakage of a part, the occurrence of which is other than a design function.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:02Z
Check the source to verify that this is the current version before use.

6.3 Ignition delay is defined as the time that lapses between the firing of the pressure element and the beginning of the continuous pressure rise on the pressure time record.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1377-A333

☆ U. S. GOVERNMENT PRINTING OFFICE: 1970-393-096/S-5157

Source: https://assist.dla.mil -- Downloaded: 202610-18T05:02Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE | CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)* | DATE

DD FORM 1 JAN 66 1426 REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202610-18T05:02Z
Check the source to verify that this is the current version before use.

FOLD

Department of the Army

Frankford Arsenal
Philadelphia, Pa. 19137

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
Department of the Army

Commanding Officer
Frankford Arsenal
ATTN: SMUFA-N1100
Philadelphia, Pa. 19137

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:02Z
Check the source to verify that this is the current version before use.