MILITARY SPECIFICATION

POWER SUPPLY: 10559345

(PFN CHARGE)

This amendment forms a part of Military Specification MIL-P-14881(MU), dated 2 March 1970.

Page 4, paragraph 3.3.1.2.5: Delete "1500 ± 30" and substitute "1330 ± 30."

Page 4, paragraph 3.3.1.2.6: Delete and substitute as follows:

"3.3.1.2.6 PFN voltage programming.- With the PFN voltage set to +1200 ± 15 Vdc by using a 100 kilohm load between P1-6 and P1-9 at room ambient (+60°F to +90°F), a change from the 100 kilohms load to 32.4 kilohms load shall change the PFN voltage to +1345 ± 40 Vdc at room ambient and to +1345 ± 95 Vdc when subjected to the high (+125°F) operating temperature extremes of 3.3.2.2. Similarly, a change from the 100 kilohms load to 3.32 megohms load shall cause a change in voltage from a setting of +1200 ± 15 Vdc to +1030 ± 30 Vdc at room ambient and to +1030 ± 71 Vdc when subjected to the low (-40°F) operating temperature extremes of 3.3.2.2."

Page 6, Figure 1: Delete "40 ± 20" and substitute "100 ± 40"; in note: Delete "40 ± 32" and substitute "100 ± 60".

Page 6, paragraph 3.3.2.2: Delete "3.3.1" and substitute "3.3.1 (except 3.3.1.2.5)".

Page 10, Table V, Test Procedure column: Delete and substitute the following: "4.6.7.1, 4.6.7.1, 4.6.7.2".

Page 15, paragraph 4.6.7, lines 4 and 5: Delete "and the tolerance requirements for vibration frequency measuring instruments shall not apply".

Page 15, paragraph 4.6.7.1, "NOTE": Delete "less than 7°F" and substitute "no greater than 3°F"; paragraphs 4.6.7.1(b) and (f): Delete "5 hours" and substitute "1 hour".

Page 16: Delete "4.6.4.2" and substitute "4.6.7.2".

Page 16, paragraph 4.6.7.2(a): Delete and substitute as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:01Z
Check the source to verify that this is the current version before use.

"(a) Test in accordance with Method 514.1, Procedure I of MIL-STD-810 for category (f) equipment, except that resonance search and dwell on resonance shall not be required and the acceleration shall not exceed ± 4g and the maximum excursion (double amplitude) shall be 0.5 inch."

Custodian:

Army - MU

Prepaing Activity:

Army - MU

Project No. 1240-A543

*U.S. GOVERNMENT PRINTING OFFICE: 1976--603-766/5784

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:01Z
Check the source to verify that this is the current version before use.