INCH POUND
MIL-E-11450C
23 November 1991
SUPERSEDING
MIL-E-11450B(DLA-DM)
4 June 1980
MIL-E-11450A
28 October 1960

MILITARY SPECIFICATION

EVACUATION BAG, CASUALTY, INSULATED

(With Liner and Carrying Bag)

This specification is approved for use by all Departments and Agencies of the Department of Defense

1 SCOPE

1 1 Scope This specification covers requirements for a casualty evacuation bag with a removable liner, and a waterproof carrying bag The carrying bag is used for transporting and protection of the rolled evacuation bag and liner

2 APPLICABLE DOCUMENTS

2 1 Government documents.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to Headquarters, Defense Personnel Support Center, ATTN Directorate of Medical Materiel, DPSC-MST, 2800 South 20th Street, Philadelphia, PA 19101, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 6530
DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:03Z
Check the source to verify that this is the current version before use.

2.1.1 Specifications, standards and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2)

SPECIFICATIONS

Federal

V-F-106	-	Fastener, Slide, Interlocking
V-T-295	-	Thread, Nylon
DDD-L-20	-	Label· For Clothing, Equipage, and Tentage, (General Use)
DDD-T-86	-	Tape, Textile, Cotton, General Purpose (Unbleached, Bleached, or Dyed)
PPP-B-566	-	Boxes, Folding, Paperboard
PPP-B-601	-	Boxes, Wood, Cleated-Plywood
PPP-B-621	-	Boxes, Wood, Nailed and Lock-Corner
PPP-B-636	-	Boxes, Shipping, Fiberboard
PPP-B-676	-	Boxes, Setup

Military

MIL-P-116	-	Preservation, Methods Of
MIL-C-332	-	Cloth, Balloon, Cotton
MIL-B-371	-	Braid, Textile, Tubular
MIL-W-530	-	Webbing, Textile, Cotton, General Purpose, Natural or in Colors
MIL-B-543	-	Buckles, Tongueless and Web Strap
MIL-T-3530	-	Thread and Twine, Mildew Resistant or Water Repellent Treated
MIL-C-5040	-	Cord, Fibrous, Nylon
MIL-C-7219	-	Cloth, Duck, Nylon
MIL-L-10547	-	Liners, Case, and Sheet, Overwrap, Water-Vaporproof, or Waterproof, Flexible
MIL-F-10884	-	Fasteners, Snap
MIL-C-14366	-	Cloth, Coated, Nylon, Twill (One Side Coated)
MIL-G-16491	-	Grommets Metallic, General Specification For
MIL-E-20652	-	Eyelet, Metallic, and Eyelet Washers, Metallic, General Specification For
MIL-C-21852	-	Cloth, Taffeta, Nylon
MIL-B-41826	-	Batting, Synthetic Fibers· Polyester, (Unquilted and Quilted)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:03Z
Check the source to verify that this is the current version before use.

MIL-F-43097	-	Feathers and Down, Waterfowl; Tan-O-Quil-QM Treated
MIL-T-43548	-	Thread, Polyester Core, Cotton, Rayon, or Polyester Covered
MIL-T-43566	-	Tape, Textile, Cotton or Polyester, General Purpose, Natural or in Colors
MIL-C-43824	-	Cloth, Synthetic Fur, Knitted
MIL-C-43876	-	Cloth, Wind Resistant Oxford, Nylon and Cotton, Quarpel Treated
MIL-C-43906	-	Cloth, Coated, Nylon, Polyurethane Double Coated

STANDARDS

Federal

FED-STD-191	-	Textile, Test Methods
FED-STD-751	-	Stitches, Seams, and Stitchings

Military

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-147	-	Palletized Unit Loads
MIL-STD-794	-	Parts and Equipment, Procedures for Packaging of

(Unless otherwise indicated copies of federal and military specifications, standards, and handbooks are available from the Navy Publishing and Printing Service Office, Building 4D NPM-NPODS, 700 Robbins Avenue, Philadelphia, PA 19111-5094)

2 1 2 Other Government documents, drawings, and publications The following other Government documents, drawings, and publications form a part of this document to the extent specified herein Unless otherwise specified, the issues are those cited in the solicitation

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:03Z
Check the source to verify that this is the current version before use.

DRAWING

Defense Personnel Support Center (DPSC)

Drawing # 24235 - Evacuation Bag, Casualty, Insulated

(Copies of the drawing may be obtained from: The Defense Personnel Support Center, 2800 South 20th Street, Philadelphia, PA 19101, ATTN: DPSC-MST)

2.2 Non-Government publications The following documents form a part of this document to the extent specified herein Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation

The Color Association of the United States, Inc

Standard Shades For Sewing Threads

(Application for copies of the standard should be addressed to The Color Association of the United States, Inc , 200 Madison Avenue, New York, NY 10016)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents These documents also may be available in or through libraries or other informational services)

2.3 Order of precedence In the event of a conflict between the text of this document and the references cited herein (except for related associated detail specifications, specification sheets, MS standards), the text of this document takes precedence Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained

3 REQUIREMENTS

3.1 Materials and components

3 1.1 Cloth, oxford, nylon and cotton The outer casing and insulating pad binding strips shall be nylon and cotton oxford cloth, olive green 107, quarpel treated,

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:03Z
Check the source to verify that this is the current version before use.

conforming to MIL-C-43876 except that colorfastness to laundering shall be fair. The length and width of the strips shall be as shown on DPSC Drawing #24235.

3 1 2 Cloth, balloon, cotton The inner casing shall be cloth, balloon, cotton, olive green 107, durable water repellent treated, preshrunk, conforming to type I, class 2 of MIL-C-332 except the shrinkage requirement may be up to 3.5 percent in the warp and 2 5 percent in the filling. The cloth shall show a rating not less than 'Satisfactory' for down and feather retention

3 1 3 Cloth, non-woven The material for the diaphragms shall be cloth, non-woven, spun-bonded nylon, 1 5 to 1.8 ounces per square yard conforming to Monsanto Company Style Number 4815-21, or equal

3 1.4 Cloth, nylon, duck The drag pad on the bottom of the bag shall be cloth, nylon, duck, 7 25 ounces per square yard, conforming to type III, class 3 of MIL-C-7219, and dyed olive green 106 to match the standard sample (see 6 7)

3 1.5 Cloth, taffeta, nylon The top of the liner shall be cloth, taffeta, nylon, 2 0 ounces per square yard, olive green 106, conforming to type III of MIL-C-21852 As an alternate, the top of the liner shall be cloth, balloon, cotton conforming to the requirements of 3.1.2.

3 1 6 Cloth, coated, nylon twill The bottom of the liner shall be nylon cloth coated with polyvinyl butyral, 3 5 ounces per square yard, conforming to type I of MIL-C-14366, except that the color of the face side shall approximate olive green 106 Marine green shall also be acceptable

3.1 7 Webbing, textile, cotton, type IIa, 1-1/4 inch and 1-1/2 inch The webbing shall be olive drab 7, type 11a, class 8, conforming to MIL-W-530

3.1 8 Tape, textile, cotton, 3/4 inch and 2-1/2 inch The tape shall be olive drab 7, type I, class 8, conforming to MIL-T-43566

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:03Z
Check the source to verify that this is the current version before use.

3 1 9 Tape, textile, cotton, 1 inch. The liner loops on inside of bag, tie-tapes and snap fastener reinforcement on the liner, shall be olive drab 7, conforming to type I, class 3 of DDD-T-86

3 1 10 Fur strips The synthetic fur strip used in the fabrication of the fur ruff shall conform to class 1 of MIL-C-43824 The strip shall be 2-1/2 (plus or minus 1/4) inches wide and length as required As an alternate the fur ruff may be constructed of the 15 6 oz acrylic and modacrylic blend specified as an alternate to 3.1.17 (see 6 10)

3 1 11 Feathers and down The insulating filling material shall be a mixture of waterfowl feathers and down, or pure down as indicated on DPSC Drawing #24235 The mixture shall conform to type III, class 1 and the down to type II, class 1 of MIL-F-43097

3 1 12 Batting, polyester The batting for the inner panels shall conform to type VI of MIL-B-41826 The inner panels consisting of the polyester batting and cotton balloon cloth shall be of quilted construction as shown on DPSC Drawing #24235 Spacing of rows of stitching shall be as shown on DPSC #24235

3 1 13 Thread, polyester, cotton-covered The thread for seaming and stitching shall conform to MIL-T-43548 The size and ply shall be as follows:

For all stitching except that used in the liner, forming longitudinal channels, and where optional stitch type 401 is used -- Ticket No 30, 3 ply for needle and bobbin

For stitching longitudinal channels except with optional stitch type 401 -- Ticket No 50, 3 ply for needle bobbin

For stitching longitudinal channels except with optional stitch type 401 -- Ticket No 50, 3 ply for needle, Ticket No 70, 2 ply for looper

For optional stitch type 401 in other than longitudinal channels -- Ticket No 30, 3 ply for needle; Ticket No. 50, 3 ply for looper

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:03Z
Check the source to verify that this is the current version before use.

3.1 13 1 Color and treatment The thread shall be dyed olive drab S-1, C A. 66022 The thread shall be water repellent treated in accordance with type II, class 3 of MIL-T-3530 The dyed thread shall show fastness to laundering equal to or better than the standard sample

3 1 14 Thread, nylon The thread for stitching the removable liner shall be dyed olive drab S-1, C.A 66022 and shall conform to type I, class B, size E of V-T-295

3 1.15 Cord, nylon. The drawcord of the carrying bag shall conform to type III, table II of MIL-C-5040

3 1 15.1 Color The color shall be olive green 106 Both ends of the drawcord shall be seared

3 1.16 Grommets The grommets used in the carrying bag shall be type III, class 3, size 0, conforming to MIL-G-16491

3.1 17 Modacrylic pile fabric The modacrylic pile fabric used for making the insulating pads shall be circular knitted with a backing yarn in each feed. The backing fabric shall have not less than 18 courses and 12 wales per inch The modacrylic pile portion of the fabric shall be evenly sheared, and shall consist of a blend of approximately equal parts of 12 and 24 denier modacrylic staple The staple length shall be such as to produce a finished fabric 1-1/4 plus or minus 1/8 inches thick when tested using a thickness gage with a foot having a minimum area of 16 square inches and exerting a load of 0 005 psi The finished pile fabric shall weigh not less than 32 nor more than 35 ounces per square yard As an alternate, two plies of 15.6 oz/sq yard minimum material may be used in lieu of one ply of the 32/35 oz However, the 2 plies shall be sewn together The pile height shall be one inch and the face shall be a blend of acrylic and modacrylic and the back polypropylene (Furtex 3598 or 3915 for one piece)

3 1 18 Fastener, slide, interlocking. The slide fastener shall be type III, style 1, size MHS of V-F-106 except that the chain shall be nylon or polyester continuous monofilament in a coil or ladder configuration, or shall be an extruded nylon chain of separate elements connected with strands of polyester yarns, conforming to the requirements stated 3.1.18.1.1 or 3.1.18.1,2, as applicable. All performance requirements governing the chain are not applicable except the crosswise breaking strength requirement which shall be 175 pounds (778 N) minimum The

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:03Z
Check the source to verify that this is the current version before use.

crosswise breaking strength shall be performed as specified in V-F-106 except the fastener shall be preconditioned

3 1.18 1 Fastener chains

3 1 18.1 1 Continuous filament chain The diameter of the chain filament shall be 033 to 0.050 inch The width of the chain when closed shall be 0 320 to 0.340 inch The chain shall be securely sewn to the tapes.

3 1.18 1 2 Extruded chain The extruded chain shall consist of a series of nylon elements connected by polyester yarns The chain when closed shall meet the size requirements specified in V-F-106 The chain shall be securely sewn to the tapes

3 1 18 1 3 Color The color of the chains shall be black or olive

3 1 18 2 Arrangement of stops, chain and sliders The stops shall be plastic (nylon), brass, aluminum, or other non-corroding metal, color black or olive drab The arrangement and location of stops, chain and sliders shall be as shown on DPSC Drawing #24235 The ends of the fastener shall be equipped with open end stops The stops shall be located to allow as complete a closure as practicable without interference between the two end sliders The length of the slide fastener chain shall be such that after the slide fastener is sewed on, the tape shall not be puckered and the sliders shall operate freely

3 1 18.3 Fastener slider and stirrup pulls The slide fastener shall be equipped with six sliders to provide an opening at any point along the chain The two head section sliders shall be non-locking and of the reversible type, equipped with single wire stirrup pulls and thongs on each side The remaining four sliders shall be non-locking and of the non-reversible type, equipped with single wire stirrup pulls and thongs operable from the outside of the bag The color of the sliders and stirrup pulls shall be black or olive drab The stirrup pulls shall be fabricated from brass or corrosion resistant steel wire, 0 058 inches minimum diameter

3.1.18.4 Slide fastener tape The slide fastener tape shall be 1 plus or minus 1/16 inch wide, dyed to match olive drab S, C.A 66519, and water repellent treated. The tape shall show fastness to laundering equal to or better than the standard sample (see 6 7) When no standard sample is

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:03Z
Check the source to verify that this is the current version before use.

available, the tape shall show good fastness to laundering

3.1.18 5 Braid thong Each stirrup pull shall be equipped with a flat tubular braid thong, looped through the opening of the slider pull and knotted at one end The thong shall finish 3-1/2 (plus 1, minus 1/2) inches long The braid for the thong shall be cotton, tubular, flat, 11/32 inch, water repellent, shade olive drab or black, conforming to type VII, class 2 of MIL-B-371.

3 1.19 Fastener, snap, brass, black chemical finish, male and female. The snap fasteners shall be style 2, finish 2, construction A, conforming to MIL-F-10884

3.1 20 Buckles, tongueless, 2-bar The buckles shall be 3/4 inch, type II, class 1, style 2, conforming to MIL-B-543, and shall have a black chemical finish

3 1 21 Eyelets The eyelets shall be No 4132 conforming to MIL-E-20652/1

3 1 22 Wire The wire stiffener for the synthetic fur ruff shall be bright copper, 0 080 plus or minus 003 inch diameter, dead soft, so that when bent 360° over a mandrel of the same diameter and the wire straightened, and the bending and straightening process repeated at the same place on the wire, the wire shall not crack or break

3.1.23 Bag, carrying The carrying bag shall conform to DPSC Drawing #24235 The coated fabric shall be cloth, coated, nylon, polyurethane, double coated, olive green 207 in accordance with type I of "MIL-C-43906".

3 1 24 Marking

3 1.24 1 Identification marking The identification labels on the evacuation bag and the liner shall conform to type I, class 5, and shall be located as shown on DPSC Drawing #24235 The identification label and the laundry instruction label for the evacuation bag may be combined The combination label shall be sewn to the cloth balloon, cotton inner casing back (lining) of the bag

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:03Z
Check the source to verify that this is the current version before use.

3.1.24.2 Laundry instructions. The laundry instruction labels shall conform to type I, class 3 The size of the print shall not be less than 3/32 to 1/8 in height All words shown in capital letters shall be 3/16 inch minimum The laundry instructions shall be as follows:

DOWN AND POLYESTER FILLED

LAUNDER IN ACCORDANCE WITH FORMULA G OF D/A FM 10-17 DO NOT DRY CLEAN

3 1 24 3 Label for carrying bag A label approximately 4" x 4", conforming to type II, class 9, of DDD-L-20 shall be stitched to the outside of the bag, along the lower edge of the drawcord channel in the location shown on DPSC Drawing #24235 The printing of the first three lines shall be in characters not less than 3/16 inch high and shall be as follows

CARRYING BAG FOR EVACUATION BAG,
INSULATED, WITH LINER
Stock number
Contract number and date

In addition, the following shall be printed in characters not less than 3/32 inch high:

THE BAG AND LINER CONTAINED HEREIN ARE TO BE USED ONLY FOR EVACUATION OR PROTECTION OF CASUALTIES
DO NOT USE AS A SLEEPING BAG

3 1.24 4 Other marking The letters "U.S." and the words "FOR CASUALTIES ONLY" on the evacuation bag and liner, shall conform to type IV, class 9 in the size characters and locations shown on DPSC Drawing #24235

3 1.24 5 Content label If required by state law, a label shall be placed at foot end of bag on inside conforming to the state requirements for the down content used in filling the bag outer panels.

3 1.24 6 Fastness All printing and marking shall show fastness to laundering as specified for class 6 labels

3 2 Design The design shall be as shown on DPSC Drawing #24235. The casualty evacuation bag shall be of quilted construction with the outer casing and weatherstrip filled with down and the inner casing filled with polyester batting The front shall have an oval opening equipped with

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:03Z
Check the source to verify that this is the current version before use.

six slide fasteners and an open face with fur ruff. The casualty evacuation bag shall be equipped with a removable liner and a waterproof carrying bag.

3 3 Patterns The patterns shall be made by the contractor in accordance with dimensions shown on DPSC Drawing #24235. The patterns shall be laid out and cut within plus or minus 1/8 inch of each dimension.

3 4 Construction. The construction shall conform to DPSC Drawing #24235 and as specified herein.

3.4 1 Stitches, seams and stitching. Stitches, seams and stitching as specified below shall conform to FED-STD-751 When stitch type 401 is used, the looper thread shall lie between the inner and outer panels of the casing so that the looper thread is not exposed on either the outside or inside panels of the bag. In all sewing operations, the smallest practical needle size shall be used in order to prevent damage to the fabric. Channels shall not be trapped at any seam point so as to prevent a free flow of down throughout all channels on the outer panels

For all stitching, except as specified below - type 301, 8 to 10 stitches per inch.

Optional method in lieu of 301 shall be type 401, 8 to 10 stitches per inch

Sewing and piecing of webbing, seaming insulation pads to bottom of bag, stitching fur ruff, seaming liner and carrying bag - type 301, 8 to 10 stitches per inch As an alternate the seaming of the carrying bag shall be type 401

Thread breaks in stitching shall be backstitched not less than 1 inch at each break

3 4.1.1 Type 301 stitching Ends of all stitching shall be backstitched 1/2 inch minimum, except where ends are turned under in a hem or held down by other stitching Thread tension shall be maintained so that there will be no loose stitching resulting in loose bobbin or top thread, or excessively tight stitching resulting in puckering of the materials sewn. The lock shall be embedded in the materials sewn.

3 4.1.2 Type 401 stitching. Thread breaks in stitching shall be overstitched not less than 1 inch at each break. Thread tension shall be maintained so that there

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:03Z
Check the source to verify that this is the current version before use.

shall be no loose stitching. The looper thread shall be on the unexposed surface of fabric in the finished bag

3 4 1.3 Bartacks. Unless otherwise specified, all bartacks shall be 1/2 plus or minus 1/16 inch long and 1/8 plus or minus 1/32 inch wide, and shall contain 28 stitches Bartacking shall be free from thread breaks and loose stitching

3 4 1 4 Thread ends All threads ends shall be trimmed to a length of not more than 1/4 inch.

3 4 2 Seam types Seams shall be formed as shown on DPSC Drawing #24235, with seam allowance and seams sewn so that no raw edges, runoffs, twists, pleats, puckers, or open seams shall result As an alternate construction (sections H-H and J-J of DPSC Drawing #24235, sheet 1), the component casings or panels shall first be over-edged with seam type SSA-1, produced with stitch class 500, or seam type SSA-2, produced with a combination of stitch type 301 or 401 and any stitch type of class 500 The casings or panels shall then be turned and all components stitched with seam type SSA-1, stitch type 301 or 401 as specified

3 4 3 Piecing In order to use short pieces, the webbing guards, binding strips, weather strips and materials which are unexposed (except nonwoven diaphragm) in the finished bag shall be pieced once only in either length or width Piecing of the 2-1/2 inch tape or 1 inch webbing shall be overlapped not less than 3/4 inch and boxstitched so that it will not interfere with the operation of the slide fastener Piecing of the 1-1/2 inch webbing or 3/4 inch tape shall not be permitted In the cutting of the cutting of the nonwoven diaphragm cloth, no spliced, open end or lapped material shall be allowed

3 4.4 Filling bag and weatherstrip The weight of each unfilled bag (including insulating pads, drag pad and fur ruff) shall be recorded in ink on an attached commercial type tag The sides and bottom section, weather strip, and top section shall be filled with the materials and in the quantities shown on DPSC Drawing #24235 During the filling operation, each bag shall be weighed three times after filling as follows:

- Sides and bottom section
- Weatherstrip
- Top section

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:03Z
Check the source to verify that this is the current version before use.

The weight of the filling material added by each operation shall be recorded on the tag. The contractor shall not remove the weight tag

3.4.5 Repairs Repairing the casualty evacuation bag by mending, patching or darning shall not be allowed

3 4.6 Beating and cleaning The completed bag shall be beaten out so that the filling material is evenly distributed throughout all channels The finished bag shall be cleaned of all feathers and down

3 4.7 Assembling A completed and closed liner, and a completed carrying bag, shall be neatly folded and placed inside each finished evacuation bag The slide fastener shall then be completely closed

3 4 8 Workmanship THe finished evacuation bag shall conform to the quality and grade of product established by this specification Occurrence of defects shall not exceed the applicable acceptable quality levels

4 QUALITY ASSURANCE PROVISIONS

4 1 Responsibility for inspection Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements

4 1 1 Responsibility for compliance All items shall meet all requirements of sections 3 and 5 The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:03Z
Check the source to verify that this is the current version before use.

indicated or actual, nor does it commit the Government to accept defective material

4 1 2 Records Records of examinations and tests performed by, or for, the contractor shall be maintained by the contractor and made available to the Government, upon the Government's request, at any time, or from time to time, during the performance of the contract, and for a period of three years after delivery of the supplies to which such records relate

4 1 3 Inspection Inspection, as used in this specification, is defined as both examination (such as visual and auditory investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties) of the item

4 1 4 Certificates of quality Certificates of quality supplied by the manufacturer of the component or material may be furnished in lieu of actual performance of such testing by the contractor, provided lot identity has been maintained and can be demonstrated to the Government The certificate shall include the name of the contractor, the contract number, the name of the manufacturer or supplier, the National Stock Number (NSN), the item identification, the name of the component/material, the lot number, the lot size, the sample size, the date of testing, the test method, individual test results, and the specification requirements

4 2 Sampling.

4 2 1 For examination Sampling for examination shall be conducted in accordance with MIL-STD-105, and table I The unit of product for examination purposes shall be one complete evacuation bag with liner and carrying bag

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:03Z
Check the source to verify that this is the current version before use.

TABLE I. Sampling for examination

Examination (Paragraph)	Inspection level	AQL's	
Examination for component and lot (4.3.1.1).	S-1	6.5	
Examination for weight of unfilled casing and dimensions of cut parts (4 3 3 1)	S-4	1.0 10 0	Major Total Major and Minor defects combined
Examination for weight of filling material (4 3.3 2 1)	S-4	2 5 4 0	Major Total Major and Minor
Examination for visual characteristics of evacuation bag, liner, and carrying bag (4.3 4 1)	II	2 5 65 0	Major Total Major and Minor defects combined
Examination for dimensions of liner (4.3 4.2)	S-4	4 0 10 0	Major Major and Minor defects combined
Examination of carrying bag (4 3 4 3)	II	4 0 10 0	Major Major and Minor defects combined

4.2.2 For tests Sampling for tests shall be conducted in accordance with MIL-STD-105 for an acceptance number of zero The inspection level for testing the evacuation bag shall be 100 percent The inspection level for component material testing shall be S-1 with not less than three samples tested regardless of lot size.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:03Z
Check the source to verify that this is the current version before use.

4 3 Examination The evacuation bag shall be examined for defects including, but not limited to, those listed in tables II through VII

4 3.1 Classification of defects. Examination shall be conducted in accordance with the classification of defects listed in tables II through VII below Examination shall not be restricted to the classified possible defects

Table II - Examination for component and lot

Component and lot expressed in terms of	Characteristic (Requirement Paragraph)	Test Method
*Modacrylic pile fabric, square yards	Courses per inch (3 1 17)	Visual
	Wales per inch (3 1 17)	Visual
	Denier of staple (3 1 17)	Standard commercial
	Weight per square yard (3 1 17	Standard commercial
	Fabric thickness	(See 3 1 17)
	Modacrylic content (3.2 17)	(See 4 4 1)
Slide fastener tape; feet-	Fastness to laundering (3 2 18)	**FED-STD-191, method 5610
*Wire feet	Material identification (3 1 22)	Standard commercial
	Diameter (3 1 22)	Standard commercial
Slide fastener	Crosswise breaking strength (3.2.18)	V-F-106 (except that the fastener shall be precondi-tioned)

*Will be accepted on the basis of contractor's certification of compliance with requirements specified. The Government reserves the right to check test components to determine validity of contractor's certification

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:03Z
Check the source to verify that this is the current version before use.

**The test specimen shall be the full width of tape 4 inches in length

The above requirement for modacrylic pile fabric, expressed in square yards, shall be applicable to the lot average with one determination per sample unit of one piece 24 by 24 inches The results shall be reported as pass or fail

The above requirement for the slide fastener tape, expressed in feet, shall be applicable to the individual unit with one determination per sample unit of one foot The results shall be reported as pass or fail

The above requirements for wire, expressed in feet, shall be applicable to the lot average The results shall be reported as pass or fail to the nearest 0 001 inch

4.3 1 1 Certification The contractor shall furnish a certificate of compliance for the nonwoven cloth (3.1.3)

4.3 2 Process inspection Inspection of sub-assemblies shall be made at any point or during any phase of the manufacturing processes to determine whether construction details which cannot be examined in the finished product are in accordance with requirements indicated in the specification and drawings Care shall be taken to see that cut parts conform to contours and dimensions indicated on drawings, and that the modacrylic pads are assembled to bottom portion of bag as specified in section B-B, of DPSC Drawing #24235 The Government reserves the right to exclude from consideration any material or service for which in-process inspection has indicated nonconformance

4.3 3 Intermediate inspection. Inspection of the unfilled bags shall be made to verify the weight of individual casings (without liners) recorded by the contractor on the tag attached to each bag This inspection shall be performed prior to filling bags and weatherstrips with down, and feather and down mixture (see 3 4 4) The sample unit for this examination shall be one unfilled bag and shall be in accordance with table III

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:03Z
Check the source to verify that this is the current version before use.

TABLE III - Examination for weight of unfilled casing and dimensions of cut

Examine	Defect (Major or Minor)
Weight of unfilled casing	More or less than weight indicated on bag: --by two ounces or less (minor) --by more than two ounces (major) Note: Utmost care shall be taken to see that scales used to perform examination are properly calibrated and register accurate weight
Dimensions of cut parts (bottom, side and top sections, and pad) Modacrylic	Any deviation exceeding the minus tolerance specified on drawings, but not exceeding twice the minus tolerance (minor) Any deviation exceeding twice the minus tolerance specified on drawings (minor) Any deviation exceeding three times the minus tolerance specified on drawings (major) Any deviation exceeding the plus tolerance specified on drawings (minor)

4 3 3 1 Filling inspection Inspection of partially filled and filled casings (see 3 4 4) shall be made to verify the weight of the filling material blown in Inspection shall be made of the sample unit after each of the filling operations The sample unit for these examinations shall be one casing selected immediately after each filling and shall be in accordance with table IV

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:03Z
Check the source to verify that this is the current version before use.

TABLE IV - Examination for weight of filling material

Examine	Defect (Major or Minor)
Weight of filling, in sides and bottom section	One ounce or less under the minimum specified (minor). More than one ounce under minimum specified (major)
Weight of filling, in top section	1/2 ounce or less under the minimum specified (minor) More than 1/2 ounce under minimum specified (major)
Weight of filling, in weatherstrip	Less than minimum specified on drawings (major) Note 1· The weight of filling material shall be as specified on drawings Note 2· To determine the weight of filling material added by each operation (see 3 4 4) subtract the total weight before from the total weight after each operation Note 3· Inspection for weight of filling material shall be performed immediately following each operation No sample shall be selected for inspection for weight if more than one hour has elapsed between the filling and the inspection

4.3.4 Examination of the end item The classification of defects found during examination shall be in accordance with table V, table VI, and table VII The sample unit for these examinations shall be one completely fabricated and filled bag with liner

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:03Z
Check the source to verify that this is the current version before use.

TABLE V - Examination for visual characteristics of evacuation bag and liner

Examine	Defect (Major or Minor)
Fabric	Any hole, cut or tear (major). Any abrasion mark, large slub, broken or missing yarn, mend, or needle chew (major) Fine or coarse filling bar (minor)
Webbing	Cut or frayed edges; not firmly or tightly woven (major) Any piecing of 1-1/2 inch webbing or 3/4 inch tape (minor)
Seams and stitching. Open seams On channel stitching	Stitch type 301. --more than 1/2 inch (minor) Stitch type 401. --any open seam (major)
On seams that would allow escape of down, or feathers and down mixture from the bag	Any open seam (major)
On all other seams	1/2 inch or less (minor) More than 1/2 inch (major) Note. A seam shall be classified as open when one or more stitches joining a seam are broken or when two or more continuous skipped stitches or run-offs occur On double stitched seams, a seam shall be considered open when either one or both sides of the seam are open
Raw edges (when securely caught in stitching)	1/2 inch or less (minor) Note. Raw edges not securely caught in stitching shall be classified as open seams.
Run-offs (see open seams) Seam and stitch type	Wrong seam or stitch type (major)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:03Z
Check the source to verify that this is the current version before use.

TABLE V - Examination for visual characteristics of evacuation bag and liner - Continued

Examine	Defect (Major or Minor)
Stitch tension	Loose tension, resulting in a loose seam (minor) Loose tension on channel stitching resulting in loosely exposed top or bobbin thread (minor) Tight tension (stitches break when normal strain is applied to seam or stitching) (minor) Note: Puckering is evidence of tight tension When puckering is evident, test seam by exerting normal pull on puckered areas
Stitches per inch	One or two less than minimum specified (minor) Three or more stitches less than minimum specified (major) One or more stitches in excess of maximum specified (minor) Note: Variation in the number of stitches per inch is to be scored only when variation on a major portion of the seam exists
Stitching margin; stitching gage	Not as specified (minor)
Stitching ends	Backstitched less than 1/2 inch (except where turned under in a hem or held down by other stitching) (minor)
Threads breaks	On stitch type 301: --Backstitched less than 1 inch (minor) On stitch type 401: --Overstitched less than 1 inch (minor). Note: Thread breaks not backstitched or not over-stitched shall be classified as open seams.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:03Z
Check the source to verify that this is the current version before use.

TABLE V - Examination for visual characteristics of evacuation bag and liner - Continued

Examine	Defect (Major or Minor)
Components and assembly	Seams badly puckered, twisted or pleated (minor) Needle chews (major) Note: Needle chews (caused by run-offs or repairs) which do not weaken the fabric shall not be considered defects Any component or required operation omitted (unless otherwise classified herein) (major)
Piecing: Casing and weatherstrip	Any component of casing or weatherstrip not pieced as specified or pieced more than once (minor)
Channels (see drawings for spacing of channels)	Number of channels less than specified (major) Any channel trapped, causing part of channel to remain unfilled (major) Channels vary from specified width by more than 1/2 inch (minor)
Filling	Any unfilled channel or weatherstrip (major) Any partially filled channel or weatherstrip (minor) Unevenly filled channels or weatherstrip (minor)
Content label and marking	Any required marking or content label omitted, illegible or incorrect (minor) Misplaced (minor)
Letters U.S.	Omitted, illegible, misplaced or not specified type or size (minor).
Cleanness	Spots or stains. Thread ends or clinging feathers and down not removed throughout the bag (minor)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:03Z
Check the source to verify that this is the current version before use.

TABLE V - Examination for visual characteristics of evacuation bag and liner - Continued

Examine	Defect (Major or Minor)
Details of construction Face opening	Wire stiffener not securely attached to wire retainer (minor)
Slide fastener	Slider jams or fails to interlock chain scoops (major) Any portion of fastener broken, bent, missing or not aligned, making fastener unusable (major)
Assembly (Slide fastener)	Thong omitted (minor) Finished length of thong less than 3-inches or more than 4-1/2 inches (minor) Slide fastener tape not assembled to bag as shown on drawings (major) Stitched too close to chain, preventing slider from sliding freely (major). Slide fastener tapes stitched to webbing strips too loose, causing a bulge which prevents slide fastener from closing easily (minor) Edge of casing not securely caught in both rows of stitching through fastener assembly for a distance of more than 3 inches (minor)
Bartacks	One or more omitted or loose (major) Not sewn through materials as shown on drawings (minor)
Weatherstrip	Not assembled to top section as shown on drawings (major) Tube portion of weatherstrip caught in slide fastener assembly stitchings or in bartacks (major).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:03Z
Check the source to verify that this is the current version before use.

TABLE V - Examination for visual characteristics of evacuation bag and liner - Continued

Examine	Defect (Major or Minor)
Loops	Not formed as shown on drawings (minor). One or more omitted; not securely caught in seam (minor) Any loop set more than 1 inch from dimensions specified on drawing (minor).
Hardware	Broken or malformed; finish omitted; corroded areas; burrs or sharp edges which may damage the item or cause injury in handling (major)
Liner Tie tapes	Not securely bartacked to liner (major) Side tapes not bartacked through reinforcement as shown on drawing (major) Mislocated by 1/2 inch or more, but not more than 1 inch (minor) Mislocated by more than 1 inch (minor) Assembled with coated side of fabric on outside (major)
Snap fasteners	Clinched excessively tight, cutting surrounding fabric (major) Loosely clinched, permitting cap or stud to rotate (minor) Male or female fastener misplaced, failing to effect a smooth and secure closure (major). Any malfunction of snap fasteners (major)
Carrying straps (A and B)	Any strap not one piece construction (minor). Handles not securely boxstitched as specified (major).
Drag pad	Misplaced (major).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:03Z
Check the source to verify that this is the current version before use.

TABLE VI - Examination for dimensions of liner

Examine	Defect (Major or Minor)
Dimensions	Overall length: --less than 7 feet, 9 inches (minor). --less than 7 feet, 8 inches (major) Width at any location less than twice the minus tolerance indicated on drawing (major)

4 3 4.1 Examination of carrying bag. Defects found during examination shall be classified in accordance with classification of defects contained in table V above In addition thereto, the carrying bag shall be examined for the characteristics in table VII .

TABLE VII - Examination of carrying bag

Examine	Defect (Major or Minor)
Handles	Either handle omitted (major). Not boxstitched as specified (minor) Misplaced: --by more than 1 inch (major) --1/2 inch or more, but not more than 1 inch (minor)
Reinforcements	Any reinforcement omitted (major)
Flap	Omitted (major)
Grommets	Size or type not as specified (major) Improperly set, clinched loosely, allowing grommet to rotate in hole (minor)
Drawcord	Any cuts or abrasions (major) Ends not seared (minor). Less than required length: --by one inch or more, but less than 2 inches (minor). --by 2 inches or more (major)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:03Z
Check the source to verify that this is the current version before use.

4.3.5 Dimensional examination. The tables shall be examined for defects in dimensions Any dimension not within the tolerances specified herein shall be classified as a defect

4 4. Tests. The methods of testing specified in specification FED-STD-191 shall be followed wherever applicable

4 4.1 Modacrylic content A specimen approximately 1 gram in weight shall be dried at 221° to 230°F to a constant weight Place the specimen in a Soxhlet or similar extractor and extract with acetone until the solution runs clear (a yellow coloration shall indicate the presence of modacrylic) Dry the specimen to constant weight as above and calculate the percentage of modacrylic as follows·

$$\frac{\text{Weight of original dry specimen -- weight of dry residue} \times 100}{\text{Weight of original dry specimen}}$$

Final result shall be the average of five specimens tested as above

4 5 Inspection of packaging The sampling and inspection of the preservation and interior package marking shall be in accordance with groups A and B quality conformance inspection requirements of MIL-P-116 The sampling and inspection of the packing and marking for shipment and storage shall be in accordance with the quality assurance provisions of the applicable container specification and the marking requirements of MIL-STD-129

5 PACKAGING

5 1 Preservation Preservation shall be level A or C, as specified (see 6 2)

5 1 1 Level A

5 1 1 1 Preservative applications Preservatives shall not be used

5.1.1.2 Evacuation bag with liner and carry bag. Each assembled bag shall be tightly rolled from the hood end and the roll secured with cotton tape. The roll shall be inserted in the carrying bag and the bag secured. The carrying bag shall be further packaged in a 3 mil plastic

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:03Z
Check the source to verify that this is the current version before use.

bag or in a corrugated fiberboard box conforming to PPP-B-636, class domestic Closure of the bag shall be secured by use of plastic coated metal twist ties or by other suitable means Closure shall be as specified in the applicable box specification.

5 1.1 3 Liner Each liner shall be neatly folded and wrapped in kraft paper or packaged in a 1.5 mil, heat sealed plastic bag or a box conforming to PPP-B-566 or PPP-B-676. Closure of the wrap or box shall be effected by use of gummed paper tape or other suitable tape

5.2 Packing Packing shall be level A, B or C, as specified (see 6 2).

5 2 1 Level A Two unit packages containing evacuation bags with liners and carrying bags or twelve unit packages containing liners shall be packed in an exterior container designed for a type 2 load and conforming to PPP-B-601, overseas type, PPP-B-621, class 2, or PPP-B-636, class weather-resistant Closure and strapping shall be as specified in the applicable box specification

5 2 1 1 Case liner Each level A wood box shall be lined with a waterproof case liner conforming to MIL-L-10547 Closure and sealing shall be as specified in the liner specification Case liner shall not be required for fiberboard boxes Each fiberboard box shall be waterproofed as specified in PPP-B-636

5.2.2 Level B Two unit packages containing evacuation bags with liners and carrying bags or twelve unit packages containing liners shall be packed in an exterior container designed for a type 2 load and conforming to PPP-B-601, domestic type, PPP-B-621, class 1, or PPP-B-636, class domestic Closure shall be as specified in the applicable box specification

5 2.3 Level C The level C packing for evacuation bags shall be packed in accordance with the requirements of MIL-STD-794 for level C

5.2 4 Packing variation permitted If the required number of units to be shipped is less than the number of units specified to be overpacked in an exterior container, such units shall be packed in an exterior container of suitable size and design, acceptable to a common carrier, which will insure safe delivery to destination.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:03Z
Check the source to verify that this is the current version before use.

5.2.5 Unitized loads Unitized loads, commensurate with the level of packing specified in the contract or order, shall be used whenever total quantities for shipment to one destination exceed 250 pounds or 20 cubic feet Loads shall be unitized on pallets conforming to MIL-STD-147 Quantities less than 20 cubic feet need not be unitized Pallet loads including the pallet shall not exceed 43 inches in length, 52 inches in width, and 54 inches in height Pallet shall conform to type IV or type V

5.2 5 1 Levels A and B Evacuation bags packed as specified in 5 2 1 and 5 2 2 shall be unitized on pallets as packed as specified in 5 2 5

5 2 5 2 Level C Evacuation bags packed as specified in 5 2 3 shall be unitized as specified in MIL-STD-794

5 3 Marking

5 3 1 Levels A, B and C Each unit pack, intermediate package, exterior container and unitized load shall be marked as specified in MIL-STD-129

5 4 General

5 4 1 Exterior container Exterior container (see 5 2 1, 5 2 2, and 5 2 3) shall be of minimum tare and cube consistent with the protection required and shall contain equal quantities of identical stock numbered items to the greatest extent practicable

5 4 2 Packaging inspection The inspection of these packaging requirements shall be in accordance with 4 5.

6 NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6 1 Intended use The casualty evacuation bag is intended for use in the evacuation of sick or wounded personnel, or to provide protection for an individual casualty under conditions of extreme cold

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:03Z
Check the source to verify that this is the current version before use.

6 2 Acquisition requirements.

a Title, number, and date of the specification

b Issue of DODISS to be cited in the solicitation and, if required, the specific issue of individual documents referenced (see 2 1)

c Selection of applicable levels of packaging and packing (see 5 1, 5 2, and 5.4).

d National Stock Number

6.3 Standard and shade samples. For access to standard samples of thread and shade samples of materials, address the procuring office issuing the invitation for bids

6 4 Direct marking ink Suggested ink for applying direct markings is the marker 8272 black ink from Markem Company, Keene, NH

6 5 Nonwoven cloth sources of supply Sources of supply for the nonwoven cloth specified in 3 1.3 are the Monsanto Company, New Enterprise Division, St Louis, MO 63166 and West Point Pepperell, NY 10018

6 6 Modacrylic pile fabric source of supply Source of supply for the acrylic/modacrylic blend specified in 3.1 10 and 3 1 17 is Furtex Corporation, Jacksboro, TN style No 3598

6 7 Commodity coverage This specification does not cover all types, classes, grades, or sizes of the commodity indicated by the title of this specification, or those which are commercially available, but is intended to cover the type which is normally procured to meet requirements

6 8 Changes from previous issue Marginal notations are not used in this revision to identify modifications, additions, corrections, and deletions from the previous issue due to the extensiveness of the changes

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:03Z
Check the source to verify that this is the current version before use.

6 9 Subject term (key word) listing

Bag, Evacuation
Batting, Synthetic Fibers
Casualty, Bag
Feathers and Down, Waterfowl
Insulated Evacuation Bag
MUST Hospital
Waterproof, Carrying Bag

6 10 National Stock Number (NSN) coverage This specification covers the following item shown in the Federal Supply Catalog

National Stock Number	Item Identification
6530-01-109-9039	EVACUATION BAG, CASUALTY, INSULATED (With Liner and Carrying Bag)

Custodians:

Army - MD
Navy - MS
Air Force - 03

Preparing activity:

DOD - MB

Agent:

DLA - DM

Civil Agency Coordinating Activities

VA
FDA - MPQAS
USPHS

Review activities:

Army - GL
Navy - MC
Air Force - 50

Project No 6530-2156

Location: EVCMIL13.A1

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:03Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I. RECOMMEND A CHANGE:	1. DOCUMENT NUMBER: MIL-E-11450C	2. DOCUMENT DATE (YYMMDD): 23 November 1991

3. DOCUMENT TITLE: EVACUATION BAG, CASUALTY, INSULATED (With Liner and Carrying Bag)

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME DEFENSE PERSONNEL SUPPORT CENTER ATTN: DPSC-MSE	b. TELEPHONE (Include Area Code) (1) Commercial: AC 215-737-2870 (2) AUTOVON: AV 444-2870
c. ADDRESS (Include Zip Code) 2800 SO. 20TH STREET PHILADELPHIA, PA 19145	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

DD Form 1426, OCT 89 — Previous editions are obsolete — 9879C

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:03Z
Check the source to verify that this is the current version before use.