NOTE: The document identifier and heading has been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.

MIL-PRF-11393D
3 June 1974
SUPERSEDING
MIL-T-11393C
8 November 1968

PERFORMANCE SPECIFICATION

* TEST SET, CONTINUITY, IGNITER CIRCUIT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

* 1.1 This specification covers a circuit test set for electroexplosive igniters, initiators, and squibs.

2. APPLICABLE DOCUMENTS

* 2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

SPECIFICATIONS

Federal

O-L-164	-	Leather Dressing, Mildew Preventive

Military

MIL-B-18	-	Batteries, Dry
MIL-R-93	-	Resistors, Fixed, Wire-wound (Accurate), General Specification for

FSC 4925

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:00Z
Check the source to verify that this is the current version before use.

MIL-T-152	-	Treatment, Moisture and Fungus-Resistant, of Communications, Electronic, and Associated Electrical Equipment
MIL-C-5015	-	Connectors, Electric, "AN" Type
MIL-M-10304	-	Meters, Electrical Indicating, Panel Type, Ruggedized, General Specification for
MIL-R-10509	-	Resistors, Fixed, Film (High Stability), General Specification for
MIL-W-13169	-	Wire, Electrical (for Instrument Test Leads)
MIL-E-17555	-	Electronic and Electrical Equipment, Accessories, and Repair Parts; Packaging and Packing of

STANDARDS

Military

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-130	-	Identification Marking of U. S. Military Property
MIL-STD-202	-	Test Methods for Electronic and Electrical Component Parts
MIL-STD-454	-	Standard General Requirements for Electronic Equipment
MIL-STD-681	-	Identification Coding and Application of Hookup and Lead Wire
MIL-STD-180	-	Environmental Test Methods

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:00Z
Check the source to verify that this is the current version before use.

* 2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

NATIONAL BUREAU OF STANDARDS (NBS)

Handbook H28 - Screw-Thread Standards for Federal Services

Circular 470 - Precision Resistors and Their Measurement

(Application for copies should be addressed to the Superintendent of Documents, U. S. Government Printing Office, Washington, DC 20402.)

NATIONAL ELECTRICAL MANUFACTURERS ASSOCIATION (NEMA)

Electrical Standards

(Application for copies should be addressed to the National Electrical Manufacturers Association, 155 East 44th Street, New York, NY 10017.)

* Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2.1), the supplier shall furnish one complete test set for first article inspection. The first article may be either a preproduction model or an initial production item which conforms to the requirements of this specification. In either case, the approved first article and the production items shall be identical and in accordance with the terms of the contract. Approval of the first article shall not relieve the supplier of the responsibility to furnish equipment in accordance with the requirements of this specification.

* 3.2 Design. The test set shall be designed for making accurate resistance measurements, at safe output current values, of igniter, initiator, and squib circuits used in missiles, jettisoning equipment, etc. The test set shall be self-contained, portable, waterproof, and ruggedized for field use. The test set shall be designed to be fail-safe (see 3.4.1.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:00Z
Check the source to verify that this is the current version before use.

3.3 General construction. The test set shall be complete so that when used it shall conform to the performance and operational requirements specified herein. All parts and materials used in fabrication of the test set shall be new and free of defects. In no event shall patching processes be used for reclaiming defective parts without the approval of the procuring activity.

* 3.3.1 Electrical construction. Electrical components, including switches and wiring, shall be in accordance with NEMA Electrical Standards except as specified herein. Wiring of the test set shall be color coded in accordance with MIL-STD-681.

* 3.3.1.1 Electrical connections. Connections of conductors and terminal parts shall be of the screw, pressure, or solder type. When soldered connections are used, the connections shall be mechanically secured before soldering (except that in solid state applications where connections cannot be mechanically secured they shall be soldered so as to maintain proper electrical continuity). Rosin base fluxes only shall be used in soldering operations. Connections to screw-type terminals shall be mechanically secured with means to prevent loss of tightness.

3.3.2 Interchangeability. All replaceable parts shall be manufactured to definite tolerances and clearances in order that any such parts of a particular type or model may be replaced or adjusted without requiring modification. Where practical, parts shall be permanently and legibly marked with the manufacturer's part number in accordance with MIL-STD-130.

* 3.3.3 Screw threads. All screw threads shall conform to Handbook H28.

3.3.4 Surfaces. All surfaces of all parts shall be cleaned and free from extraneous materials. External surfaces shall be smooth and free from sharp edges. All exterior corners shall be rounded.

3.3.5 Fastening devices. All screws, pins, bolts, and similar parts shall be installed with means for preventing loss of tightness. All such parts when subject to removal or adjustment shall not be permanently deformed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:00Z
Check the source to verify that this is the current version before use.

3.3.6 Dissimilar metals. Contact between dissimilar metals, especially aluminum or magnesium in contact with steel, copper, or brass, shall be avoided whenever possible.

3.4 Performance and product characteristics.

3.4.1 Performance. The test set shall employ a readout type indicator in conjunction with a null balance meter to indicate resistance values within the requirements specified herein.

* 3.4.1.1 Range capability.

* 3.4.1.1.1 For Army and Air Force procurements. The test set shall indicate circuit resistance values within a range of 0 to 30 ohms the resistance values being easily read in increments of 0.01 ohm.

* 3.4.1.1.2 For Navy procurements. The test set shall indicate circuit resistance values within a range of 0 to 30 ohms (x 1 scale) the resistance values being easily read in increments of 0.01 ohm, and within an expanded range of 0 to 3,000 ohms (x 100 scale) the resistance values being easily read in increments of 1 ohm.

3.4.1.2 Current limitation. It is essential that the test set shall not, under any conditions, deliver an output current through the external circuit in excess of 5 milliamperes.

* 3.4.1.3 Accuracy.

* 3.4.1.3.1 For Army and Air Force procurements. The test set shall indicate circuit resistance values within the following accuracies:

Resistance values	Accuracy
0 - 5 ohms	± 0.02 ohm
5 - 30 ohms	± 0.10 ohm

* 3.4.1.3.2 For Navy procurements. The test set shall indicate curcuit resistance values within the following accuracies:

	Resistance values	Accuracy
on x 1 scale	0 - 5 ohms	± 0.02 ohm
	5 - 30 ohms	± 0.10 ohm
on x 100 scale	0 - 1,000 ohms	± 5.00 ohms
	1,000 - 2,000 ohms	±10.00 ohms
	2,000 - 3,000 ohms	±15.00 ohms

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:00Z
Check the source to verify that this is the current version before use.

3.4.2 Weight. Weight of the test set, including test leads and battery, shall not exceed 6 pounds.

3.4.3 Operating temperatures. The test set shall meet the requirements of 3.4.1 through 3.4.1.3 at all temperatures within the range of -45° Fahrenheit (F) to +130°F.

* 3.4.4 Storage temperatures. The test set shall withstand without damage and shall meet the requirements of 3.4.1 through 3.4.1.3 when stabilized at a temperature of +70°F to +90°F after having been subjected to:

(a) An ambient temperature of -60°F to -65°F for a period of 72 hours.

(b) A cycle of ambient temperatures starting with the test set stabilized at +85°F to +95°F, followed by 5 hours of steady increase to +150° F to +155°F, 4 hours at +150°F to +155°, and 5 hours of steady decrease to +70°F to +90°F.

* 3.4.5 Humidity conditions. The test set shall withstand without damage and shall meet the requirements of 3.4.1 through 3.4.1.3:

(a) After having been subjected, with cover removed, to 20 hours exposure to and while at a relative humidity of 93 to 97 percent in an air temperature of +73°F to +77°F, air movement and radiation negligible.

(b) After having been subjected with cover removed, to 4 hours exposure to and while at a relative humidity of 5 to 10 percent in an air temperature of +110°F to +115°F, air movement and radiation negligible.

* 3.4.6 Rain. The test set shall withstand without damage and shall meet the requirements of 3.4.1 through 3.4.1.3 after having been subjected, with cover closed, to a rain test in accordance with method 506 of MIL-STD-810.

* 3.4.7 Salt spray. Unless otherwise specified (see 6.2.1), the test set shall withstand without damage and shall meet the requirements of 3.4.1 through 3.4.1.3 after having been subjected, with cover removed, to a 5 percent salt spray in accordance with method 101 of MIL-STD-202 except that the salt spray shall be for a 24-hour period.

* 3.4.8 Vibration. The test set shall withstand without damage and shall meet the requirements of 3.4.1 through 3.4.1.3 after having been subjected to vibration in accordance with method 201 of MIL-STD-202 with the following exceptions: frequency range of 5 to 55 hertz (Hz), and the motion shall be applied for a period of 1 hour in each of three mutually perpendicular directions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:00Z
Check the source to verify that this is the current version before use.

* 3.4.9 Shock. The test set shall withstand without damage and shall meet the requirements of 3.4.1 through 3.4.1.3 after having been subjected to impacts in accordance with test condition G, method 213, of MIL-STD-202 except that the test set shall be subjected to shock in each individual position stated below:

(a) Bottom down

(b) Right side down

(c) Top down

3.5 Details of components.

3.5.1 Component mounting. Mounting of the battery and the test harness receptacle may be incorporated as part of the housing or the test panel at the option of the manufacturer. All other components shall be mounted on the test panel, or on a chassis attached to the panel, so that the components are removed from the housing when the test panel is removed. All controls and instruments shall be legibly and permanently marked as to function.

* 3.5.2 Test set housing. The test set housing shall be fabricated of lightweight nonferrous metal or plastic and shall be of seamless construction. The test set housing shall include a completely removable cover which, when in a closed position, totally encloses the test panel components. Means shall be provided for securely holding the cover in a closed position. A compartment shall be provided for stowage of at least one set of test leads and one instruction handbook. A carrying handle or strap shall be attached to the main part of the housing (which contains the test panel) to facilitate portability of the test set. Leather, if used, shall be treated in accordance with O-L-164. Resilient nonmetallic rest buttons shall be attached near each corner of the bottom surface of the housing and near each corner of the side opposite the carrying handle. The buttons shall be of sufficient strength to preclude breaking loose from their mounting screws when the test set is slid across a shelf or flat surface.

* 3.5.3 Battery. The test set shall be powered by an internally mounted battery of the mercury type conforming to MIL-B-18. Battery identification, including type and Federal Stock Number, shall be conspicuously marked adjacent to the battery holder. The battery holder shall be designed to preclude installation of a battery of higher voltage than that for which the test set is designed. The battery holder shall be physically isolated from the test circuit so as to preclude the battery falling out of the holder into the circuitry. The battery holder shall be easily accessible to allow rapid changing of batteries without removing the test panel and without the use of special tools.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:00Z
Check the source to verify that this is the current version before use.

Conductors shall not be soldered to the battery. Battery replacement shall not affect the moisture integrity of the test set. Protection against injury to other components by any emitted chemicals or fumes from the battery shall be provided. The battery shall not be used to illuminate the test panel or panel components. Unless otherwise specified (see 6.2.1), test sets shall be supplied without batteries.

* 3.5.4 Special test harness receptacle. An environment resisting box mounting receptacle conforming to designation MS 3102R14S-9S of MIL-C-5015 shall be provided. The connector pins shall be connected in parallel with the binding posts.

3.5.5 Binding posts. Binding posts of a heavy duty low resistance type suitable for spade lugs shall be provided.

3.5.6 Battery switch. A momentary contact type switch shall be provided to allow the operator to energize the test set and test lead terminals.

3.5.7 Null meter. The null meter shall be a ruggedized galvanometer conforming to MIL-M-10304.

* 3.5.8 Readout indicator. Unless otherwise specified (see 6.2.1), the readout indicator shall be a digital, counter, or decade type. If the indicator is a digital or counter type, a readout control shall be provided to vary the resistance indicated. The control shall be of a range sufficient to comply with 3.4.1.1. The indicator shall be clearly legible.

3.5.9 Test set circuitry. Circuits should be kept as simple as possible in the interest of maximum realiability. Resistors used in test set circuits shall conform to MIL-R-10509 or MIL-R-93. If the test set housing is of a conductive material no portion of the test circuitry shall be grounded to the housing. The leads of the current circuit, if not completely insulated, shall be not less than 0.5 inch apart.

3.5.10 Test leads. One set of test leads shall be furnished as standard equipment with each test set. Test leads shall be a minimum of 12 feet in length and shall conform to MIL-W-13169. Test leads shall have spade lugs on one end and test prods on the other end. The test leads shall be provided with tip jack adapter alligator clips.

3.6 Fungus control. Unless otherwise specified (see 6.2.1), the test set shall be treated for fungus resistance in accordance with the type II requirements of MIL-T-152, except that the statement of treatment is not required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:00Z
Check the source to verify that this is the current version before use.

* 3.7 Painting. Unless otherwise specified (see 6.2.1), painting and finishing of the test set shall be in accordance with the supplier's standard practice provided the following minimum criteria are met or exceeded: all surfaces to be painted shall have been cleaned to be free of all foreign matter detrimental to painting, and at least one coat of primer and one coat of enamel have been applied.

* 3.8 Identification marking. All test sets of one manufacturer, supplied under a single contract or purchase order, shall be serial numbered and marked for identification in accordance with MIL-STD-130 and unless otherwise specified (see 6.2.1), shall include the Federal Stock Number.

* 3.9 Operating instructions and safety precautions. Instructions for proper operation of the test set and a conspicuous warning that it shall not be used near transmitters, antennas, or power equipment shall be permanently and legibly marked on the front of the test set.

* 3.10 Technical data. Data shall be furnished as specified (see 6.2.2).

* 3.11 Workmanship. Standards of workmanship shall be such as to assure that the manufacturer's production items are uniform in dimensions, component location, and appearance. Specific workmanship requirements shall be in accordance with Requirement 9 of MIL-STD-454.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

(a) First article inspection (see 4.2.1).

(b) Quality conformance inspection (see 4.2.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:00Z
Check the source to verify that this is the current version before use.

4.2.1 First article inspection. First article inspection shall be applied to the preproduction model or initial production item noted in 3.1. Unless otherwise specified (see 6.2.1), first article inspection shall consist of the examination in 4.3 and all tests under 4.4. Failure of the first article to pass the examination or any of the tests shall be cause for rejection.

* 4.2.2 Quality conformance inspection. Quality conformance inspection shall be applied to each production item offered for acceptance except 4.2.2(c). Failure of any item to pass the examination or testing shall be cause for rejection of that item.

(a) Product examination. Each production item shall be examined to determine compliance with the characteristics specified in 4.3.

(b) Performance test. Each production item shall be subjected to the test in 4.4.1.

(c) Inspection of preparation for delivery (see 4.5). Sampling for inspection shall be conducted in accordance with MIL-STD-105, Special Inspection Level S-3. Acceptance will be based on an Acceptable Quality Level of 4.0.

* 4.2.2.1 Lot. All items of the same type presented for acceptance at the same time shall be considered a lot for the purpose of inspection.

* 4.3 Product examination. Production items shall be examined to determine compliance with the requirements of the contract. As a minimum, the product characteristics contained in 4.3.1 shall be examined.

* 4.3.1 Product characteristics. *See note.

Design not as specified (see 3.2)
Construction characteristics not as specified (see 3.3 thru 3.3.6)
Component characteristics not as specified (see 3.5.1 thru 3.5.10)*
Fungus control not as specified (see 3.6)*
Painting not as specified (see 3.7)
Marking not as specified (see 3.8 and 3.9)
Technical data not furnished as specified (see 3.10)
Poor workmanship affecting function (see 3.11)

*NOTE: Vendor certifications required for components referenced to product and process specifications.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:00Z
Check the source to verify that this is the current version before use.

4.4 Tests.

* 4.4.1 Performance test. Except for operating temperature tests, performance testing shall be conducted in an ambient air temperature of +70° F to +90° F. The test set shall be tested for performance by measuring values of known resistance standards in accordance with the applicable requirements of NBS Circular 470. Resistances of 0.1 ohm, 0.5 ohm, 1 ohm, 3 ohms, and 5 ohms shall be used for testing in the 0 to 5 ohm range. Resistances of 10 ohms, 15 ohms, 20 ohms, 25 ohms, and 30 ohms shall be used for testing in the 5 to 30 ohm range. These resistance standards shall be known to be correct to within 0.001 ohm at +70° F to +90° F. When the expanded range is supplied (see 3.4.1.1.2), resistances of 50 ohms, 100 ohms, 500 ohms, 1,000 ohms, 1,500 ohms, 2,000 ohms, 2,500 ohms, and 2,900 ohms shall be used for testing in the 0 to 3,000 ohm range. These resistance standards shall be known to be correct to within 1 ohm at +70° F to +90° F. Accuracy of the test set shall be determined by measuring the known resistance standards. The null meter shall be brought to the balance condition, the leads attached to the binding posts and shorted together at the ends, and the reading noted. The leads shall then be applied across the 0.1 ohm resistance and a reading taken. The reading obtained when the leads are shorted together shall be subtracted from the reading obtained when measuring the test standard in order to obtain the actual resistance reading of the test standard. The procedure shall be repeated to obtain actual resistance readings of the remaining test standards. Five complete cycles of this test shall be made and deviation of readings obtained from the same test standards shall not exceed ± 0.02 ohm for the 0 to 5 ohm range, ± 0.1 ohm for the 5 to 30 ohm range, ± 5 ohms for the 0 to 1,000 ohm range, ± 10 ohms for the 1,000 to 2,000 ohm range, and ± 15 ohms for the 2,000 to 3,000 ohm range. At no time during the test shall the test set output current exceed 5 milliamperes. Failure of the test set to meet these performance requirements shall be cause for rejection of the test set (see 3.4.1 through 3.4.1.3).

4.4.2 Operating temperature tests.

4.4.2.1 High temperature test. The test set, being in an ambient air temperature of +125° F to +130° F until stabilized, shall be tested in accordance with 4.4.1 (see 3.4.3).

4.4.2.2 Low temperature test. The test set, being in an ambient air temperature of -40° F to -45° F until stabilized, shall be tested in accordance with 4.4.1 (see 3.4.3).

4.4.3 Storage tests.

* 4.4.3.1 High temperature storage test. The test set shall be subjected to a cycle of ambient temperatures starting with the test set stabilized at +85° F to +95° F, followed by 5 hours of steady increase to +150° F to

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:00Z
Check the source to verify that this is the current version before use.

+155° F, 4 hours at +150° F to +155° F, and 5 hours of steady decrease to +70° F to +90° F. The test set shall then be inspected for evidence of damage and tested in accordance with 4.4.1 (see 3.4.4).

4.4.3.2 Low temperature storage test. The test set shall be placed in an ambient air temperature of -60° F to -65° F for a period of 72 hours. At the end of this time, the test set shall be removed and allowed to stabilize at an air temperature of +70° F to +90° F. The test set shall then be inspected for evidence of damage and tested in accordance with 4.4.1 (see 3.4.4).

* 4.4.4 Humidity test. The test set, with cover removed, shall be subjected to 20 hours exposure at a relative humidity of 93 to 97 percent in an air temperature of +73° F to +77° F, air movement and radiation negligible. While at this condition the test set shall be tested in accordance with 4.4.1 (see 3.4.5). Following the above, the test set with cover removed, shall be subjected to 4 hours exposure at a relative humidity of 5 to 10 percent in an air temperature of +110° F to +115° F, air movement and radiation negligible. While at this condition the test set shall be tested in accordance with 4.4.1 (see 3.4.5).

* 4.4.5 Rain test. The test set, with cover closed, shall be subjected to a rain test in accordance with method 506 of MIL-STD-810, then inspected for evidence of damage and tested in accordance with 4.4.1 (see 3.4.6).

4.4.6 Salt spray test. Unless otherwise specified (see 6.2.1), the test set, with cover removed, shall be subjected to a 5 percent salt spray in accordance with method 101 of MIL-STD-202 except that the salt spray shall be for a 24-hour period. The test set shall then be inspected for evidence of damage and tested in accordance with 4.4.1 (see 3.4.7).

4.4.7 Vibration test. The test set shall be rigidly mounted on a vibration machine and subjected to vibration in accordance with method 201 of MIL-STD-202 with the following exceptions: frequency range of 5 to 55 Hz and the motion shall be applied for a period of 1 hour in each of three mutually perpendicular directions. The test set shall then be removed from the machine, inspected for evidence of damage, and tested in accordance with 4.4.1 (see 3.4.8).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:00Z
Check the source to verify that this is the current version before use.

* 4.4.8 Shock test. The test set shall be subjected to impacts in accordance with test condition G, method 213, of MIL-STD-202 except that the test set shall be subjected to shock in each individual position stated below:

(a) Bottom down

(b) Right side down

(c) Top down

The test set shall then be inspected for evidence of damage and tested in accordance with 4.4.1 (see 3.4.9).

* 4.5 Inspection of preparation for delivery. Preservation-packaging, packing, and marking for shipment and storage shall be inspected to determine compliance with the requirements of section 5.

5. PREPARATION FOR DELIVERY

* 5.1 Preservation-packaging, packing, and marking. Unless otherwise specified (see 6.2.1), preservation-packaging, packing, and marking shall be in accordance with MIL-E-17555. The levels of preservation-packaging, and packing shall be as specified (see 6.2.1).

6. NOTES

* 6.1 Intended use. The test set covered by this specification is a sensitive test instrument used for testing electroexplosive igniter, initiator, and squib circuits used in missiles, jettisoning equipment, etc.

* 6.2 Ordering data. Procurement documents should specify:

* 6.2.1 Procurement requirements.

(a) Title, number, and date of this specification.

(b) First article, when required (see 3.1).

(c) Salt spray requirement, if different (see 3.4.7).

(d) Battery, if required (see 3.5.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:00Z
Check the source to verify that this is the current version before use.

(e) Readout indicator, if different (see 3.5.8).

(f) Fungus control, if different (see 3.6).

(g) Painting, if different (see 3.7).

(h) Identification marking, if different (see 3.8).

(i) First article inspection, if different (see 4.2.1).

(j) Salt spray test, if different (see 4.4.6).

(k) Preservation-packaging, packing, and marking if different (see 5.1).

(l) Selection of applicable level of preservation-packaging and packing (see 5.1).

* 6.2.2 Contract data requirements. Required technical data, such as safety precautions, operator's manuals, parts lists, drawings, schematics, wiring instructions, and other instructions for operation and maintenance, as identified on a numbered DD Form 1664, should be specified on a DD Form 1423 incorporated into the contract (see 3.10).

6.3 The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - WC
Navy - OS
Air Force - 70

Review activities:
Army - MI, SM
Navy - None
Air Force - 70

User activities:
Army - None
Navy - AS, MC
Air Force - None

Preparing activity:
Army - WC

Project No. 4925-0016

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:00Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

MIL-T-11393D; Test Set, Continuity, Igniter Circuit

NAME OF ORGANIZATION AND ADDRESS	CONTRACT NUMBER
	MATERIAL PROCURED UNDER A ☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO (If "Yes", in what way?)

4. REMARKS

SUBMITTED BY (Printed or typed name and address - Optional)	TELEPHONE NO
	DATE

DD FORM 1 JAN 73 1426 REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:00Z
Check the source to verify that this is the current version before use.