MIL-C-11430D
31 December 1985
SUPERSEDING
MIL-C-11430C
19 May 1970

MILITARY SPECIFICATION

CASE, MILITARY WATER CAN

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers an insulated case fabricated from vinyl coated cotton cloth.

2. APPLICABLE DOCUMENTS

* 2.1 Government documents. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this document to the extent specified herein.

SPECIFICATIONS

FEDERAL

L-P-375	- Plastic Film, Flexible, Vinyl Chloride
V-F-106	- Fasteners, Slide, Interlocking
V-T-285	- Thread, Polyester
FF-R-556	- Rivet, Solid, Small; Rivet, Split, Small; Rivet, Tubular, Small; Flat Washer (Burr); and Cap, Rivet; General Purpose
FF-S-111	- Screw, Wood
UU-P-268	- Paper, Kraft, Wrapping

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to U.S. Army Natick Research and Development Center, Natick, MA 01760-5014, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 7240

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:02Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

DDD-L-20	- Label: for Clothing, Equipage, and Tentage, (General Use)
LLL-B-810	- Building Board, (Hardboard) Hard Pressed, Vegetable Fiber
MMM-A-1617	- Adhesive, Rubber Base, General Purpose
PPP-B-636	- Boxes, Shipping, Fiberboard

MILITARY

MIL-C-496	- Clips, End, Strap
MIL-W-530	- Webbing, Textile, Cotton, General Purpose, Natural or in Colors
MIL-B-543	- Buckles, Tongueless and Web Strap
MIL-C-10799	- Cloth, Coated, Cotton, Vinyl Coated, Fire and Mildew Resistant

STANDARDS

FEDERAL

FED-STD-751	- Stitches, Seams, and Stitchings

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	- Marking for Shipment and Storage
MIL-STD-147	- Palletized Unit Loads

DRAWINGS

U.S. ARMY NATICK RESEARCH AND DEVELOPMENT CENTER

2-2-127	- Case, Military Water Can; Assemblies and Illustration
2-2-128	- Sections "A"
2-2-129	- Sections "B"
2-2-130	- Details "A"
2-2-131	- Details "B"
2-2-132	- Details "C"
2-2-133	- Details "D"

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:02Z
Check the source to verify that this is the current version before use.

2-2-134 - Details "E"
2-2-135 - Base Assembly Details

(Copies of documents required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

* 2.2 Other publications. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this document to the extent specified herein.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 1518 - Standard Test Method for Thermal Transmittance of Textile Fabric and Batting Between Guarded Hot-Plate and Cool Atmosphere

D 2016 - Standard Test Methods for Moisture Content of Wood

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of conflict between the text of this document and the references cited herein, the text of this document shall take precedence.

3. REQUIREMENTS

3.1 First article. When specified, a first article sample shall be subjected to first article approval (see 4.3, 6.2, and 6.3).

* 3.2 Materials. Recycled material may be used (see 6.5).

3.2.1 Cloth, coated, cotton, vinyl coated. The cloth shall be dyed olive drab shade No. 7 and shall conform to type II, class 1 of MIL-C-10799.

3.2.2 Webbing, textile, cotton. Webbing shall be dyed olive drab shade No. 7 and shall conform to type III, class 4, 1 1/2 and 2 inch widths of MIL-W-530.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:02Z
Check the source to verify that this is the current version before use.

3.2.3 Thread, polyester. Thread for all stitching shall conform to type I, class 1, sub-class B, size FF, dyed shade S-1 (Cable No. 66022) of V-T-285. The dyed thread shall show color fastness to chlorine bleaching equal to or better than the standard shade sample (see 6.4). If no standard shade sample is available, the thread shall show good color fastness to chlorine bleaching.

3.2.4 Adhesive.

3.2.4.1 Water dispersed. Adhesive used to bond the flexible vinyl plastic film to the glass fiber insulation shall be synthetic rubber water dispersion cement.

* 3.2.4.2 Solvent dispersed. Adhesive used to bond together the flexible waterproof film where it is lapped and joined shall be a rubber adhesive conforming to type III of MMM-A-1617.

3.2.5 Hardboard. Hardboard shall be 1/8-inch thick conforming to type II, surfaces 1 or 2, finish A, design a of LLL-B-810.

3.2.6 Film, vinyl plastic, flexible. The film shall be 0.0040-inch thick conforming to type I of L-P-375.

3.2.7 Insulation. The insulating material shall be composed of glass fibers firmly bonded with a thermosetting plastic resin into a resilient mat structure 1-inch thick (plus 3/4 inch, minus 0) having a weight of 2.1 pounds (plus or minus 10 percent) per 24 square feet when tested as specified in 4.4.1.1. The heat transmission value for the insulation, together with one thickness on each side of it of the flexible vinyl plastic film specified in 3.2.6, and the vinyl coated cloth specified in 3.2.1 shall not exceed 0.21 BTU per hour, per square foot, per degree Fahrenheit, taken at a mean temperature of 60°F, when tested as specified in 4.4.1.1.

3.2.8 Wood. Wood for end and side base assemblies shall be free from decay, knots, shakes, checks, splits, or splintery surfaces. The end and side base assemblies shall be of the design and dimensions shown on Drawing 2-2-135 and shall contain not more than 12 percent moisture when tested as specified in 4.4.1.1. Any of the following woods may be used:

Ash	Cedar	Hickory	Pecan	Spruce
Beech	Douglas fir	Maple	Pine	Sycamore
Birch	Hemlock	Oak	Poplar	Tupelo

3.2.9 Buckles, double bar with slide. Buckles shall conform to type III, style 1, class 1 of MIL-B-543.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:02Z
Check the source to verify that this is the current version before use.

3.2.10 Clips, end, strap. End clips shall conform to type I, class 1, size 1 1/2 inch of MIL-C-496.

3.2.11 Fasteners, slide, interlocking. Slide fasteners shall conform to type I, style 18, size MH, with brass or aluminum chains, brass sliders and single wire stirrup pull with thong of V-F-106. A stop shall be applied on one side of the chain, at the center of the chain lengthwise, to prevent movement of the two sliders beyond the midpoint of the fastener. The slide-fastener tape shall be 1-inch wide, dyed to match olive drab shade S (Cable No. 66519), water repellent, and mildew resistant treated. The tape shall show good fastness to weathering.

3.2.12 Rivets. Rivets shall conform to type XII, class 1, grade F, 9/64-inch nominal diameter, with type II, grade F cap of FF-R-556. The length of the rivets shall be such to provide a secure clinch.

3.2.13 Screws, wood. Wood screws shall be steel, zinc coated, and shall conform to style 2s, 1/2 inch, No. 6 of FF-S-111.

3.2.14 Washers. Washers shall be steel, zinc coated, of the type and size shown on drawings.

3.3 Construction. Construction shall conform to the drawings listed in section 2 and as specified herein.

3.3.1 Coated cloth. During manufacture of the case, the smooth side (side having the heavier coating) of the vinyl coated cloth shall be to the outside.

3.3.2 Stitching, machine. All stitching shall conform to type 301 of FED-STD-751, 5 to 7 stitches per inch.

3.3.2.1 Thread breaks. Thread breaks shall be overstitched not less than 1 inch at each break.

3.3.2.2 Stitching ends. Ends of stitching shall be overstitched not less than 1 inch except where ends are turned under in a hem, where ends are held down by other stitching, or where stitching is performed automatically. Where stitching is performed automatically on stitch patterns such as box, box with cross-stitch, "W" stitching, or straight line tacking, three or more tying, overlapping, or backstitches shall be used to secure the ends.

3.3.2.3 Skipped stitches. Two or more consecutively skipped stitches shall be overstitched not less than 1 inch.

3.3.2.4 Lubricants. The addition of any lubricant to the polyester thread prior to or during the sewing operations is prohibited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:02Z
Check the source to verify that this is the current version before use.

3.3.3 Bonding. The flexible vinyl plastic film shall be bonded to the glass fiber insulation, where specified on the drawings, by spraying a fine film of the adhesive specified in 3.2.4.1 on the glass fiber insulation and then laying the flexible film on the adhesive. The flexible film shall be bonded together where it is lapped and joined by means of adhesive specified in 3.2.4.2. Care shall be exercised in applying adhesive so that no adhesive shall come in direct contact with the vinyl coated fabric. All bonded pieces shall be allowed to dry thoroughly before inclusion in the case.

3.3.4 Setting of end clips. Webbing shall be inserted the full depth of the clips. The clips shall be attached without cutting the webbing, and the webbing shall lie flat at the point of entrance.

3.3.5 Setting of tubular rivets. Holes shall be formed by the rivets when driven into the material and not punched prior to insertion of the rivets. All rivets shall be set without damage to the materials.

3.3.6 Setting of wood screws. Wood screws shall be driven and set. When the screws are driven by powered screwdrivers, care shall be taken that screw threads shall not be stripped by over-driving. The driving of screws by means of a hammer shall not be permitted. The size of the pilot hole for insertion of screws shall be in accordance with the manufacturer's procedure.

3.3.7 Attachment of slide fasteners. Care shall be exercised to trim all thread ends to 1/2 inch or less and to maintain specified distances between edges of fabric attached to slide fastener tape so that there will be no interference with the operation of the slider. The length of the slide fastener chains shall be such that, after the slide fasteners are sewed on, the tapes shall not be puckered and the sliders shall operate freely.

3.4 Marking. All marking shall conform to DDD-L-20.

3.4.1 Special marking. The application of the letters "US" on the case shall be in accordance with type IV, class 9. Class 9 marking shall be legible after subjection to accelerated weathering. The letters shall be in the size character and location shown on Drawing 2-2-130.

3.4.2 Identification marking. Identification marking shall conform to type IV, class 5 and shall be located as shown on Drawing 2-2-127.

3.5 Workmanship. Cloth components shall be clean and free of holes, cuts, tears, scratch or abrasion marks, or cloth defects such as uncoated areas, blisters, tunnels, foreign matter, delamination of coating, lumps, or heavily coated areas. Webbing and tapes shall not have frayed or scalloped edges. Thread tension shall be maintained so that there will be no loose or tight

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:02Z
Check the source to verify that this is the current version before use.

stitching. Seam allowances shall be maintained with seams properly sewed so that no runoffs, pleats, or open seams shall result. Care shall be taken to see that no needle chews occur. All thread ends shall be trimmed to 1/2 inch or less. Metal components shall be free of burrs, sharp edges, or corroded areas, and shall not be broken or malformed.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article (see 4.3 and 6.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article sample is required, it shall be examined for defects listed in table II and dimensions specified. The presence of any visual defect or any dimension not within the specified requirements shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.4.1.1 Testing of components. In addition to the quality assurance provisions of the subsidiary documents, tests shall be performed on components and materials listed in table I for the characteristics shown. A lot shall consist of all insulation, adhesive, washers, and wood, as applicable, offered for inspection at one time. Requirements are applicable to the sample unit. For each characteristic, the inspection level shall be S-1, and the acceptable quality level (AQL) shall be 6.5, expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:02Z
Check the source to verify that this is the current version before use.

TABLE I. Component tests

Component	Characteristic	Requirement paragraph	Test method	Number of determinations per sample unit	Results reported as	Sample unit
Adhesive	Material identification	3.2.4.1	Commercial	1	Pass or fail	1 pint
Insulation	Thickness	3.2.7	Commercial	3	Avg of 3 deter to nearest 1/16 inch	1 piece 24 inches by 30 inches
	Weight	3.2.7	Direct weighing	1	Pass or fail	
	Heat transmission	3.2.7	4.5.1	3	Avg of 3 deter to nearest 0.01 Btu/hr/sq ft/degree F	
Wood	Moisture content	3.2.8	4.5.2	3	Avg of 3 deter	1 base assembly (end and side)
Washers	Material identification	3.2.14	Commercial	1	Pass or fail	1 each

4.4.2 In-process inspection. Examination shall be made at appropriate stages of fabrication to determine conformance to specified requirements. Whenever nonconformance is noted, correction shall be made to the affected items and to the process. The following shall be inspected:

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:02Z
Check the source to verify that this is the current version before use.

a. Wood end and side base assemblies shall contain no decay, knots, shakes, checks, split, or splintery surfaces for compliance with 3.2.8.

b. There shall be no lubrication of polyester thread prior to or during sewing operation for compliance with 3.3.2.4.

c. Bonding of flexible film to glass fiber insulation and bonding of glass fiber insulation pieces shall be in accordance with 3.3.3 and the drawings.

d. Setting of tubular rivets and caps shall be performed as specified in 3.3.5.

e. Construction of base assembly shall be as specified on Drawing 2-2-135.

4.4.3 End item inspection. The end item shall be inspected for visual defects and proper dimensions. The lot shall consist of all completely fabricated cases offered for inspection at one time. The sample unit shall be one case.

* 4.4.3.1 Visual examination. Visual examination shall be made of the case for defects in table II. The inspection level shall be II, and the AQL shall be 2.5 for major defects and 15.0 for total defects, expressed in terms of defects per hundred units.

TABLE II. Classification of visual defects

Examine	Defect	Classification	
		Major	Minor
			A B
Fabric	Any hole, cut, tear	X	
	Exposed fabric, delamination of coating	X	
	Scratch or abrasion, blister, tunnel, crease, or wrinkle		X
Webbing, tape	Edge frayed or scalloped		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:02Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of visual defects - Continued

Examine	Defect	Classification		
		Major	Minor A	Minor B
Hardware	Broken	X		
	Malformed:			
	- fails to perform intended function	X		
	- but will perform intended function		X	
	Corroded area			X
	Burr or sharp edge which may cause injury in handling or damage to fabric	X		
End clips	Improperly clinched (i.e., webbing not flat at point of entrance into clip)			X
	Clinched excessively tight, cutting webbing or loosely clinched (i.e., clip becomes disengaged from webbing)	X		
Buckle	Not assembled to strap as specified (i.e., reversed, failing to effect a fastening of strap)	X		
Wood screws and washers	Any screw or washer missing or not set	X		
Seams and stitching	Open seam:			
	- 1/2 inch or less			X
	- more than 1/2 inch, but not more than 1 inch		X	
	- more than 1 inch	X		
	NOTE: A seam shall be classified as open when one or more stitches joining a seam are broken, or when one or more skipped or runoff stitches occur. On double stitched seams, a seam shall be classified as open when either one or both sides of a seam are open.			

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:02Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of visual defects - Continued

Examine	Defect	Classification		
		Major	Minor A	Minor B
	Thread breaks overstitched less than 1 inch			X
	Needle chews resulting in hole, cut, or tear	X		
	Skipped stitches overstitched less than 1 inch (where 2 or more consecutively skipped stitches occur)			X
	NOTE: Skipped stitches not overstitched shall be classified as open seams.			
Seam type	Wrong seam type	X		
Stitch type	Wrong stitch type	X		
Stitch tension	Loose, resulting in an exposed bobbin or top thread for more than 6 inches in length			X
	Tight, as evidenced by puckering on seams for more than 6 inches in length			X
Stitches per inch	Less than minimum specified:			
	- one stitch			X
	- two or more stitches		X	
	More than maximum specified:			
	- one stitch			X
	- two or more stitches		X	
	NOTE: Variation in the number of stitches caused by the operator speeding up the machine and pulling the fabric in order to sew over heavy places or heavy seams or in turning corners shall be classified as follows:			

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:02Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of visual defects - Continued

Examine	Defect	Classification		
		Major	Minor A	Minor B
	a. Within the minor "B" defect classification - no defect.			
	b. Within the minor "A" defect classification - minor "B" defect.			
Stitching margin	Larger than specified by more than 1/16 inch:			
	- for more than 1 inch, but not more than 4 inches in length			X
	- for more than 4 inches in length		X	
Stitching gage	Not as specified		X	
Stitching ends	Overstitched less than 1 inch (except where ends are held down by other stitching, turned under in a hem or where stitching is performed automatically)			X
	Secured with less than three tying, overlapping, or backstitches when automatic stitching is performed			X
Components and assembly	Any component part not fabricated of applicable referenced material	X		
Seams	Pleated			X
Slide fastener tapes	Slider jams or fails to interlock chain	X		
	Any tape improperly assembled, causing failure of chain to effect a closure	X		
Marking	Omitted, incorrect, illegible, misplaced, or size of characters not as specified			X

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:02Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of visual defects - Continued

Examine	Defect	Classification	
		Major	Minor A	Minor B
Cleanness	Grease or oil stains			X
	Thread ends not trimmed to 1/2 inch or less (except in slide fastener area)			X
	Thread ends not trimmed to 1/2 inch or less in slide fastener area		X	

* 4.4.3.2 Dimensional examination. Dimensional examination shall be made of the completely fabricated case for the defects in table III. The inspection level shall be S-3, and the AQL shall be 4.0 for major defects and 10.0 for total major and minor defects combined, expressed in defects per hundred units.

TABLE III. Classification of dimensional defects

Examine	Defect	Classification	
		Major	Minor
Overall dimensions	Smaller than specified dimensions less applicable minus tolerances indicated on drawings	117	
	Larger than specified dimensions and applicable plus tolerance indicated on drawings		227
Location dimensions	Not within the specified requirements		228

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:02Z
Check the source to verify that this is the current version before use.

4.4.4 Packaging inspection. An examination shall be made to determine that preservation, packing, and marking comply with the requirements of section 5. Defects shall be as specified in table IV. The lot shall be the number of shipping containers offered for inspection at one time. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2, and the AQL shall be 2.5, expressed in terms of defects per hundred units.

TABLE IV. Packaging inspection

Examine	Defect
Marking and interior	Omitted, incorrect, illegible, or of improper size, location, sequence, or method of application
Materials	Any component missing or damaged
Workmanship	Bulged or distorted container
Content	Number per container is more or less than required Not completely covered on the top and bottom with kraft paper

4.4.5 Examination for palletization. When palletization is required, an examination shall be made to determine that palletization requirements comply with section 5. Defects shall be scored in accordance with table V. The lot shall be the number of palletized unit loads in the inspection lot. The sample unit shall be one palletized unit load fully packaged. The inspection level shall be S-1, and the AQL shall be 6.5, expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:02Z
Check the source to verify that this is the current version before use.

TABLE V. Examination of palletization

Examination	Defect
Finished dimensions	Length, width, or height exceeding specified maximum requirements
Palletization	Not as specified Container pattern not as specified Load not bonded with required straps, as specified
Weight	Exceeds maximum load limits
Marking	Omitted, incorrect, illegible, or of improper size, location, sequence or method of application

4.5 Tests.

4.5.1 Heat transmission value. The heat transmission value (U_2) shall be tested for in accordance with ASTM D 1518. U_2 is the intrinsic transmittance coefficient of the insulation and shall be determined by the following formula:

$$U_2 = \frac{Ubp \times U_1}{Ubp - U_1}$$

where

Ubp = transmittance coefficient of the bare plate when exposed to air, not covered by a sample, and

U_1 = combined transmittance coefficient of the specimen plus the air when the plate is operated with the sample in place.

4.5.2 Moisture content of wood. Moisture content of the wood end and side base assemblies shall be determined by either the oven-drying or electric moisture meter method referenced in ASTM D 2016.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:02Z
Check the source to verify that this is the current version before use.

5. PACKAGING

* 5.1 Preservation. Preservation shall be level A or Commercial, as specified (see 6.2).

5.1.1 Level A. Each case shall have the slide fasteners closed and the carrying strap adjusted to the smallest dimension. The carrying strap excess shall then be folded back over the top of the unit and tucked underneath itself.

* 5.1.2 Commercial. Cases shall be preserved in accordance with ASTM D 3951.

* 5.2 Packing. Packing shall be level A, B, or Commercial, as specified (see 6.2).

5.2.1 Level A packing. Three cases, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC-L, V2s of PPP-B-636. The inside of each PPP-B-636 container shall be fitted with a box liner conforming to type CF, class weather resistant, variety DW, grade V15c of PPP-B-636. Level A unit packs shall be packed with the back down, three in length, within a shipping container having approximate inside dimensions of 31 inches in length, 23 1/2 inches in width, and 17 1/2 inches in depth. Approximate dimensions are furnished as a guide only. Each shipping container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to type I, grade B of UU-P-268. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V, and reinforced as specified in the appendix of PPP-B-636.

5.2.2 Level B packing. Three cases, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC-L, type CF, variety SW or SF, class domestic, grade 275 of PPP-B-636. The inside of each container shall be fitted with a box liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. Level B unit packs shall be packed with the back down, three in length, within a shipping container having approximate inside dimensions of 31 inches in length, 23 1/2 inches in width, and 17 1/2 inches in depth. Approximate dimensions are furnished as a guide only. Each shipping container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to type I, grade B of UU-P-268. Each container shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:02Z
Check the source to verify that this is the current version before use.

5.2.2.1 Weather-resistant containers. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, and V4s fiberboard box fabricated in accordance with method III as specified in PPP-B-636 and closed in accordance with the appendix of PPP-B-636.

* 5.2.3 Commercial packing. Cases, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Palletization. When specified (see 6.2), cases packed as specified, shall be palletized in accordance with load type Ia of MIL-STD-147. Pallet type shall be type I (4-way entry), type IV, or type V in accordance with MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L or film bonding means O or P. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of load shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern intended to be used shall be submitted to and approved by the contracting officer prior to its use.

* 5.4 Marking. In addition to any special marking required by the contract or purchase order, interior packages, shipping containers, and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

6.1 Intended use. The insulated case is primarily for use in cold climate areas as a case for the 5-gallon water can to keep water from freezing. The case may also be used for transporting warm food, coffee, or other supplies to troops in the field.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. First article (see 3.1, 4.3, and 6.3).
c. Selection of the applicable levels of preservation and packaging (see 5.1 and 5.2).
d. When weather-resistant boxes are required for level B shipments (see 5.2.2.1).
e. When palletization is required (see 5.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:02Z
Check the source to verify that this is the current version before use.

* 6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample and should consist of one unit. The contracting officer should include specific instructions, in all procurement instruments, regarding arrangements for examination and approval of the first article.

6.4 Standard sample. For access to a standard shade sample of thread, address the contracting activity issuing the invitation for bids.

* 6.5 Recycled material. The contractor is encouraged to use recycled material for nontextile material, provided that it meets the requirements of this document (see 3.2).

6.6 Changes from previous issue. The margins of this document are marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:

Army - GL

Review activities:

Army - MD
Air Force - 84
DLA - GS

User activity:

Navy - MC

Preparing activity:

Army - GL

Project No. 7240-0230

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:02Z
Check the source to verify that this is the current version before use.