INCH-POUND
MIL-PRF-55182/9F
AMENDMENT 2
14 June 2001

PERFORMANCE SPECIFICATION

RESISTORS, FIXED, FILM, NONESTABLISHED RELIABILITY,
ESTABLISHED RELIABILITY, AND SPACE LEVEL, STYLE RNC90

This amendment forms a part of MIL-PRF-55182/9F, dated 9 June 97, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

1.2.1.2, characteristic Z, delete and substitute:

"Z - Nonhermetically sealed - Resistance temperature characteristic (referenced to +25°C) = ±2.0 ppm/°C up to and including +125°C; and ±2.0 ppm/°C from +125°C to +175°C. 300 volts maximum working voltage."

PAGE 3

* 3.5, delete and substitute.

"3.5 Voltage Rating. The maximum continuous working voltage shall not exceed 300 volts."

Custodians:
Army - CR
Navy - EC
Air Force - 11
NASA - NA

Review activities:
Army - AR
Navy - AS, CG, MC, OS
Air Force - 19, 99
DLA - CC

Preparing activity:
Army - CR

Agent:
DLA-CC

(Project 5905-1626)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:36Z
Check the source to verify that this is the current version before use.