INCH-POUND
MIL-A-55339/2A
AMENDMENT 2
15 May 1996
SUPERSEDING
AMENDMENT 1
20 July 1982

MILITARY SPECIFICATION SHEET

ADAPTERS, CONNECTOR, COAXIAL, RADIO FREQUENCY, (SERIES SMA),
CLASS 2, RIGHT ANGLE, MALE TO FEMALE

This amendment forms a part of Military Specification MIL-A-55339/2A, dated 4 August 1975, and is approved for use by all Department and Agencies of the Depatment of Defense.

PAGE 1

* Configuration drawing, add new note 4 as follows:

"4. Interface dimensions shall be in accordance with MIL-STD-348.".

PERFORMANCE, delete and substitute:

"PERFORMANCE (for each test of a threaded coupling connector where the test is performed on mated pairs, the pairs shall be torqued 7 to 10 inch pounds (.791 to 1.13 Nm)."

Coupling proof torque: Delete "max" and substitute "min.".

PAGES 2 and 3

* FIGURE 2. Mating dimensions, delete in its entirety.

PAGE 4

VSWR, delete and substitute:

"VSWR: 1.05 +.010 F (F in GHz) max at .5 to 12.4 GHz".

The margins of this amendment are marked with an asterisk to indicate where changes from the previous amendment were made. This was done as a convenoence only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the material notations and relationship to the last previous amendment.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 85

Preparing activity:
DLA - ES

(Project 5935-4057-02)

Review activities:
Army - AR, AT, EA, MI
Navy - AS, MC, OS, SH
Air Force - 19, 99

FSC 5935

AMSC N/A

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:04Z
Check the source to verify that this is the current version before use.