MILITARY SPECIFICATION

CONVERTER, LIQUID OXYGEN GCU-2A/A

This amendment forms a part of MIL-C-25777C(USAF), dated 15 Jan 1971, and is approved for use within the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* Delete "2.1" and add:
"2.1 Government documents."

* Add:
"2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation."

Under SPECIFICATIONS, Federal add:
"PPP-B-636 Box, Shipping, Fiberboard."

Under SPECIFICATIONS, Military, delete "MIL-E-5272".
Add:
"MIL-P-116 Preservation-Packaging, Methods of"

Under STANDARDS, Military, Add:
* "MIL-STD-129 Marking for Shipment and Storage."
"MIL-STD-794 Parts and Equipment, Procedures for Packaging and Packing of"

Delete: "MIL-STD-781".

Add boxed paragraph to bottom center of page.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Oklahoma City Air Logistics Center/MMEDO, Tinker AFB OK 73145-5990 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

PAGE 2

3.1, Last line: Delete "4.4" and substitute "4.3".

FSC 1660

AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T07:16Z
Check the source to verify that this is the current version before use.

PAGE 3

Figure 1: Delete "(Front View)" from the title.

PAGE 6

3.4.7 Delete and substitute:
"3.4.7 Delivery rate. The converter shall deliver a flow of gaseous oxygen at a flow rate of 72 (plus or minus 10) liters per minute for not less than 1-1/2 hours with the operating pressure (measured in the gaseous phase of the system) remaining between 70 psig and 80 psig after the first 15 minutes of flow. Pressures in the supply line shall remain between 55 psig and 105 psig during the entire period of flow. The flow at the specified rate shall be initiated within 10 minutes after the converter has reached the operating pressure."

PAGE 8

* Delete paragraph "4.4.5".

PAGE 9

Delete pargraph "4.6.3".

Delete section 5 in its entirety and substitute the following:

* "5 PACKAGING

5.1 Preservation-packaging. Preservation-packaging shall be level A unless otherwise specified by the contracting activity (see 6.2).

5.1.1 Level A. Each converter pressurized to a maximum of 25 lbs PSI shall be preserved in accordance with Method III of MIL-P-116.

5.1.1.1 Cleaning and drying. Each converter shall be cleaned and dried for oxygen service in accordance with industry practice according to the applicable processes of MIL-P-116. Petroleum and other flammable solvents shall not be used.

5.1.1.2 Unit packaging. Unless otherwise specified by the contracting activity, oxygen converters shall be individually packaged in accordance with MIL-P-116, Method III, insuring compliance with the applicable requirements of that specification.

5.2 Packing. Packing shall be level A, B, or C as specified. (see 6.2)

5.2.1 Level A. Unless otherwise specified by the contracting activity, oxygen converters packaged as specified in 5.1 shall be packed in shipping containers applicable to level A requirements of MIL-STD-794. Insofar as practical, exterior shipping containers shall be of uniform shape, size, minimum tare and cube consistent with the protection required.

5.2.2 Level B. Unless otherwise specified by the contracting activity, oxygen converters shall be packed in shipping containers conforming to PPP-B-636, Style RSC, Type CF, Class WR, Grade V3C. Other requirements as specified in 5.2.1 are applicable.

Source: https://assist.dla.mil -- Downloaded: 20260-20T07:16Z
Check the source to verify that this is the current version before use.

5.2.3 Level C. Unless otherwise specified by the contracting activity, oxygen converters shall be packed in shipping containers conforming to PPP-B-636, Style RSC, Type CF, Class Dom Grade 275. Other requirements as specified in 5.2.1 are applicable.

5.3 Marking. In addition to any other marking required by the contract or order (see 6.2), interior and exterior containers shall be marked in accordance with MIL-STD-129.

5.3.1 Precautionary marking. The following precautionary marking shall appear on each package:

LIFE SUPPORT ITEM
All oil, grease, shop residue or other contaminants have been removed.
DO NOT OPEN UNTIL READY FOR USE

6.3 Delete last sentence and substitute: "The activity responsible for the Qualified Products List is Oklahoma City Air Logistics Center/MMEDO, Tinker AFB OK 73145-5990, and information pertaining to qualification of products may be obtained from that activity.

6.4 Delete and substitute the following:
"6.4 Reclaimed materials. The use of reclaimed materials shall be encouraged to the maximum extent possible."

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Air Force - 99

Preparing Activity:
Air Force - 71

Project Number:
1660 - F549

Source: https://assist.dla.mil -- Downloaded: 202640-20T07:16Z
Check the source to verify that this is the current version before use.