MIL-R-2726/7A(SH)
3 July 1986
SUPERSEDING
MIL-R-2726/7(SHIPS)
30 June 1967

MILITARY SPECIFICATION SHEET

RECEPTACLE, ELECTRICAL, 2-PIN, 40-AMPERE, 125-VOLT, DIRECT CURRENT (SYMBOL NOS. 756.1 AND 756.2)


(A) This specification is approved for use within the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

(A) The requirements for acquiring the receptacle described herein shall consist of this specification and the latest issue of MIL-R-2726.

(A) denotes changes.

AMSC N/A FSC 5935
DISTRIBUTION STATEMENT A Approved for public release; distribution unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T15:21Z
Check the source to verify that this is the current version before use.



SH 9077

Part number M2726/7-001

(A) Symbol no. 756.1


NOTES:

1. Dimensions are in inches. Unless otherwise specified, tolerances are ± 1/64 inch for fractions and ± 0.005 inch for decimals. Angular tolerance is ± 1/2 degree.
2. Supersedes: Drawing 9000-S6202-73882, pc. 7, symbol 756.

(A) FIGURE 1. Receptacle (metal housing and shell).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T15:21Z
Check the source to verify that this is the current version before use.

Ⓐ MOLDED PLASTIC RECEPTACLE
(SAME AS FIGURE 1 EXCEPT AS SHOWN)



SH 9078

Part number M2726/7-002

Ⓐ Symbol no. 756.2

Ⓐ FIGURE 2. Receptacle (plastic) body.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T15:21Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

1. Dimensions and configurations: See figures 1 and 2.
2. Effectiveness of enclosure: Watertight in accordance with MIL-STD-108 when mounted in a suitable enclosure.
3. Material: Housing - optional - polyamide (nylon) or metal.
   Receptacle insulator and cap - in accordance with type MAI-60 of MIL-M-14.
   Contact - in accordance with copper alloy number 175, HT temper of MIL-C-46087.
4. Contact hardness: Minimum of Rockwell 80F.
5. Mating plug: MIL-R-2726/1, part number M2726/1-001 (not furnished).
6. Cap assembly: MIL-R-2726/13, part number M2726/13-001 (not furnished).
7. Design. Plastic housing and insulation may be a one piece molded unit.
8. Gasket: Neoprene, commercial (COML), durometer number 20. Lubricate with silicon compound.
9. O-ring: MS28775-229
10. Electrical rating: 40-ampere, 125-volt, direct current.
11. Part number: M2726/7-001 (metal housing and shell).
    M2726/7-002 (plastic body).
12. Contact finish: Silver plate.

QUALITY ASSURANCE:

Quality assurance shall be as specified in MIL-R-2726 and table I herein. The first article and quality conformance inspections shall consist of the inspections as specified in table I, in the order shown.

TABLE I. First article and quality conformance inspection.

Inspection	Requirement	Test method	First article	Quality conformance
Examination	3.1, 3.3, 3.4, 3.5, 3.6 and 3.7	4.6.1	X	X
Insulation resistance	3.5.1	4.7.1	X	X
Dielectric withstanding voltage	3.5.2	4.7.2	X	X
Contact resistance	3.5.3.1	4.7.3.1	X	X
Endurance	3.5.5	4.7.5	X	
Salt spray	3.5.11	4.7.11	X	
Contact resistance	3.5.3.1	4.7.3.1	X	
Current load	3.5.12	4.7.12	X	
Vibration	3.5.9	4.7.9	X	
Shock	3.5.10	4.7.10	X	
Effectiveness of enclosure	3.5.4	4.7.4	X	X
Dielectric withstanding voltage	3.5.2	4.7.2	X	
Mechanical abuse	3.5.8	4.7.8	X	
Ball drop impact	3.5.15	4.7.15	X	
Strain relief	3.5.7	4.7.7	X	
Rockwell hardness	3.5.14	4.7.14	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T15:21Z
Check the source to verify that this is the current version before use.

Preparing activity:
Navy - SH
(Project 5935-N255-8)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T15:21Z
Check the source to verify that this is the current version before use.