METRIC

A-A-3103
December 31, 1996

COMMERCIAL ITEM DESCRIPTION

TAB, INDEX, PRESSURE-SENSITIVE, TRANSPARENT

The General Services Administration has authorized the use of this commercial item description, for all federal agencies. This replaces Federal Specification UU-T-001655, which has been canceled.

1. SCOPE: This commercial item description covers transparent pressure sensitive index tab sets for identifying segregation in file and directory reference material, alphabetical or otherwise.

2. CLASSIFICATION:

2.1 Types and classes. The tabs shall be furnished in the following types and classes, as specified.

Type I- Individual printed tab sets.
Class 1-Angle Projection
Class 2-Round Projection

Type II-Transparent insertable 6 inch tab strips.

3. REQUIREMENTS:

3.1 Material. The material shall be as specified herein. Where material is not definitely defined, it shall be of the quality, composition, and thickness best suited for the intended purpose.

3.1.1 Plastic The transparent plastic film shall conform to the physical requirements specified in table I.

Beneficial comments, recommendations, additions, deletions, clarifications etc. Any data which may improve this document should be sent to:

General Services Administration:
Federal Supply Service,
Engineering Branch (2FYEE)
26 Federal Plaza, New York, NY 10278

FSC 7510

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:30Z
Check the source to verify that this is the current version before use.

TABLE 1 Tensile strength and elongation.

Tensile strength,	kpascals per square inch, minimum	36643 5300
Elongation at rupture, percent, minimum		25

3.1.1.1 Transparency of tab skirt. The tab skirts shall be sufficiently transparent to allow easy reading of 10 point type.

3.1.2 Adhesive. The adhesive shall be a pressure sensitive, transparent, water soluble homogenous material capable of withstanding changes in temperature and humidity experienced in normal atmospheric conditions. The adhesive shall require no moisture, heat, or other special preparation prior to applying tab to paper.

3.1.3 Release liner or backing. The paper of the release liner of backing shall be treated with an appropriate release liner treatment material that allows pressure sensitive tabs to be released from the liner or backing without tearing or causing separation of the adhesive from the tab.

3.1.4 Insert labels, blank and alphabetical (type II). The paper stock shall conform to the physical requirements specified in table 2. The paper shall have a smooth surface receptive to writing or typing with ink without feathering or spreading.

TABLE 2 Physical Properties.

Basis weight (25-1/2 x 30-1/2 inch-500) pounds		65 minimum	Tappi Test Method T 410
Thickness,	cm inches	0.014 minimum 0.0055 minimum	

3.2 Type I

3.2.1 Design and construction. The tabs shall be manufactured of material as specified in 3.1. The tabs shall be pre-cut individually, and shall be the dimensions specified in table 3. The tabs shall be made of such material and designed and constructed so that the projection will stand erect. Forty percent or more of the lower portion of the skirt shall be evenly coated with an adhesive conforming to 3.1.2. The adhesive shall be protected by release liner or backing conforming to 3.1.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:30Z
Check the source to verify that this is the current version before use.

3.2.1.1 Tab dimensions and legends. The tabs and legends shall be as specified in table 3. The legend shall be permanently and legibly printed on the plastic projection or on appropriate white paper securely attached to the inside of the tab protection, at the option of the manufacturer. The letters U and V and X, Y, and Z may be combined on one tab each. The name of the months and states may be abbreviated. The tab sets with the names of states shall at least contain all 50 states plus the District of Columbia.

TABLE 3 Type I, classes 1 and 2.

Legend of tab	# of tabs/set	Tab projection width tolerance+/- .0794cm +/-1/32inch **	Tab projection Length minimum *	Shirt width minimum **	Height of legend minimum
Alphabet (a) +(b)	23	.635, .952, or 1.27 cm 1/4, 3/8, or 1/2 inch	1.27cm 1/2 inch	.794cm 5/16 inch	.317cm 1/8 inch
Numbers 1-31 (a) +(b)	31	.635, .952, or 1.27 cm 1/4, 3/8, or 1/2 inch	1.27cm 1/2 inch	.794cm 5/16 inch	.317cm 1/8 inch
Month (a) +(b)	12	.635, .952, or 1.27 cm 1/4, 3/8, or 1/2 inch	1.27cm 1/2 inch	.794cm 5/16 inch	.317cm 1/8 inch
States (a) +(b)	51	.635, .952, or 1.27 cm 1/4, 3/8, or 1/2 inch	1.27cm 1/2 inch	.794cm 5/16 inch	.317cm 1/8 inch

Notes: (a) Side attachment, vertical reading.
(b) Top attachment, horizontal reading

* Length is the dimension parallel with the edge of the item to which attached.
** Width is the measurement taken at right angle to which attached.

3.2.2 Type II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:30Z
Check the source to verify that this is the current version before use.

3.2.2.1 Design and construction. The tabs shall be manufactured of material as specified in 3.1. The dimensions shall be as specified in Table 4. The tab shall be one continuous 15.24cm strip that may be cut to the desired length. The tab shall be made of such material and designed and constructed so that the projection will stand erect with or without the insert. The projection shall have a double beaded edge, and the projection and skirt shall be physically divided by a divider (saddle). The divider shall serve to hold paper insert label in place, and serve as a stop when attaching tab to the paper. Forty percent or more of the lower portion of the skirt shall be evenly coated with adhesive conforming to 3.1.2. The adhesive shall be protected by release liner conforming to 3.1.3.

3.2.2.2 Tab dimensions. legends of tabs, and height of legend. The dimensions, and legend of tabs, and height of the Legend shall be as specified in Table 4. (see3.2.2.3 and 3.2.2.4):

TABLE 4 Type II, tabs

Legend of tab	Tab projection width tolerance+/- .1191cm +/- 1/32inch **	Tab length minimum +/- 1/8 inch *	Shirt width minimum **	Height of legend minimum
Alphabet	.855cm 1/3 inch	15.24cm 6 inches	.794cm 5/16 inch	.317cm 1/8 inch
Alphabet	1.27cm 1/3 inch	15.24cm 6 inches	.794cm 5/16 inch	.317cm 1/8 inch

* Length is the dimension parallel with the edge of the item to which attached.
** Width is the measurement taken at right angle to which attached.

3.2.2.3 Sets. Each set shall contain the following: two strips of 15.24cm insertable tabs; two strips of insert labels, each consisting of not less than 15.24cm of blank insert labels, and insert labels with not less than two complete alphabets, or one complete alphabet and two series of letters A through H. The letters U and V, and X,Y,Z may be on one tab. each.

3.2.2.4 Insert labels. The insert labels shall be made of materials as specified in 3.1.4. The labels shall be connected in one continuous strip to facilitate feeding into a typewriter. The strip shall be perforated for ease in tearing apart, and shall be scored or perforated along the longitudinal center line to permit and facilitate folding of the label. When inserted, the folded label shall cover the entire inside of the projection. When printed insert labels are folded, the same letter shall appear on both sides of the insert label. To enable each tab to be used for vertical and horizontal indexing, one letter shall be printed parallel to the longitudinal center line of the label and the other at right angle to the center.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:30Z
Check the source to verify that this is the currentversion before use.

3.2.2.5 Color. Unless otherwise specified in the procurement document, the 15.24cm insertable tab strip shall be clear, colorless, and transparent plastic, and the insert labels shall be white paper (see 3.1.4). When colored tabs are specified, the 15.24cm insertable tab projection, or the projection skirt shall be made of transparent colored plastic, or the insert labels shall be of the color specified, or one side of the label shall be of the color specified and the reverse side shall be white. When colored insert labels (other than white) are supplied, the letters shall be printed on the colored side. On white insert labels the

letters shall be black, and on colored inserts the letters shall be of a contrasting color that will assure legibility.

3.3 Identification marking. Each box or envelopes of index tabs or strips shall be permanently and legibly marked with the name or trademark of the manufacturer.

3.4 Workmanship. The finished tabs shall be clean and uniform, and the edges shall be clean-cut and shall be free from any defects which may affect appearance or serviceability.

3.5 Shelf life. The tabs shall under normal conditions retain their serviceability as defined by this commercial item description for not less than 18 months from the time of shipment. Suppliers shall make replacements, without charge to the Government, of all tabs failing to meet theses requirements.

4. REGULATORY REQUIREMENTS: The offeror /contractor is encouraged to use recovered materials to the maximum extent practicable in accordance with paragraph 23.403 of the Federal Acquisition Regulation(FAR).

5. QUALITY ASSURANCE PROVISIONS:

5.1 Product Conformance: The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards,and quality assurance practices and be the same product offered for in the commercial sale market. The government reserves the right to require proof of such conformance.

6. PACKAGING, PACKING, LABELING, MARKING, AND PALLETIZATION:

Packaging, packing, labeling, marking and, palletization shall be as specified in the contract or order.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:30Z
Check the source to verify that this is the current version before use.

7. NOTES

7.1 Referenced Documents: The following documents form a part of this Commercial Item Description to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposal shall apply:

7.1.1 **TAPPI** test methods are available from:
Technical Association of the Pulp and Paper Industry,Technology Park/Atlanta,
P.O. Box 105113, Atlanta, GA 30348

7.1.2 **Federal Acquisition Regulation(FAR)** is available from:
The Superintendent of Documents, Government Printing Office,Washington DC 20402

7.2 Ordering Data: Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

(1) Type and Class
(2) Specific packaging, packing, labeling, marking and, palletization requirements.
(3) Tabs with different legends, dimensions, color or # of tabs per set if different from what is specified in this cid.

7.3 List Of NSN'S

7510-00-147-8460
7510-00-147-8462
7510-00-147-8463
7510-00-147-8471
7510-00-147-8475
7510-00-147-8477
7510-00-147-8480
7510-00-147-8487
7510-00-147-8488
7510-00-147-8465
7510-00-147-8468
7510-00-147-8470
7510-00-147-8484
7510-00-147-8486

MILITARY INTERESTS

MILITARY
None: DoD has no registered interest in revisions and amendments to this Commercial Item Description until further notice

PREPARING ACTIVITY
GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:30Z
Check the source to verify that this is the current version before use.