INCH-POUND

A-A-59114
08 AUGUST 1997

COMMERCIAL ITEM DESCRIPTION

TRUCK, FIRE FIGHTING, (BRUSH)
(4x4 BRUSH FIRE TRUCK (BFT))

The General Services Administration has authorized the use of this Commercial Item Description (CID) by all federal agencies.

1. **SCOPE.** This Commercial Item Description (CID) describes a commercial, diesel engine driven, automatic transmission, four wheel drive, two person cab, BFT. The BFT shall be based on a commercially available two person cab and chassis, with a mounted utility body, containing a modular agent and delivery system, fire fighting tools and equipment. The BFT is intended to operate over public roads and off-road terrain in support of a wild-land and brush fire fighting mission.

2. **SALIENT CHARACTERISTICS.**

2.1 The BFT shall be an assembly of new materials and shall be free of defects in design and construction affecting, maintainability, serviceability, durability and appearance. The BFT shall conform to the more stringent of State or Federal laws applicable to a vehicle of this type, for operation on and off the public roads for the defined purpose. All components of the BFT shall be represented in the manufacturer's commercial sales literature as standard or optional equipment. The BFT shall meet the requirements of the criteria found in NFPA 1906, Standard for Wildland Fire Apparatus, 1995 Edition, as applicable to the configuration specified. Failure of the BFT to meet the defined salient characteristics shall be cause for rejection of the vehicle. The BFT shall be provided with and/or meet all of the following:

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any data which may improve this document should be sent to: WR-ALC/TILBA, 420 SECOND STREET, SUITE 100, ROBINS AFB GA 31098-5609

AMSC N/A **FSC 4210**

DISTRIBUTION STATEMENT A. Approved for public release: distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:01Z
Check the source to verify that this is the current version before use.

2.1.1 Performance. The BFT shall maintain a minimum speed of 30 miles per hour (MPH) while ascending an 8% dry paved grade, and a minimum speed of 5 MPH while ascending a 30% dry paved grade.

2.1.2 Chassis and vehicle components.

a. The BFT shall be based on a commercially available two door, two person cab and chassis, equipped with a mounted utility body. The BFT shall have a minimum Gross Vehicle Weight Rating (GVWR) of 14,000 pounds. A slip-in fire-fighting module shall be located in the utility body.

b. The BFT engine shall have a driver controlled emergency engine shutdown.

c. The BFT engine exhaust shall be directed away from the standing access positions to the agent pump controls and equipment compartment access.

d. The BFT shall have dual parallel piped fuel filters.

e. The BFT shall have an electric fuel priming pump.

f. The BFT shall use a 12 volt electrical and starting system. The battery system shall be the largest reserve capacity chassis option available.

g. The BFT shall use a single alternator charging system. The minimum output of the alternator, at engine idle, shall exceed the total simultaneous operation of all electrical components, excluding the hose reel rewind motors, by 10%.

h. The BFT shall be equipped with a minimum 15 amp battery charger. The battery charger shall be powered from a covered, recessed male, 120 volt, AC receptacle, located adjacent to the driver's door. A 2.5 inch charge meter shall be installed next to the AC receptacle. A 25 foot long, three wire, 20 amp rated, 120 volt, AC, power cable shall be provided.

i. The BFT shall have a spare wheel and tire assembly included, but not mounted.

j. When specified, the BFT shall be equipped with a chassis winterization system. The winterization system shall maintain the engine coolant, lubricants, fuel, and electrical system, such that the truck can be started and operated down to 0 degrees F.

k. When specified, the BFT shall be equipped with a cab air conditioning system.

l. The BFT shall have adjustable head, combination flat and convex, west coast style mirror on each side of the cab. The mirror brackets shall be a fold-back design.

m. The BFT shall be equipped with a front mounted 8000 pound-pull winch. The winch shall be mounted behind the front bumper, guarded and within the approach angle of the truck. The

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:01Z
Check the source to verify that this is the current version before use.

winch shall be electric powered and shall have one or more forward and reverse speeds. The winch shall have a four-way cable guide and shall be wound with at least 125 feet of 3/8 inch galvanized aircraft cable, with a 36 inch end chain and hook. A minimum 10 foot long remote operation control cable shall be provided.

2.1.3 Lights, warning devices and electrical circuits.

a. The BFT shall have an in-cab dedicated 15 amp accessory circuit, with breaker, for the owner's use.

b. The cab and all compartments shall be provided with white lighting to enable personnel to identify and select equipment during night functions. Automatic switches shall illuminate the cab and compartment lights when their respective doors are opened. Cab light levels shall be high enough for reading maps and manuals.

c. A minimum 50,000 candlepower spotlight shall be installed at the top center of the cab. The spotlight shall be guarded, shall adjust vertically, and shall rotate at least 350 degrees. Light control and switch shall be within reach of the driver and passenger.

d. The warning light requirements of NFPA 1906 shall use red strobe lights. Strobe lights shall flash at a rate of approximately 60 cycles per minute. All warning light groups shall be separately switched from the warning light panel. A master switch shall activate all emergency light circuits. All warning lights shall be guarded from damage during off-road operation.

e. When specified, an alternating flashing headlight system shall be provided. The high beam headlights shall flash alternately. A separate switch on the instrument panel shall activate the flashing headlights.

f. When specified, the rearward red strobe light lenses shall be replaced with amber.

g. When specified, all red warning and strobe light lenses shall be replaced with blue.

h. The BFT shall be equipped with an electronic siren with cab mounted amplifier unit, capable of: volume control and selection of "Radio", "PA.", "Manual", "Yelp", "Wail" and "Hi-Lo" siren modes and shall have a two-way radio audio tap and microphone. Foot operated activation switches shall be located in front of the driver and passenger's seats. The siren speaker shall be mounted at the front of the truck, within the approach angle, and guarded from damage during off-road operations.

2.1.4 Pumping system.

a. The slip-in fire-fighting module shall include a 250 gallon agent tank, a separate diesel engine driven pumping system capable of delivering 120 gallons per minute (GPM) flow rate at 180 pounds per square inch pump head pressure, and two hose reels with 100 feet of one inch booster hose attached to each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:01Z
Check the source to verify that this is the current version before use.

b. The agent tank shall be fabricated of non-coated materials that can survive the stresses of off-road operation, and shall be capable of containing low quality water, from brackish to clear, without corrosion. The top of the tank shall have a manhole installed or shall be removable, to allow access to all compartments of the tank. In addition to the standard tank fill connection, a 2 ½ inch female connection, with a check valve and a chained on plug, shall be located at the rear of the truck. The fill rate of the 2 ½ inch connection shall be 250 GPM at 80 per square inch gauge (PSIG). The agent tank vent and overflow piping shall be capable of compensating for the maximum fill or pumping rates.

c. The pump shall be an all bronze design and shall be connected with corrosion resistant piping or hoses to the agent tank and the hose reels. Discharge lines shall slope up from the pump discharge to the hose reel connections. An impeller housing drain valve shall be provided and controlled from the rear of the truck.

d. The pump engine shall be connected to the truck chassis electrical and fuel systems. The pump engine shall be capable of starting at 0 degrees F. The starter controls shall be accessible from the rear of the BFT while standing on the ground. Engine/pump impeller speed shall be regulated by an adjustable discharge head pressure sensor.

e. The hose reels shall be equipped with adjustable friction brakes, four way hose guides, electric and manual rewinds. Electric and manual rewind functions shall be capable of being performed while standing on the ground. The manual rewind handle shall be provided and mounted inside a compartment. An air fitting shall be provided at each hose reel for the purpose of blowing water out of the hoses.

2.1.5 Utility body.

a. Provide an aluminum utility body, with a minimum of 50 cubic feet of compartment storage space and a rear access load area for the slip-in agent tank, pumping and hose reel module. The tops of the compartments and the center load area shall be decked with diamond tread and shall support a person's weight without permanent deflection.

b. All compartments shall be accessible while standing on the ground. Compartment floor shall support a minimum of 200 pounds of equipment without permanent deflection. At least one compartment shall be long enough to store shovels, rakes and hoes. Provide drip rails over each or combined compartment doors.

c. Compartment doors may be of a double wall design, hinged at front or hinged at top arrangement or of a counterbalanced roll-up design.

d. Provide a lighted license plate bracket at the left rear of the truck.

2.1.6 Brush guard protection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:01Z
Check the source to verify that this is the current version before use.

a. The BFT shall be equipped with the full complement of brush rails, grille guards and skid plates. Additional structural steel tubing and reinforced expanded flattened metal shall protect the approach angle of the BFT.

b. Metal edges shall be rolled over or welded to tubing to eliminate exposed sharp edges.

c. Guards shall protect the warning lights on the cab roof and the utility body.

2.1.7 Finish.

a. Exterior surfaces of the BFT shall be finished in Red, NO. 11136, Lime Yellow, NO. 13670, or Forest Green, NO. 24052, of FED-STD-595, as specified at time of purchase.

b. With Red or Lime Yellow colors, the cab upper body (from the bottom of windshield up) and the cab roof shall be painted White, NO. 17875 of FED-STD-595. Interior compartment surfaces shall be finished in accordance with commercial practice. A horizontal reflective band shall be applied around the truck in an approximate plane with the headlights. Offsets in the band shall be made to maximize the length of reflective surface. The reflective band may be interrupted where bright metal trim or tread plate occurs. The reflective band pattern shall be seven inches wide with three white reflective stripes: one inch white reflective, one inch body color, three inches white reflective, one inch body color, and one inch white reflective. All chrome or polished metal parts, hinges and treadplate shall not be painted.

c. When Forest Green color is specified, all surfaces, including all normally bright metal and the interior surfaces visible with any compartment door open, shall be painted Forest Green. A four inch wide horizontal black reflective band shall be applied around the truck in an approximate plane with the headlights. Offsets in the band shall be made to maximize the length of reflective surface.

3. **REGULATORY REQUIREMENTS.**

3.1 The offeror/contractor is encouraged to use recovered materials in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

3.1.1 For the purpose of this requirement, recovered materials are those materials that have been collected from solid waste and reprocessed to become a source of raw materials, as distinguished from virgin raw materials. The components, pieces and parts incorporated in the vehicle may be newly fabricated from recovered materials to the maximum extent practicable, provided the vehicle produced meets all other requirements of this CID. Used, rebuilt or re-manufactured components, pieces and parts shall not be incorporated.

4. **QUALITY ASSURANCE PROVISIONS.**

4.1 Product conformance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:01Z
Check the source to verify that this is the current version before use.

4.1.1 The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

4.2 Commercial item requirement.

4.2.1 The vehicle furnished must meet the “commercial item” definition, as specified in FAR 2.101, as of the date of award. The government reserves the right to ask the offeror/ contractor to prove that their product meets the referenced commerciality requirements. The offeror/contractor shall provide two copies of their commercial descriptive catalogs with their offer, as specified in Clause I106. The offeror/contractor shall identify all modifications made to their commercial model in order to meet the performance and descriptive requirements of the CID or referenced documents. In regard to the offered item, the offeror/contractor shall identify any/all variations from compliance with or modifications to the performance requirements of the CID or the referenced documents.

4.3. Contractor requirements.

4.3.1 The contractor shall provide, at the time of delivery, two sets of manuals, including operation, maintenance and parts with each truck delivered. The part's manuals shall list the contractor's component part numbers and the component and equipment manufacturer's part numbers, as applicable. Manuals shall be provided for review 30 days prior to the time of demonstration. The contractor shall provide a product familiarization video tape with each truck, that verbally and visually provides the users with all information required for operation and routine maintenance of the truck and its components, using the commercial manuals as a baseline.

4.4 Testing.

4.4.1 The first production truck shall be demonstrated to the purchaser, prior to delivery, for compliance with the requirements of this CID, the referenced document, and tests 4.4.3 through 4.4.6, by the Contractor, at his facility. Production trucks shall perform tests 4.4.3 and 4.4.6.

4.4.2 Failure to comply with the requirements of the CID, reference documents, or the tests identified herein shall be cause for reconfiguration and retest. Causes for reconfiguration shall include: structural failure; misalignment or interference between components; conditions presenting a safety hazard to the user or maintainer; instability in handling during on and off-road operation; spillage of fuel or coolant; and/or overheating.

4.4.3 Examination of product. A check list of specific requirements from the CID and reference documents shall be compared to the final configuration of the truck. Where specific certifications are required, copies shall be provided.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:01Z
Check the source to verify that this is the current version before use.

4.4.4 Performance test. The top speed, acceleration, braking, gradeability and the turning diameter, of 2.1.1, of a fully loaded truck shall be demonstrated. If site conditions do not exist for gradeability tests, calculations will be accepted.

4.4.5 Sound test. Sound reading shall be taken at the inside and outside ear level of each seated position to demonstrate compliance with reference documents.

4.4.6 Operational test. Each compartment shall be uniformly loaded to the individual maximum design capacity. Each cab seat shall be loaded with 250 pounds. The fully loaded truck shall be driven over 10 miles of paved and ten miles of off-road terrains. All loads shall be removed and all surfaces inspected for permanent deflection.

5. **PACKAGING.**

5.1 Preservation and packaging shall be the minimum necessary to afford protection against corrosion, deterioration and physical damage during shipment from the supply source to the first receiving activity.

5.2 Unless otherwise provided in the contract, the truck shall be prepared for delivery by common carrier. An identification plate, permanently marked, shall be securely mounted at the driver's compartment. The identification plate shall contain the following information:

NOMENCLATURE
MANUFACTURER'S MAKE AND MODEL
MANUFACTURER'S SERIAL NUMBER
REGISTRATION NUMBER
NATIONAL STOCK NUMBER (NSN)
VEHICLE CURB WEIGHT: kg(pounds)
PAYLOAD, MAXIMUM: kg(pounds)
GROSS VEHICLE WEIGHT (GVW): kg(pounds)
GROSS VEHICLE WEIGHT RATING: kg(pounds)
DATE OF DELIVERY (month and year)
WARRANTY (month and km(miles))
CONTRACT NUMBER
US PROPERTY

6. **NOTES.**

6.1 Options.

6.1.1 The purchaser shall specify the following at time of purchase:

a. If a chassis winterization system is required, (see 2.1.2.j.).

b. If a cab air conditioning system is required, (see 2.1.2.k.).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:01Z
Check the source to verify that this is the current version before use.

c. If alternating flashing headlights are required, (see 2.1.3.e.).

d. If amber colored rear warning lights are required, (see 2.1.3.f.).

e. If all red warning lights shall be replaced with blue, (see 2.1.3.g.).

f. Finish color of BFT (Red, Lime Yellow or Forest Green), (see 2.1.7.a.).

CUSTODIAN:
AIR FORCE - 99

PREPARING ACTIVITY:
AIR FORCE - 84

REVIEWER:
DLA - CS

AGENT:
AIR FORCE - 99

Project Number: 4210-0002

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:01Z
Check the source to verify that this is the current version before use.