INCH-POUND

MIL-DTL-14639/33B
20 January 2004
SUPERSEDING
MIL-DTL-14639/33A
30 January 1998

DETAIL SPECIFICATION SHEET

INSIGNIA, RANK, CAPTAIN, NAVY AND COLONEL, ARMY, AIR FORCE, AND MARINE CORPS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-14639.



DASH NO.
- -1: Regular Size, Army and Air Force
- -2: Miniature Size, Army and Air Force
- -3: Regular Size, Subdued, Army and Air Force
- -4: Regular Size, Navy and Marine Corps
- -5: Miniature Size, Navy and Marine Corps

MATERIAL:
- -1, -2, -4, -5: Red Brass or Nickel Silver
- -3: Red Brass or Zinc Aluminum

DIMENSIONS:

HEIGHT (overall):
- -1, -3, -4: 3/4 inch (REF)
- -2, -5: 1/2 inch (REF)

WIDTH (overall):
- -1, -3, -4: 1-1/2 inches (REF)
- -2, -5: 31/32 inch (REF)

THICKNESS (on shield):
- -1, -3, -4: 0.100 inch ± 0.005 inch
- -2, -5: 0.080 inch ± 0.005 inch

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:05Z
Check the source to verify that this is the current version before use.

FINISH:

-1, -2: Nickel Plated (Red Brass only), Mirror-like Polished, and shall match TIOH Metal Finish Chip Number 16.
-3: Dull Flat Black Baked Enamel.
-4, -5: Nickel Plated (Red Brass only), Rhodium Plated, Mirror-like Polished

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Attaching device shall be prong and clutch type. Location of prongs shall be as follows:

a. -1, -3, -4: Prongs shall be located on the horizontal center line 1/8 inch ± 1/64 inch below the top of the wings, equidistant from each end and 1 inch ± 1/64 inch apart.

b. -2, -5: Prongs shall be located on the horizontal center line 1/16 inch ± 1/64 inch below the top of the wings, equidistant from each end and 5/8 inch ±1/64 inch apart.

3. -1, -3, -5 shall be dapped in the horizontal plane along a 4 inch ± 1/64 inch radius.

4. The dull flat black enamel for -3 shall match Color Chip No. 37038 from FED-STD-595.

5. Insignia are to be made and packaged in pairs with one eagle facing right and one eagle facing left.

6. Navy and Marine Corps insignia may be made from sterling silver for commercial sale and, if so, the thickness dimensions are for reference only. A minimum weight of 52 grains for -4 and 18 grains for -5 shall govern. The finish shall be mirror-like polished.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH
Air Force - 11
Navy - NU

Preparing activity:
Army - IH
(Project No. 8455-0135/001)

Review activities:
Navy - MC
DLA - CT

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at www.dodssp.daps.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:05Z
Check the source to verify that this is the current version before use.