INCH-POUND

MIL-DTL-14639/33D
4 October 2016
SUPERSEDING
MIL-DTL-14639/33C
15 November 2011

DETAIL SPECIFICATION SHEET

INSIGNIA, RANK, CAPTAIN, NAVY AND COLONEL, ARMY, AIR FORCE AND MARINE CORPS

This specification is approved for use by all
Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-14639.



DASH NO.
-1: Regular Size, Army and Air Force
-2: Miniature Size, Army and Air Force
-3: Regular Size, Subdued, Army, Air Force and Marine Corps
-4: Regular Size, Navy and Marine Corps
-5: Miniature Size, Navy and Marine Corps

MATERIAL:
-1, -2, -4, -5: Red Brass 85/15 (UNS Alloy No. C-230) or Nickel Silver 65/35 (UNS Alloy No. C-752)
-3: Red Brass 85/15 (UNS Alloy No. C-230) or Zinc Aluminum

FINISH:
-1, -2: Nickel Plated (Red Brass only), Mirror-like Polished, and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 16.
-3: Dull Flat Black and shall match TIOH metal Finish Chip Number 21.
-4, -5: Nickel Plated (Red Brass only), Mirror-like Polished, and shall match TIOH metal Finish Chip Number 16

DIMENSIONS:
HEIGHT (Overall):
-1, -3, -4: 3/4 inch (REF)
-2, -5: 1/2 inch (REF)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:05Z
Check the source to verify that this is the current version before use.

WIDTH (Overall):
-1, -3, -4: 1-1/2 inches (REF)
-2, -5: 31/32 inch (REF)
THICKNESS (On shield):
-1, -3, -4: 0.100 inch ± 0.005 inch
-2, -5: 0.080 inch ± 0.005 inch

ATTACHING DEVICE:

1. Attaching device shall be prong and wing clutch type.

2. Location of prongs shall be as follows: -1, -3, -4: Prongs shall be located on the horizontal center line 1/8 inch ± 1/64 inch below the top of the wings, equidistant from each end and 1 inch ± 1/64 inch apart. -2, -5: Prongs shall be located on the horizontal center line 1/16 inch ± 1/64 inch below the top of the wings, equidistant from each end and 5/8 inch ±1/64 inch apart.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. -1, -3, -5 shall be dapped in the horizontal plane along a 4 inch ± 1/64 inch radius.

3. Insignia are to be made and packaged in pairs with one eagle facing right and one eagle facing left.

4. Navy and Marine Corps insignia may be made from sterling silver for commercial sale and, if so, the thickness dimensions are for reference only. A minimum weight of 52 grains for -4 and 18 grains for -5 shall govern. The finish shall be mirror-like polished.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH
Navy - NU
Air Force - 11

Preparing activity:
Army - IH

Review activities:
Navy - MC
DLA - CT

(Project No. 8455-2016-766)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:05Z
Check the source to verify that this is the current version before use.