NOT MEASUREMENT SENSITIVE

MIL-DTL-14639/43B
12 April 2021
SUPERSEDING
MIL-DTL-14639/43A
27 May 2016

DETAIL SPECIFICATION SHEET

INSIGNIA, RANK, LIEUTENANT (JG) AND ENSIGN U.S. NAVY, LIEUTENANT AND SECOND LIEUTENANT, U.S. MARINE CORPS

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-14639.

DASH NO.
-1: Lieutenant (JG), Navy and First Lieutenant, Marine Corps, Regular Size
-2: Lieutenant (JG), Navy and First Lieutenant, Marine Corps, Miniature Size
-3: Ensign, Navy and Second Lieutenant, Marine Corps, Regular Size
-4: Ensign, Navy and Second Lieutenant, Marine Corps, Miniature Size

MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230) or Nickel Silver 65/35 (UNS Alloy No. C-752)

FINISH:
-1,-2: Nickel Plated, Rhodium Plated, Mirror-like Polished and shall match The Institute of heraldry (TIOH) Metal Finish Chip Number 16.

-3,-4: 24K Gold Plated, Mirror-like Polished and shall match (TIOH Metal Finish Chip Number 6.

DIMENSIONS:
HEIGHT (Overall):
-1, -3: 3/8 inch (REF)
-2, -4: 1/4 inch (REF)
WIDTH (Overall):
-1, -3: 1-1/8 inches (REF)
-2, -4: 3/4 inch (REF)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:09Z
Check the source to verify that this is the current version before use.

THICKNESS (At edge):
-1, -3: 0.070 inch ± 0.005 inch
-2, -4: 0.050 inch ± 0.005 inch
ATTACHING DEVICE:
1. Attaching device shall be prong and wing clutch type.

2. Prongs shall be located on the vertical center line, equidistant from each end and the following distance apart: For -1,-3: 13/16 inch ± 1/64 inch and -2,-4: 9/16 inch ± 1/64 inch

3. For -1 and -3 shall be dapped along a radius of 5 inch ± 1/64 inch radius on a horizontal plane.

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. For -1 and -3 may be made from sterling silver for commercial sale and if so, the thickness dimensions are for reference only. A minimum weight of 70 grains for -1 and 25 grains for - 2 shall govern. The finish shall be as specified except the nickel plating requirement shall not apply.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH
Navy - NU

Preparing activity:
Army - IH

Review activities:
Navy - MC
DLA - CT

(Project No. 8455-2021-339)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:09Z
Check the source to verify that this is the current version before use.