NOT MEASUREMENT SENSITIVE

MIL-DTL-14639/45
20 December 1996
SUPERSEDING
MIL-I-3949/13D
20 March 1995

DETAIL SPECIFICATION SHEET

INSIGNIA, RANK, COMMANDER AND LIEUTENANT COMMANDER, NAVY AND LIEUTENANT COLONEL AND MAJOR, MARINE CORPS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-14639 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

DASH NO.
- -1: Commander, Navy and Lieutenant Colonel, Marine Corps, Regular Size
- -2: Commander, Navy and Lieutenant Colonel, Marine Corps, Miniature Size
- -3: Lieutenant Commander, Navy and Major, Marine Corps, Regular Size
- -4: Lieutenant Commander, Navy and Major, Marine Corps, Miniature Size

MATERIAL: Red Brass or Nickel Silver

DIMENSIONS:
- HEIGHT (Overall):
  - -1,-3: 1 inch (2.54 cm) (REF)
  - -2,-4: 23/32 inch (1.83 cm) (REF)
- WIDTH (Overall):
  - -1,-3: 15/16 inch (2.38 cm) (REF)
  - -2,-4: 5/8 inch (1.59 cm) (REF)
- THICKNESS:
  - -1,-3 (At Edge): 0.040 inch ± 0.005 inch (0.101 cm ± 0.012 cm)
  - -2,-4 (At Center): 0.100 inch ± 0.005 inch (0.254 cm ± 0.012 cm)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:09Z
Check the source to verify that this is the current version before use.

FINISH:
-1,-2: Nickel Plated, Rhodium Plated, Brightly Polished.
-3,-4: Gold Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 6.

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Attaching device shall be prong and clutch type. Prongs shall be located on the vertical center line, equidistant from each end and the following distance apart:

-1,-3: 3/4 inch ± 1/32 inch (1.91 cm ± 0.08 cm)
-2,-4: 15/32 inch ± 1/64 inch (1.19 cm ± 0.04 cm)

3. Dash No. -1 and -3 shall be spherically dapped to a radius of 1 inch ± 1/64 inch (2.54 cm ± 0.04 cm).

4. A forcer may be used to bring up the design for Dash No. -1 and -3.

5. A minimum thickness of 0.035 inch (0.088 cm) shall be maintained throughout for Dash No. -1 and -3.

6. Insignia may be made from sterling silver for commercial sale and if so, the thickness dimensions are for reference only. A minimum weight of 84 grains for Dash No. -1 and 36 grains for Dash No. - 2 shall govern. The finish shall be as specified except the nickel plating requirement shall not apply.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH
Navy - NU

Preparing activity:
Army - IH

Review activities:
Navy - MC
DLA - CT

(Project No. 8455-0874)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:09Z
Check the source to verify that this is the current version before use.