The documentation and process conversion measures necessary to comply with this amendment shall be completed by 8 August 1998.

INCH POUND

MIL-PRF-19500/116K
AMENDMENT 2
8 May 1998
SUPERSEDING
AMENDMENT 1
18 April 1997

PERFORMANCE SPECIFICATION SHEET

SEMICONDUCTOR DEVICE, DIODE, SILICON, SWITCHING
TYPES 1N914, 1N914UR, 1N4148-1, 1N4148UR-1, 1N4148UB, 1N4531, AND 1N4531UR,
JAN, JANTX, JANTXV, JANHC, AND JANKC

PAGE 1

* 1.3, maximum rating table, I_{FSM} column, 1N4148UB row, delete "1" and substitute "2".

* 1.4, table, type column, add "1/", below table, add "1/ Electrical characteristics for surface mount devices are equivalent to the corresponding non surface mount devices unless otherwise noted."

PAGE 8

* 4.3, screen 10, screen number column, add "2/", JANTX and JANTXV column, delete as added in amendment 1 and substitute "method 1038, condition A, t = 48 hrs"; screen 13, delete "2/".

* 4.3.1, delete burn-in conditions table and replace as follows:

"

TYPE	T_A + 30°C +/- 5 °C V_{RWM} = 75 V (pk) f = 50 - 60 Hz	T_A = 30°C +/- 5°C
1N914, 1N914UR	I_O = 75 mA	I_F = 150 mA min
1N4531, 1N4531UR	I_O = 125 mA	I_F = 5 mA min
1N4148-1, 1N4148UR-1, 1N4148UB	I_O = 200 mA	I_F = 200 mA min

"

* 4.4.2, second sentence, delete “group A, subgroup 2 herein” and substitute “group A, subgroup 2 herein except for the thermal impedance test.”.

PAGE 9

* 4.4.3, second sentence, delete “group A, subgroup 2 herein” and substitute “group A, subgroup 2 herein except for the thermal impedance test.”; subgroup C2 (second occurrence), conditions, delete "UB" and substitute "UB or UR".

PAGE 10

* 4.5.7.1, delete paragraph number and substitute "4.5.6.1".

* 4.5.7.2, delete paragraph number and substitute "4.5.6.2".

PAGE 12

* TABLE I, subgroup 4, reverse recovery time, conditions column, delete " I_{RR} = 1.0 mA dc" and substitute " $i_{R(REC)}$ = 1.0 mA dc".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:15Z
Check the source to verify that this is the current version before use.

PAGE 14

* TABLE II, subgroup 2, inspection column, delete "steady-state dc"; subgroup 4, delete "4.5.7" and substitute "4.5.6" (two occurrences each); thermal resistance leaded devices test, conditions column, delete "T_H " and substitute "t_H "**;** subgroup 5, delete "4.5.6"; subgroup 5, conditions column, add "not required for UB suffix devices.".

NOTE: The margins of this amendment are marked with asterisks to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 17

Review activities:
Army - AR, MI, SM
Navy - AS, CG, MC
Air Force - 19, 85, 99

Preparing activity:
DLA - CC

(Project 5961-1948)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:15Z
Check the source to verify that this is the current version before use.