INCH-POUND

MIL-PRF-19500/120D
W/AMENDMEMT 1
18 November 2020
SUPERSEDING
MIL-PRF-19500/120D
12 June 2015

The documentation and process conversion measures necessary to comply with this document shall be completed by 16 March 2021.

PERFORMANCE SPECIFICATION SHEET

TRANSISTOR, NPN, SILICON, SWITCHING, LOW-POWER,
THROUGH-HOLE MOUNT, TYPE 2N706, QUALITY LEVEL JAN

Inactive for new design after 7 June 1999.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-19500.

1. SCOPE

1.1 Scope. This specification covers the performance requirements for NPN, silicon, switching, medium power transistors. One level of product assurance (JAN) is provided for encapsulated devices.

1.2 Package outlines. The device package outline is a modified TO-206AA (formerly TO-18) in accordance with figure 1 for all encapsulated device types.

1.3 Maximum ratings. Unless otherwise specified, T_A = +25 °C.

P_T (1) T_A = +25 °C	V_{CBO}	V_{EBO}	V_{CEO}	V_{CER}	$R_{\theta JA}$	T_{STG}
mW	V dc	V dc	V dc	V dc	°C/W	°C
300	25	5.0	15	20	500	-65 to +200

(1) Derate linearly 2.0 mW/°C for T_A > +25 °C.

1.4 Primary electrical characteristics. Unless otherwise specified, T_A = +25 °C.

Limits	h_{FE1} V_{CE} = 1.0 V dc I_C = 10 mA dc	$\lvert h_{FE} \rvert$ V_{CE} = 10 V dc I_C = 10 mA dc f = 100 MHz	$V_{CE(sat)}$ I_C = 10 mA dc I_B = 1.0 mA dc	$V_{BE(sat)}$ I_C = 10 mA dc I_B = 1.0 mA dc	Switching		
					t_s	t_{on}	t_{off}
			V dc	V dc	nsec	nsec	nsec
Min	30	2.0	---	0.7	5.0	---	---
Max	120	7.0	0.5	0.9	35	40	75

Comments, suggestions, or questions on this document should be addressed to DLA Land and Maritime, ATTN: VAC, P.O. Box 3990, Columbus, OH 43218-3990, or emailed to Semiconductor@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A

FSC 5961

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:17Z
Check the source to verify that this is the current version before use.

1.5 Part or Identifying Number (PIN). The PIN is in accordance with MIL-PRF-19500, and as specified herein. See 6.4 for PIN construction example, 6.5 for a list of available PINs, and 6.6 for supersession information.

1.5.1 JAN certification mark and quality level. The only quality level designator for encapsulated devices that is applicable for this specification sheet is the base quality level "JAN" that uses no modifiers.

1.5.2 Device type. The designation system for the device types of transistors covered by this specification sheet are as follows.

1.5.2.1 First number and first letter symbols. The transistors of this specification sheet use the first number and letter symbols "2N".

1.5.2.2 Second number symbols. The only second number symbol for the transistors covered by this specification sheet is "706".

1.5.3 Suffix symbols. Suffix symbols are not applicable for this specification sheet.

1.5.4 Lead finish. The lead finishes applicable to this specification sheet are listed on QPDSIS-19500.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-PRF-19500 – Semiconductor Devices, General Specification for.

DEPARTMENT OF DEFENSE STANDARDS


MIL-STD-750 – Test Methods for Semiconductor Devices.

(Copies of these documents are available online at https://quicksearch.dla.mil.)

2.3 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:17Z
Check the source to verify that this is the current version before use.

Symbol	Dimensions				Note
	Inches		Millimeters		
	Min	Max	Min	Max	
CD	.178	.195	4.52	4.95	3
CH	.170	.210	4.32	5.33	
HD	.209	.230	5.31	5.84	3
LC	.100 TP		2.54 TP		4
LD	.016	.021	0.41	0.53	5
LL	.5	.75	12.7	19	5
LU	.016	.019	0.41	0.48	5
L_1		.050		1.27	5
L_2	.250		6.35		5
P	.100		2.54		
Q		.030		0.76	3
TL	.028	.048	0.71	1.22	6, 7
TW	.036	.046	0.91	1.17	
r		.010		0.25	8
α	45° TP		45° TP		4



NOTES:

1. Dimensions are in inches. Millimeters are given for general information only.
2. Terminal 1 = emitter, terminal 2 = base, terminal 3 = collector. The collector shall be internally connected to the case.
3. Body contour optional within zone defined by HD, CD, and Q.
4. Leads at gauge plane .054 +.001 -.000 inch (1.37 +0.03 -0.00 mm) below seating plane shall be within .007 inch (0.18 mm) radius of true position (TP) at maximum material condition (MMC) relative to tab at MMC. The device may be measured by direct methods or by gauging procedure.
5. Dimension LU applies between L_1 and L_2. Dimension LD applies between L_2 and LL minimum. Diameter is uncontrolled in L_1 and beyond LL minimum. Applies to all three leads.
6. Dimension TL measured from maximum HD.
7. Beyond r (radius) maximum, TL shall be held for a minimum length of .011 (0.28 mm).
8. Dimension r (radius) applies to both inside corners of tab.
9. In accordance with ASME Y14.5M, diameters are equivalent to Øx symbology.

FIGURE 1. Physical dimensions and configuration of modified TO-206AA (formerly TO-18) package.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:17Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 General. The individual item requirements shall be as specified in MIL-PRF-19500 and as specified herein.

3.2 Qualification. Devices furnished under this specification shall be products that are manufactured by a manufacturer authorized by the qualifying activity for listing on the applicable qualified manufacturer's list (QML) before contract award (see 4.2 and 6.3).

3.3 Abbreviations, symbols, and definitions. The abbreviations, symbols, and definitions used herein shall be as specified in MIL-PRF-19500.

3.4 Interface requirements and physical dimensions. The interface requirements and physical dimensions shall be as specified in MIL-PRF-19500 and herein. The device package style is a modified TO-206AA in accordance with figure 1 for all device types.

3.4.1 Lead finish. Unless otherwise specified, lead finish shall be solderable in accordance with MIL-STD-750, MIL-PRF-19500, and herein. Where a choice of lead finish is desired, it shall be specified in the acquisition document (see 6.2).

3.4.2 Pin-out. The pin-out of the device shall be as shown on figure 1. Terminal 1 is the emitter, terminal 2 is the base, and terminal 3 is the collector. The collector shall be electrically connected to the case.

3.5 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics shall be as specified in 1.3, 1.4, and table I herein.

3.6 Marking. Marking shall be in accordance with MIL-PRF-19500.

3.7 Workmanship. The devices covered by this specification sheet shall be processed in such a manner as to be uniform in quality and shall be free from other defects that will affect life, serviceability, or appearance.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Screening (see 4.3).

c. Conformance inspection (see 4.4 and tables I and II).

4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL-PRF-19500, and as specified herein.

4.2.1 Group E qualification. Group E inspection shall be performed for qualification or re-qualification only. In case qualification was awarded to a prior revision of the specification sheet that did not request the performance of table II tests, the tests specified in table II herein that were not performed in the prior revision shall be performed on the first inspection lot of this revision to maintain qualification.

4.3 Screening. Screening is not applicable for devices compliant to this specification sheet.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:17Z
Check the source to verify that this is the current version before use.

4.4 Conformance inspection. Conformance inspection shall be in accordance with MIL-PRF-19500, and as specified herein.

4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with MIL-PRF-19500 and table I herein. Electrical measurements (end-points) shall be in accordance with table I, subgroup 2 herein.

4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the tests and conditions specified for subgroup testing in table E-VIB of MIL-PRF-19500 and herein.

Subgroup	Method	Conditions
B3	1027	T_A = +25 °C, P_T = 300mW, V_{CB} = 15V dc, t = 340 hours.

4.4.3 Group C inspection. Group C inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-VII of MIL-PRF-19500 and as follows herein.

Subgroup	Method	Conditions
C1	1051	Test condition C; 25 cycles exposure time at temperature extremes = 15 minutes (min); test to be completed within 72 hours.
C2	2036	Test condition E.
C6	1026	T_A = 25 °C; P_T = 300 mW; V_{CB} = 15 V d.

4.4.4 Group E inspection. Group E inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-IX of MIL-PRF-19500 and as specified in table II herein.

4.5 Method of inspection. Methods of inspection shall be as specified in the appropriate tables and as follows.

4.5.1 Thermal impedance. The thermal impedance measurements shall be performed in accordance with method 3131 of MIL-STD-750 using the guidelines in that method for determining V_H, V_{CE}, I_M, I_H, t_H, t_{SW}, and t_{MD}. The thermal impedance limit used in table I, subgroup 2 shall be set statistically by the supplier submitted to the qualifying activity for approval. See table II, subgroup 4 and figure 2 herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:17Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection.

Inspection 1/	MIL-STD-750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 1						
Visual and mechanical examination	2071					
Subgroup 2						
Thermal impedance 2/	3131	See 4.5.1	ΔV_{BE}			mV
Collector to base, breakdown to voltage	3001	Bias condition D, I_C = 100 µA dc	$V_{(BR)CBO}$	25		V dc
Collector to emitter breakdown voltage	3011	Bias condition D, I_C = 10 mA dc	$V_{(BR)CEO}$	15		V dc
Emitter to base, breakdown to voltage	3026	Bias condition D, I_E = 100 µA dc	$V_{(BR)EBO}$	5.0		V dc
Collector to emitter breakdown voltage	3011	Bias condition B, I_C = 50 mA dc, R_{BE} = 10 ohms, tp = 167 µsec, duty cycle 1 percent	$V_{(BR)CER}$	20		V dc
Collector to base, cutoff current	3036	Bias condition D, V_{CB} = 15 V dc	I_{CBO1}		0.1	µA dc
Forward-current transfer ratio	3076	V_{CE} = 1.0 V dc, I_C = 10 mA dc	h_{FE1}	30	120	
Forward-current transfer ratio	3076	V_{CE} = 1.0 V dc, I_C = 0.1 mA dc	h_{FE2}	10		
Forward-current transfer ratio	3076	V_{CE} = 1.0 V dc, I_C = 1.0 mA dc	h_{FE3}	20		
Collector to emitter voltage (saturated)	3071	I_C = 10 mA dc, I_B = 1.0 mA dc	$V_{CE(sat)}$	---	0.5	V dc
Base emitter voltage (saturated or nonsaturated)	3066	Test condition A; I_C = 10 mA dc, I_B = 1.0 mA dc	$V_{BE(sat)}$	0.7	0.9	V dc
Magnitude of common emitter small-signal, short-circuit forward-current transfer ratio	3306	V_{CE} = 10 V dc, I_C = 10 mA dc, f = 100 MHz	$\lvert h_{FE} \rvert$	2.0	7.0	
Open circuit output capacitance	3236	V_{CB} = 10 V dc, I_E = 0, 100 kHz ≤ f ≤ 1 MHz	C_{obo}		6.0	pf

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:17Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection – Continued.

Inspection 1/	MIL–STD–750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 2 − continued						
Input capacitance (output open-circuit)	3240	V_{EB} = 0.5 V dc, I_C = 0, 100 kHz ≤ f ≤ 1 MHz	C_{ibo}		9.0	pf
Subgroup 3						
High temperature operation		T_A = +150 °C				
Collector to base cut-off current	3036	Bias condition D; V_{CB} = 15 V dc	I_{CBO2}		20	µA dc
Low temperature operation		T_A = -55 °C				
Forward-current transfer ratio	3076	V_{CE} = 10 V dc, I_C = 10 mA dc	h_{FE}	12		
Subgroup 4						
Charge-storage time		See figure 3	t_s		35	nsec
Turn-on time		See figure 4	t_{on}	---	40	nsec
Turn-off time		See figure 4	t_{off}	---	75	nsec
Subgroups 5 and 6						
Not applicable						

1/ For sampling plan, see MIL-PRF-19500.
2/ This test required for the following end-point electrical measurements only:
Group B, subgroups 3, 4 and 5 (JANS).
Group B, subgroups 2 and 3 (JAN, JANTX, JANTXV).
Group C, subgroups 2 and 6.
Group E, subgroup 1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:17Z
Check the source to verify that this is the current version before use.

TABLE II. Group E inspection (all quality levels) − for qualification and requalification only.

Inspection	MIL-STD-750		Sample plan
	Method	Conditions	
Subgroup 1			45 devices, c = 0
Temperature cycling (air to air)	1051		
Hermetic seal	1071	Fine and gross leak.	
End-point electrical measurements		See table I, subgroup 2 herein.	
Subgroup 2			45 devices, c = 0
Intermittent operation life	1037	T_A = 25 °C, P_T = 300 mW, V_{CB} = 15 V dc, adjust device current, or power, to achieve a minimum delta T_J of +100 °C.	
End-point electrical measurements		See table I, subgroup 2 herein.	
Subgroup 4			Sample size N/A
Thermal impedance curves		See table E-IX, subgroup 4 of MIL-PRF-19500.	
Subgroup 5			
Not applicable			
Subgroup 8			45 devices, c = 0
Reverse stability	1033	Condition B.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:17Z
Check the source to verify that this is the current version before use.





FIGURE 2. Thermal impedance graph (TO-206AA) ($R_{\theta JA}$).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:17Z
Check the source to verify that this is the current version before use.




VOLTAGE WAVEFORMS

NOTES:
1. The input waveform is supplied by a pulse generator with the following characteristics: Zout = 50 ohm, $t_r \leq 1$ nsec, PW ≥ 300 nsec, duty cycle ≤ 2 percent.
2. Output waveforms are monitored on a sampling oscilloscope with the following characteristics: $Z_{in} \geq 100$ K ohms, $t_r \leq 1$ nsec.

FIGURE 3. Charge storage time.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:17Z
Check the source to verify that this is the current version before use.



VOLTAGE WAVEFORMS

NOTES:

1. V_{BB} = -4.0 V dc for t_{ON}, +17.0 V dc for t_{off}.
2. The input waveform is supplied by a pulse generator with the following characteristics: Zout = 50 ohm, $t_r \leq 1$ nsec, PW ≥ 300 nsec, duty cycle ≤ 2 percent.
3. Output waveforms are monitored on a sampling oscilloscope with the following characteristics: $Z_{in} \geq 100$ K ohms, $t_r \leq 1$ nsec.

FIGURE 4. Turn-on and turn-off time test circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:17Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the Military Service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory. The notes specified in MIL-PRF-19500 are applicable to this specification.)

6.1 Intended use. Semiconductors conforming to this specification are intended for original equipment design applications and logistic support of existing equipment.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.


b. Packaging requirements (see 5.1).

c. Lead finish (see 3.4.1).

d. The complete PIN, see 1.5 and 6.4.

6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Manufacturers List (QML 19500) whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from DLA Land and Maritime, ATTN: VQE, P.O. Box 3990, Columbus, OH 43218-3990 or e-mail vqe.chief@dla.mil. An online listing of products qualified to this specification may be found in the Qualified Products Database (QPD) at https://qpldocs.dla.mil.

6.4 PIN construction example. The PINs for encapsulated devices are constructed using the following form.



6.5 List of PINs. There is currently only one possible PIN available on this specification sheet. It is JAN2N706.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:17Z
Check the source to verify that this is the current version before use.

6.6 Supersession information and superseded PINs.

6.6.1 Lead finish. The original issue of this specification through MIL-S-19500/120B (26 June 1963) did not specify a lead finish. MIL-S-19500/120C (15 April 1970) specified that the lead finish as "gold (as specified in MIL-STD-1276)". That same revision also allowed for "tin-coated over gold". Tin is no longer acceptable as a lead finish. Later amendments such as MIL-S-19500/120C with amendment 2 (7 August 1974) changed the lead finish to "gold or tin-plated".

6.6.2 Lead material. Because of the performance format of this document, lead material is no longer specified.

6.7 Amendment notations. The margins of this specification are marked with vertical bars to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Custodians:
Army − CR
Navy − SH
Air Force − 85
DLA − CC

Review activities:
Army − AR, AV, MI, SM
Navy − AS, CG, MC, OS, SH
Air Force − 19, 70, 170
NASA − NA

Preparing activity:
DLA − CC

(Project 5961−2020−092)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:17Z
Check the source to verify that this is the current version before use.