MILITARY SPECIFICATION

MAINTENANCE KIT, ELECTRICAL CONNECTORS, GENERAL SPECIFICATION FOR

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the general requirements for a maintenance kit used for repair and maintenance of electrical connectors (see 6.1).

1.2 Part number. Part number shall be specified on applicable specification sheet (see 3.1).

2. APPLICABLE DOCUMENTS

2.1 Government documents

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

MMM-A-121	-	Adhesive, Bonding Vulcanized Synthetic Rubber to Steel.
MMM-A-130	-	Adhesive, Contact.
MMM-A-132	-	Adhesive, Heat Resistant, Airframe Structural, Metal to Metal.
MMM-A-134	-	Adhesive, Epoxy Resin, Metal to Metal Structural Bonding.
PPP-C-1752	-	Cushioning Material, Packaging, Unicellular Polyethylene Foam, Flexible.

MILITARY

MIL-C-4150	-	Cases, Transit and Storage, Waterproof and Water-Vaporproof.
MIL-P-19834	-	Plates, Identification or Instruction, Metal Foil, Adhesive Backed, General Specification for.
MIL-C-22520	-	Crimping Tools, Terminal, Hand or Power Actuated, Wire Termination, and Tool Kits, General Specification for.
MIL-T-45542	-	Tool Sets, Shop Sets and Kits, Maintenance, Modification and Tool Packaging of.
MIL-F-81334	-	Foam, Plastic, Flexible, Open Cell, Polyester Type Polyurethane.
MIL-I-81969	-	Installing and Removal Tools, Connector Electrical Contact, General Specification for.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Electronic Support Division, 2750 ABW/ES, Gentile AF Station, Dayton, Ohio 45444, by using the self addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:34Z
Check the source to verify that this is the current version before use.

STANDARDS

FEDERAL

FED-STD-595 - Colors.

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-130 - Identification Marking of US Military Property.
MIL-STD-202 - Test Methods for Electronic and Electrical Component Parts.
MIL-STD-810 - Environmental Test Methods.

(Copies of the specifications and standards required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Specification sheets. The individual item requirements shall be as specified herein and in accordance with the applicable specification sheets. In the event of any conflict between the requirements of this specification and the specification sheet, the latter shall govern.

3.2 Materials. Materials shall be as specified herein. However, when a definite material is not specified, a material shall be used which will enable the kits to meet the performance requirements of this specification and the applicable specification sheet. Acceptance or approval of any constituent material shall not be construed as a guaranty of the acceptance of the finished product.

3.2.1 Cases. Unless otherwise specified (see 3.1), the case shall be of the following categories.

3.2.1.1 Category 1. Ruggedized case shall meet the requirements of MIL-C-4150.

3.2.1.2 Category 2. Environmental case shall meet the following requirements of MIL-STD-810, methods 500, 501 procedure II, 502, 505 procedure II, 506, 507 procedure II, 508, 509, 510, 512 procedure I, 514 procedure XI, 516 procedure II, except drop shall be on top and bottom only, unless otherwise specified.

3.2.1.3 Category 3. Nonenvironmental case shall meet the best commercial practice (see 3.1).

3.2.2 Adhesives. Unless otherwise specified (see 3.1), adhesive shall be in accordance with MMM-A-121, MMM-A-130, MMM-A-132, or MMM-A-134.

3.2.3 Cushioning material. Unless otherwise specified (see 3.1), cushioning material shall be in accordance with PPP-C-1752 or MIL-F-81334.

3.3 Design and construction. Kits shall be of the design, construction, and physical dimensions specified (see 3.1).

3.3.1 Cases. Cases, metal or fiberglass shall be designed as specified (see 3.1).

3.3.2 Color. The kit color shall be in accordance with FED-STD-595.

3.3.3 Installing and removal tools. Unless otherwise specified (see 3.1), all installing and removal tools shall be in accordance with MIL-I-81969, or approved equivalent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:34Z
Check the source to verify that this is the current version before use.

3.3.4 Crimping tools, dies, turret, positioners, and gauges. Unless otherwise specified (see 3.1), all crimping tools, dies, turrets, positioners, and gauges shall be in accordance with MIL-C-22520, or approved equivalent.

3.4 Marking. All marking shall be in accordance with MIL-STD-130 and shall be permanent and legible.

3.4.1 Nameplates. Nameplates on tool cases shall be marked with information as specified (see 3.1). The plates shall be 0.003 to 0.005 inch thick aluminum foil in accordance with MIL-P-19834 and shall be permanently mounted. Marking shall be black on a light background.

3.4.2 Content charts and instruction sheets. Content charts and instruction sheets shall be white vinyl 0.020 inch thick or approved equivalent with black lettering. The lettering shall be protected with a transparent coating.

3.5 Workmanship. The tool cases and tools contained therein shall have no sharp edges, burrs, or other features which are potential personal hazards to the operator during normal usage.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspection. The inspection of the kit shall be classified as follows:

a. Materials inspection (see 4.3).

b. Quality conformance inspection (see 4.5).

4.3 Materials inspection. Materials inspection shall consist of certification supported by verifying data that the materials, as specified herein and on the specification sheet (see 3.1), used in fabricating the kits, are in accordance with the applicable referenced specifications or requirements prior to such fabrication.

4.4 Inspection conditions. Unless otherwise specified herein, all inspections shall be performed in accordance with the test conditions specified in the "GENERAL REQUIREMENTS" of MIL-STD-202.

4.5 Quality conformance inspection.

4.5.1 Inspection of product for delivery. Inspection of product for delivery shall consist of group A inspection.

4.5.1.1 Inspection lot. An inspection lot shall consist of all tool kits covered by a single specification sheet, produced under essentially the same conditions, and offered for inspection at one time.

4.5.1.2 Group A inspection. Group A inspection shall consist of the inspections specified in table I, in the order shown.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:34Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection.

Inspection	Requirement paragraph	Test method paragraph	AQL (percent defective) Major	AQL (percent defective) Minor
Visual and mechanical inspection				
Material	3.1, 3.2	4.6.1	0.65	---
Finish	3.1, 3.2	4.6.1	1.5	---
Marking	3.4	4.6.1	---	2.5
Workmanship	3.5	4.6.1	1.0	---

4.5.1.2.1 Sampling plan. Statistical sampling and inspection shall be in accordance with MIL-STD-105 for general inspection level II. The acceptable quality level (AQL) shall be as specified in table I. Major and minor defects shall be as defined in MIL-STD-105.

4.5.1.2.2 Rejected lots. If an inspection lot is rejected, the contractor may rework it to correct the defects, or screen out the defective units, and resubmit for reinspection. Resubmitted lots shall be inspected using tightened inspection criteria in accordance with MIL-STD-105, level II, for the AQL value specified in table I.

4.5.1.2.3 Disposition of group A sample. The kit which has passed group A inspection may be delivered on the contract if the lot is accepted.

4.5.2 Inspection of packaging. The sampling and inspection of the preservation, packing and container marking shall be in accordance with MIL-T-45542.

4.6 Methods of inspection.

4.6.1 Visual and mechanical inspection. The kit and contents shall be examined to verify that the design, construction, physical dimensions, markings, and workmanship are in accordance with applicable requirements (see 3.1, 3.2, 3.3, 3.4, and 3.5).

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-T-45542 for type I kits. In addition, unit packs and shipping containers shall be marked with the following information.

a. Number (revision and amendment, if applicable) of this commodity specification.

b Military part number and title

c Manufacturer's name.

d. Manufacturer's part number.

e. Month and year inspected.

6. NOTES.

6.1 Intended use. Kits and contents therein covered by this specification are intended to be used for repair and maintenance of electrical connectors, contacts, and other components equipment as specified in MIL-STD-1646.

6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following

a. Title, number, and date of this specification and applicable specification sheet.

b. Military part numbers for tool kits as required.

c. Quantity of kits desired.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:34Z
Check the source to verify that this is the current version before use.

6.3 Subject term (key word) listing.

Connectors, electrical, maintenance kit for
Maintenance kit

6.4 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians
Army - CR
Navy - AS
Air Force - 85

Review activities:
Army - AR, AT, GL, MI
Navy - AS, OS, SH
Air Force - 11, 12, 99
DLA - ES

User activities.
Army - AV, ME
Navy - MC
Air Force - 11, 19, 80

Preparing activity:
Air Force - 85

Agent.
DLA - ES

(Project 5935-3503)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:34Z
Check the source to verify that this is the current version before use.