INCH-POUND

MIL-DTL-83723/82E
w/AMENDMENT 2
8 March 2024
SUPERSEDING
MIL-DTL-83723/82E
w/AMENDMENT 1
25 January 2018

DETAIL SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, CIRCULAR, ENVIRONMENT RESISTING, RECEPTACLE, FLANGE MOUNT, THREADED COUPLING, CRIMP SOCKET CONTACT, SERIES III, CLASSES A, G, K, M, N, R, S, T, W AND Z

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-83723.






FIGURE 1. Classes A, G, K, M, R, T, W and Z.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:22Z
Check the source to verify that this is the current version before use.






NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerances are ± .005 (0.13 mm) for three place decimals and ± .01 (0.25 mm) for two place decimals and ±1° for all angles.
4. Coupling indicator line shall be color coded red.
5. Rear accessory interchangeability dimensions shall be in accordance with MIL-DTL-83723.
6. Shell size 8 will not mate with MIL-DTL-26500 connectors.
7. See table I for contact cavities requiring this dimension.
8. Phantomed configuration optional.
9. The centerline of indicated projection must be located on vertical centerline ± 2°.

FIGURE 1. Classes A, G, K, M, R, T, W and Z - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:22Z
Check the source to verify that this is the current version before use.




NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerances are ± .005 (0.13 mm) for three place decimals and ± .01 (0.25 mm) for two place decimals and ±1° for all angles.
4. Coupling indicator line shall be color coded red.
5. Rear accessory interchangeability dimensions shall be in accordance with MIL-DTL-83723.
6. Shell size 8 will not mate with MIL-DTL-26500 connectors.
7. See table I for contact cavities requiring this dimension.
8. Phantomed configuration optional.
9. The centerline of indicated projection must be located on vertical centerline ± 2°.

FIGURE 2. Classes N and S.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:22Z
Check the source to verify that this is the current version before use.



.116 MIN CLEARANCE BETWEEN .125 PANEL AND COUPLING RING WHEN MOUNTING FLANGE IS IN BACK OF THE PANEL

Shell size	A thread	B	C	D	F
08	.562-24 UNEF-2A	.394 (10.01)	.418 (10.62) .413 (10.49)	.290 (7.37)	.562 (14.27)
10	.688-24 UNEF-2A	.515 (13.08)	.535 (13.59) .530 (13.46)	.388 (9.86)	.696 (17.68)
12	.875-20 UNEF-2A	.685 (17.40)	.705 (17.91) .700 (17.78)	.558 (14.17)	.875 (22.23)
14	.938-20 UNEF-2A	.754 (19.15)	.774 (19.66) .769 (19.53)	.627 (15.93)	.936 (23.77)
16	1.062-18 UNEF-2A	.881 (22.38)	.901 (22.89) .896 (22.76)	.772 (19.61)	1.062 (26.97)
18	1.188-18 UNEF-2A	.987 (25.07)	1.007 (25.58) 1.002 (25.45)	.860 (21.84)	1.187 (30.15)
20	1.312-18 UNEF-2A	1.112 (28.24)	1.132 (28.75) 1.127 (28.63)	.985 (25.02)	1.312 (33.32)
22	1.438-18 UNEF-2A	1.237 (31.42)	1.257 (31.93) 1.252 (31.80)	1.110 (28.19)	1.437 (36.50)
24	1.562-18 UNEF-2A	1.362 (34.59)	1.382 (35.10) 1.377 (34.98)	1.235 (31.37)	1.562 (39.67)

FIGURE 3. Dimensions and configurations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:22Z
Check the source to verify that this is the current version before use.

Shell size	G	H	R number of teeth	S +.005 / -.000	T
08	.594 (15.09)	.812 (20.62)	12	.490 (12.45)	.076 (1.93) .071 (1.80)
10	.719 (18.26)	.937 (23.80)	15	.636 (16.15)	.089 (2.26) .084 (2.13)
12	.812 (20.62)	1.031 (26.19)	21	.806 (20.47)	
14	.906 (23.01)	1.125 (28.58)	24	.875 (22.23)	
16	.969 (24.61)	1.250 (31.75)	30	1.002 (25.45)	
18	1.062 (26.97)	1.343 (34.11)	33	1.108 (28.14)	
20	1.156 (29.36)	1.437 (36.50)	36	1.233 (31.32)	
22	1.250 (31.75)	1.562 (39.67)	39	1.358 (34.49)	
24	1.375 (34.93)	1.703 (43.26)	42	1.483 (37.67)	

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerances are ± .005 (0.13 mm) for three place decimals and ± .01 (0.25 mm) for two place decimals and ±1° for all angles.
4. Coupling indicator line shall be color coded red.
5. Rear accessory interchangeability dimensions shall be in accordance with MIL-DTL-83723.
6. Shell size 8 will not mate with MIL-DTL-26500 connectors.
7. See table I for contact cavities requiring this dimension.
8. Phantomed configuration optional.
9. The centerline of indicated projection must be located on vertical centerline ± 2°.

FIGURE 3. Dimensions and configurations - Continued.

REQUIREMENTS:

Dimensions and configurations: See figures 1 and 3 for classes A, G, K, M, R, T, W and Z. See figures 2 and 3 for classes N and S.

This connector mates with MIL-DTL-83723/87, MIL-DTL-83723/92, MIL-DTL-83723/96 and MIL-DTL-83723/98.

Insert arrangements and polarizing positions: See MIL-STD-1554 and table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:22Z
Check the source to verify that this is the current version before use.

TABLE I. Insert arrangements requiring reduced diameter for lead-in chamfers on outer row of contact cavities as indicated.

Shell size	Insert arrangements	Contact cavities
08	03, 98	1, 2, 3
10	06	1, 2, 3, 4, 5, 6

O-ring: See MIL-DTL-83723.

Part or Identifying Number (PIN) example:

M83723/ 82 W 08 55 N

M83723/	Military designation
82	Specification sheet number
W	Class
08	Shell size
55	Insert arrangement
N	Polarizing position

Amendment notations. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Referenced documents. In addition to MIL-DTL-83723, this document references the following:

MIL-DTL-26500
MIL-DTL-83723/87
MIL-DTL-83723/92
MIL-DTL-83723/96
MIL-DTL-83723/98
MIL-STD-1554

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:22Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - AS
Air Force - 85
DLA - CC

Review activities:
Army - AR, MI
Navy - EC
Air Force - 19, 99

Preparing activity:
DLA - CC

(Project 5935-2024-061)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:22Z
Check the source to verify that this is the current version before use.