INCH-POUND

MIL-DTL-83723/92D
1 October 2009
SUPERSEDING
MIL-C-83723/92C
24 April 1992

DETAIL SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, (CIRCULAR, ENVIRONMENT RESISTING), PLUG, (RFI, THREADED COUPLING, CRIMP PIN CONTACT), (SERIES III, CLASSES G, M, R, T, W AND Z)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-83723.




FIGURE 1. Dimensions and configurations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:23Z
Check the source to verify that this is the current version before use.




FIGURE 1. Dimensions and configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:23Z
Check the source to verify that this is the current version before use.

Shell size	A Thread UNEF-2B	B	C	H min	J	K	W max
8	.5625-24	.290 (7.37)	.025 (.64)	.294 (7.47)	.405 (10.29) .396 (10.06)	.575 (14.61)	.776 (19.71)
10	.6875-24	.388 (9.86)	.031 (.79)	.428 (10.87)	.526 (13.36) .517 (13.13)	.707 (17.96)	.906 (23.01)
12	.875-20	.558 (14.17)		.598 (15.19)	.696 (17.68) .687 (17.45)	.895 (22.73)	1.078 (27.38)
14	.9375-20	.627 (15.93)		.667 (16.94)	.765 (19.43) .756 (19.20)	.957 (24.31)	1.141 (28.98)
16	1.0625-18	.772 (19.61)		.794 (20.17)	.892 (22.66) .883 (22.43)	1.084 (27.53)	1.266 (32.16)
18	1.1875-18	.860 (21.84)		.900 (22.86)	.998 (25.35) .989 (25.12)	1.209 (30.71)	1.375 (34.93)
20	1.3125-18	.985 (25.02)		1.025 (26.04)	1.123 (28.52) 1.114 (28.30)	1.334 (33.88)	1.510 (38.35)
22	1.4375-18	1.110 (28.19)		1.150 (29.21)	1.248 (31.70) 1.239 (31.47)	1.459 (37.06)	1.625 (41.28)
24	1.5625-18	1.235 (31.37)		1.275 (32.39)	1.373 (34.87) 1.364 (34.65)	1.584 (40.23)	1.760 (44.70)

FIGURE 1. Dimensions and configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:23Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm	Inches	mm	Inches	mm
.005	0.13	.144	3.66	.598	15.19	1.078	27.38
.007	0.18	.198	5.03	.627	15.93	1.084	27.53
.008	0.20	.204	5.18	.667	16.94	1.110	28.19
.015	0.38	.215	5.46	.675	17.15	1.114	28.29
.018	0.46	.235	5.97	.687	17.45	1.123	28.52
.020	0.51	.243	6.17	.691	17.55	1.141	28.98
.022	0.56	.260	6.60	.696	17.68	1.150	29.21
.025	0.64	.290	7.37	.707	17.96	1.180	29.97
.031	0.79	.294	7.47	.756	19.20	1.209	30.71
.032	0.81	.330	8.38	.765	19.43	1.235	31.37
.035	0.89	.388	9.86	.772	19.61	1.239	31.47
.042	1.07	.396	10.05	.776	19.01	1.248	31.70
.046	1.17	.400	10.16	.794	20.17	1.266	32.15
.048	1.22	.405	10.29	.860	21.84	1.275	32.39
.065	1.65	.428	10.87	.883	22.43	1.334	33.88
.068	1.73	.433	11.00	.892	22.66	1.364	34.65
.069	1.75	.479	12.17	.895	22.73	1.373	34.87
.084	2.13	.500	12.70	.900	22.86	1.375	34.93
.090	2.29	.510	12.95	.906	23.01	1.459	37.06
.097	2.46	.517	13.13	.957	24.31	1.510	38.35
.101	2.57	.526	13.36	.985	25.02	1.584	40.23
.106	2.69	.558	14.71	.998	25.35	1.625	41.28
.112	2.84	.575	14.60	1.025	26.03	1.760	44.70
.125	3.18						
.138	3.51						

NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerances are ± .005 (0.13 mm) for three place decimals and ± .01 (0.25 mm) for two place decimals and ± 1° for all angles.
4. The dimensions showing the relationship between the coupling ring and shell apply only when the coupling ring is in the fully forward position.
5. Rear accessory interchangeability dimensions shall be in accordance with MIL-DTL-83723.
6. Shell size 8 will not mate with MIL-DTL-26500 connectors.
7. The centerline of indicated projection must be located on vertical centerline ± 2°.
8. See table I for contact cavities requiring this dimension.

FIGURE 1. Dimensions and configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:23Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configurations: See figure 1.

This connector mates with MIL-DTL-83723/82 and MIL-DTL-83723/84.


Insert arrangements and polarizing positions: See MIL-STD-1554 and table I.

TABLE I. Insert arrangements requiring reduced diameters for raised seal barriers on contact cavities.

Shell size	Insert arrangements	Contact cavities
8	03	1, 2, 3
10	06	1, 2, 3, 4, 5, 6

Connector accessories: See SAE-AS85049.

Part or Identifying Number (PIN) example:



Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue, due to the extent of the changes.

Referenced documents. In addition to MIL-DTL-83723, this document references the following:

MIL-STD-1554
MIL-DTL-26500
MIL-DTL-83723/82
MIL-DTL-83723/84
SAE-AS85049

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:23Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - AS
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

Review activities:
Army - AR, MI
Navy - EC
Air Force - 19, 99

(Project 5935-2008-169)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:23Z
Check the source to verify that this is the current version before use.