INCH-POUND


MIL-PRF-83536/15C
w/AMENDMENT 1
19 November 2024
SUPERSEDING
MIL-PRF-83536/15C
11 October 2023

PERFORMANCE SPECIFICATION SHEET

# RELAYS, ELECTROMAGNETIC, ESTABLISHED RELIABILITY, 4PDT, LOW LEVEL TO 10 AMPERES, PERMANENT MAGNETIC DRIVE, HERMETICALLY SEALED, ALL WELDED, DC COIL

This specification is approved for use by all
Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist
of this specification sheet and the latest issue of MIL-PRF-83536.





NO MOUNT

FIGURE 1. Dimensions and configurations.

AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

FSC 5945

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:52Z
Check the source to verify that this is the current version before use.





RAISED VERTICAL FLANGE MOUNT (RVFM)

FIGURE 1. Dimensions and configurations - Continued.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:52Z
Check the source to verify that this is the current version before use.





HORIZONTAL FLANGE MOUNT (HFM)


FIGURE 1. Dimensions and configurations - Continued.




Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:52Z
Check the source to verify that this is the current version before use.





SOLDER PIN TERMINAL





SOCKET PIN TERMINAL




SOLDER HOOK TERMINAL




MOUNTING HOLE LAYOUT (RVFM)





MOUNTING HOLE LAYOUT (HFM)

FIGURE 1. Dimensions and configurations - Continued.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:52Z
Check the source to verify that this is the current version before use.




CIRCUIT DIAGRAM

FIGURE 1. Dimensions and configurations - Continued.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:52Z
Check the source to verify that this is the current version before use.

| Inches | mm | Inches | mm | Inches | mm |
|---|---|---|---|---|---|
| 0.001 | 0.03 | 0.172 | 4.37 | 0.937 | 23.80 |
| 0.002 | 0.05 | 0.200 | 5.08 | 1.010 | 25.65 |
| 0.005 | 0.13 | 0.218 | 5.54 | 1.025 | 26.04 |
| 0.040 | 1.02 | 0.270 | 6.86 | 1.062 | 26.98 |
| 0.050 | 1.27 | 0.310 | 7.87 | 1.396 | 35.46 |
| 0.062 | 1.58 | 0.312 | 7.92 | 1.406 | 35.71 |
| 0.150 | 3.81 | 0.625 | 15.88 | 1.446 | 36.73 |
| 0.156 | 3.96 | 0.810 | 20.57 | 1.718 | 43.64 |

NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ± 0.010 (0.25 mm).
4. There shall be affixed to the relay a suitable legible circuit diagram that identifies each terminal location specified.
5. These relays are polarized monostable.
6. This relay shall not operate or be damaged by reverse polarity.
7. Permanent magnet drive consists of a permanent magnet with its flux path switched and combined with the electro-magnet flux.
8. Applicable to horizontal flange mount only. The circuit diagram, manufacturer's PIN, and the military PIN shall be marked on the near side. The remaining portion of the nameplate data shall be marked on the far side.
9. Applicable to horizontal flange mount only. Relays shall be marked with the manufacturer's name or CAGE code and date code. Marking shall be with the bottom of the print adjacent to the near side.
10. Socket pin terminals shall provide the operational, environmental, and interface characteristics to provide a reliable interconnect to gold-plated contacts. Terminals shall be gold plated. One system for gold plating that may be used is ASTM-B488, type 3, class 1.25 with a nickel underplate of 50 to 150 microinches thick. The gold plating system shall enable the product to meet the performance requirements of this specification and shall be approved by the qualifying activity.
11. Gasket shall provide a reliable seal between the relay and mating socket that will meet the environmental, operational, and interface requirements of the relay with the mating socket. The gasket shall have shore hardness 15 to 35, thickness 0.050 ± 0.010. Gasket material according to SAE-AMS3332 has been considered acceptable.
12. Indicated terminal shall be identified by a contrasting bead.
13. Plane of critical motion for vibration and shock is Y-axis.

FIGURE 1. Dimensions and configurations - Continued.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:52Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Contact data:

Load ratings: See table I.

Low level: 10 to 50 μA at 10 to 50 mV dc or peak ac.

Intermediate current: Applicable.

Mixed loads: Applicable.

TABLE I. Rated contact load and cycles (amperes per pole).

| Type of load (high level) | Cycles x $10^3$ | 28 V dc | 115 V ac 1 phase 400 Hz | 115 V ac 1 phase 50/60 Hz 1/ | 115/200 V ac 3 phase 400 Hz | 115/200 V ac 3 phase 50/60 Hz 1/ |
|---|---|---|---|---|---|---|
| Resistive | 100 | 10 | 10 | 2.5 | 10 | 2.5 |
| Inductive | 20 | 8 | 8 | N/A | 8 | N/A |
| Inductive | 10 | N/A | N/A | 2.5 | N/A | 2.5 |
| Motor | 100 | 4 | 4 | 2 | 4 | 2 |
| Lamp | 100 | 2 | 2 | 1 | N/A | N/A |

1/ For 50/60 Hz rating, rupture and overload are not applicable and life for each load shall be 10,000 cycles.

Life: 100,000 cycles, unless otherwise specified (see table I).

Contact voltage drop or resistance:

Initial contact voltage drop: 0.100 volt maximum. Rated resistive current at 6 V dc or peak ac. Relays shall not make or break this load.

Initial contact resistance: 0.010 ohm maximum. 50 mA max at 6 V dc or peak ac.

High level life (contact voltage drop):

During life: 10 percent open circuit voltage maximum.

After life: 0.125 volt maximum.

Intermediate current (contact resistance):

During intermediate current: 3 ohms maximum.

After intermediate current: 0.150 ohm maximum.

Low level (contact resistance):

During low level: 100 ohms maximum.

After low level: 0.150 ohm maximum at 100 mA and 28 V dc.

Contact bounce: 1.0 millisecond maximum.

Contact stabilization time: 2.5 milliseconds maximum.

Overload current: 40 amperes dc (60 amperes ac).



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:52Z
Check the source to verify that this is the current version before use.

Rupture current: 50 amperes dc, 80 amperes ac.

Time current relay characteristics: See table II.

TABLE II. Time current relay characteristics. 1/

| Successive application | Amperes | Time |
|---|---|---|
| 1 | 15 | 1 hour |
| 2 | 50 | 5.0 seconds |
| 3 | 100 | 1.2 seconds |
| 4 | 250 | 0.2 second |
| 5 | 350 | 0.1 second |

1/ All relays shall withstand overload and fault currents. Relays must be able to sustain five applications (make and carry only) of power concurrently on adjacent poles at each of five different current levels in the sequence listed in table II. Separate relays shall be tested at 28 V dc and 115/200 V ac, 400 Hz 3-phase. Cooling time between successive applications shall be 30 minutes. Tests shall be performed on both normally open and normally closed contacts. There shall be no failures or evidence of welding or sticking and relays shall pass contact voltage drop at the conclusion.

Coil data 1/: See table III.

Operate time: 15 milliseconds maximum with rated coil voltage over the temperature range.

Release time: 15 milliseconds maximum from rated coil voltage over the temperature range.

Duty rating: Continuous.

Coil transient suppression: Not applicable.

Neutral screen: Not applicable.

Electrical data:

Insulation resistance:

Initial: 100 megohms minimum at 500 V dc.

After life or environmental tests: 50 megohms minimum at 500 V dc.

1/ CAUTION: Due to possible interaction of relay magnetic fields, the following spacing requirements, as a minimum, shall be considered in dense packaging situations:

a. Row to row assisting fields: .125 (3.18 mm).

b. Row to row opposing fields: .1875 (4.763 mm).

c. Side to side alternating fields: .0625 (1.588 mm).

d. Side to side like fields: .125 (3.18 mm).



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:52Z
Check the source to verify that this is the current version before use.

TABLE III. Dash numbers and characteristics. 1/

| Dash number 2/ | | | Mount | Coil data | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | At 25°C | | | | | | Over temperature range | | | Maximum pickup voltage | |
| Solder pin | Solder hook | Socket pin | | Coil voltage (V dc) 3/ | | Coil resistance (ohms) (minimum) | Specified pickup voltage (V dc) 4/ | Specified hold voltage (V dc) 4/ | Specified dropout voltage (V dc) 4/ | Specified pickup voltage (V dc) 4/ | Specified hold voltage (V dc) 4/ | Specified dropout voltage (V dc) 4/ | High temper-ature test | Continuous current test |
| | | | | Rated | Max | | | | | | | | | |
| 001 | 002 | 003 | No mount | 6 | 7.3 | 16 | 3.2 | 1.6 | 0.4 | 4.5 | 2.3 | 0.25 | 5.0 | 5.7 |
| 004 | 005 | 006 | RVFM | 6 | 7.3 | 16 | 3.2 | 1.6 | 0.4 | 4.5 | 2.3 | 0.25 | 5.0 | 5.7 |
| 007 | 008 | --- | HFM | 6 | 7.3 | 16 | 3.2 | 1.6 | 0.4 | 4.5 | 2.3 | 0.25 | 5.0 | 5.7 |
| 009 | 010 | 011 | No mount | 12 | 14.5 | 63 | 6.5 | 3.3 | 0.75 | 9.0 | 4.5 | 0.5 | 9.9 | 11.25 |
| 012 | 013 | 014 | RVFM | 12 | 14.5 | 63 | 6.5 | 3.3 | 0.75 | 9.0 | 4.5 | 0.5 | 9.9 | 11.25 |
| 015 | 016 | --- | HFM | 12 | 14.5 | 63 | 6.5 | 3.3 | 0.75 | 9.0 | 4.5 | 0.5 | 9.9 | 11.25 |
| 017 | 018 | 019 | No mount | 28 | 5/ 29 | 260 | 13.5 | 5.5 | 2.3 | 18.0 | 7.0 | 1.5 | 19.8 | 22.5 |
| 020 | 021 | 022 | RVFM | 28 | 5/ 29 | 260 | 13.5 | 5.5 | 2.3 | 18.0 | 7.0 | 1.5 | 19.8 | 22.5 |
| 023 | 024 | --- | HFM | 28 | 5/ 29 | 260 | 13.5 | 5.5 | 2.3 | 18.0 | 7.0 | 1.5 | 19.8 | 22.5 |
| 025 | 026 | 027 | No mount | 48 | 50 | 800 | 24.0 | 12.0 | 3.0 | 36.0 | 14.0 | 2.0 | 38.0 | 42.0 |
| 028 | 029 | 030 | RVFM | 48 | 50 | 800 | 24.0 | 12.0 | 3.0 | 36.0 | 14.0 | 2.0 | 38.0 | 42.0 |
| 031 | 032 | --- | HFM | 48 | 50 | 800 | 24.0 | 12.0 | 3.0 | 36.0 | 14.0 | 2.0 | 38.0 | 42.0 |

1/ Each relay possesses high level and low level capabilities. However, relays previously tested or used above 10 mA resistive at 6 V dc maximum or peak ac open circuits are not recommended for subsequent use in low level applications.
2/ The suffix letter L, M, P, or R to designate the applicable failure rate level shall be added to the applicable listed dash number. Failure rate level (percent per 10,000 cycles): L, 3.0; M, 1.0; P, 0.1; R, 0.01. Example: 001L, 002R.
3/ CAUTION: The use of any coil voltages less than the rated coil voltage will compromise the operation of the relay.
4/ Pickup, hold, and dropout voltages as shown are for test purposes only and are not to be used for design criteria.
5/ When maximum ambient temperature does not exceed +85°C, the maximum coil voltage shall be 32 V dc.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:52Z
Check the source to verify that this is the current version before use.

Dielectric withstanding voltage 2/:

| | Coil to case | All other points |
|---|---|---|
| Sea level: | | |
| Initial: | 1,000 | 1,250 |
| After life: | 1,000 | 1,000 |
| Altitude: | | |
| At 80,000 feet: | 350 | 350 |

Environmental characteristics:

Temperature range: -70°C to +125°C.

Maximum altitude rating: 80,000 feet.

Shock (specified pulse): Applicable, MIL-STD-202-213, test condition C, 200 g's for 6 ±1 ms, except horizontal flange mount peak g value shall be 100 g's for 6 ±1 ms. Contact chatter shall not exceed 10 microseconds maximum for closed contacts and 1 microsecond maximum closure for open contacts.

Vibration (sinusoidal): Applicable, MIL-STD-202-204, 30 g's, except frequency range shall be 10 to 3,000 Hz. Horizontal flange mount shall be 20 g's, 57 to 3,000 Hz. Contact chatter shall not exceed 10 microseconds maximum for closed contacts and 1 microsecond maximum closure for open contacts.

Vibration (random): Applicable to qualification and group C inspection. Test in accordance with MIL-STD-202-214, test condition IG (0.4 $g^2$/Hz, 50 to 2,000 Hz); for horizontal flange mount test condition IE (0.2 $g^2$/Hz). Contact chatter shall not exceed 10 microseconds maximum for closed contacts and 1 microsecond maximum closure for open contacts.

Acceleration: Applicable, except 15 g's.

Physical data:

Dimensions and configurations: See figure 1.

Weight: 0.17 pound (77 grams).

Terminal strength:

Solder hook terminals:

Pull force: 10 pounds ±1.0 pound.

Bend: Not applicable to leads 0.047 (1.19 mm) and larger.

Twist: Not applicable.

Solder pin terminals:

Pull force; For 0.062 diameter terminals: 10 pounds ±1.0 pound.

Bend: Not applicable to leads 0.047 (1.19 mm) and larger.

Twist: Not applicable.

2/ Dielectric may be improved by suitable insulation of terminals and wiring after installation.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:52Z
Check the source to verify that this is the current version before use.

Socket pin terminals:

Pull force: For .062 diameter terminals: 10 pounds ±1.0 pound.

Bend: Not applicable to leads 0.047 (1.19 mm) and larger.

Twist: Not applicable.

Terminal solderability: Applicable to solder pin and solder hook terminals only.

Seal: Hermetic.

Marking: Applicable.

Part or Identifying Number (PIN): M83536/15 (dash number from table III and suffix letter designating failure rate level).

Qualification inspection:

Qualification inspection and sample size: See table IV.

TABLE IV. Qualification inspection and sample size. 1/

| Single submission | Group submission | |
|---|---|---|
| 18 units plus 1 open unit for level L at C = 0 2/<br>33 units plus 1 open unit for level M at C = 0 2/<br>Qualification inspection as applicable | M83536/15-022<br>M83536/15-022<br>M83536/15-022<br>M83536/15-018<br>M83536/15-023<br>M83536/15-002<br>M83536/15-014<br>M83536/15-031 | 18 units plus 1 open unit for level L at C = 0 2/<br>33 units plus 1 open unit for level M at C = 0 2/<br>Qualification inspection as applicable<br>2 units, qualification inspection table, Q2, shock, vibration, acceleration, terminal strength, and seal.<br>2 units, qualification inspection table, Q1 |

1/ For retention of qualification or extension of qualification to lower failure rate levels, all life test data accumulated on MIL-PRF-83536/16 may be used in addition to MIL-PRF-83536/15 data. Prior to performance of retention of qualification testing, the relay manufacturer shall preselect the sampling plan.

2/ The number of units required for qualification testing shall be increased as required in Q5, table II of MIL-PRF-83536, if the contractor elects to test the number of units permitting one or more failures. Prior to performance of qualification testing, the relay manufacturer shall preselect the sampling plan.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:52Z
Check the source to verify that this is the current version before use.

Qualification inspection (reduced testing) (sample size - 2 units each coil voltage and 1 unsealed unit). See table V.

If the relays produced for MIL-PRF-83536/15 are similar in construction and design except for the suppression network to the relays produced for MIL-PRF-83536/16, then reduced testing for qualification of MIL-PRF-83536/15 relays may be performed concurrent with or subsequent to successful qualification of MIL-PRF-83536/16 relays. For reduced testing, see table V.

TABLE V. Qualification inspection (reduced testing).

| Inspection |
|---|
| 2 units each coil voltage<br>Q1 of qualification inspection table<br>1 additional unsealed sample unit for internal inspection |

Supersession data: See table VI.

TABLE VI. Supersession data.

| Superseded PIN MS27400- | Replacement PIN M83536/15- |
|---|---|
| 5 | 021 |
| 6 | 022 |
| 9 | 021 |
| 10 | 022 |
| 19 | 024 |
| 21 | 024 |
| 35 | 020 |
| 36 | 020 |
| 40 | 018 |
| 41 | 017 |
| 44 | 018 |
| 45 | 017 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:52Z
Check the source to verify that this is the current version before use.

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents. In addition to MIL-PRF-83536, this document references the following:

MIL-PRF-83536/16 MIL-STD-202-213 MIL-STD-202-204 MIL-STD-202-214 SAE-AMS3332
ASTM-B488

Custodians:
Army - CR
Navy - EC
Air Force -85
DLA – CC

Preparing activity:
DLA - CC

(Project 5945-2025-006)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:52Z
Check the source to verify that this is the current version before use.