MIL-C-55194 (Sig C)

AMENDMENT 3
21 AUGUST 1964

MILITARY SPECIFICATION

CONTROL, INTERCOMMUNICATION SET C-1611 ( )/AIC

Page 1, paragraph 2.1. Under SPECIFICATIONS, FEDERAL, delete:

PPP-T-97 – Tape Pressure Sensitive Adhesive, Filament Reinfoced.

PPP-B-585 – Boxes, Wirebound.

PPP-B-591 – Boxes, Wood Cleated Fiberboard.

Add:

PPP-T-76 – Tape, Pressure Sensitive, Adhesive, Filament Reinforced.

PPP-F-320 – Fiberboard, Sheet, Stock and Cut Shapes.

QQ-S-781 – Strapping, Flat, Steel.

Page 2. Under SPECIFICATIONS, MILITARY, add:

MIL-P-11268 – Parts, Materials and Processes Used in Electronic Communication Equipment.

Page 2. Under DRAWINGS, SIGNAL CORPS, delete:

SC-A-362100 – Requirement for Preparation of Packaging and Packing Illustrations and Bills of Material.

Add:

SC-DL-488800 – Drawing and Data List C-1611B/AIC.

Page 3, paragraph 3.2 *Size and weight*. Delete in its entirety.

Page 3, paragraph 3.3 *Procurement model*. Delete and replace with:

"3.3 Construction. Construction shall be in accordance with Drawing and Data List SC-DL-488800."

Page 3, paragraph 3.5 *Parts, materials and processes: general*. Delete in its entirety.

Page 4, paragraph 3.5.4.1 *Conformal coatings*. Add: "Thickness of coating shall be 0.008 ± .004 inch."

Page 5, paragraph 3.6.4 *Volume control*. Change first line to read: "Full output of 200 milliwatts shall be obtained with an input of 50 milliwatts (2.7V) when the control is rotated to approximately its 11 to 12 o'clock position."

Page 6, paragraph 3.7.1.2 *Distortion*. Add after the word "second," the following: "except that maximum distortion shall not exceed 7 percent at 300 cps."

FSC 5931

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:36Z
Check the source to verify that this is the current version before use.

Page 7, paragraph 3.7.1.8 *Power output*. Change to read: "With a fixed 50 mw (2.7V) input connected to pin 14, and output connected to pin 4, using figure 1, the maximum unclipped power output at 1000 cycles per second shall be 200 milliwatts − 2 db."

Page 9, paragraph 3.8 *Noise in output due to ripple on DC line*. Delete, "With 3.0 volts ac peak-to-peak" and substitute. "With 1.0 volts rms".

Page 9, paragraph 3.8.1 *Microphonics*. Replace with:

"3.8.1 *Microphonics*. Microphonics in the amplifier circuits shall be no greater than 0.1 V rms as measured with a VTVM at output pin 4, with zero microphone input signal. The holding test fixture, without the control unit to be tested, shall be free of mechanical resonance."

Page 9, paragraph 3.9.1 *Power source transient*. Change "MIL-E-7894" to read "MIL-STD-704."

Page 9, paragraph 3.10 *Interference limits*. Add: "A 5-foot cable simulating installation in aircraft shall be used between the C-1611 sample and the load test fixture during all interference tests."

Page 10, paragraph 3.14.2 *Temperature (see 4.7.5)*. Delete Paragraphs (a) and (b).

Add:

"The equipment shall meet the temperature and altitude tests, paragraph 4.1 of MIL-T-5422E(ASG). At the extremes from readings noted at room temperature and altitude, degradation of frequency response of 1.5 db and degradation of gain and distortion of 15 percent is allowed."

Page 10, paragraph 3.14.4 *Elevation (See 4.7.6)*. Delete in its entirety.

Page 11, paragraph 3.15.2 *Bounce and shock*. Delete requirements for bounce test and shock, bench handling.

Page 11, paragraph 3.17 *Workmanship*. Replace with:

"**3.17 Workmanship.** The equipment shall be manufactured and assembled in accordance with the equipment drawings and applicable portions of the following paragraphs in MIL-P-11268: Soldering, Riveting, Wiring, Cleaning, Welding, and Securing of Parts."

Page 12, paragraph 4.1 *Contractor's responsibility*. Delete and replace with:

"**4.1 Responsibility for inspection.** Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements."

Page 13, paragraph 4.3 *Preproduction inspection*. Delete "Bounce" from Table IV.

Page 14, paragraph 4.4.3 *Group C inspection*. Add, "and Altitude," after "Temperature." Delete, "Altitude, Rqt. para. 3.14.4, Test Para. 4.7.7."

Page 15, paragraph 4.6 *Electrical tests*. Change "specied" to "specified."

Page 17, paragraph 4.6.3 *Volume Control (See 3.6.4)*. Delete Paragraph (a) and replace with:

"(a) Referring to figure 1, connect the

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:36Z
Check the source to verify that this is the current version before use.

input to pin 14 and the output to pin 4. Set the input level to 50 mw (2.7 Output level with volume control in CCW position shall be 2 mw ± 1 mw. Increase output level with volume control until output just begins to clip. Volume control position at point of clipping shall be approximately between 11 and 12 o'clock, and output of 200 mw ± 2 db shall be obtained in this position. Rotation of the volume control fully clockwise from the position of maximum unclipped output shall not increase the amplitude of the output signal when monitored on an oscilloscope. Turn volume control fully clockwise. Reduce input level until clipping is again just occurring. Note input voltage. Difference in input voltage shall be within 6 to 12 db."

Page 17, paragraph 4.6.4.2 *Distortion* (*See 3.7.1.2*). Add after "6000 cps" the following: "except that maximum distortion shall not exceed 7 percent at 300 cps."

Page 18, paragraph 4.6.4.5 *Speech-peak clipping*. Replace with:

"4.6.4.5 *Speech-peak clipping*. Using the same test setup as in paragraph 4.6.4.1, set the input level to 2.7 V, 1000 cps, and increase the volume control until clipping just takes place at either the top or the bottom of the sine wave. Clipping shall appear at approximately between 11 ahd 12 o'clock position of the volume control. Note output voltage. Increase volume control until the remaining half of the sine wave begins to clip. Note output voltage. Difference in output voltages shall not exceed 1 db. Turn volume control fully clockwise. Reduce input level until clipping is again just occurring. Note input voltage again. Difference in input voltages shall be within 6 to 12 db."

Page 19, paragraph 4.7.1 *Vibration test*. Replace with:

"4.7.1 *Vibration test*. The equipment shall be subjected to the vibration test of MIL-T-5422 for compliance with Curve IV of figure 2. Frequency change shall be controlled automatically. Upon completion of the test, the tests of paragraph 4.6 of this specification shall be made. No deterioration of mechanical or electrical characteristics shall be evident."

Page 20, paragraph 4.7.2 *Bounce test*. Delete in its entirety

Page 20, paragraph 4.7.3 Shock test: *Bench-handling*. Delete in its entirety.

Page 21, paragraph 4.7.4. *Shock test: service and crash*. After MIL-STD-202 add the following: "except that the shock testing apparatus shall be Barry Controls Shock Test Machine Type VP-35 or equal."

Page 21, paragraph 4.7.5 *Temperature tests*. Delete and replace with:

"4.7.5 *Temperature and altitude tests*. Temperature and altitude tests shall be performed as specified in paragraph 4.1 of MIL-T-5422E(ASG) for Class 1A equipment."

Page 22, paragraph 4.7.7 *Elevation*. Delete in its entirety.

Page 25, section 5, replace with:

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.

5.1.1 *Level A*. Each Control Intercommunication Set C-1611 ()/AIC shall be preserved and packaged in accordance with the procedures specified for the designated methods as prescribed in Specification MIL-P-

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:36Z
Check the source to verify that this is the current version before use.

116 and described in the following paragraphs.

5.1.1.1 Control Intercommunication Set C-1611 ( )/AIC shall be packaged Method IC-5 as follows: Cushion each Control Intercommunication Set C-1611 ( )/AIC on all surfaces with cells or pads or both fabricated of fiberboard, Type CF, Class weather resistant, Variety SW, Grade W5c, conforming to specification PPP-F-320. Place the cushioned Control Intercommunication Set C-)/AIC within a close-fitting Style ype 1, Class 2, W5c, fiberboard box conforming to Specification PPP-B-636. Closure shall be made in accordance with the appendix of the box specification. In addition seal all seams and joints with pressure-sensitive tape conforming to Specification PPP-T-76.

5.1.2 *Level C.* Control Intercommunication Set C-1611 ( )/AIC shall be preserved and packaged in accordance with commercial practice and in a manner that will afford protection against corrosion, deterioration and physical damage during direct shipment to the first receiving activity.

Package performance. Package testing shall be performed in accordance with the requirements of Specification MIL-P-116. The rough handling and functional test will be required only when invoked in the bid request or contract (see 6.2).

5.2 Packing.

5.2.1 *Level A.* Control Intercommunication Set C-1611 ( )/AIC shall be packed for shipment as follows: Place a quantity of Control Intercommunication Sets C-1611 ( )/AIC, packaged as specified in 5.1.1.1, within a Class 2, Style 4, nailed wood box or Class 2, Type III, Style A, cleated plywood box conforming to Specification PPP-B-621 or PPP-B-601, respectively. Fabricate the box to fit contents snugly. The gross weight of any shipping container shall not exceed approximately 200 pounds. Box closure shall be in accordance with the appendix of the applicable box specification.

5.2.1.1 *Metal strapping.* Shipping containers shall be strapped with flat metal strapping conforming to Specification QQ-S-781, Type I, Class b, in accordance with the requirements of the appendix of the applicable box specification.

5.2.2 *Level B.* Control Intercommunication Set C-1611 ( )/AIC shall be packed as specified in 5.2.1 except that nailed wood box shall be Class I and the cleated plywood box shall be Type IV, Class I.

5.2.3 *Level C.* Control Intercommunication Set C-1611 ( )/AIC shall be packed in shipping containers of the type, size and kind commonly used for the purpose in a manner that will insure acceptance by common carrier and safe delivery at destination. Shipping containers shall comply with the rules or regulations of the common carrier applicable to the mode of transportation.

5.3 **Marking.** Interior packages and exterior shipping containers shall be marked in accordance with Military Standard MIL-STD-129.

Page 27, paragraph 6.6, replace with:

"Verification inspection. Verification by the Government will be limited to the amount deemed necessary to determine compliance with the contract and will be limited in severity to the definitive quality assurance provisions established in this specification and the contract. The amount of verification inspection by the Government will be adjusted to make maximum utilization of the contractor's quality control system and the quality history of the product.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:36Z
Check the source to verify that this is the current version before use.

Custodian:

Army—EL

Preparing activity:

Army—EL

Project No. 5831-A004

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:36Z
Check the source to verify that this is the current version before use.

To detach this form, cut along this line

SPECIFICATION ANALYSIS SHEET

Form Approved Budget Bureau No. 119-R084

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

ORGANIZATION	CITY AND STATE

CONTRACT NO	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 APR 63 1426 REPLACES NAVSHIPS FORM 4463, WHICH IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:36Z
Check the source to verify that this is the current version before use.

FOLD

HEADQUARTERS
U. S. ARMY ELECTRONICS MATERIEL SUPPORT AGENCY
FORT MONMOUTH, NEW JERSEY 07703

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

Commanding Officer
U. S. Army Electronics Materiel Support Agency
Fort Monmouth, New Jersey 07703

FOLD

To detach this form, cut along this line

Source: https://assist.dla.mil -- Downloaded: 202610-22T22:36Z
Check the source to verify that this is the current version before use.