INCH-POUND

MIL-C-63521 (AR)
AMENDMENT 8
15 July 1991
SUPERSEDING
AMENDMENT 7
18 August 1987

MILITARY SPECIFICATION

CONTAINER, AMMUNITION, METAL, FOR CARTRIDGE 105MM, APFSDS-T, M833

This amendment forms a part of Military Specification MIL-C-63521 (AR), dated 14 June 1982, and is approved for use within the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Title: Delete in its entirety and substitute: "CONTAINER, AMMUNITION, METAL, FOR CARTRIDGE, 105MM, TANK AMMUNITION".

1.1: Delete "Kinetic energy tank ammunition" and substitute "105mm tank ammunition, M456A2, M735, M774, M833."

2.1.1 Specifications and standards. Under STANDARDS, MILITARY, delete "1188 - Commercial Packaging of Supplies and Equipment."

PAGE 2

2.1.2 Other Government documents, drawings and publications. Under DRAWINGS add:

"9378187 - Container, Ammo, Metal for Cartridge, 105mm, APFSDS-T: M735 or M774."

"12551938 - Container, Ammo, Metal for Cartridge, 105mm, HEAT-T-MP: M456A2."

2.2 Other publications. Under AMERICAN SOCIETY FOR TESTING MATERIALS, add:

"ASTM-D3951 - Commercial Packaging, Standard Practices for."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:02Z
Check the source to verify that this is the current version before use.

PAGE 3

3.2 Containers. First sentence: delete "9345252" and substitute "9345252, 9378187 or 12551938".

PAGE 7

Table I Spring, unpainted. Delete in its entirety.

PAGE 10

4.4.2.2 Spring: Next higher assembly block, add "9344044".

Delete Major defect 103 in its entirety.

NOTES: Delete Note (b) in its entirety.

PAGE 11

4.4.2.3 Support, shaft: Delete Major defects 105, 107 and 108 in their entireties.

PAGE 13

4.4.2.5 Handle: Delete Major defects 103 and 104 in their entireties.

Delete Major defect 106 in its entirety and substitute:

"106 Distance from center of shaft hexhole to outer edge of tabs (Dim. B) 0.40% 3.2 Gage".

Delete Minor defect 201 in its entirety.

PAGE 16

4.4.2.8 Retainer, washer:

Delete Major defect 103 in its entirety and substitute:

"103 Material certification (a) 3.2 Certification".

Delete Major defect 104 in its entirety.

Add Note (a): "(a) With each lot of material submitted."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:02Z
Check the source to verify that this is the current version before use.

PAGE 17

4.4.2.9 Cover:

Delete Major defect 105 in its entirety and substitute:

"105 Depth from rim of inside of cover base 0.40% 3.2 Gage".

Major defect 107: Delete "rib" and substitute "rim".

PAGE 18

* 4.4.2.10 Gasket: Delete in its entirety and substitute new Page 18, included.

PAGE 22

* 4.4.2.14 Rim: Delete in its entirety and substitute new Page 22, included.

PAGE 23

* 4.4.2.15 Ring: Delete in its entirety and substitute new Page 23, included.

PAGE 26

* 4.4.2.18 Plug, Stacking: Delete in its entirety and substitute new Page 26, included.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:02Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.10	Gasket	1 OF 1	12910349-3
			NEXT HIGHER ASSEMBLY 9344031

CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Material certification			3.2	Certification
102	Hardness test	5		3.2	4.5.6/Gage
103	Inside diameter, max.		.40%	3.2	Gage
104	Large width		.40%	3.2	Gage
105	Middle width		.40%	3.2	Gage
106	Height of rectangular cross section		.40%	3.2	Gage
Minor					
201	Workmanship		.65%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may be used.

Source: https://assist.dla.mil -- Downloaded: 2026-04-03T03:02Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.14	Rim				9344028
					NEXT HIGHER ASSEMBLY
					9344032
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Depth from edge of rim to inside flat		.40%	3.2	Gage
102	Length of slot on side of rim		.40%	3.2	Gage
103	Location of slot from inside flat		.40%	3.2	Gage
104	Location of bayonet slot, 4 places		.40%	3.2	Gage
105	Inside dimension across flats, 2 places (Dim. A)		.40%	3.2	Gage
106	Inside dimension across corner, 2 places (Dim. D)		.40%	3.2	Gage
107	Width of slot		.40%	3.2	Gage
108	Inside diameter of rim		.40%	3.2	Gage
Minor					
201	Drainage hole missing		.65%	3.2	Visual
202	Workmanship		.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:02Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.15	Ring				9344029
					NEXT HIGHER ASSEMBLY 9344032
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Distance from edge of ring to outside flat		.40%	3.2	Gage
102	Length of slot on side of ring		.40%	3.2	Gage
103	Location of slot from inside flat		.40%	3.2	Gage
104	Inside dimension across flats, 2 places (Dim. A)		.40%	3.2	Gage
105	Width of slot		.40%	3.2	Gage
106	Inside diameter of ring		.40%	3.2	Gage
Minor					
201	Drainage hole missing		.65%	3.2	Visual
202	Workmanship		.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22 T03:02Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.18	Plug, Stacking				9344045
					NEXT HIGHER ASSEMBLY 9344032
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length of plug		.40%	3.2	Gage
102	Width of plug		.40%	3.2	Gage
Minor					
201	Workmanship		.65%	3.7	Visual

COVER:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:02Z
Check the source to verify that this is the current version before use.

PAGE 27

4.4.2.19: Body Weldment (body assembly), prior to painting:

Major defect 101: Delete Paragraph Reference "4.5.8.2" and substitute "4.5.8.1".

Major defect 102: Delete "Weld of rings to body" and substitute "Weld of rim to body".

PAGE 28

4.4.2.20 Container, ammo, metal:

Add new Major defect 104 as follows:

"104 Screw torque test (a) 0.40% 3.2 4.5.10".

Add Note (a): "(a) The screw torque test shall be performed after the air pressure test has been performed and the screw has been reassembled."

PAGE 29

4.4.2.21 Support, sabot: Delete in its entirety and substitute new page 29, included.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:02Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.21	Support Assembly		9362624
			NEXT HIGHER ASSEMBLY 9345252

CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Outside diameter		1.0%	3.2	Gage
202	Length		1.0%	3.2	Gage
203	Presence of chamfer		1.0%	3.2	Visual
204	Large inside diameter		1.0%	3.2	Gage
205	Small inside diameter		1.0%	3.2	Gage
206	Material certification	(a)		3.2	Certification
207	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES: (a) With each lot of material submitted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:02Z
Check the source to verify that this is the current version before use.

Page 30

4.4.2.22 Spacer: Under Next Higher Assembly, delete "9345284" and substitute "9345252".

PAGE 32

4.4.2.24 Cushion: Under Next Higher Assembly, add "9332584".

PAGE 33

4.4.2.25 Cushion assembly: Under Next Higher Assembly, add "9345252".

Page 34

4.4.2.26 Cushion: Under Next Higher Assembly, delete "9332584" and substitute "9345252".

PAGE 35

4.4.2.27 Support: Delete in its entirety.

PAGE 36

4.4.2.28: Lift collar assembly:

Under Drawing Number, delete "9345282" and substitute "9378280".

Delete Minor defect 201 in its entirety.

Minor defect 202: Delete in its entirety and substitute:

"202 Strap missing or improper 1.0% 3.2 Visual".

PAGE 37

Add new paragraphs:

4.4.2.30, Page 37A (included)
4.4.2.31, Page 37B (included)
4.4.2.32, Page 37C (included)
4.4.2.33, Page 37D (included)
4.4.2.34, Page 37E (included)
4.4.2.35, Page 37F (included)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:02Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.30	Spacer (M735 and M774)				9378189
					NEXT HIGHER ASSEMBLY 9378187
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Material certification	(a)		3.2	Certification
202	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:
(a) With each lot of material submitted.

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:02Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.31	Support Assembly, Alt. (M735 and M774)		9378188
			NEXT HIGHER ASSEMBLY 9378187

CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Outside diameter		1.0%	3.2	Gage
202	Length		1.0%	3.2	Gage
203	Presence of chamfer		1.0%	3.2	Visual
204	Large inside diameter		1.0%	3.2	Gage
205	Small inside diameter		1.0%	3.2	Gage
206	Material certification	(a)		3.2	Certification
207	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES: (a) With each lot of material submitted.

AMSM[illegible] orm 1570, 1 Feb 85 R[illegible] ces DRSMC-QA (D) Form 160, 1 Aug 83, which may[illegible] be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:02Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.32	Container, Ammo, Metal, for Cartridge 105mm, APFSDS-T, M735 or M774				9378187
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Any component missing or damaged		0.40%	3.2	Visual
Minor 201	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:02Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63521 (AR)
AMENDMENT 8

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.33	Adapter (M456A2)				12551936
					NEXT HIGHER ASSEMBLY 12551938
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Material certification	(a)		3.2	Certification
202	Outside diameter		1.0%	3.2	Gage
203	Thickness		1.0%	3.2	Gage
204	Size of recess		1.0%	3.2	Gage
205	Poor workmanship		1.0%	3.7	Visual
NOTES:	(a) With each lot of material submitted.				

AMSM Form 1570, 1 Feb 85 Replaces DRSMC-QA (O) Form 160, 1 Aug 83, which may be used.

Source: https://assist.dla.mil -- Downloaded: 2024-07-20T03:02Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.34	Support, Nose, Plastic (M456A2)				12551937
					NEXT HIGHER ASSEMBLY 12551938
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Material certification	(a)		3.2	Certification
202	Distance from end to inside shoulder		1.0%	3.2	Gage
203	Presence of 30° chamfer inside end		1.0%	3.2	Gage
204	Large inside diameter		1.0%	3.2	Gage
205	Large diameter on front protrusion		1.0%	3.2	Gage
206	Small diameter on front protrusion		1.0%	3.2	Gage
207	Poor workmanship		1.0%	3.7	Visual

NOTES:
(a) With each lot of material submitted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:02Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.35	Container, Ammo, Metal, for Cartridge 105mm, HEAT-T-MP, M456A2				9378188
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Any component missing or damaged		0.40%	3.2	Visual
Minor 201	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-27T03:02Z
Check the source to verify that this is the current version before use.

PAGE 39

4.5.5 Deflection load of spring. Delete in its entirety.

4.5.8.1 Air pressure of unpainted cover assembly and unpainted body assembly. First sentence: Delete "core assemblies" and substitute "cover assemblies".

4.5.8.1.1: Add new paragraph 4.5.8.1.1 as follows:

"4.5.8.1.1 Alternate air pressure test for unpainted cover assembly and unpainted body assembly (Water Method). Subject the cover assembly and container body while under water, to the specified internal air pressure for the test time specified. For the cover assembly, apply the pressure when the cover assembly is assembled to a master body assembly (or its equivalent) equipped with a gasket. For the body assembly, apply the pressure when the body assembly is assembled to a master cover (or equivalent) and gasket.

The master cover and master body assembly shall be provided with satisfactory means for applying and maintaining the pressure during the test and for showing evidence of leakage. No bubbles (other than surface bubbles) shall be permitted. A cover assembly or body assembly which does not meet the requirement shall be classed defective."

PAGE 40

4.5.10: Add new paragraph 4.5.10 as follows:

"4.5.10 Screw torque test. The minimum applicable torque shall be applied to the screw. Any evidence of motion of the screw before reaching the minimum acceptable torque shall be cause for rejection of the container assembly being tested. Any container assembly which fails the screw torque test may be reworked and returned to the lot after passing the screw torque test."

PAGE 41

5.2 Packing: Delete "paragraph 2.3.1 of MIL-STD-1188" and substitute "ASTM D3951".

5.3 Marking: First sentence: Delete in its entirety and substitute "Shipping marking shall comply with the following instructions."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:02Z
Check the source to verify that this is the current version before use.

NOTE: The margins of this Amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army - AR

Preparing activity:
Army - AR

(Project 8140-A832)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:02Z
Check the source to verify that this is the current version before use.