MIL-C-70455(AR)
13 July 1984
SUPERSEDING
FA-PD-MI-2602, REV 0
20 November 1963

MILITARY SPECIFICATION

CASE, CARTRIDGE, BLANK 75MM, M9A1B1

This specification is approved for use by the US Army Armament, Munition and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification contains requirements not covered by the drawings and provides quality assurance provisions for the fabrication of the Case, Cartridge, Blank 75MM, M9A1B1.

2. APPLICABLE DOCUMENTS

2.1 Applicable documents. The following documents of the issue in effect on date of invitation for bids, or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078	-	Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables For Inspection by Attributes

FEDERAL

FED-STD-151	-	Metals; Test Methods

FSC: 1315

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Center, Attn. DRSMC-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:28Z
Check the source to verify that this is the current version before use.

2.1.1 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS (See 6.6)

U.S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT CENTER (ARDC)

7548320	-	Ammunition for Interplant Shipment of Brass, Aluminum and Spirally Wrapped Steel Cartridge Cases, Empty, 75MM to 120MM Inclusive.
10521899	-	Case, Cartridge, Blank, 75MM, M9A1B1

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.1.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with the applicable drawings and specifications.

3.2 Parts. The parts shall comply with all requirements specified on drawing (dwg.) 10521899, associated drawings and with all requirements specified in applicable specifications, and standards.

3.3 Protective finish. Protective finish shall be in accordance with the applicable drawing and the specification listed.

3.4 Corrosion resistance. Following exposure to five percent salt spray for 168 hours. Test pieces shall comply with the requirements of the applicable drawing and the specification listed.

3.5 Maximum profile. The maximum profile of the cartridge case shall comply with the requirements of the applicable drawing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:28Z
Check the source to verify that this is the current version before use.

3.6 Workmanship. Each cartridge case shall be free from cracks, splits, seams, deep scratches, burrs (those which may interfere with assembly or prove injurious to personnel handling the item) of foreign matter which may impair proper functioning.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First article inspection.

b. Quality conformance inspection.

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of 30 Cases, Cartridge, Blank, 75MM, M9A1B1. Four cases of the 30 shall be used for protective finish tests after completion of Mechanical/Visual inspections.

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. See MIL-A-48078.

a. Sampling Plans. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for Major and Minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:28Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS MIL-C-70455 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 10521899
	Case, Cartridge Blank, 75MM, M9A1B1				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Case, Cartridge, Blank 75MM, M9A1B1 (Dwg. 10521899)				
	Examination for defects	30	-	3.2	4.4.2.1
	Protective finish	4	-	3.4	4.5.1
NOTES:					

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:28Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70455 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER 10521899
4.4.2.1	Case, Cartridge, Blank 75MM, M9A1B1				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	True position of primer hole with body		0.40%	3.2	Gage
102	True position of primer hole counterbore with primer hole		0.40%	3.2	Gage
103	Diameter of primer hole		0.40%	3.2	Gage
104	Diameter of primer hole counterbore, min.		0.40%	3.2	Gage
105	Depth of primer hole counterbore, min.		0.40%	3.2	Gage
106	Depth from front face of shoulder to bottom of primer hole counterbore, min		0.40%	3.2	Gage
107	Thickness of head, min.		0.40%	3.2	Gage
108	Taper in primer hole, incorrect		0.40%	3.2	Gage
109	Diameter of flange		0.40%	3.2	Gage
110	Diameter of body under shoulder		0.40%	3.2	Gage
111	Thickness of flange		0.40%	3.2	Gage
112	Wall thickness at mouth		0.40%	3.2	Gage
113	Taper on body outside diameter		0.40%	3.2	Gage
Minor					
201	Diameter of mouth inside, min.		0.65%	3.2	Gage
202	Diameter of shoulder under flange, min.		0.65%	3.2	Gage
203	Length to basic diameter, min.		0.65%	3.2	Gage
204	Length total		0.65%	3.2	Gage
205	Wall thickness near head, at basic dimension		0.65%	3.2	Gage

NOTES:

DRSMC-QA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:28Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 10521899
4.4.2.1	Case, Cartridge, Blank 75MM, M9A1B1				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
206	Surface finish, improper		0.65%	3.2	Visual
207	Protective finish, inadequate or damaged		0.65%	3.3	Visual
208	Stamping, missing, incorrect or illegible		0.65%	3.2	Visual
209	Workmanship		0.65%	3.6	visual

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:28Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70455 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.2	Carton, Ammo for Interplant Shipment of Brass, Aluminum & Spirally Wrapped Steel Ctg. Cases, Empty, 75MM to 120MM Inclusive	1 OF 1	7548320
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major	None defined.				
Minor	(Prior to Sealing)				
201	Improper assembly		0.65%	3.2	Visual
	(After Sealing)				
201	Carton damaged (cut or gouged through all layers)		0.65%	3.2	Visual
202	Sealing improper		0.65%	3.2	Visual
203	Marking, missing, incorrect or illegible		0.65%	3.2	Visual

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:28Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection Table.

4.4.3.1 Maximum profile. Each cartridge case shall be gaged in a contractor certified maximum profile gage. Failure of any cartridge case to freely enter the gage in such manner as to permit the slide to close without interference shall be cause for rejection of the cartridge case.

4.4.3.2 Protective finish.

4.4.3.2.1 Salt spray. Four cartridge cases from the initial production sample and four cartridge cases from each production lot shall be subjected to this test to determine compliance with 3.4. Failure of one or more cartridge cases to comply shall be cause for rejection of the initial production sample or production lot.

4.4.4 Inspection equipment. The contractor shall submit for approval inspection equiment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and Paragraph 6.3 herein.

4.5 Test methods and procedures.

4.5.1 Salt spray. Procedures and equipment used in performing this test shall be as perscribed in Federal Test Method Standard No. 151.

5. PACKAGING

5.1 Packaging requirements. Packaging shall be as specified on Dwg. 7548320.

6. NOTES

6.1 Intended use. The components covered by this specification are intended for use on 75MM Howitzers.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection procedures and equipment designs for approval. See MIL-A-48078. Submit equipment designs, as required, to Commander, US Army Armament Research and Development Center, ATTN: DRSMC-QAR-I(D), Dover, New Jersey 07801.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:28Z
Check the source to verify that this is the current version before use.

6.4 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Center may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, Picatinny Arsenal or ARRADCOM drawings. Technical data originally prepared by these activities is now under the congnizance of ARDC.

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1315-A597)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:28Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use submitting comments and suggestions for improvements. All users of military standardization documents are invited to prov suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, a mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAG
NECESSAR
IF MAILED
IN THE
UNITED STAT

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12062 WASHINGTON D C
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
US ARMY ARMAMENT RESEARCH &DEVELOPMENT CENTER
ATTN: DRSMA-QA
DOVER, NJ 07801 5001

Source: https://assist.dla.mil - Downloaded: 2026-10-23T03:28Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-70455	CASE, CARTRIDGE, BLANK 75MM, M9A1B1

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:28Z
Check the source to verify that this is the current version before use.