MILITARY SPECIFICATION

CONTAINER, SHIPPING AND STORAGE: PA122

This specification is approved for use within the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification provides requirements and quality assurance provisions for the fabrication and inspection of one type of container used in the packaging of the Mine Dispenser: M138.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-W-8604	-Welding, Fusion; Aluminum Alloys, Process and Performance of.
MIL-W-22248	-Weldment, Aluminum, and Aluminum Alloy.
MIL-C-46168	-Coating, Aliphatic Polyurethane, Chemical Agent Resistant.
MIL-W-63150	-Weapons and Support Materiel, Standard Quality Assurance Provisions for.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to Commander, U.S Army Armament Munitions and Chemical Command, Attn AMSMC-QA, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

STANDARDS

MIL-STD-105	-Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105).
MIL-STD-1595	-Qualification of Aircraft, Missile and Aerospace Fusion Welders.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

US ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

9378330	-Packing and Marking for Shipping and Storage Container: PA 122 For Dispenser, Mine: M138.
9378331	-Shipping and Storage Container: PA 122
9381561	-Gasket

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Materials. Material shall be in accordance with the applicable drawings, specifications and standards.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

3.2 Assembly. The assembly shall comply with all requirements specified on Drawing (Dwg.) 9378331 and all associated drawings and with all requirements specified in applicable specifications.

3.3 Welding. Welding shall be performed in accordance with the requirements of MIL-W-22248 (Arc Welding) or MIL-W-8604 (Resistance Spot Welding), as applicable, by operators currently qualified in accordance with MIL-STD-1595. Welds shall exhibit characteristics of fusion, penetration and soundness of weld deposit representative of good weld practice. Inspection shall be performed in accordance with 4.5.10.

3.3.1 Specimens. Prior to production fabrication of any welded joints, the contractor shall prepare workmanship specimens of all welded joints representing the acceptable weld quality to be used in production. These specimens shall also represent the minimum acceptable cleaning procedure. These specimens shall be prepared using the welding procedures to be used in production and may be an actual part or sample simulating all of the proposed welds.

3.3.2 Capability of welder equipment and welder operaters. The contractor shall be responsible for determining the capability of the welding equipment and welding operators. The production welding operator shall perform the welding as prescribed in the contractor’s or manufacturer’s welding procedure and meet the requirements established by the approved workmanship samples.

3.4 Performance characteristics. The container, when loaded with the Mine Dispenser and associated hardware, shall comply with all requirements specified on dwg. 9378330 and with all requirements specified in this specification without evidence of loose or broken parts or structural members, or cracks which render the container unsafe. Minor dents or creases in non-structural members shall not be considered objectionable. The container shall be useable after completion of the tests listed below. Before testing and after completion of all tests, container shall comply with the pressure retention requirements of 3.6 and there shall be no physical damage to the container which would preclude its opening, closing and effective continued use. When opened, there shall be no physical damage to the mine dispenser and associated hardware which would render them unserviceable as determined by the procuring activity. All tests shall be conducted at a temperature of 72 ± 18°F.

3.4.1 Vibration. The loaded container shall meet the requirements of 3.4 when tested as specified in 4.5.3.

3.4.2 Edgewise drop. The loaded container shall meet the requirements of 3.4 when tested as specified in 4.5.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

3.4.3 Cornerwise drop. The loaded container shall meet the Requirements of 3. 4 when tested as specified in 4.5.5.

3.4.4 Rollover. The loaded container shall meet the requirements of 3.4 when tested as specified in 4.5.6.

3.4.5 Stacking. The loaded container shall be capable of supporting a simulated stacking load equal to seven (7) times the weight of a loaded container without evidence of permanent set or breakage in any of its structural members when tested as specified in 4.5.7.

3.5 Fit and function. The container shall support, protect and permit the normal installation, handling and removal of Government furnished mine dispenser, clamp assembly, protective cover , connector adapter, adapter lock, electrical cable assembly, 7/16 and 9/16 wrenches and tool carrier. Testing shall be performed in accordance with 4.5.9.

3.6 Pressure retention. After the container is temperature stabilized, the container shall maintain an internal pressure of 3 pounds min. per square inch (psi) gauge for a minimum of 10 minutes with a maximum pressure loss of .025 psi gauge. Testing shall be performed in accordance with 4.5.2.

3.7 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be specified in the contract.

3.8 Workmanship. Requirements for workmanship shall be as indicated on applicable dwgs. in applicable specifications and as specified herein.

3.8. Cleaning and surface preparation. All parts, surfaces and assemblies shall be free of dirt, grease, rust, corrosion, welding flux, scale, unacceptable weld spatter (see 4.5.10e), metal filings or shavings or any other foreign matter prior to assembly or application of any primers or finish. Cleaning methods shall not be injurious to any parts or assemblies, nor shall the parts or assemblies be contaminated by the cleaning agent.

3.8.2 Finish. Paint and finishes shall comply with all applicable drawing requirements. Prior to the application of any finish, parts and assemblies shall be dry and throughly clean and free of dirt, dust or any other foreign material. Unless otherwise specified on drawings, primary coats shall be thoroughly dry before application of any finished coat. Finish coats shall cover all required surfaces and be continuous with the possible exception of a few light scratches not exposing base metal. Paint shall not appear on any part or area where explicitly excluded by drawing requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

3.8.3 Metal characteristics. All parts and assemblies shall be free of warpage, porosity, inclusions, cracks, burrs or sharp edges as applicable. Threads shall be full and undamaged for the entire minimum length or depth as required by applicable drawings.

3.8.4 Marking. Marking shall be specified on drawings and shall be neat and sharply defined.

3.8.5 Assembly details. Assemblies shall be complete in accordance with drawing requirements with particular attention to the following details, as applicable:

(a) All hardware shall be present and of the correct type.

(b) All fastening devices i.e., handle, operated and crosspin, stud ejector pin and ejector cup shall be tight and secure.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Unless otherwise specified herein, or in the contract, the provisions of MIL-W-63150 shall apply and are hereby made a part of this detail specification.

4.1.1 Responsibility for compliance. All items must meet all requirements-of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor’s overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. The following types of inspections shall be conducted on this item:

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.4).

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated:

Part Description	Drawings	Quantity
Shipping and Storage Container: PA 122	9378331	1
Gasket	9381561	1

4.3.2 Inspections to be performed. See MIL-W-63150 and Table I specified herein.

4.3.3 Rejection. If any assembly, component or test specimen fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of an assembly, component or test specimen in the sample to comply with any of the stated requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70627A(AR)

PARAGRAPH	TITLE: Shipping and Storage Container: PA 122		SHEET 1 OF 1		DRAWING NUMBER: See Below
					NEXT HIGHER ASSEMBLY: --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Shipping and Storage Container: PA 122 (Dwg. 9378331)	1			
	Examination for defects		3.2	4.4.2.1 thru 4.4.2.5	
	Vibration test		3.4.1	4.5.3	
	Edgewise drop test		3.4.2	4.5.4	
	Cornerwise drop test		3.4.3	4.5.5	
	Rollover test		3.4.4	4.5.6	
	Stacking test		3.4.5	4.5.7	
	Pressure retention test	1/	3.6	4.5.2	
	Fit and function		3.5	4.5.9	
	Gasket, Container (Dwg. 9381561)	1			
	Examination for defects		3.2	4.4.2.3	

NOTES: 1/ Pressure retention test shall be conducted before and after all other tests have been performed.

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-STD-105.

4.4.2 Sampling plans. Unless otherwise specified in the Classification of Defects and Tests Tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70627A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.4.2.1	Base, Shipping and Storage Container, Mine Dispenser				9390617
					NEXT HIGHER ASSEMBLY 9378331
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Structural and welding, damaged or defective		0.40%	3.2/3.3	Visual
102	Location of cover locating pin incorrect		0.40%	3.2	Gage
103	Location of small hole(s) incorrect (4 places)		0.40%	3.2	Gage
104	Components missing or improperly assembled		0.40%	3.2	Visual
105	Outside length incorrect (less flanges)		0.40%	3.2	Gage
106	Outside width incorrect (less flanges)		0.40%	3.2	Gage
107	Outside height incorrect (less flanges)		0.40%	3.2	Gage
108	Inside height to surface of flange incorrect		0.40%	3.2	Gage
109	Location of base stand-off hole(s) incorrect (4 places)		0.40%	3.2	Gage
110	Height of mount, pintle incorrect		0.40%	3.2	Gage
111	Location of clamp, tie down rod incorrect		0.40%	3.2	Gage
112	Orientation of hole in clamp, tie down rod incorrect		0.40%	3.2	Gage
113	Location of rear base support incorrect		0.40%	3.2	Gage
114	Length of rear base support incorrect		0.40%	3.2	Gage

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70627A(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.1	Base, Shipping and Storage Container, Mine Dispenser				9390617
					NEXT HIGHER ASSEMBLY 9378331
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
115	Height of rear base support incorrect		0.40%	3.2	Gage
116	Width of rear base support incorrect		0.40%	3.2	Gage
117	Location of left base support assy incorrect		0.40%	3.2	Gage
118	Height of left base support assy. incorrect		0.40%	3.2	Gage
119	Length of left base support assy. incorrect		0.40%	3.2	Gage
120	Width of left base support assy. incorrect		0.40%	3.2	Gage
121	Location of right base support assy incorrect		0.40%	3.2	Gage
122	Length of right base support assy. incorrect		0.40%	3.2	Gage
123	Height of right base support assy. incorrect		0.40%	3.2	Gage
124	Width of right base support assy. incorrect		0.40%	3.2	Gage
125	Location of spacer incorrect (4 places)		0.40%	3.2	Gage
126	Location of clamp, spacer incorrect		0.40%	3.2	Gage
127	Location of tie down, slotted		0.40%	3.2	Gage
128	Location of base, pivot, tie down incorrect		0.40%	3.2	Gage
129	Location of plate, support incorrect		0.40%	3.2	Gage
130	Location of handle (6 places)		0.40%	3.2	Gage
131	Location of reinforcing rib (10 places)		0.40%	3.2	Gage
132	Location of latch hole(s) (14 places)		0.40%	3.2	Gage
133	Diameter of latch hole(s) (14 places)		0.40%	3.2	Gage
Minor					
201	Poor workmanship		1.00%	3.8	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70627A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.2	Cover, Shipping and Storage Container, Mine Dispenser	1 OF 1	9390618
			NEXT HIGHER ASSEMBLY: 9378331

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Location of hole(s) incorrect (14 plcs)		0.40%	3.2	Gage
102	Diameter of hole(s) incorrect (14 plcs)		0.40%	3.2	Gage
103	Location of receptacle, turnlock incorrect (14 places)		0.40%	3.2	Gage
104	Structural and welding damaged or defective		0.40%	3.2/3.3	Visual
105	Location of dimple(s) incorrect (4 plcs)		0.40%	3.2	Gage
106	Inside length incorrect		0.40%	3.2	Gage
107	Inside width incorrect		0.40%	3.2	Gage
108	Inside height incorrect		0.40%	3.2	Gage
109	Misalignment of dessicant baskets door		0.40%	3.2	Gage
110	Location of storage assembly		0.40%	3.2	Gage
111	Misalignment of storage assembly door fasteners		0.40%	3.2	Gage
112	Location of locating hole incorrect		0.40%	3.2	Gage
113	Location of small holes incorrect (4 plcs)		0.40%	3.2	Gage
114	Location of support, storage weldment (6 places)		0.40%	3.2	Gage
Minor					
201	Poor workmanship		1.00%	3.8	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70627A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9381561
4.4.2.3	Gasket				NEXT HIGHER ASSEMBLY 9378331
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Inside length incorrect		0.40%	3.2	Gage
102	Inside width incorrect		0.40%	3.2	Gage
103	Cross section width incorrect		0.40%	3.2	Gage
104	Cross section height incorrect		0.40%	3.2	Gage
105	Inside hole diameter incorrect		0.40%	3.2	Gage
106	Vulcanized joint strength incorrect	10	10-0-1	3.2	4.5.1
Minor					
201	Poor workmanship		1.00%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70627A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Support,Shipping and Storage Container, Mine Dispenser				9395701
					NEXT HIGHER ASSEMBLY 9378331
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside length incorrect		0.40%	3.2	Gage
102	Inside height incorrect		0.40%	3.2	Gage
103	Width incorrect		0.40%	3.2	Gage
104	Inside length incorrect		0.40%	3.2	Gage
105	Location of slots incorrect		0.40%	3.2	Gage
106	Protective finish incorrect, damaged or inadequate		0.40%	3.2	4.5.8/Visual
Minor					
201	Poor workmanship		1.00%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70627A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Shipping and Storage Container: PA 122				9378331
					NEXT HIGHER ASSEMBLY: --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Surface treatment incorrect (Perform prior to assembly of pressure equalizing valve, humidity indicator and gasket		0.40%	3.2	4.5.8/Visual
102	The closed container fails the pressure retention test prior to application of protective finish		100%	3.2	4.5.2
103	Failure of the shipping container to close or misalignment of base and cover assemblies		0.40%	3.4	Visual
104	Improper adjustment of latching handle locking force (16 places)		0.40%	3.2	Visual
105	Components missing		0.40%	3.2	Visual
106	Protective finish incorrect, damaged, or defective		0.40%	3.2	4.5.8/Visual
Minor					
201	Marking(s) missing, incorrect or illegible		0.65%	3.2	Visual
202	Poor workmanship		1.00%	3.8	Visual
NOTES:					

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection Tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and test prescribed in this specification is identified, either directly or by reference, in the "Paragraph Reference/Inspection Method" column Of the First Article or Quality Conformance Inspection Tables herein. The contractor shall submit inspection equipment designs to the Government for approval in accordance with the terms of the contractor. See 3.8 of MIL-W-63150 and 6.3 herein.

4.5 Methods of inspection.

4.5.1 Gasket vulcanized joint strength. The gasket shall be held in an approved test fixture on either side of the vulcanized joints and the specified pull force shall be applied. Observation shall be made for conformance with the applicable drawing requirements. Any gasket that fails to comply with the specified requirement shall be classed defective. (Non-destructive test)

4.5.2 Pressure retention test. After assembly, with the fasteners and locking devices secured tightly and with the pressure equalizing valve blocked off, the container shall be subjected to the pressure retention test specified on Dwg. 9378331. The container shall be connected to equipment having gage(s) with the capability and sensitivity for measuring and monitoring the test pressure and any pressure drop during the specified test interval. Any container that fails to comply with the applicable drawing requirements shall be classed defective. (Non-destructive test)

4.5.3 Vibration. The container, loaded as specified in 3.4, shall be subjected to the vibrations as specified in Table II in the vertical, transverse, and longitudinal axes. The container shall be assembled to an approved fixture with the cover closed and all latches fastened in a normal manner. Adequate safety precautions shall be observed to preclude endangering personnel and equipment. Any container failing to conform with the requirements as specified in 3.4 shall be classed defective. (Non-destructive test)

TABLE II - FREQUENCY/ACCELERATION

Frequency (Hertz)	Acceleration (G's) or Double Amplitude (IN.)
5.0 to 11.0	.4 DA
11.0 to 37.0	2.5 G's
37.0 to 52.0	034 DA
52.0 to 500.0	5.0 G's

Sweep rate: 0.8 octaves per minute for total of 60 minutes/axis, total time 3 hours.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

4.5.4 Edgewise drop. The container, loaded as specified in 3.4, shall be supported at one end of its base on a platform approximately five (5) inches in height. The other end of the container shall be raised and allowed to fall freely from a 24 inch height to a concrete or similarly hard surface. The test shall be applied to both ends of the container. Any container that fails to comply with the requirements as specified in 3.4 shall be classed defective. (Non-destructive Test)

4.5.5 Cornerwise drop. The container, loaded as specified in 3.4, shall be supported at one corner of its base on a platform approximately five (5) inches high. A block approximately twelve (12) inches high shall be placed under the other corner of the same end of the container. The other end of the container shall be raised up 24 inches and allowed to fall freely onto a concrete or similarly rigid impact surface. This test shall be applied to the diagonally opposite corners of the container. Any container that fails to comply with the requirements as specified in 3.4 shall be classed defective. (Non-destructive Test)

4.5.6 Rollover test. The container, loaded as specified in 3.4, shall be erected on its base on a concrete or similarly rigid impact surface. The container shall be tipped slowly sideways until it falls freely by its own weight from the base to the side, side to the top, top-to-the other side and from the other side to the base, completing one revolution. Any container that fails to comply with the requirements as specified in 3.4 shall be classed defective. (Non-destructive Test)

4.5.7 Stacking. The required load (2000 pounds, minimum) shall be placed on top of the container in such a manner as to simulate stacking of seven (7) additional loaded containers thereon. Any container that fails to comply with the requirements as specified in 3.4 shall be classed defective. (Non-destructive Test)

4.5.8 Protective finish. The contractor shall prepare test panels of the same material as used in the container, at the time of finishing the assemblies, subjected to the same finishing process, and shall submit the test panels for the tests specified in MIL-C-46168, 3.6.6, 3.6.7, 3.6.8, 3.6.10, 3.6.11 and 3.6.14.

4.5.9 Fit and function (see 3.5). The following assembly procedure shall be followed to check fit and function using government furnished equipment, see dwg. 9378330.

(a) Place mine dispenser on mount, pintle and rotate dispenser 360°. Check for obstructions.

(b) Examine the three base supports for physical defects. Install the government furnished mine dispenser, shelf side down, pintle end at locating pin end, into container. Check fit of shelf in base holders.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

(c) Install support, shipping and storage container, mine dispenser and its associated hardware. Assemble all screws hand tight. Once assembled, the support, shipping and storage container, mine dispense should firmly secure the dispenser into the container.

(d) Check fit of clamp on tie down rod.

(e) With the clamp on tie down rod check the fit of the clamp assembly pin into the hole in the tie down rod.

(f) Place 16 units of dessicant into dessicant basket.

(g) Check fit of dessicant compartment door.

(h) Place electrical cable, protective cover, connector adaptor, adaptor lock, 2 wrenches and tool carrier into storage assembly to check fit.

(i) Close storage assemble door and check alignment of receptacles and handle, operated by fully engaging handle into receptacle.

(j) Install gasket on container base.

(k) Place cover on top of base and check alignment of receptacles and handle, operated by engaging handles (close and open).

4.5.10 Welding quality (see 3.3). Weld quality shall be visually inspected for the requirements of MIL-W-22248 (Class 3) or MIL-W-8604 (Class B) as applicable, with particular attention to the following details:

(a) Surfaces to be welded shall be free of dirt, grease, oil, paint or other foreign material prior to welding.

(b) When multiple welds are deposited, each layer shall be thoroughly clean and free of slag and gas pits before deposit of another layer.

(c) Tack welds, when used, shall be deposited in such a manner as to assure their incorporation into the final weld without causing discontinuity in the deposit. Cracks in tack welds in inaccessible locations or not affecting container, structural or seal integrity are acceptable.

(d) Final welds shall be of approximately the weld size specified on the dwg. Visual inspection for this requirement will suffice; gaging of the weld size will not be required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

(e) Welds shall be free of discontinuities, overlaps, gas holes, slag, flux, or any other obvious defects representative of poor weld practice. There shall be no weld spatter on functional or machined mating surfaces. Weld spatter, when present on other surfaces, shall be removed by chipping, grinding or other commercial practice and the underlying surface refinished to the satisfaction of the Government QAR. Removal of weld spatter shall not puncture, tear, distort or otherwise damage the underlying metal surface.

(f) The contractor shall provide all necessary shrinkage controls to assure the finished item complies with dwg. dimensional requirements after welding.

(g) When required by dwgs., dye penetrant inspection of welds shall be performed in accordance with MIL-W-22248 (Class 3).

5. PACKAGING

5.1 Preservation and packaging. The container shall be preserved and packaged in accordance with Special Packaging Instruction Sheet (SPI) P9378331. All items which are to be procured as repair parts shall be preserved and packed in accordance with their applicable SPI.

5.2 Packing. Packing of the container shall be in accordance with SPI P9378331. Repair parts shall be packed in accordance with its applicable SPI.

5.3 Marking. Marking for container and repair parts shall be in accordance with SPI P9378331 and the applicable SPI for each spare part.

5.4 Shipping. When containers from more than one lot are shipped as a carload, each lot shall be kept separated, and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

6.1 Intended use. The container is intended to be used for the shipping and storage of the Dispenser, Mine: M138 and its associated hardware.

6.2 Ordering data. See MIL-W-63150.

6.3 Submission of inspection equipment designs for approval. See MIL-W-63150. Submit equipment designs as required to Commander, U.S. Army Armament Research, Development and Engineering Center (ARDEC), AMSMC-QAT-I (D), Picatinny Arsenal, New Jersey 07806-5000.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

6.4 Distribution of ammunition data cards and test data. Distribution of data cards and functioning test data shall include the following: Commander, U. S. Army Armament Research, Development and Engineering Center, AMSMC-QAT-M(D), Picatinny Arsenal, New Jersey 07806-5000.

6.5 Drawings. Drawings listed in Section 2 of this specification under the heading U.S. Army Armament Research, Development and Engineering Center (ARDEC) may also include drawings prepared by, and identified as U. S. Army Armament Research and Development Command (ARRADCOM) , Edgewood Arsenal, Frankfor Arsenal, Rock Island Arsenal, Or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

6.6 Government loaned items. The items specified below shall be furnished by the Government on loan to the contractor to perform the inspections and tests required herein. When required, additional items shall be built by the contractor in accordance with dwgs. and instructions from the procuring agency.

Item and Description	Quantity
Dispenser, Mine (Dwg. 9359984)	1
Clamp Assembly (Dwg. 9359850)	1
Cover, Protective, Mine Dispenser (Dwg . 5-10-43)	1
Cable Assembly, Power , Electrical: Dispenser (Dwg. 9360017)	1
Lock, Adapter (Dwg. 9360063)	1
Adapter, Connector (Dwg. 11677570)	1
Wrench, OPEN-END, Fixed: DBLE-HD Type, 15° Angle, 7/16 in. & 3/8 in. openings (NSN 5120-00-277-2342)	1
Wrench, OPEN-END, Fixed: DBLE-HE Type 15° Angle, 9/16 in. & 1/2 in. openings (NSN 5120-00-187-7124)	1
Carrier, Tool (Dwg. 11655787)	1

6.7 Subject term (key word) listing.

Mine Dispenser
Marking
Pressure Retention
Stacking
Storage Container

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

6.8 Changes from previous issue. The margins of this specification are marked with asterisks (or vertical lines) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army - AR

Preparing activity:
Army - AR

(Project 1345-A455)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.