INCH-POUND

MIL-T-62340A(AT)
AMENDMENT 2
20 August 1991
SUPERSEDING
AMENDMENT 1
5 May 1989

# MILITARY SPECIFICATION

## TANK, COMBAT, FULL-TRACKED, M1, SERIES; PROCESSING FOR SHIPMENT AND STORAGE OF

This amendment forms a part of MIL-T-62340A(AT) 14 March 1988, and incorporates all the requirements of amendment 1, 5 May 1989. It is approved for use by the US Army Tank-Automotive Command, Department of the Army, and is available for use by all departments and Agencies of the Department of Defense.

PAGE 1

1.1 Line 5: Delete "and M1A1 tanks." and substitute "M1A1, and M1A2 tanks."

PAGE 3

2.1.1: Under the heading "MILITARY" add "MIL-L-3150 - Lubricating Oil, Preservative, Medium."

PAGE 6

2.1.2: Under the heading "ORDNANCE" delete "12273123 - Fitting, Quick Disconnect."

PAGE 10

3.2.3 line 7: Delete "3.4.16" and substitute "3.4.15".

AMSC N/A AREA PACK

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:33Z
Check the source to verify that this is the current version before use.

PAGE 11

3.3.1 line 9: Delete "VV-L-800." and substitute "MIL-L-3150 or MIL-L-21260, type I, grade 10."

PAGE 12

3.3.5.1.2 Delete entire paragraph and substitute: "Oil System. The oil tank should be filled with new normal seasonal operational oil as specified in the lubrication order. Add four, 8 ounce cans of Brayco 599 oil preservative compound (NSN 6850-00-142-9582) to the engine oil tank. Run the engine until normal operating temperature is reached. Subsequent running of the engine for short periods is acceptable without represervation of the oil system."

PAGE 13

3.3.5.3.1 line 9: Delete "12273123-2." and substitute "of the quick disconnect fitting."

PAGE 15

3.3.7.1 line 3: Delete "VV-L-800." and substitute "MIL-L-3150 or MIL-L-21260, type I, grade 10."

3.3.7.2 line 3: Delete "VV-L-800." and substitute "MIL-L-3150 or MIL-L-21260, type I, grade 10."

3.3.7.2.1 line 2: Delete "H12" and substitute "B2".

PAGE 16

3.3.7.4.1 line 3: Delete "grease conforming to MIL-G-10924." and substitute "preservative oil conforming to MIL-L-3150 or MIL-L-21260, type I, grade 10."

3.3.7.4.1 line 5: After "...conforming to QQ-A-1876." Insert "A strip of 2 inch wide tape conforming to type II of MIL-T-22085 shall be centered on the plug and applied from the top to the bottom."

3.3.7.4.2 line 3: Delete "grease conforming to MIL-G-10924." and substitute "preservative oil conforming to MIL-L-3150 or MIL-L-21260, type I, grade 10.

3.3.7.4.2 line 4: Delete "H11" and substitute "B2".



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:33Z
Check the source to verify that this is the current version before use.

PAGE 16

3.3.7.4.2 line 5: After "...conforming to QQ-A-1876." Insert "A strip of 2 inch wide tape conforming to type II of MIL-T-22085 shall be centered on the plug and applied from the top to the bottom."

3.3.7.6 line 2: Delete "VV-L-800" and substitute "MIL-L-3150 or MIL-L-21260, type I, grade 10".

PAGE 18

3.3.8.3.1 line 7: delete "type I, grade C" and substitute "type 2, grade A".

3.3.8.3.1 line 10: Delete "VV-L-800" and substitute "MIL-L-3150 or MIL-L-21260, type I, grade 10".

3.3.8.3.2 line 22: Delete "VV-L-800" and substitute "MIL-L-3150 or MIL-L-21260, type I, grade 10".

3.3.8.4.1 line 3: delete "in accordance with ..... D-4 of MIL-P-116." and substitute "with P-D-680, and wiped dry."

PAGE 19

3.3.8.4.2 line 3: delete "in accordance with ..... D-4 of MIL-P-116." and substitute "with P-D-680, and wiped dry."

3.3.8.6 line 2: delete "in accordance with ..... D-4 of MIL-P-116." and substitute "with P-D-680, and wiped dry."

3.3.9.A.3: After "Commander's weapon sight" substitute "(not applicable to M1A2)".

3.3.9.A.6: Delete "Gunner's vision blocks" and substitute "Loader's periscope".

Add a new line 3.3.9.A.7 as follows: "7. Driver's periscope".

3.3.9.B.2: Delete "windows" and substitute "window (not applicable to M1A2)".

3.3.9.B.3: Delete "Driver's hatch windows" and substitute "Driver's center and side periscopes".

3.3.9.B.4: Delete "Loader's hatch windows" and substitute "loader's periscope".



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:33Z
Check the source to verify that this is the current version before use.

PAGE 19

Add a new line 3.3.9.B.7 as follows: "7. Commander's independent thermal viewer window (M1A2 only)".

PAGE 20

3.3.9 line 5: Delete entire sentence "Headrests of the ...conforming to type II of MIL-T-22085".

3.3.9 line 9: After "The exterior optics" insert ", with the exception of the M1A2 commander's independent thermal viewer (CITV),".

3.3.9 line 13: Delete entire sentence "All exposed ..... MIL-G-10924".

3.3.9 line 15: After "... from the inside." insert "The Commander's independent thermal viewer (CITV) shall have the ballistic shield in the closed position (this is applicable only to the M1A2)."

3.3.9 line 19: Delete "B20 through B22." substitute "B16 through B19 (figures B16 through B19 are not used on the M1A2)."

PAGE 21

3.3.10 line 5: After "...every 4 years." substitute "(The CEU is not used on the M1A2.)"

3.3.14: Delete and substitute:

"3.3.14 Ventilation. The driver's and engine compartment drain valves/ports shall be secured in the open position. Unpainted metallic surfaces shall be coated with preservative compound conforming to MIL-C-16173, Grade 1. Remove the driver's center and loader's periscopes installed (see 3.4.17 for packaging instructions). Screens conforming to figures B1 and B3 through B15 shall be constructed and installed in drain valve openings and driver's center and loader's periscope openings as illustrated in figures B3, B5, and B7. Prepare a red tag conforming to UU-T-81 imprinted with the following: "REMOVE SCREENS, VENTILATION BAFFLES, AND CLOSE DRAINS BEFORE OPERATING VEHICLE." Secure the red tag in a conspicuous location in the driver's compartment."



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:33Z
Check the source to verify that this is the current version before use.

PAGE 22

3.3.16 line 4: Delete "3.4.10" and substitute "3.4.9".

3.3.18: Delete entire paragraph, and substitute new paragraph 3.3.18 as follows:

"3.3.18 Commander's weapon cradle assembly. The commander's weapon cradle assembly shall be removed from the "A" frame at bracket assembly 12549035. Exposed, unpainted, unplated metal surfaces shall be cleaned and coated with grease conforming to MIL-G-10924. (This is applicable only to the M1A2.)"

Add a new paragraph 3.3.20 as follows:

"3.3.20: Hull/Turret Electronics Unit (H/TEU). The test connector dust cap must be in place. When the vehicle is to be stored for a period longer than 30 days without running the engine, the H/TEU battery shall be removed and stored. (This is applicable only to the M1A2.)"

PAGE 23

3.4.7: Delete entire paragraph and substitute:

"3.4.7 Commander's weapon cradle assembly. Immediately after preservation (see 3.3.18), the commander's weapon cradle assembly shall be packaged in accordance with Level A requirements of MIL-STD-2073-1, identified as to contents, and securely stowed within the vehicle. (This is applicable only to the M1A2.)"

PAGE 24

3.4.15: Delete and substitute:

"3.4.15 Loader's seat. The loader's seat back shall be folded down on the seat bottom."

Add a new paragraph 3.4.17 as follows:

"3.4.17 Driver's center and loader's periscopes. Clean in accordance with 3.3.9, pack in accordance with the applicable packing requirements for the part removed, identify in accordance with MIL-STD-129 and securely stow within the vehicle."



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:33Z
Check the source to verify that this is the current version before use.

PAGE 24

Add a new paragraph 3.4.18 as follows:

"3.4.18 Commander's Independent Thermal Viewer (CITV). The ballistic shield of the commander's independent thermal viewer shall be sealed with tape conforming to type II of MIL-T-22085. (This is applicable to the M1A2 only.)"

Add a new paragraph 3.4.19 as follows:

"3.4.19 Digital Electronics Control Unit (DECU). If the vehicle has a DECU, it shall be removed, and packaged in accordance with the Level A requirements of Special Packaging Instruction (SPI) AK13311526. The package shall be marked with the following two notes:

- "The unit must be stored in a controlled warehouse in temperatures of 50 °F or lower."

- "Battery pack last charged on date:" (Followed by the date that the battery pack was last charged.)

The battery pack charged date is the latest date found on the DECU battery cover underneath the battery pack serial number and is formatted in year/month/day."

PAGE 25

3.6.2 line 2: delete "security pins and ..... through F-5." and substitute "attaching pins shall be secured by replacing the retaining clip (CAGE 99984, PN 9656) with a Trans-Lock pin (CAGE 71182, PN 9251500-2Q) secured in place. Place the retaining clips in a MIL-B-117, Class B bag. Close by tape, stapeling or heat sealing. Mark the bag with part number and nomenclature, and secure in vehicle.

3.7.1: Delete in its entirety.

PAGE 26

3.7.4 after line 2 add "Any fuel left in the tanks shall be stabilized with Biobar/Biocide per MIL-S-53021."

3.7.9: Delete entire paragraph, and note "NOT USED."



Source: https://assist.dla.mil -- Downloaded: 202610-23T01:33Z
Check the source to verify that this is the current version before use.

PAGE 27

3.8.1 line 1: after "Loading of flat cars." add "The main gun tube shall be secured with wire rope, MIL-W-83420, as depicted in Figure A1."

3.10.1 line 2: after ".... of the vehicles." add "The fuel shall be stabilized with Biobar/Biocide per MIL-S-53021."

PAGE 34

Table I: For "Fire control, periscopes and optical items" under the column heading "Preservation Level B" change 3.3.7.1 to 3.3.9, and under column heading "Packaging and Storage" change 3.3.9 to 3.4.17.

Table I: Under the column heading "Component or Processing Activity" add "Hull/Turret electronics unit". On the same line under the column heading "Preservation Level A and Level B" add "3.3.20".

PAGE 35

Table I: Under the column heading "Component or Processing Activity" delete "Miscellaneous preservation". On the same line under the column heading "Packaging/Stowage" delete "3.3.18 and 3.7.9".

Under the column heading "Component or Processing Activity" opposite "Crosswind sensor mast". On the same line under the column heading Cleaning, and Preservation Level A and Level B add "3.2.7". Under Packaging/Stowage" delete "3.4.5" and add "3.2.7".

Under the column heading "Component or Processing Activity" delete "Grenade launcher cradle" and substitute "Grenade launcher cable".

Under the column heading "Packaging/Stowage" lines 12 through 23 delete "3.4.6 through 3.4.15" and substitute "3.4.5 through 3.4.14" respectively.

Under the column heading "Packaging/Stowage" delete "3.4.17" and substitute "3.4.16".



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:33Z
Check the source to verify that this is the current version before use.

PAGE 37

6.4 line 3: Delete "-30" and substitute "-34".

PAGE 39

line 2: Delete "valve" and substitute "valve/port".

PAGE 40

Add the following: "(4.50 $^{+ .00}_{- .06}$ DIA.)" beneath "4.06 $^{+ .00}_{- .06}$", "(3.75)" beneath "2.62", "(7.50)" beneath "5.25", and "(8.00 DIA.)" beneath "5.88 DIA.".

Add in the notes block: "DIMENSIONS:
( ) IS A DIMENSION FOR THE 120mm GUN."

PAGE 41

Delete "valve" and substitute "valve/port".

Delete "3.50 SQ." and substitute "4.00 SQ.".

PAGE 42

Delete "6.00 DIA." and substitute "6.00 SQ.".

PAGE 193 through 199

Delete figures F1 through F5.

PAGE 221

Delete figure H1.

Custodian:
Army - AT

Preparing Activity:
Army - AT

(Project Number PACK-A372)



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:33Z
Check the source to verify that this is the current version before use.