MIL-T-82300/27(TD)
1 July 1970

MILITARY SPECIFICATION

TRANSPARENCY, ANIMATED; INFRA-RED RETICLE (SIDEWINDER)

This specification has been approved by the Naval Training Device Center, Department of the Navy

The technical requirements for procuring the animated transparency described herein shall consist of this document and the issue in effect of Specification MIL-T-82300.

1. SCOPE

1.1 This specification covers the requirements for an animated transparency of the infra-red reticle guidance system for the Sidewinder guided missile.

1.1.1 This item has been designated by the Naval Training Device Center as Device 3G68 for Navy procurement. (see 6.2).

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bid or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

QQ-C-320	Chromium Plating (Electrodeposited)

Military

MIL-T-82300	Transparencies; Animated, General Specification for

DRAWINGS

Naval Training Device Center (NAVTRADEVCEN)

DL860450	A/T, Guided Missile Infra-red Recticle (Sidewinder), Device 3G68

/FSC 6910/

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:02Z
Check the source to verify that this is the current version before use.

PHOTOGRAPHS

Naval Training Device Center (NAVTRADEVCEN)

BXA-14039-6-70 and BXA-14040-6-70	A/T, Guided Missile Infra-red Recticle (Sidewinder), Device 3G688

PUBLICATIONS

Naval Training Device Center (NAVTRADEVCEN)

NAVEXOS P-2175	Guide for Animated Transparency, Infra-red Reticle, Guided Missile (Sidewinder), Device 3G68

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

3. REQUIREMENTS

3.1 Materials.- Materials shall be in accordance with 3.1.1 through 3.1.3. Materials not specified in 3.1.1 through 3.1.3 shall be in accordance with the materials requirements of MIL-T-82300.

3.1.1 Cements.- Cements used for joining plastic components shall be those cements recommended by the manufacturer of the plastic and tested by the contractor as suitable for meeting the cementing and performance requirements of this specification.

3.1.2 Metals.- Except for springs, all metal parts and fastenings used in the device shall be corrosion resistant steel or be protectively plated in accordance with QQ-C-320.

3.1.3 Wood and wood products.- Materials for the top and bottom of the carrying case shall be 1/4 inch thick exterior grade plywood, smooth two sides.

3.2 Design.- The animated transparency shall be designed in accordance with the design requirements of MIL-T-82300, NAVTRADEVCEN Drawing DL860450 and shall be capable of demonstrating all the utilization requirements of NAVEXOS P-2175.

3.3 Construction.- The animated transparency shall be constructed in accordance with the NAVTRADEVCEN Drawing DL860450. Construction details not specified on the drawing shall be as shown on NAVTRADEVCEN photographs BXA-14039-6-70 and BXA-14040-6-70. Construction details, not specified in this specification shall be in accordance with the construction requirements of MIL-T-82300.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:02Z
Check the source to verify that this is the current version before use.

3.3.1 Cementing.- Cementing shall be limited to those areas where assembly with screws is clearly impractical. Cemented joints shall be free of air bubbles and stress-crazing and shall have the transparency of the original plastic throughout the joint. The surfaces to be cemented shall be thoroughly softened by means of a solvent, so that a soft layer or cushion is produced on each surface and the subsequent uniting and hardening will effect a strong homogeneous bond. Bonding by capillary attraction shall require specific written approval of the procuring activity for each specific variance. For recommendations on cementing acrylic plastics; the publications cited in the cementing requirements of MIL-T-82300 may be used.

3.3.2 Foil transparency.- Separate foil transparencies shall be provided showing the illustrations as shown in the drawings of 3.3.

3.3.2.1 The foil transparencies shall each be mounted in a pressboard mount approximately 10 1/2 inches by 12 inches.

3.4 Performance.- The animated transparency, when used on the overhead projector, shall withstand the temperatures produced by a 1,000 watt projection lamp for a period of 45 minutes with the projector's heat filter removed, in a room with ambient temperatures ranging to 90 degrees Fahrenheit. At the end of this period, the animated transparency shall meet the conditions listed in the performance requirements of MIL-T-82300.

3.5 Details of components.-

3.5.1 Baseplate.- Except as specified in 3.5.1.1, the baseplate shall be in accordance with the baseplate requirements of MIL-T-82300.

3.5.1.1 Dust seal.- The parting line between the layers of the baseplate shall be sealed with white opaque polyester film so as to be dustproof and to mask edge lighting effects. Dust seals shall be provided wherever a laminated component or flap is used. Such seals, in projectable areas, shall be applied to the edges only.

3.5.2 Movable components.- Movable components shall be in accordance with 3.5.2.1 and 3.5.2.2. Components not specified in 3.5.2.1 and 3.5.2.2 shall be in accordance with the movable components requirements of MIL-T-82300.

3.5.2.1 Overall height.- The maximum thickness of the sum of those components which are projected shall not exceed 1/2-inch from the top of the lowest projectable component to the top plane of the highest component. The projected image shall be sharp and clear. Projectable movable components shall have a vertical separation to prevent abrasion of the moving parts. This separation shall not be less than 1/32-inch during the operating test of MIL-T-82300.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:02Z
Check the source to verify that this is the current version before use.

3.5.2.2.1 Selection of screws.- The minimum practical number of screws and the smallest practical head diameter of screws for fastening components shall be used within the projected image area. The size of screws to be used on components having a small projectable area shall be dependent on the largest head diameter that will not interfere with the clarity and outline of the individual component when projected on the screen.

3.5.3 Stops.- Stops for flaps and slides shall be provided as specified in the stops requirements of MIL-T-82300.

3.5.4 Controls.- Controls for actuating the various components shall be as shown on the drawing of 3.3 to meet the utilization requirements of NAVEXOS P-2175. All controls shall be movable by light finger pressure.

3.5.5 Carrying case.- The carrying case shall be in accordance with the carrying case requirements of MIL-T-82300.

3.6 Dimensions and tolerances.- Dimensions and tolerances shall be in accordance with the dimensions and tolerance requirements of MIL-T-82300.

3.7 Finish and color.-

3.7.1 Finish.- Finish shall be in accordance with the finish requirements of MIL-T-82300.

3.7.2 Color.- Colors for projectable components shall be as specified on the drawing of 3.3. Colors not spedified on the drawing shall be as shown on the NAVTRADEVCEN 35mm color slides of 3.3.

3.7.2.1 Colors listed in Table I of MIL-T-82300, or equivalent in hue, clarity, transparency and durability as its corresponding commercial acrylic color, shall be used.

3.7.3 Cleaning.- Cleaning shall be in accordance with the cleaning requirements of MIL-T-82300.

3.7.4 Waxing.- Waxing shall be in accordance with the wax requirements of MIL-T-82300.

3.8 Nameplates or product markings.- Except as specified in 3.8.1 and 3.8.2, nameplates or product markings shall be in accordance with the nameplates and product markings requirements of MIL-T-82300.

3.8.1 Nameplate.- A nameplate shall be affixed to each animated transparency in the location specified on the photographs of 3.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:02Z
Check the source to verify that this is the current version before use.

3.8.2 Product markings.- Product markings, nomenclature and notes shall be as shown on the photographs of 3.3.

3.9 Workmanship.- Workmanship shall be in accordance with the workmanship requirements of MIL-T-82300.

4. QUALITY ASSURANCE PROVISIONS

4.1 Except as specified in 4.1.1, quality assurance provisions shall be in accordance with the quality assurance provisions of MIL-T-82300.

4.1.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

5. PREPARATION FOR DELIVERY

5.1 Preparation for delivery shall be in accordance with preparation for delivery requirements of MIL-T-82300.

6. NOTES

6.1 Except as specified in 6.2, the notes of MIL-T-82300 shall be applicable.

6.2 Ordering data.- Procurement documents should specify the following:

(a) Title, number and date of this specification

(b) Procuring activity designation (see 1.1.1)

(c) Selection of applicable levels of preservation, packaging and packing

(d) Gross weight of shipping containers

(e) Government-furnished and Government-loaned property.

CUSTODIAN:

Navy-TD

PREPARING ACTIVITY:

Navy-TD
Project No. 6910-N-247

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:02Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:02Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

Commanding Officer
Naval Training Device Center
Specifications Control Division (3335)
Orlando, Florida 32813

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:02Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity (as indicated on reverse hereof).

SPECIFICATION

ORGANIZATION *(Of submitter)*

CITY AND STATE

CONTRACT NO.

QUANTITY OF ITEMS PROCURED

DOLLAR AMOUNT
$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*

DATE

DD FORM 1 APR 63 1426 REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:02Z
Check the source to verify that this is the current version before use.