[INCH-POUND]
A-A-59590/4A
21 June 2002
SUPERSEDING
A-A-59590/4
27 November 2000

COMMERCIAL ITEM DESCRIPTION
SPECIFICATION SHEET

HOLDERS, ELECTRICAL CARD, WEDGE RETAINERS, 3 PIECE, SCREW ACTUATED DRIVE, .225 X .260 INCH BODY SIZE

The General Services Administration has authorized the use of this commercial item description (CID) for all federal agencies.

The complete requirements for procuring electrical card holders described herein shall consist of this document and the latest issue in effect of A-A-59590.

SCOPE. This CID specification sheet covers 3 piece card holders that use screw actuated wedges to hold circuit card assemblies into their installed positions in heat sinking devices (cold plates, heat exchanger) or other applications. Card holders covered by this CID are intended to provide 60g/6ms resistance to shock, withstand 25 G-rms of vibration and provide 2 to 4 degrees C/W/inch thermal resistance between the circuit card assemblies and the heat sink surfaces. Items covered by this CID specification sheet are intended for commercial/industrial applications.

CLASSIFICATION. This CID specification sheet uses a classification system which is included in the Part Identification Number (PIN) as shown in the following example (see notes).

AA59590	/04	C, B ,H	N, J, T, V, K, R, S	* *	W, D, E
CID number	Applicable CID sheet	Finish	Mounting	Length	Options

SALIENT CHARACTERISTICS.

Performance. Card holders shall hold the circuit card firmly in place providing high resistance to shock and vibration while providing maximum thermal transfer.

Interface and physical dimensions. The card holders supplied to this CID specification sheet shall be as specified herein and the general CID.


Expanded and relaxed dimensions. Expanded and relaxed dimensions shall be as specified in figure 1.

Mounting options. The mounting options shall be as specified in A-A-59590.

Mounting holes (when required). Two mounting holes are required on card holders less than 6.00 inches (152.4 mm) in length. Three mounting holes are required on card holders 6.00 inches or greater in length. The third mounting hole shall be centered on the mounting body. See table I and figure 1 for mounting hole spacing requirements.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:19Z
Check the source to verify that this is the current version before use.



Inches	mm	Inches	mm	Inches	mm	Inches	mm
.07	1.8	.20	5.1	.250	6.4	.325	8.3
.12	3.1	.225	5.7	.270	6.9	.70	17.8

NOTES:
1. Dimensions are in inches. Metric equivalents are given for information only.
2. Unless otherwise specified, tolerances are ± .02 (0.5 mm), for 2 places and ± .010 (0.25 mm), for 3 places.

FIGURE 1. Relaxed and expanded dimensions.

TABLE I. Assembly dimensions.

PIN length designator	Dimension “LENGTH” ± .02 (± 0.5)	Dimension “B” ± .03 (± 0.8)	Dimension “M” ± .005 (± 0.13)
28	2.8 (71.1)	2.30 (58.4)	.90 (22.9)
30	3.0 (76.2)	2.50 (63.5)	1.10 (27.9)
35	3.5 (88.9)	3.00 (76.2)	1.60 (40.6)
38	3.8 (96.5)	3.30 (83.8)	1.90 (48.3)
48	4.8 (121.9)	4.30 (109.2)	2.90 (73.7)
53	5.3 (134.6)	4.80 (121.9)	3.40 (86.4)
55	5.5 (139.7)	5.00 (127.0)	3.60 (91.4)
58	5.8 (147.3)	5.30 (134.6)	3.90 (99.1)
61	6.1 (154.9)	5.60 (142.2)	4.20 (106.7)
67	6.7 (170.2)	6.20 (157.5)	4.80 (121.9)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:19Z
Check the source to verify that this is the current version before use.

Options. Card holders can have the following options. Card holders not requiring one of the following options shall leave the options position in the PIN blank.

Lockwasher and flat washer (see figure 2). A lockwasher and flat washer located under the screw head will provide for additional resistance to loosening from shock and vibration. Card holders requiring a lockwasher and flat washer option shall include a suffix “W” in the PIN (see classification and notes).




FIGURE 2. Lockwasher and flat washer details.

Screw self-locking element (see figure 3). The use of a screw self-locking element will provide prevailing torque for resistance to loosening from shock vibration. Card holders requiring a screw self-locking element shall include a suffix “E” in the PIN (see classification and notes).




FIGURE 3. Screw self-locking element details.

Lockwasher, flat washer, and screw self-locking element. Card holders requiring a lockwasher, flat washer, and screw self-locking element option shall include a suffix “D” in the PIN (see classification and notes).

NOTES.

PIN. The PIN should be used for government purposes to buy commercial products to this CID specification sheet. See the classification section for PIN format example.

Commercial products. As part of the market analysis and research effort, this CID specification sheet was coordinated with the following manufacturers of commercial products. At the time of CID specification sheet preparation and coordination, these manufacturers were known to have commercial products that would meet the requirements of this CID specification sheet. (NOTE: This information should not be considered as a list of approved manufacturers or be used to restrict procurement to only the manufacturers shown.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:19Z
Check the source to verify that this is the current version before use.

Manufacturer CAGE	Manufacturer name and address	Manufacturer contact information
18915	APW Electronic Solutions 14100 Danielson Street Poway, CA 92064–6898	Tel: (858) 679–4550 Toll Free: (800) 854–7086 Fax: (858) 679–4555 E-mail: sales.electronicsolutions@apw.com URL: www.apw.com
52094	Calmark Corporation 4915 Walnut Grove Avenue San Gabriel, CA 91776–2099	Tel: (626) 287–0451 Fax: (626) 287–7350 E-mail: sales@calmark.com URL: www.calmark.com

Part number (P/N) supersession data. This CID specification sheet supersedes the following manufacturer's P/Ns as shown. This information is being provided to assist in reducing proliferation in the government inventory system.

TABLE II. Commercial P/N supersession data. 1/

PIN designator AA59590/04	Vendor similar designator or type part number 2/ CAGE 18915	Vendor similar designator or type part number 2/ CAGE 52094
CJ28	40–6	225CR2.80H
CN28	40–6–A	225CR2.80
CT28	40–6–T	225CR2.80T0
CV28	40–6–S	225CR2.80T2
CJ28E	40–6–L	225CR2.80HL
CN28E	40–6–A–L	225CR2.80L
CT28E	40–6–T–L	225CR2.80T0L
CV28E	40–6–S–L	225CR2.80T2L
CJ28W	40–6–LF	W225CR2.80H
CN28W	40–6–LF–A	W225CR2.80
CT28W	40–6–LF–T	W225CR2.80T0
CV28W	40–6–LF–S	W225CR2.80T2
CJ28D	40–6–LF–L	W225CR2.80HL
CN28D	40–6–LF–A–L	W225CR2.80L
CT28D	40–6–LF–T–L	W225CR2.80T0L
CV28D	40–6–LF–S–L	W225CR2.80T2L

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:19Z
Check the source to verify that this is the current version before use.

TABLE II. Commercial P/N supersession data. - Continued.

PIN designator AA59590/04	Vendor similar designator or type part number 2/ CAGE 18915	Vendor similar designator or type part number 2/ CAGE 52094
BJ28	40–6–B	A225CR2.80H
BN28	40–6–B–A	A225CR2.80
BT28	40–6–B–T	A225CR2.80T0
BV28	40–6–B–S	A225CR2.80T2
BJ28E	40–6–B–L	A225CR2.80HL
BN28E	40–6–B–A–L	A225CR2.80L
BT28E	40–6–B–T–L	A225CR2.80T0L
BV28E	40–6–B–S–L	A225CR2.80T2L
BJ28W	40–6–B–LF	WA225CR2.80H
BN28W	40–6–B–LF–A	WA225CR2.80
BT28W	40–6–B–LF–T	WA225CR2.80T0
BV28W	40–6–B–LF–S	WA225CR2.80T2
BJ28D	40–6–B–LF–L	WA225CR2.80HL
BN28D	40–6–B–LF–A–L	WA225CR2.80L
BT28D	40–6–B–LF–T–L	WA225CR2.80T0L
BV28D	40–6–B–LF–S–L	WA225CR2.80T2L
HJ28	40–6–B3	HA225CR2.80H
HN28	40–6–B3–A	HA225CR2.80
HT28	40–6–B3–T	HA225CR2.80T0
HV28	40–6–B3–S	HA225CR2.80T2
HJ28E	40–6–B3–L	HA225CR2.80HL
HN28E	40–6–B3–A–L	HA225CR2.80L
HT28E	40–6–B3–T–L	HA225CR2.80T0L
HV28E	40–6–B3–S–L	HA225CR2.80T2L
HJ28W	40–6–B3–LF	WHA225CR2.80H
HN28W	40–6–B3–LF–A	WHA225CR2.80
HT28W	40–6–B3–LF–T	WHA225CR2.80T0
HV28W	40–6–B3–LF–S	WHA225CR2.80T2
HJ28D	40–6–B3–LF–L	WHA225CR2.80HL
HN28D	40–6–B3–LF–A–L	WHA225CR2.80L
HT28D	40–6–B3–LF–T–L	WHA225CR2.80T0L
HV28D	40–6–B3–LF–S–L	WHA225CR2.80T2L

1/ CID PINs listed only with length designator “28”.
2/ The manufacturer's part number shall not be used for procurement to the requirements of this CID specification sheet. At the time of preparation of this CID specification sheet, the aforementioned commercial products were reviewed and could be replaced by the CID PIN shown. For actual part marking requirements, see the marking paragraph of the basic CID.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:19Z
Check the source to verify that this is the current version before use.

TABLE III. Example of PIN with available length designators.

PIN designator AA59590/04	Vendor similar designator or type part number 1/ CAGE 18915	PIN designator AA59590/04	Vendor similar designator or type part number 1/ CAGE 52094
CJ28	40–6	CJ28	225CR2.80H
CJ30	40–5009–3.00	CJ30	225CR3.00H
CJ35	40–5009–3.50	CJ35	225CR3.50H
CJ38	40–8	CJ38	225CR3.80H
CJ48	40–10	CJ48	225CR4.80H
CK53	40–11	CJ53	225CR5.30H
CJ55	40–5009–5.50	CJ55	225CR5.50H
CK58	40–12	CJ58	225CR5.80H
CJ61	40–5009–6.10	CJ61	225CR6.10EH
CJ67	40–5009–6.70	CJ67	225CR6.70EH

1/ The manufacturer's P/N shall not be used for procurement to the requirements of this CID specification sheet. At the time of preparation of this CID specification sheet, the aforementioned commercial products were reviewed and could be replaced by the CID PIN shown. For actual part marking requirements, see the marking paragraph of the basic CID.

TABLE IV. Supersession information.

Superseded (old) PIN in accordance with DSCC Drawing 84103	Superseding (new) CID PIN	Superseded (old) PIN in accordance with DSCC Drawing 84103	Superseding (new) CID PIN
84103–01B	AA59590/04BJ28	84103–01C	AA59590/04CJ28
84103–02B	AA59590/04BJ30	84103–02C	AA59590/04CJ30
84103–03B	AA59590/04BJ35	84103–03C	AA59590/04CJ35
84103–04B	AA59590/04BJ38	84103–04C	AA59590/04CJ38
84103–05B	AA59590/04BJ48	84103–05C	AA59590/04CJ48
84103–06B	AA59590/04BJ53	84103–06C	AA59590/04CJ53
84103–07B	AA59590/04BJ58	84103–07C	AA59590/04CJ58

MILITARY INTERESTS:

Custodians:
Army – CR
Navy – EC
Air Force – 11
DLA – CC

CIVIL AGENCY COORDINATING ACTIVITY:

GSA – 7FXE

Preparing Activity

DLA – CC

Project 5998–0113

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:19Z
Check the source to verify that this is the current version before use.