[INCH-POUND]
A-A-58072
June 26, 1996

COMMERCIAL ITEM DESCRIPTION

TEST SET, TELEPHONE

The General Services Administration has authorized
the use of this Commercial Item Description (CID) for all federal agencies.

1. SCOPE.

This CID describes a Telephone Test Set (TTS), also known as a "Span-Repeater Test Set", which monitors and tests T-carrier systems by performing error detection, fault isolation, and repeater testing. This CID outlines the minimum requirements for this Telephone Test Set. Only those manufacturers which offer products that meet or surpass the following requirements are qualified per this CID.

2. SALIENT CHARACTERISTICS.

The TTS covered by this CID shall be commercially-available equipment modified to the extent necessary to meet the following description. The TTS offered to meet this CID will be fully assembled upon delivery and capable of being bid sample tested within the accuracies, limits, and specifications as follows:

2.1 Method of operation. The TTS shall combine automatic fault location with error detections, conduct counting and analysis, and transmit fault locating patterns.

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any data which may improve this document should be sent to: Technology & Industrial Services Division, SA-ALC/TILDD, 306 Tinker Dr., Bldg. 206, Kelly AFB, TX 78241-5916, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) included with this document, or a letter response.

AMSC N/A FSC 6625
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

2.2 Electrical Power Sources. The equipment shall operate from nominal commercial, military and shipboard power sources of 110/220 volts AC ± 10% at line frequencies of 50 to 60 Hz. Power consumption shall not exceed 250 VA.

2.3 Safety and Environmental. This test equipment shall be solid state and enclosed to provide protection from electrical shock. During operation of this test equipment, all electrically conductive external surfaces shall be at earth ground potential. Safety grounding shall include precautions when RFI filters and input power cables are used.

2.3.2 Leakage Current Protection. Protection shall be provided from leakage current in excess of from any accessible conductive parts of equipment (including control shafts with knobs broken or removed and recessed calibration or adjustment controls) to either pole of the power source for any position of the power switches.

2.4 Preconditioning. Each TTS shall be capable of being subjected to environmental screening effects of burn-in and thermal cycling, with thermal cycling being accomplished in the sample testing phase.

2.5 Calibration and Maintenance Adjustments. The calibration interval shall be a period of one year or greater based on an operating time of 2,000 hours. These adjustments shall be provided by variable value components which are adjustable by simple means. The calibration by substitution of selected components or parts is unacceptable. The calibration adjustments shall be accessible without removal of the instrument case or modules.

2.6 Performance Characteristics. This test set shall be capable of meeting or exceeding the measurement parameters listed below:

2.6.1 Test Capability. TTS shall be able to test office and line repeaters, perform span line fault location, and performance tests on T1 and T1C systems. The transmitter signal patterns are:

a) Quasi-random
b) All Ones;
c) Measure 1, 2, and 3.

2.6.2 Audio Frequencies. The following 12 audio frequencies shall be available and switch selectable for the transmitter and receiver. (Fault locate frequency tolerance in Hz: ± 0.5%):

A: 832	B: 928	C: 1048	D: 1206
E: 1340	F: 1508	G: 1722	H: 2008
J: 2193	K: 2413	L: 2680	M: 3017

2.6.3 Transmitter Output Level shall be 6 volts, Peak to Peak, ± 10%.

2.6.4 Transmitter Output Impedance: 100 ohms ± 10% balanced.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

2.6.5 Clock Frequency at ± 50 Hz: T1 1.544 MHz
T1C 3.152 MHz

2.6.6 Time Slot: T1 648 nsec.
T1C 317 nsec.

2.6.7 Pulse Widths at ± 10%: T1 324 nsec. ± 10%.
T1C 160 nsec. ± 10%.

2.7 Receiver Specifications. This test set's receiver shall have the same fault locating frequencies as listed in 2.6.2.

2.7.1 Receiver Input Level Range: -90 to 0 dBm.

2.7.2 Noise Measure Range: 0 to 70 dBrnc.

2.7.3 Nominal Input Impedance: 900 ohms balanced.

2.7.4 Meter Reading Accuracy: ±1.0 dB.

2.7.5 Filter Bandwidth: 4 Hz.

2.8 Error Detection:

a) Input Level: 0.3 to 3.3 Volts Peak to Base
b) Input Impedance: 200 ohms
c) Artificial Line Loss: This test set shall provide at least 4 selectable attenuation steps between 0 and 43 dB at 772 Hz.

2.9 Repeater Modules. TTS shall include repeater tester modules capable of testing the "min" repeaters.

2.10 Temperature Requirements.

2.10.1 The TTS shall meet its performance and accuracy requirements in an operating environment of 0 to +50 degrees Celsius.

2.10.2 The TTS shall meet its performance and accuracy requirements after being in a non-operating environment (storage temperature) of -10 degrees to +60 degrees Celsius.

2.11 Dimensions. The unit's recommended nominal dimensions, viewed as if rackmounted, are 13.0 inches wide, 9.0 inches high and 11.0 inches deep.

2.12 Weight. The test set's total weight including all accessories, but excluding manuals, shall not exceed 21 pounds.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

2.13 Manuals. Each test set shall be delivered with a user's manual that contains information on the operation and maintenance of the equipment. The manual shall include a parts breakout or a parts list.

3. REGULATORY REQUIREMENTS.

In accordance with Section 23.403 of the Federal Acquisition Regulations, the Government's policy is to acquire items composed of the highest percentage of recoverable materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing the supplier's employees to undue hazards from the recovered materials.

4. QUALITY ASSURANCE.

Product Conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial market. The Government reserves the right to require proof of such conformance.

5. PACKAGING.

The test set shall be packed in accordance with normal commercial practice and packed to assure acceptance by common carrier. Product protection against loss and damage during multiple shipments, handling, and storage shall be provided. The shipping shall be in compliance with national motor freight classification and uniform freight classification. Shipping container shall be marked as specified in the contract or order.

6. NOTES.

6.1 Metrics Products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within specified tolerances using conversion tables contained in the latest version of Federal Standard No. 376, and all other requirements of this CID are met.

6.2 Federal and military documents are available from: Defense Documents Order Desk
Building 4D, 700 Robbins Ave.
Philadelphia, PA 19111-5094
Phone: 215/697-2179

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

6.3 Known Acceptable Products. The following product is known to have previously met the salient characteristics of this CID. All other manufacturers must meet the requirements of this CID and may be requested to submit products for bid testing and certification.

Manufacturer	Part Number	NSN
Joslyn-Sierra Corp.	425A-TW with C02979601 adapter	NSL at this time

MILITARY INTERESTS:

Custodian
Air Force - 99
Army - MI
Navy - SH

Reviewing Activities:
Army - MI
Navy - SH
DLA - ES
GSA - FSS

CIVIL AGENCY COORDINATING ACTIVITIES:

GSA-FSS

Preparing Activity:
Air Force - 82

Project : 6625-0825

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.