(INCH-POUND)
A-A-58079
18 Oct 96

COMMERCIAL ITEM DESCRIPTION

TRUCK, LIFT, FORK, DIESEL-ENGINE-DRIVEN, PNEUMATIC-TIRED, 6,000 POUNDS CAPACITY AT 24 INCH LOAD CENTER

The General Services Administration has authorized the use of this commercial item description, for all federal agencies.

1. SCOPE. This commercial item description covers the general requirements for a diesel engine driven, front wheel drive, rear wheel steer, pneumatic tired, 6,000 pound at 24 inch load-center capacity, forklift truck. It shall be used for handling cargo in and around warehouses, loading platforms, and docks; on paved or other hard surfaces.

2. SALIENT CHARACTERISTICS:

2.1 Safety. The forklift shall comply with ANSI B56.1, and OSHA standards in effect at the time of manufacture. A seatbelt conforming to SAE J386, and restraint devices designed to ensure the operator's upper body remains entirely within the protection of the overhead guard in the event of tip-over shall be provided. Unless otherwise specified in the contract, the final color shall be yellow for safe operation in an indoor environment.

2.2 Environmental requirements. The engine shall start without preheating within 5 minutes, and the truck shall operate as specified herein within 15 minutes after engine start, in any ambient temperature from 0 to 120 degrees F. The forklift shall be capable of continuous operation as specified herein at any ambient temperature up to 120 degrees F.

2.3 Engine. A diesel fueled engine, or when specified (see 2.28), a liquid petroleum gas (LPG) fueled engine shall be provided.

2.4 Fuel system.

(1) When a diesel engine is furnished, all necessary filters, water separators, and other components required for diesel fuel operation shall be provided. It shall have a fuel tank of sufficient capacity to allow at least 8 hours of continuous operation.

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any data which may improve this document should be sent to: WR-ALC/LVR, 225 Ocmulgee Court, Robins AFB GA 31098-1647

AMSC N/A FSC 3930

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

(2) When a LPG fuel system is provided, all necessary filters and components required for LPG operation shall be provided. It shall be of sufficient capacity to provide at least 6 hours of continuos operation. A means shall be provided to prevent fuel flow when the engine run control (ignition switch) is off, or if the engine should stop running.

2.5 Starting system. The engine starter motor shall not be capable of energizing while the engine is running, or while the transmission is in a forward or reverse gear.

2.6 Transmission. A torque converter and a powershift type of transmission shall be furnished. The transmission shall provide for positive inching control, or declutch control, that permits lifting of rated load at maximum lifting speed while the transmission control is in either forward or reverse direction, without vehicle movement. This control shall also apply the service brakes.

2.7 Hydraulic system. A pressure relief protection device is required along with pump(s), cylinders, control valves, filter(s), reservoir, hoses, and all other components necessary to make a complete hydraulic system.

2.8 Uprights and carriage. With no load on the forks, the seated operator shall be able to see at least one fork tip at all lift heights and fork positions.

2.9 Forks. Fork dimensions shall be 2.38 inches maximum thickness, 6.06 inch maximum width, and 42.0 (+ or - 0.5 inch) long. Fork thickness at the tip shall be not more than 0.5 inch, and there shall be a taper on the underside of the forks of not less than 14 inches.

2.10 Fork positioner. A powered, adjustable fork positioner, controlled from the operator's seat, shall be furnished. The forks shall have spacing of 14.0 inches (or less) when in most closed position, and 45.0 inches (or more) when in most spread position. These dimensions shall be measured to the outside edges of the forks.

2.11 Side shift. Hydraulically powered side shifting shall be furnished. It shall be controlled by seated operator, with at least 4.0 inches side shift each side of center (8.0 inches minimum total travel) with rated load on the forks.

2.12 Load backrest. The load backrest, in conjunction with the forks and carriage, shall provide a vertical rear load guard of at least 48 inches high, measured from the load horizontal carrying surfaces of the forks.

2.13 Steering. Power steering shall be furnished.

2.14 Service brakes. Service brakes shall be furnished. They shall conform to ANSI B56.1, except the maximum brake pedal force during stopping distance and drawbar drag tests shall be not more than 80 pounds.

2.15 Parking brake. Parking brake shall conform to ANSI B56.1.

2.16 Electrical system. All components necessary to make a complete electrical system shall be furnished.

2.17 Instruments. The instruments, gauges or warning indicator lights that are on the manufacturer's standard commercial model shall be furnished. In addition, an unlighted hourmeter capable of totaling at least 9999 hours shall be included.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

2.18 External lights. Minimum of three floodlights shall be furnished. Two in front, mounted on the upright, facing forward, and one mounted in the rear, facing rearward.

2.19 Taillight. One combination stoplight and taillight shall be provided.

2.20 Horn. A horn shall be furnished, with the horn actuator located in the center of the steering wheel.

2.21 Operator's overhead guard. The guard shall be in accordance with ANSI B56.1, including inside clearances. It shall also be a falling-object-protective-structure (FOPS) conforming to ANSI B56.1. The height, from the ground to the top of the overhead guard shall be not more than 91.5 inches.

2.22 Cab. When specified (see 2.28), a cab shall be furnished. It shall have FOPS capability per ANSI B56.1, and shall have two opening doors, and at least one fan for ventilation. There shall be sufficient window area to permit at least 250 degrees of horizontal visibility by the seated operator. The height, from the ground to the top of the cab shall be not more than 91.5 inches. A heater and defroster with fan shall be provided. There shall be at least three wipers, one on the front windshield, one on the rear window, and one on the roof window.

2.23 Painting. The forklift shall be primed and painted using standard commercial practices. Unless otherwise specified (see 2.28), the final color shall be yellow.

2.24 Walkway coating. Step surfaces shall be made of, or covered with, a non-slip material.

2.25 Slinging and tie-down provisions. There shall be permanently installed slinging devices that enable the truck to be lifted in its normal travel position, and tie-downs that enable the truck to be tied down to the floor of the transportation media. All devices shall be capable of accepting a chain and hook with an outside diameter of 3.0 inches and shall have a structural safety factor of at least 2.0 to 1, based on static load. The notation “LIFT HERE” or “TIE DOWN” shall be stenciled, in black letters, near each lifting and tie-down device.

2.26 Identification plate. A corrosion resistant identification plate shall be permanently installed at an easily accessible place on the truck. It shall contain the following information:

NOMENCLATURE:
MANUFACTURER'S NAME:
MANUFACTURER'S ADDRESS:
MANUFACTURER'S SERVICE PHONE NUMBER:
MANUFACTURER'S MODEL NUMBER:
MANUFACTURER'S SERIAL NUMBER:
DATE OF MANUFACTURE:
CONTRACT NUMBER:
NATIONAL STOCK NUMBER:
REGISTRATION NUMBER:

2.27 Performance. The truck shall be capable of meeting the following performance requirements:

(1) Capability to safely handle a 6,000 pound, 48 inch per side cube with the center of gravity at the center of the cube. This shall be defined, and referred to in this document, as the rated load. The forklift shall be able to safely handle this rated load at all lift heights and fork side shift positions that it is capable of attaining.

(2) Load lifting speed: Shall be capable of raising rated load at a speed of at least 55 feet per minute.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

(3) Load lowering speed: Not more than 80 feet per minute with rated load of forks and not less than 40 feet per minute with no load on the forks.

(4) Right angle turn: With rated load on the forks and forklift located perpendicular to a wall, and with the front of the load against the wall, the truck shall be able to back up and make a complete right angle turn (ending up parallel to the wall) within 200 inches.

(5) Travel speed: 10 miles per hour minimum, in both forward and reverse, while carrying rated load on the forks.

(6) Slope ascension: With the truck facing up the slope and with rated load on the forks it shall be able to accelerate up a 20 percent slope from a dead stop.

(7) Upright tilt: With no load on the truck the forks shall have at least 3.0 degrees forward tilt, and at least 6.0 degrees of rear tilt.

(8) Lowest upright height (collapsed mast height): The dimension from ground to top surface of the uprights, with uprights vertical, shall not exceed 91.5 inches maximum with no load on the forks.

(9) Maximum fork lift height. At least 130.0 inches with rated load on forks and forks horizontal, when measured from ground to top surfaces of the forks.

(10) Free lift height. The height that the forks can raise the rated load before the collapsed mast height is increased shall be at least 40 inches.

(11) Drift of load. With hydraulic fluid at ambient temperature, lift assembly shall hold rated load at maximum lift height for at least 10.0 minutes with not more than 1-3/4 inch of vertical drift, and not more than 1.0 degree of rotational drift.

(12) Stability. The forklift shall meet the ANSI B56.1 "forward stacking", "forward travel", "lateral stacking", and "lateral travel" stability requirements.

(13) Noise limits. The maximum allowable at the operator's ear is 95 db(A). If the noise level at the operator's ear exceeds 84 db(A) (85 to 95 db(A)), a warning sign stating that operator’s hearing protection is required shall be installed at the operator’s station. The sign shall be at least 4 inches square, with a yellow background.

(14) Electromagnetic radiation. The forklift shall not exceed the limits of electromagnetic radiation specified in SAE J551.

2.28 Options. When specified the following shall be furnished:
a. A liquid petroleum gas (LPG) fuel system (see 2.3).
b. Cab (see 2.22).
c. Final color other than yellow (see 2.23).

3. REGULATORY REQUIREMENTS.

3.1 The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR). However, used, rebuilt, or remanufactured components, pieces, and parts shall not be incorporated in the forklift.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS.

4. 1 Product Conformance. The products provide shall conform to the producer's own drawings, specifications, standards and quality assurance practices and shall be the same product offered for sale in the commercial market. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

4.2 Market Acceptability. The following market acceptability criteria are necessary to document the quality of the product to be provided under this CID.

4.2.1 Commercial. The vehicle furnished shall be, as of the date of award, the latest model (with minor modifications, as that term is defined in DoD FAR Supplement 252.211-7012, Paragraph K-85 of the solicitation) of an established product previously produced and sold in substantial commercial quantities (exceeding the criteria at FAR 15.804-3(f)(2)(ii)(A)) for at least three years. The vehicle furnished, or earlier models of it, absent minor modifications, shall have routinely been supported with spare/repair parts which were produced or sold in the normal course of business. At the time of delivery, the contractor shall furnish the Administrative Contracting Officer with verification of compliance with these requirements. Offers shall provide, as part of their proposals, the following information on the vehicle (or its earlier models) being offered as a commercial item:

(1) Total sales to the U.S. Government or to contractors for U.S. Government use during the three years.
(2) Total sale of the item to the general public during the three years.
(3) Length of time the item has been sold in the commercial market place.

5. PACKAGING. Preservation, packing and marking shall be specified in the contract or order.

6. NOTES.

6.1 Source of Documents.

6.1.1 ASME /ANSI documents may be obtained from American Society of Mechanical Engineers, 345 East 47th St., New York NY 10017.

6.1.2 ANSI documents may be obtained from American National Standards Institute, 11 West 42nd Street, New York NY 10036.

6.1.3 SAE documents may be obtained from Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale PA 15096.

MILITARY INTERESTS:

CUSTODIANS:
Air Force - 99
Army-AT
Navy-SA

CIVIL AGENCY COORDINATING ACTIVITY:
GSA-FSS

PREPARING ACTIVITY:
Air Force - 84

Project Number 3930-0685

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.