INCH-POUND
A-A-58080B
29 December 2009
SUPERSEDING
A-A-58080A
25 December 2004

COMMERCIAL ITEM DESCRIPTION

TRUCK, LIFT, FORK, DIESEL ENGINE-DRIVEN, PNEUMATIC-TIRES 4,000 POUND CAPACITY AT 24 INCH LOAD CENTER

The General Services Administration has authorized the use of this Commercial Item Description (CID) for all federal agencies.

1. SCOPE.

1.1 Scope. This commercial item description covers the general requirements for a diesel engine-driven, front wheel-drive, rear wheel steer, pneumatic-tired, 4,000 pound at 24 inch load-center capacity, forklift truck. It will be used for handling cargo in and around warehouses, loading platforms, and docks on paved or other hard surfaces.

2. CLASSIFICATION.

2.1 Classification. The operator driven vehicle covered by this CID shall be commercially available and may be modified to the extent necessary to meet this description.

3. SALIENT CHARACTERISTICS.

3.1 Safety. The operator driven vehicle shall be capable of operation within the accuracies, limits, and specifications herein. The forklift shall comply with ANSI/ITSDF B56.1 and OSHA standards in effect at the time of manufacture. A seatbelt conforming to SAE J386, and restraint devices designed to ensure the operator's upper body remains entirely within the protection of the overhead guard in the event of tip-over shall be provided. Unless otherwise specified in the contract, the final colder shall be yellow for safe operation in an indoor environment.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any other data that may improve this document should be sent to 642 CBSG/GBEC, 460 Richard Ray Blvd, Suite 200, Robins AFB, GA 31098-1813. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at http://assist.daps.dla.mil .

FSC 3930

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

3.2 Environmental requirements. The engine shall start without preheating within 5 minutes, and the truck shall operate as specified herein within 15 minutes after engine start; in any ambient temperature from 0 to 120 degrees F. The forklift shall be capable of continuous operation as specified herein at any ambient temperature up to 120 degrees F. The truck, with type C winterization, shall be capable of operating in temperatures ranging from -25 degrees F to + 125 degrees F.

3.3 Engine. A diesel fueled engine, or when specified (see 7.3), a liquid petroleum gas (LPG) fueled engine shall be provided.

3.3.1 Emissions. The vehicle emissions shall comply with the EPA regulations in effect at the time of vehicle manufacture. When there is a change in EPA regulations during a contract, EPA provisions shall be consulted to determine which regulations apply (e.g. TIER 1 or TIER 2 or TIER 3). The vehicle shall comply with the emissions requirements of the destination state at the time of vehicle manufacture.

3.4 Fuel System. The following shall apply:

(1) When a diesel engine is furnished, all necessary filters, water separators, and other components required for diesel fuel operation shall be provided. It shall have a fuel tank of sufficient capacity to allow at least 8 hours of continuous operation.

(2) When a LPG fuel system is provided, all necessary filters and components required for LPG operation shall be provided. It shall be of sufficient capacity to provide at least 6 hours of continuous operation. A means shall be provided to prevent fuel flow when the engine run control (ignition switch) is off, or if the engine should stop running.

3.5 Starting System. The engine starter motor shall not be capable of energizing while the engine is running, or while the transmission is in a forward or reverse gear.

3.6 Transmission. A torque converter and a power-shift type of transmission shall be furnished. The transmission shall provide for positive inching control, or declutch control, that permits lifting of rated load at maximum lifting speed while the transmission control is in either forward or reverse direction, without vehicle movement. This control shall also apply the service brakes.

3.7 Hydraulic System. A pressure relief protection device is required along with pump(s), cylinders, control valves, filter(s), reservoir, hoses, and all other components necessary to make a complete hydraulic system.

3.8 Uprights and carriage. With no load on the forks, the seated operator shall be able to see at least one fork tip at all lift heights and fork positions.

3.9 Forks. Fork dimensions shall be 1.86 inches maximum thickness, 5.06 inch maximum width, and 42.0 (± 0.5 inch) long. Fork thickness at the tip shall be not more than 0.5 inch, and there shall be a taper on the underside of the forks of not less than 14 inches.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

3.10 Fork Positioner. Manually (operator) adjusted fork positioning shall be furnished. The forks shall have spacing of 12.0 inches (or less) when in most closed position, and 32.0 inches (or more) when in most spread position. These dimensions shall be measured to the outside edges of the forks.

3.11 Side shift. Hydraulically powered side shifting shall be furnished. It shall be controlled by seated operator, with at least 4.0 inches side shift each side of center (8.0 inches minimum total travel) with rated load on the forks.

3.12 Load Backrest. The load backrest, in conjunction with the forks and carriage, shall provide a vertical rear load guard of at least 48 inches high, measured from the load horizontally carrying surfaces of the forks.

3.13 Steering. Power steering shall be furnished.

3.14 Service Brakes. Service brakes shall be furnished. They shall conform to ANSI/ITSDF B56.1, except the maximum brake pedal force during stopping distance and drawbar drag tests shall be not more than 80 pounds.

3.15 Parking Brake. Parking brake shall conform to ANSI/ITSDF B56.1.

3.16 Electrical System. All components necessary to make a complete electrical system shall be furnished.

3.17 Instruments. The instruments, gauges, or warning indicator lights that are on the manufacturer's standard commercial model shall be furnished. In addition, an unlighted hour meter capable of totaling at least 9999 hours shall be included.

3.18 External Lights. Minimum of three floodlights shall be furnished. Two in front, mounted on the upright, facing forward, and one mounted in the rear, facing rearward.

3.19 Taillight. One combination stoplight and taillight shall be provided.

3.20 Horn. A horn shall be furnished, with the horn actuator located in the center of the steering wheel.

3.21. Operator's overheard guard. The guard shall be in accordance with ANSI/ITSDF B56.1 including inside clearances. It shall also be a falling-object-protective-structure (FOPS) conforming to ANSI/ITSDF B56.1. The height from the ground to the top of the overhead guard shall be not more than 86.5 inches.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

3.22 Cab. When specified (see 7.3), a cab shall be furnished. It shall have FOPS capability in accordance with ANSI/ITSDF B56.1, and shall have two opening doors, and at least one fan for ventilation. There shall be sufficient window area to permit at least 250 degrees of horizontal visibility by the seated operator. The height, from the ground to the top of the cab shall be not more than 86.5 inches. A heater and defroster with fan shall be provided. There shall be at least three wipers, one on the front windshield, one on the rear window, and one on the roof window. A commercial fire extinguisher shall be mounted on the truck in an easily accessible location. The fire extinguisher shall be a minimum 2-1/2 pound capacity ABC type, or equivalent. The fire extinguisher shall be UL listed.

3.23 Painting. The forklift shall be primed and painted using standard commercial practices. Unless otherwise specified (see 7.3), the final color shall be yellow.

3.24 Walkway Coating. Step surfaces shall be made of, or covered with, a non-slip material.

3.25 Lifting and Tie-down Provisions. There shall be permanently installed slinging devices that enable the truck to be lifted in its normal travel position, and tie-down devices that enable the truck to be tied-down to the floor of the transportation media. All devices shall be capable of accepting a chain and hook with an outside diameter of 3.0 inches and shall have a structural safety factor of at least 2.0 to 1, based on static load. The notation “LIFT HERE” or “TIE DOWN” shall be stenciled, in black letters, near each lifting and tie-down device.

3.26 Identification Plate. A corrosion resistant identification plate shall be permanently installed at an easily accessible place on the truck. It shall contain the following:

NOMENCLATURE:
MANUFACTURE’S NAME:
MANUFACTURER’S ADDRESS:
MANUFACTURER’S SERVICE PHONE NUMBER:
MANUFACTURER’S MODEL NUMBER:
MANUFACTURER’S SERIAL NUMBER:
DATE OF MANUFACTURER:
CONTRACT NUMBER:
NATIONAL STOCK NUMBER:
REGISTRATION NUMBER:

3.27 Performance. The truck shall be capable of meeting the following performance requirements:

(1) Capability to safely handle a 4,000 pound, 48 inch-per-side cube, with the center of gravity at the center of the cube. This shall be defined, and referred to in this document, as the rated load. The forklift shall be able to safely handle this rated load at all lift heights and fork side shift positions that it is capable of attaining.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

(2) Load lifting speed: Shall be capable of raising rated load at a speed of at least 55 feet per minute.

(3) Load lowering speed: Not more than 80 feet per minute with rated load on the forks and not less than 40 feet per minute with no load on the forks.

(4) Right angle turn: With rated load on the forks and forklift located perpendicular to a wall, and with the front of the load against the wall, the truck shall be able to back up and make a complete right angle turn (ending up parallel to the wall) within 170 inches.

(5) Travel speed: 10 miles per hour minimum, in both forward and reverse, while carrying rated load on the forks.

(6) Slope ascension: With the truck facing up the slope and with rated load on the forks it shall be able to accelerate up a 20 percent (11 degree) slope from a dead stop.

(7) Upright tilt: With no load on the truck the forks shall have at least 3.0 degrees forward tilt, and at least 6.0 degrees of rear tilt.

(8) Lowest upright height (collapsed mast height): The dimension from ground to top surface of the uprights, with uprights vertical, shall not exceed 86.5 inches maximum with no load on the forks.

(9) Maximum fork lift height: At least 144.0 inches with rated load on forks and forks horizontal, when measured from ground to top surfaces of the forks.

(10) Free lift height: The height that the forks can raise the rated load before the collapsed mast height is increased shall be at least 45.0 inches.

(11) Drift of load: With hydraulic fluid at the ambient temperature, lift assembly shall hold rated load at maximum lift height for at least 10.0 minutes with not more than 1-3/4 inch of vertical drift, and not more than 1.0 degree of rotational drift.

(12) Stability: The forklift shall meet the ANSI/ITSDF B56.1 “forward stacking”, “forward travel”, “lateral stacking”, and “lateral travel” stability requirements.

(13) Noise limits: The maximum allowable at the operator’s ear is 92 db(A). If the noise level at the operator’s ear exceeds 84 db(A) (85 to 92 db(A)), a warning sign stating that operator’s hearing protection is required shall be installed at the operator’s station. The sign shall be as least 4 inches square, with a yellow background.

(14) Electromagnetic interference (EMI): The forklift shall comply with the EMI requirements shown in Table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

TABLE I. Electromagnetic interference (EMI)

Name	Description	Parameters
SAE J551-1	Compatibility	N/A
CISPR 12 & CISPR 25	Emissions	(Frequency Range: 30 to 1000 MHz)
SAE J551-11	Susceptibility	(Frequency Range: 100 kHz to 18 GHz) 20 V/m (100 kHz to 200 MHz) 50 V/m (above 200 MHz)

3.28 Backup alarm. An audible backup alarm shall be furnished. The alarm shall automatically activate when the transmission selector is placed in reverse.

3.29 Winterization. When specified (see 7.3), the truck shall be furnished with Type C winterization that shall protect to -25 degrees F and shall consist of the following:

(1) Starting Aid. Glow plug(s) or a measured-shot ether injection system shall be furnished.

(2) Cab. The cab shall meet the requirements of 3.22, and shall also contain thermal insulation, if necessary, to meet the heating requirements of 3.29(3).

(3) Cab heater and defroster. The heater shall have sufficient capacity to maintain a temperature of at least + 40 degrees F at cab floor level in an ambient temperature of -20 degrees F.

(4) Antifreeze. Engine coolant shall be protected to -25 degrees F with antifreeze.

3.30 Tires. The tires shall be pneumatic, and tire loading shall not exceed those specified in the Tire and Rim Association yearbook. When specified, (see 7.3), the tires shall be solid-pneumatic.

3.31 Tropical rust-proofing. When specified (see 7.3), tropical rust-proofing shall be provided. This should be considered a premium rust-proofing package usually consisting of an additional coating. The truck shall be treated with a corrosion preventative compound complying with A-A-59295. A copy of A-A-59295 can be requested from 642 CBSG/GBEC. Many of these vehicles are used in tropical/coastal environments and experience high humidity and salt spray. Therefore, they usually exhibit high levels of corrosion in the areas listed below. At a minimum, these areas shall be coated. (1) Cab, interior (2) Cab, exterior (3) Seams (4) Welds (5) Hidden recessed areas (6) Locations where dissimilar metals come in contact (7) Area above fuel tank(s) (8) Engine oil pan & transmission oil pan (9) Radiator support structure (10) Battery box.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

4. REGULATORY REQUIREMENTS

4.1 Recycled, recovered, or environmentally preferable materials. Recycled, recovered, or environmentally preferable materials should be used to the maximum extent possible provided that the material meets or exceeds the operational and maintenance requirements, and promotes economically advantageous life cycle costs. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4.2 Green Procurement Program. Green Procurement Program (GPP) is a mandatory federal acquisition program that focuses on the purchase and use of environmentally preferable products and services. GPP requirements apply to all acquisitions using appropriated funds, including services and new requirements. FAR 23.404(b) applies and states the GPP requires 100% of EPA designated product purchase that are included in the Comprehensive Procurement Guidelines list that contains recovered materials, unless the item cannot be acquired: a) competitively within a reasonable timeframe; b) meet appropriate performance standards, or c) subcontractors comply with this requirement.

5. PRODUCT CONFORMANCE PROVISIONS

5.1 Product conformance. The products provided shall conform to the producer's own drawings, specifications, standards, and quality assurance practices and shall be the same product offered for sale in the commercial market. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

5.2 Market Acceptability. The following market acceptability criteria are necessary to document the quality of the product to be provided under this CID.

5.2.1 Commercial. The vehicle furnished shall be, as of the date of award, the latest model (with minor modifications, as that term is defined in DoD FAR Supplement 252.211-7012, Paragraph K-85 of the solicitation) of an established product previously produced and sold in substantial commercial quantities (exceeding the criteria at FAR 15.804-3(f)(2)(ii)(A)) for at least three years. The vehicle furnished, or earlier models of it, absent minor modifications, shall have routinely been supported with spare/repair parts which were produced or sold in the normal course of business. At the time of delivery, the contractor shall furnish the Administrative Contracting Officer with verification of compliance with these requirements. Offers shall provide, as part of their proposals, the following information on the vehicle (or its earlier models) being offered as a commercial item:

(1) Total sales to the U.S. Government or to contractors for U.S. Government use during the three years.

(2) Total sales of the item to the general public during the three years.

(3) Length of time the item has been sold in the commercial market place.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

6. PACKAGING

6.1 Packaging. Preservation, packing, and marking shall be as specified in the contract. Unless otherwise specified in the contract, the items shall be packaged according to normal commercial practice and packed to assure acceptance by common carrier and provide product protection against loss and damage during multiple shipment, handling, and storage. Shipping containers shall be properly marked and in compliance with both national and uniform motor freight classifications.

7. NOTES

7.1 Intended use. The vehicle is intended for use in handling cargo in and around warehouses, loading platforms, and docks; on paved or other hard surfaces.

7.2 Source of documents.

7.2.1 Military Specifications, Standards, and Handbooks referenced herein may be obtained at http://assist.daps.dla.mil or available from the Standardization Documents Order Desk, 700 Robbins Ave, Bldg 4, Section D, Philadelphia, PA 19111-5094.

7.2.2 Society of Automotive Engineers, Inc. (SAE) Copies of SAE standards may be obtained online at http://www.sae.org/ or from the Society of Automotive Engineers, 400 Commonwealth Drive, Warrendale, PA 15096.

7.2.3 Industrial Truck Standards Development Foundation (ITSDF) Standards may be obtained from www.itsdf.org or the Industrial Truck Standards Development Foundation Suite 460, 1750 K Street NW, Washington, DC 20006.

7.2.4 Underwriters Laboratories, Inc. (UL) Copies of UL standards may be obtained from www.ul.com or the Underwriters Laboratories, Inc., 333 Pfingsten Road, Northbrook, IL 60062.

7.2.5 FAR and DFARS may be obtained from the Superintendent of Documents, P.O. Box 371954, Pittsburgh, PA 15250-7954. Electronic copies of the FAR may be obtained from http://www.arnet.gov/far Electronic copies of the DFARS may be obtained from http://www.acq.osd.mil/dpap/dars/dfars/index.htm .

7.2.6 Comité International Spécial des Perturbations Radioélectriques (CISPR) document may be obtained online at http://www.iec.ch/zone/emc/emc_cis.htm.

7.2.7 Occupational Safety and Health Association (OSHA) copies may be obtained online at http://www.osha.gov/ or from OSHA, 200 Constitution Ave., Washington, D.C. 20210.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

7.3 Options. When specified the following shall be furnished:

a. A liquid petroleum gas (LPG) fuel system (see 3.3).
b. Cab (see 3.22).
c. Final color other than yellow (see 3.23).
d. Winterization (see 3.29).
e. Tires (see 3.30)
f. Tropical rust proofing (see 3.31).

7.4 Key Words.

Cargo
Loading platforms
Warehouses

MILITARY INTERESTS:

Custodians:
Air Force – 84
Army - AT
Navy - SA

Civil Agency and
Coordinating Activity:
GSA-FSS

Preparing Activity:
Air Force – 84

Reviewers:

Air Force – 99
DLA - IS

Agent:
Air Force – 99

(Project 3930-2010-002)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil .

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.