(INCH-POUND)
A-A-58081
18 Oct 96

COMMERCIAL ITEM DESCRIPTION

TRUCK, LIFT, FORK, ELECTRIC, FRONT/SIDE LOADING, SIT-DOWN OPERATOR, 4,000 POUNDS CAPACITY, EE RATED

The General Services Administration has authorized the use of this commercial item description for all federal agencies.

1. SCOPE. This commercial item description covers the general requirements for a 4,000 pound at 24 inch load-center capacity, electric, front/side loading, forklift truck. It shall be capable of picking up and depositing loads that are directly in front, and 90 degrees to the side, of the truck. It shall be EE rated in accordance with UL 583. It shall be used for handling cargo in narrow aisle warehouses, loading platforms, and docks; on paved or other hard surfaces.

2. SALIENT CHARACTERISTICS:

2.1 Safety. The forklift shall comply with ANSI B56.1, UL 583, and OSHA standards in effect at the time of manufacture. A seatbelt conforming to SAE J386 shall be furnished. The final color shall be yellow for safe operation in an indoor environment.

2.2 Environmental requirements. The truck shall operate continuously as specified herein in any ambient temperature from 0 to 120 degrees F.

2.3 Mast pivot. The mast, including the carriage and forks, shall pivot 90 degrees to one side.

2.4 Battery. The battery shall have sufficient capacity to provide at least 6 hours of normal, industrial type operation. Battery leads shall be equipped with type “SB” locking half connectors.

2.5 Hydraulic system. All components, including filter(s), necessary to make a complete hydraulic system shall be provided.

2.6 Uprights and carriage. With no load on the forks, the seated operator shall be able to see at least one fork tip when the forks are at their lowest position and straight ahead.

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any data which may improve this document should be sent to: WR-ALC/LVR, 225 Ocmulgee Court, Robins AFB GA 31098-1647

AMSC N/A FSC 3930
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

2.7 Forks. Fork dimensions shall be 2.06 inches maximum thickness, 5.56 inch maximum width, and 40.0 (+0.0, -1.0) inch long. Fork thickness at the tip shall be not more than 0.5 inch, and there shall be a taper on the underside of the forks of not less than 14 inches.

2.8 Fork positioner. The forks shall be adjusted manually without the need for tools. They shall have spacing of 20.0 inches (or less) when in most closed position, and 37.0 inches (or more) when in most spread position. These dimensions shall be measured to the outside edges of the forks.

2.9 Side shift. Hydraulically powered side shifting controlled by the seated operator shall be furnished. With the forks in the front loading position, there shall be at least 6.0 inches side shift each side of center (12.0 inches minimum total travel) with rated load on the forks.

2.10 Load backrest. The load backrest, in conjunction with the forks and carriage, shall provide a vertical rear load guard of at least 48 inches high, measured from the load horizontal carrying surfaces of the forks.

2.11 Long loads. With the forks in side handling position (full 90 degree side pivot) the truck shall be capable of carrying a 4,000 pound load that is 20 foot long and 16 inch wide. It shall be carried parallel to the longitudinal centerline of the forklift. For safety and stability while traveling, this load, in this position, shall be supported by both the forks and the structure of the truck. This load, where it interfaces with the truck, shall be within the plan outline of the forklift.

2.12 Steering. Power steering shall be furnished.

2.13 Service brakes. Service brakes shall be furnished. They shall conforming to ANSI B56.1, except the maximum brake pedal force during stopping distance and drawbar drag tests shall be not more than 80 pounds.

2.14 Parking brake. Parking brake shall conform to ANSI B56.1.

2.15 Electrical system. All components necessary to make a complete electrical system shall be furnished.

2.16 Instruments. The instruments, gauges or warning indicator lights that are on the manufacturer’s standard commercial model shall be furnished. In addition, an unlighted hourmeter capable of totaling at least 9999 hours shall be included..

2.17 External lights. Minimum of one front facing and one rear facing floodlights shall be furnished. The front facing light shall be mounted on, and pivot with, the upright or mast.

2.18 Taillight. One combination stoplight and taillight shall be provided.

2.19 Horn. A horn shall be furnished, with the horn actuator located with reach of the seated operator.

2.20 Operator's overhead guard. The guard shall be in accordance with ANSI B56.1, including inside clearances. It shall also be a falling-object-protective-structure (FOPS) conforming to ANSI B56.1. The height, from the ground to the top of the overhead guard shall be not more than 84.0 inches.

2.21 Cab. When specified (see 2.30), a cab shall be furnished. It shall have inside clearances and FOPS capability in accordance with ANSI B56.1. There shall be sufficient window area to permit at least 250 degrees of horizontal visibility by the seated operator. The height, from the ground to the top of the cab shall be not more than 84.0 inches. There shall be at least three wipers, one on the front windshield, one on the rear window, and one on the roof window.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

2.22 Painting. The forklift shall be primed and painted using the contractor's standard commercial practices. Unless otherwise specified (see 2.30), the final color shall be yellow.

2.23 Walkway coating. Step surfaces shall be made of, or covered with, a non-slip material.

2.24 Lifting and tie-down provisions. There shall be permanently installed lifting devices that enable the truck to be lifted in its normal travel position, and tie-down devices that enable the truck to be tied down to the floor of the transportation media. All devices shall be capable of accepting a chain and hook with an outside diameter of 3.0 inches and shall have a structural safety factor of at least 2.0 to 1, based on static load. The notation "LIFT HERE" or "TIE DOWN" shall be stenciled in black letters, near each lifting and tie-down device.

2.25 Towing device. A pin type towing device shall be recessed in the center of the truck. It shall not protrude beyond the outside surface of the truck. The pin shall accept a lunette with an inside diameter of 1.25 inches and a circular cross section of 1.0 inches in diameter.

2.26 Overall dimensions. The maximum overall width of the truck shall be 46.0 inches. The maximum overall height shall be 84.0 inches.

2.27 Cautions and warnings. All cautions and warnings in the form of by decals, stencils, etc. furnished on the manufacturer's standard commercial forklift, shall be installed on the truck.

2.28 Identification plate. A corrosion resistant identification plate shall be permanently installed at an easily accessible place on the truck. It shall contain the following information:

NOMENCLATURE:
MANUFACTURER'S NAME:
MANUFACTURER'S ADDRESS:
MANUFACTURER'S SERVICE PHONE NUMBER:
MANUFACTURER'S MODEL NUMBER:
MANUFACTURER'S SERIAL NUMBER:
DATE OF MANUFACTURE:
CONTRACT NUMBER:
NATIONAL STOCK NUMBER:
REGISTRATION NUMBER:

2.29 Performance. The truck shall be capable of meeting the following performance requirements:

(1) Capacity: The truck shall have the capability to safely handle a 4,000 pound, 48 inch per side cube with the center of gravity at the center of the cube. This cube shall be defined, and referred to in this document, as the rated load. The forklift shall be able to safely handle this rated load at all lift heights, mast pivot positions, and fork side shift positions that it is capable of attaining.

(2) Load lifting speed: The truck shall be capable of raising rated load at a speed of at least 50 feet per minute.

(3) Load lowering speed: Fork lowering speed shall be not more than 80 feet per minute with rated load of forks and not less than 40 feet per minute with no load on the forks.

(4) Right angle turn: With rated load on the forks and forklift located perpendicular to a wall, and with the front of the load against the wall, the truck shall be able to back up and make a complete right angle turn (ending up parallel to the wall) within 160 inches.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

(5) Travel speed: While carrying rated load on the forks, the truck shall be capable of traveling at a speed of at least 5.0 miles per hour, in both forward and reverse directions.

(6) Slope ascension: With the forklift facing toward the ramp and with rated load on the forks, the truck shall have adequate ground clearance to drive from a horizontal surface up a ramp with a 15 percent slope, with no contact between the ramp and forklift (except for tires). It shall have adequate power to accelerate up a ramp with a 15 percent slope, from a dead stop on the ramp.

(7) Upright tilt: With no load on the truck the forks shall have at least 3.0 degrees forward tilt, and at least 4.0 degrees of rear tilt.

(8) Lowest upright height (collapsed mast height): The dimension from ground to top surface of the uprights, with uprights vertical and the mast in its lowest position, shall not exceed 84.0 inches with no load on the forks.

(9) Raised fork height: The truck shall be capable of raising the rated load at least 180.0 inches above ground level. This shall be with forks horizontal, and when measured from ground to top (load carrying) surface of the forks.

(10) Free lift height: The height that the forks can raise the rated load before the collapsed mast height is increased shall be not less than 50.0 inches.

(11) Drift of load: With hydraulic fluid at normal operating temperature, the lift assembly shall hold rated load at maximum lift height for at least 2.0 minutes with not more than 1-3/4 inch of vertical drift, and not more than 1.0 degrees of rotational drift from the vertical.

(12) Stability: The forklift shall meet all ANSI B56.1 "forward stacking", "forward travel", "lateral stacking", and "lateral travel" stability requirements for counter balanced front/side loader lift trucks.

(13) Electromagnetic radiation: The forklift shall not exceed the limits of electromagnetic radiation specified in SAE J551.

2.30 Options. When specified the following shall be furnished:

a. Cab (see 2.21).

b. Final color other than yellow (see 2.22).

3. REGULATORY REQUIREMENTS.

3.1 The offer/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR). However, used, rebuilt, or remanufactured components, pieces, and parts shall not be incorporated

4. QUALITY ASSURANCE PROVISIONS.

4.1 Product conformance. The products provided shall conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial market. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

4.2 Market acceptability. The following market acceptability criteria are necessary to document the quality of the product to be provided under this CID.

4.2.1 Commercial. The vehicle furnished shall be, as of the date of award, the latest model (with minor modifications, as that term is defined in DoD FAR Supplement 252.211-7012, Paragraph K-85 of the solicitation) of an established product previously produced and sold in substantial commercial quantities (exceeding the criteria at FAR 15.804-3(f)(2)(ii)(A)) for at least three years. The vehicle furnished, or earlier models of it, absent minor modifications, shall have routinely been supported with spare/repair parts which were produced or sold in the normal course of business. At the time of delivery, the contractor shall furnish the Administrative Contracting Officer with verification of compliance with these requirements. Offers shall provide, as part of their proposals, the following information on the vehicle (or its earlier models) being offered as a commercial item:

(1) Total sales to the U.S. Government or to contractors for U.S. Government use during the three years.
(2) Total sale of the item to the general public during the three years.
(3) Length of time the item has been sold in the commercial market place.

5. PACKAGING. Preservation, packing, and marking for shipment shall be as specified in the contract.

6. NOTES.

6.1 Source of Documents.

6.1.1 UL documents may be obtained from Underwriters Laboratories, Inc. 333 Pfingsten Road, Northbrook, IL 60062-2096.

6.1.2 ANSI documents may be obtained from American National Standards Institute, 11 West 42nd Street, New York NY 10036.

6.1.3 SAE documents may be obtained from Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale PA 15096.

MILITARY INTERESTS:

CUSTODIANS:
Air Force - 99
Army-AT
Navy-SA

CIVIL AGENCY COORDINATING ACTIVITY:
GSA-FSS

PREPARING ACTIVITY:
Air Force - 84

Project 3930-0687

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.