INCH – POUND

A-A-58081A
25 December 2004
SUPERSEDING
A-A-58081
18 October 1996

COMMERCIAL ITEM DESCRIPTION

TRUCK, LIFT, FORK, ELECTRIC, FRONT/SIDE LOADING, SIT-DOWN OPERATOR, 4,000 POUND CAPACITY, EE RATED

The General Services Administration has authorized the use of this Commercial Item Description (CID) for all federal agencies.

1. SCOPE.

1.1 Scope. This commercial item description covers the general requirements for 4,000 pound at 24-inch load-center capacity, electric, front/side loading, forklift truck. It will be capable of picking up and depositing loads that are directly in front, and 90 degrees to the side of the truck. It will be EE rated in accordance with UL 583. It will be used for handling cargo in narrow aisle warehouses, loading platforms, and docks; on paved or other hard surfaces.

2. CLASSIFICATION.

2.1 Classification. The operator driven vehicle covered by this CID shall be commercially available and may be modified to the extent necessary to meet this description.

3. SALIENT CHARACTERISTICS.

3.1 Safety. The operator driven vehicle shall be capable of operation within the accuracies, limits, and specifications herein. The forklift shall comply with ANSI B56.1 and OSHA standards in effect at the time of manufacture. A seatbelt conforming to SAE J386, and restraint devices designed to ensure the operator's upper body remains entirely within the protection of the overhead guard in the event of tip-over shall be provided. Unless otherwise specified in the contract, the final color shall be yellow for safe operation in an indoor environment.

Comments, suggestions, or questions on this document should be addressed to WR-ALC/LEEV, 295 Byron St., Warner Robins AFB, GA 31098-1611 or emailed to robert.david@robins.af.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at http://assist.daps.dla.mil .

FSC 3930

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

3.2 Environmental requirements. The forklift shall be capable of continuous operation as specified herein at any ambient temperature from 0 to + 120 degrees F.

3.3 Mass pivot. The mast, including the carriage and forks, shall pivot 90 degrees to one side.

3.4 Battery. The battery shall have sufficient capacity to provide at least 6 hours of normal, industrial type operation. Battery leads shall be equipped with “SB” locking half connectors. When specified (see 7.3), an additional battery or battery charger shall be supplied.

3.5 Hydraulic System. All components, including filter(s), necessary to make a complete hydraulic system shall be provided.

3.6 Upright and carriage. With no load on the forks, the seated operator shall be able to see at least one fork tip when the forks are at their lowest position and straight ahead.

3.7 Forks. Fork dimensions shall be 2.06 inches maximum thickness, 5.56 inch maximum width, and 40.0 (+0.0, -1.0) inch long. Fork thickness at the tip shall be not more than 0.5 inch, and there shall be a taper on the underside of the forks of not less than 14 inches.

3.8 Fork Positioner. The forks shall be adjusted manually without the needs for tools. They shall have spacing of 20.0 inches (or less) when in most closed position, and 37.0 inches (or more) when in most spread position. These dimensions shall be measured to the outside edges of the forks.

3.9 Side shift. Hydraulically powered side shifting controlled by seated operator shall be furnished. With the forks in the front loading position, there shall be at least 6.0 inches side shift each side of center (12.0 inches minimum total travel) with rated load on the forks.

3.10 Load Backrest. The load backrest, in conjunction with the forks and carriage, shall provide a vertical rear load guard of at least 48 inches high, measured from the load horizontally carrying surfaces of the forks.

3.11 Long loads. With the forks in side handling position (full 90 degrees side pivot) the truck shall be capable of carrying a 4,000 pound load that is 20 feet long and 16 inches wide. It shall be carried parallel to the longitudinal centerline of the forklift. For safety and stability while traveling, this load, in this position, shall be supported by both the forks and the structure of the truck. This load, where it interferes with the truck, shall be within the plan outline of the forklift.

3.12 Steering. Power steering shall be furnished.

3.13 Service Brakes. Service brakes shall be furnished. They shall conform to ANSI. B56.1, except the maximum brake pedal force during stopping distance and drawbar drag tests shall be not more than 80 pounds.

3.14 Parking brake. Parking brake shall conform to ANSI B56.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

3.15 Electrical system. All components necessary to make a complete electrical system shall be furnished.

3.16 Instruments. The instruments, gauges, or warning indicator lights that are on the manufacturer's standard commercial model shall be furnished. In addition, an unlighted hour-meter capable of totaling at least 9999 hours shall be included.

3.17 External Lights. Minimum of one front facing and one rear facing floodlight shall be shall be furnished. The front facing light shall be mounted on, and pivot with, the mast.

3.18 Taillight. One combination stoplight and taillight shall be provided.

3.19 Horn. A horn shall be furnished, with the horn actuator located within reach of the seated operator.

3.20 Operator's overheard guard. The guard shall be in accordance with ANSI B56.1 including inside clearances. It shall also be a falling-object-protective-structure (FOPS) conforming to ANSI B56.1. The height, from the ground to the top of the overhead guard shall be not more than 91.0 inches.

3.21 Cab. When specified (see 7.3), a cab shall be furnished. It shall have inside clearances and FOPS capability per ANSI B56.1. The cab shall be equipped with an adjustable ventilation fan, not less than 6 inches in diameter. There shall be sufficient window area to permit at least 250 degrees of horizontal visibility by the seated operator. The height, from the ground to the top of the cab shall be not more than 91.0 inches. A heater and defroster with fan shall be provided. There shall be at least three wipers, one on the front windshield, one on the rear window, and one on the roof window.

3.22 Painting. The forklift shall be primed and painted using the contractor's standard commercial practices. Unless otherwise specified (see 3.30), the final color shall be yellow.

3.23 Walkway Coating. Step surfaces shall be made of, or covered with, a non-slip material.

3.24 Tie-down Provisions. There shall be permanently installed tie-downs devices that enable the truck to be tied down to the floor of the transportation media. All devices shall be capable of accepting a chain and hook with an outside diameter of 3.0 inches and shall have a structural safety factor of at least 2.0 to 1, based on static load. The notation "TIE DOWN" shall be stenciled, in black letters, near each tie-down device.

3.25 Towing device. A pin type towing device shall be recessed in the center of the truck. It shall not protrude beyond the outside surface of the truck. The pin shall accept a lunette with an inside diameter of 1.25 inches and a circular cross section of 1.0 inches in a diameter.

3.26 Overall dimensions. The maximum overall width of the truck shall be 46.0 inches. The maximum overall height shall be 91.0 inches.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

3.27 Cautions and warnings. All cautious and warnings in the form of decals, stencils, etc. furnished on the manufacturer's standard commercial forklift, shall be installed on the truck.

3.28 Identification Plate. A corrosion resistant identification plate shall be permanently installed at an easily accessible place on the truck. It shall contain the following:

NOMENCLATURE:
MANUFACTURE'S NAME:
MANUFACTURER'S ADDRESS:
MANUFACTURER'S SERVICE PHONE NUMBER:
MANUFACTURER'S MODEL NUMBER:
MANUFACTURER'S SERIAL NUMBER:
DATE OF MANUFACTURER:
CONTRACT NUMBER:
NATIONAL STOCK NUMBER:
REGISTRATION NUMBER:

3.29 Performance. The truck shall be capable of meeting the following performance requirements:

(1) Capacity: The truck shall have the capability to safely handle a 4,000 pound, 48 inch-per-side cube, with the center of gravity at the center of the cube. This cube shall be defined, and referred to in this document, as the rated load. The forklift shall be able to safely handle this rated load at all lift heights, mast pivot positions, and fork side shift positions that it is capable of attaining.

(2) Load lifting speed: The truck shall be capable of raising rated load at a speed of at least 50 feet per minute.

(3) Load lowering speed: Fork lowering speed shall not be more than 80 feet per minute with rated load on the forks and not less than 40 feet per minute with no load on the forks.

(4) Right angle turn: With rated load on the forks and forklift located perpendicular to a wall, and with the front of the load against the wall, the truck shall be able to back up and make a complete right angle turn (ending up parallel to the wall) within 160 inches.

(5) Travel speed: While carrying rated load on the forks, the truck shall be capable of traveling at a speed of at least 5.0 miles per hour, in both forward and reverse directions.

(6) Slope ascension. With the forklift facing toward the ramp and with rated load on the forks, the truck shall have adequate ground clearance to drive from a horizontal surface up a ramp with a 15 percent slope, with no contact between the ramp and forklift (except for tires). It shall have adequate power to accelerate up a ramp with a 15 percent slope, from a dead stop on the ramp.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

(7) Upright tilt: With no load on the truck the forks shall have at least 3.0 degrees forward tilt, and at least 4.0 degrees of rear tilt.

(8) Lowest upright height (collapsed mast height): The dimension from ground to top surface of the uprights, with uprights vertical, and the mast in its lowest position, shall not exceed 91.0 inches maximum with no load on the forks.

(9) Raised fork height. The truck shall be capable of raising the rated load at least 180.0 inches above ground level. This shall be with forks horizontal, and when measured from ground to top (load carrying) surface of the forks.

(10) Free lift height. The height that the forks can raise the rated load before the collapsed mast height is increased shall be not less than 50.0 inches.

(11) Drift of load. With hydraulic fluid at normal temperatures, lift assembly shall hold rated load at maximum lift height for at least 2.0 minutes with not more than 1-3/4 inch of vertical drift, and not more than 1.0 degree of rotational drift from the vertical.

(12) Stability. The forklift shall meet the ANSI B56.1 “forward stacking”, “forward travel”, “lateral stacking”, and “lateral travel” stability requirements for counter balanced front/side loader trucks.

(13) Electromagnetic radiation. The forklift shall comply with the EMI requirements shown in table I.

Table I. Electromagnetic Interference (EMI)

Name	**Description**	Parameters
SAE J551/1	Compatibility	N/A
SAE J551/2	Emissions	Frequency Range: 30 to 1000 MHz
SAE J551/11	Susceptibility	Frequency Range: (100 kHz to 18 GHz) 20 v/m (100 kHz to 200 MHz) 50 v/m (above 200 MHz)

3.30 Tires. The tires shall be solid. Tire loading shall not exceed those specified in the Tire and Rim Association Yearbook.

3.31 Noise limits. Maximum allowable noise level shall not exceed 84dB(A) at the operator’s ear. If the noise level at the operator’s ear is between 85 to 92dB(A), a permanent warning decal or placard shall be installed inside the cab clearly visible to the operator. Noise level shall not exceed 92dB(A).

3.32 Fire extinguisher. A commercial fire extinguisher shall be mounted on the truck in an easily accessible location. The fire extinguisher shall be a minimum 2 ½ pound capacity ABC type, or equivalent. The fire extinguisher shall be UL listed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

3.33 Backup alarm. An audible backup alarm shall be furnished. The alarm shall automatically activate when the transmission selector is placed in reverse.

3.34 Tropical rust-proofing. When specified (see 7.3), tropical rust-proofing shall be provided. This should be considered a premium rust-proofing package usually consisting of an additional coating. The truck shall be treated with a corrosion preventative compound complying with A-A-59295. a copy of A-A-59295 can be requested from WR-ALC/LESVG. Many of these vehicles are used in tropical/coastal environments and experience high humidity and salt spray. Therefore, they usually exhibit high levels of corrosion in the areas listed below. At a minimum, these areas shall be coated: (1) Cab, interior (2) Cab, exterior (3) Seams (4) Welds (5) Hidden recessed areas (6) Locations where dissimilar metals come in contact (7) Area above fuel tank(s) (8) Engine oil pan & transmission oil pan (9) Radiator support structure (10) Battery box.

4. REGULATORY REQUIREMENTS

4.1 Recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR). However, used, rebuilt, or remanufactured components, pieces, and parts shall not be incorporated in the forklift.

5. PRODUCT CONFORMANCE PROVISIONS

5.1 Product conformance. The products provided shall conform to the producer's own drawings, specifications, standards, and quality assurance practices and shall be the same product offered for sale in the commercial market. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

5.2 Market Acceptability. The following market acceptability criteria are necessary to document the quality of the product to be provided under this CID.

5.2.1 Commercial. The vehicle furnished shall be, as of the date of award, the latest model (with minor modifications, as that term is defined in DoD FAR Supplement 252.211-7012, Paragraph K-85 of the solicitation) of an established product previously produced and sold in substantial commercial quantities (exceeding the criteria at FAR 15.804-3(f)(2)(ii)(A)) for at least three years. The vehicle furnished, or earlier models of it, absent minor modifications, shall have routinely been supported with spare/repair parts which were produced or sold in the normal course of business. At the time of delivery, the contractor shall furnish the Administrative Contracting Officer with verification of compliance with these requirements. Offers shall provide, as part of their proposals, the following information on the vehicle (or its earlier models) being offered as a commercial item:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

(1) Total sales to the U.S. Government or to contractors for U.S. Government use during the three years.

(2) Total sales of the item to the general public during the three years.

(3) The vehicle must have been sold to the government or commercial market. This product must have been offered for at least two years.

6. PACKAGING

6.1 Packaging. Preservation, packing, and marking shall be as specified in the contract. Unless otherwise specified in the contract, the items shall be packaged according to normal commercial practice and packed to assure acceptance by common carrier and provide product protection against loss and damage during multiple shipment, handling, and storage. Shipping containers shall be properly marked and in compliance with both national and uniform motor freight classifications.

7. NOTES

7.1 Intended use. The vehicle is intended for use in handling cargo in and around warehouses, loading platforms, and docks; on paved or other hard surfaces

7.2 Source of documents.

Military Specifications, Standards, and Handbooks referenced herein may be obtained online at http://assist.daps.dla.mil/ or from the Standardization Document Order Desk, Building 4, Section D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.

The Society of Automotive Engineers (SAE) documents may be obtained online at http://www.sae.org/ or from SAE, 400 Commonwealth Drive, Warrendale, PA 15096.

ANSI/ASME documents may be obtained online at http://www.asme.org/ or from the American Society of Mechanical Engineers, 345 East 47th Street, New York, NY 10017.

Underwriters Laboratories (UL) copies may be obtained online at http://ulstandradsinfonet.ul.com/ or from: COMM 2000, 1414 Brook Drive, Downers Grove, IL 60515-5000.

Federal Acquisition Regulation (FAR) referenced online at http://www.arnet.gov/far/ or from the Superintendent of Documents at commercial phone (202) 512-1800.

The Tire and Rim Association Standards. (T&RA) Copies of T&RA standards may be obtained online at http://www.us-tra.org/ or from the Tire and Rim Association, 3200 West Market Street, Akron, OH 44313-1500.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

7.3 Options. When specified the following shall be furnished:

a. Battery (see 3.4)
b. Battery charger (see 3.4)
c. Cab. (see 3.21)
d. Final color other than yellow (see 3.22)
e. Tropical rust-proofing (see 3.34)

7.4 Ordering Data. Procurement documents must specify the title, number, and date of this CID, issue of DODISS to be cited in the solicitation, and preservation and packaging requirements.

MILITARY INTERESTS:

Custodians:
Air Force – 99
Army – AT
Navy – SA

Civil Agency and
Coordinating Activity:
GSA-FSS

Preparing Activity:
Air Force – 84

Agent:
Air Force – 99

(Project 3930-0037)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil .

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.