INCH-POUND
A-A-58081B
18 February 2010
SUPERSEDING
A-A-58081A
25 December 2004

COMMERCIAL ITEM DESCRIPTION

TRUCK, LIFT, FORK, ELECTRIC, FRONT/SIDE LOADING, SIT-DOWN OPERATOR, 4,000 POUND CAPACITY, EE RATED

The General Services Administration has authorized the use of this Commercial Item Description (CID) for all federal agencies.

1. SCOPE.

1.1 Scope. This commercial item description covers the general requirements for 4,000 pound at 24-inch load-center capacity, electric, front/side loading, forklift truck. It will be capable of picking up and depositing loads that are directly in front, and 90 degrees to the side of the truck. It will be EE rated in accordance with UL 583. It will be used for handling cargo in narrow aisle warehouses, loading platforms, and docks; on paved or other hard surfaces.

2. CLASSIFICATION.

2.1 Classification. The operator driven vehicle covered by this CID shall be commercially available and may be modified to the extent necessary to meet this description.

3. SALIENT CHARACTERISTICS.

3.1 Safety. The operator driven vehicle shall be capable of operation within the accuracies, limits, and specifications herein. The forklift shall comply with ANSI/ITSDF B56.1 and OSHA standards in effect at the time of manufacture. A seatbelt conforming to SAE J386, and restraint devices designed to ensure the operator's upper body remains entirely within the protection of the overhead guard in the event of tip-over shall be provided. Unless otherwise specified in the contract, the final color shall be yellow for safe operation in an indoor environment.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any other data that may improve this document should be sent to 642 CBSG/GBEC, 460 Richard Ray Blvd, Suite 200, Robins AFB, GA 31098-1813. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.daps.dla.mil/online/ .

FSC 3930

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

3.2 Environmental requirements. The forklift shall be capable of continuous operation as specified herein at any ambient temperature from 0º to + 120º F.

3.3 Mass pivot. The mast, including the carriage and forks, shall pivot 90 degrees to one side.

3.4 Battery. The battery shall have sufficient capacity to provide at least 6 hours of normal, industrial type operation. Battery leads shall be equipped with "SB" locking half connectors. When specified (see 7.3), an additional battery or battery charger shall be supplied.

3.5 Hydraulic System. All components, including filter(s), necessary to make a complete hydraulic system shall be provided.

3.6 Upright and carriage. With no load on the forks, the seated operator shall be able to see at least one fork tip when the forks are at their lowest position and straight ahead.

3.7 Forks. Fork dimensions shall be 2.06 inches maximum thickness, 5.56 inch maximum width, and 40.0 (+0.0, -1.0) inch long. Fork thickness at the tip shall be not more than 0.5 inch, and there shall be a taper on the underside of the forks of not less than 14 inches.

3.8 Fork Positioner. The forks shall be adjusted manually without the needs for tools. They shall have spacing of 20.0 inches (or less) when in most closed position, and 37.0 inches (or more) when in most spread position. These dimensions shall be measured to the outside edges of the forks.

3.9 Side shift. Hydraulically powered side shifting controlled by seated operator shall be furnished. With the forks in the front loading position, there shall be at least 6.0 inches side shift each side of center (12.0 inches minimum total travel) with rated load on the forks.

3.10 Load Backrest. The load backrest, in conjunction with the forks and carriage, shall provide a vertical rear load guard of at least 48 inches high, measured from the load horizontally carrying surfaces of the forks.

3.11 Long loads. With the forks in side handling position (full 90 degrees side pivot) the truck shall be capable of carrying a 4,000 pound load that is 20 feet long and 16 inches wide. It shall be carried parallel to the longitudinal centerline of the forklift. For safety and stability while traveling, this load, in this position, shall be supported by both the forks and the structure of the truck. This load, where it interferes with the truck, shall be within the plan outline of the forklift.

3.12 Steering. Power steering shall be furnished.

3.13 Service Brakes. Service brakes shall be furnished. They shall conform to ANSI/ITSDF B56.1, except the maximum brake pedal force during stopping distance and drawbar drag tests shall be not more than 80 pounds.

3.14 Parking brake. Parking brake shall conform to ANSI/ITSDF B56.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

3.15 Electrical system. All components necessary to make a complete electrical system shall be furnished.

3.16 Instruments. The instruments, gauges, or warning indicator lights that are on the manufacturer's standard commercial model shall be furnished. In addition, an unlighted hour-meter capable of totaling at least 9999 hours shall be included.

3.17 External Lights. Minimum of one front facing and one rear facing floodlight shall be shall be furnished. The front facing light shall be mounted on, and pivot with, the mast.

3.18 Taillight. One combination stoplight and taillight shall be provided.

3.18.1 Cab. When specified (see 7.3), a cab shall be furnished. It shall have FOPS capability per ANSI/ITSDF B56.1, and shall have two opening doors, and at least one fan for ventilation. There shall be sufficient window area to permit at least 250 degrees of horizontal visibility by the seated operator. The height from the ground to the top of the cab shall not be more than 84 inches. There shall be at least three wipers, one on the front windshield, one on the rear window, and one on the roof window.

3.18.1.1 Winterization C. When specified (see 7.3), the truck shall be equipped with a cab and shall protect to -25 degrees F. A cab heater and cab defroster shall be provided. If necessary, the cab shall contain thermal insulation to meet the heating requirements.

3.19 Horn. A horn shall be furnished, with the horn actuator located within reach of the seated operator.

3.20 Operator's overheard guard. The guard shall be in accordance with ANSI/ITSDF B56.1 including inside clearances. It shall also be a falling-object-protective-structure (FOPS) conforming to ANSI/ITSDF B56.1. The height, from the ground to the top of the overhead guard shall be not more than 91.0 inches.

3.21 Cab. When specified (see 7.3), a cab shall be furnished. It shall have inside clearances and FOPS capability per ANSI/ITSDF B56.1. The cab shall be equipped with an adjustable ventilation fan, not less than 6 inches in diameter. There shall be sufficient window area to permit at least 250 degrees of horizontal visibility by the seated operator. The height, from the ground to the top of the cab shall be not more than 91.0 inches. A heater and defroster with fan shall be provided. There shall be at least three wipers, one on the front windshield, one on the rear window, and one on the roof window.

3.22 Painting. The forklift shall be primed and painted using the contractor's standard commercial practices. Unless otherwise specified (see 3.30), the final color shall be yellow.

3.23 Walkway Coating. Step surfaces shall be made of, or covered with, a non-slip material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

3.24 Tie-down Provisions. There shall be permanently installed tie-downs devices that enable the truck to be tied down to the floor of the transportation media. All devices shall be capable of accepting a chain and hook with an outside diameter of 3.0 inches and shall have a structural safety factor of at least 2.0 to 1, based on static load. The notation "TIE DOWN" shall be stenciled, in black letters, near each tie-down device.

3.25 Towing device. A pin type towing device shall be recessed in the center of the truck. It shall not protrude beyond the outside surface of the truck. The pin shall accept a lunette with an inside diameter of 1.25 inches and a circular cross section of 1.0 inches in a diameter.

3.26 Overall dimensions. The maximum overall width of the truck shall be 46.0 inches. The maximum overall height shall be 91.0 inches.

3.27 Cautions and warnings. All cautions and warnings in the form of decals, stencils, etc. furnished on the manufacturer's standard commercial forklift, shall be installed on the truck.

3.28 Identification Plate. A corrosion resistant identification plate shall be permanently installed at an easily accessible place on the truck. It shall contain the following:

NOMENCLATURE:
MANUFACTURE'S NAME:
MANUFACTURER'S ADDRESS:
MANUFACTURER'S SERVICE PHONE NUMBER:
MANUFACTURER'S MODEL NUMBER:
MANUFACTURER'S SERIAL NUMBER:
DATE OF MANUFACTURER:
CONTRACT NUMBER:
NATIONAL STOCK NUMBER:
REGISTRATION NUMBER:

3.29 Performance. The truck shall be capable of meeting the following performance requirements:

(1) Capacity: The truck shall have the capability to safely handle a 4,000 pound, 48 inch-per-side cube, with the center of gravity at the center of the cube. This cube shall be defined, and referred to in this document, as the rated load. The forklift shall be able to safely handle this rated load at all lift heights, mast pivot positions, and fork side shift positions that it is capable of attaining.

(2) Load lifting speed: The truck shall be capable of raising rated load at a speed of at least 50 feet per minute.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

(3) Load lowering speed: Fork lowering speed shall not be more than 80 feet per minute with rated load on the forks and not less than 40 feet per minute with no load on the forks.

(4) Right angle turn: With rated load on the forks and forklift located perpendicular to a wall, and with the front of the load against the wall, the truck shall be able to back up and make a complete right angle turn (ending up parallel to the wall) within 160 inches.

(5) Travel speed: While carrying rated load on the forks, the truck shall be capable of traveling at a speed of at least 5.0 miles per hour, in both forward and reverse directions.

(6) Slope ascension. With the forklift facing toward the ramp and with rated load on the forks, the truck shall have adequate ground clearance to drive from a horizontal surface up a ramp with a 15 percent slope, with no contact between the ramp and forklift (except for tires). It shall have adequate power to accelerate up a ramp with a 15 percent slope, from a dead stop on the ramp.

(7) Upright tilt: With no load on the truck the forks shall have at least 3.0 degrees forward tilt, and at least 4.0 degrees of rear tilt.

(8) Lowest upright height (collapsed mast height): The dimension from ground to top surface of the uprights, with uprights vertical, and the mast in its lowest position, shall not exceed 91.0 inches maximum with no load on the forks.

(9) Raised fork height. The truck shall be capable of raising the rated load at least 180.0 inches above ground level. This shall be with forks horizontal, and when measured from ground to top (load carrying) surface of the forks.

(10) Free lift height. The height that the forks can raise the rated load before the collapsed mast height is increased shall be not less than 50.0 inches.

(11) Drift of load. With hydraulic fluid at normal temperatures, lift assembly shall hold rated load at maximum lift height for at least 2.0 minutes with not more than 1-3/4 inch of vertical drift, and not more than 1.0 degree of rotational drift from the vertical.

(12) Stability. The forklift shall meet the ANSI/ITSDF B56.1 “forward stacking”, “forward travel”, “lateral stacking”, and “lateral travel” stability requirements for counter balanced front/side loader trucks.

(13) Electromagnetic radiation. The forklift shall comply with the EMI requirements shown in table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

Table I. Electromagnetic Interference (EMI)

Name	Description	Parameters
SAE J551-1	Compatibility	N/A
CISPR 12 & CISPR 25	Emissions	Frequency Range: 30 to 1000 MHz
SAE J551-11	Susceptibility	Frequency Range: (100 kHz to 18 GHz) 20 v/m (100 kHz to 200 MHz) 50 v/m (above 200 MHz)

3.30 Tires. The tires shall be solid. Tire loading shall not exceed those specified in the Tire and Rim Association Yearbook.

3.31 Noise limits. Maximum allowable noise level shall not exceed 84 dB(A) at the operator's ear. If the noise level at the operator's ear is between 85 to 92 dB(A), a permanent warning decal or placard shall be installed inside the cab clearly visible to the operator. Noise level shall not exceed 92 dB(A).

3.32 Fire extinguisher. A commercial fire extinguisher shall be mounted on the truck in an easily accessible location. The fire extinguisher shall be a minimum 2 ½ pound capacity ABC type, or equivalent. The fire extinguisher shall be UL listed.

3.33 Backup alarm. An audible backup alarm shall be furnished. The alarm shall automatically activate when the transmission selector is placed in reverse.

3.34 Tropical rust-proofing. When specified (see 7.3), tropical rust-proofing shall be provided. This should be considered a premium rust-proofing package usually consisting of an additional coating. The truck shall be treated with a corrosion preventative compound complying with A-A-59295. A copy of A-A-59295 can be found in the ASSIST database or requested from 642 CBSG/GBEC. Many of these vehicles are used in tropical/coastal environments and experience high humidity and salt spray. Therefore, they usually exhibit high levels of corrosion in the areas listed below. At a minimum, these areas shall be coated: (1) Cab, interior (2) Cab, exterior (3) Seams (4) Welds (5) Hidden recessed areas (6) Locations where dissimilar metals come in contact (7) Area above fuel tank(s) (8) Engine oil pan & transmission oil pan (9) Radiator support structure (10) Battery box.

4. REGULATORY REQUIREMENTS

4.1 Recycled, recovered, or environmentally preferable materials. Recycled, recovered, or environmentally preferable materials should be used to the maximum extent possible provided that the material meets or exceeds the operational and maintenance requirements, and promotes economically advantageous life cycle costs. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR). However, used, rebuilt, or remanufactured components, pieces, and parts shall not be incorporated in the forklift.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

4.2 Green Procurement Program. Green Procurement Program (GPP) is a mandatory federal acquisition program that focuses on the purchase and use of environmentally preferable products and services. GPP requirements apply to all acquisitions using appropriated funds, including services and new requirements. FAR 23.404(b) applies and states the GPP requires 100% of EPA designated product purchase that are included in the Comprehensive Procurement Guidelines list that contains recovered materials, unless the item cannot be acquired: a) competitively within a reasonable timeframe; b) meet appropriate performance standards, or c) at a reasonable price. The prime contractor is responsible for ensuring that all subcontractors comply with this requirement.

5. PRODUCT CONFORMANCE PROVISIONS

5.1 Product conformance. The products provided shall conform to the producer's own drawings, specifications, standards, and quality assurance practices and shall be the same product offered for sale in the commercial market. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

5.2 Market Acceptability. The following market acceptability criteria are necessary to document the quality of the product to be provided under this CID.

5.2.1 Commercial. The vehicle furnished shall be, as of the date of award, the latest model (with minor modifications, as that term is defined in DoD FAR Supplement 252.211-7012, Paragraph K-85 of the solicitation) of an established product previously produced and sold in substantial commercial quantities (exceeding the criteria at FAR 15.804-3(f)(2)(ii)(A)) for at least three years. The vehicle furnished, or earlier models of it, absent minor modifications, shall have routinely been supported with spare/repair parts which were produced or sold in the normal course of business. At the time of delivery, the contractor shall furnish the Administrative Contracting Officer with verification of compliance with these requirements. Offers shall provide, as part of their proposals, the following information on the vehicle (or its earlier models) being offered as a commercial item:

(1) Total sales to the U.S. Government or to contractors for U.S. Government use during the three years.
(2) Total sales of the item to the general public during the three years.
(3) The vehicle must have been sold to the government or commercial market. This product must have been offered for at least two years.

6. PACKAGING

6.1 Packaging. Preservation, packing, and marking shall be as specified in the contract or order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

7. NOTES

7.1 Intended use. The vehicle is intended for use in handling cargo in and around warehouses, loading platforms, and docks; on paved or other hard surfaces.

7.2 Source of documents.

Military Specifications, Standards, and Handbooks referenced herein may be obtained online at https://assist.daps.dla.mil/online/ or from the Standardization Document Order Desk, Building 4, Section D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.

The Society of Automotive Engineers (SAE) documents may be obtained online at http://www.sae.org/ or from SAE, 400 Commonwealth Drive, Warrendale, PA 15096.

Underwriters Laboratories (UL) copies may be obtained online at http://ulstandardsinfonet.ul.com/ or from: COMM 2000, 1414 Brook Drive, Downers Grove, IL 60515-5000.

FAR and DFARS may be obtained from the Superintendent of Documents, P.O. Box 371954, Pittsburgh, PA 15250-7954. Electronic copies of the FAR may be obtained from https://www.acquisition.gov/far/ . Electronic copies of the DFARS may be obtained from http://www.acq.osd.mil/dpap/dars/dfars/index.htm .

Comité International Spécial des Perturbations Radioélectriques (CISPR) document may be obtained online at http://www.iec.ch/zone/emc/emc_cis.htm.

7.3 Ordering Data. The contract or order should specify the following:

a. Battery (see 3.4)
b. Battery charger (see 3.4)
c. Cab. (see 3.21)
d. Final color other than yellow (see 3.22)
e. Tropical rust-proofing (see 3.34)

7.4 Key Words.

Cargo
Narrow aisles
Warehouses

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Custodians:
Air Force – 84
Army – AT
Navy – SA

Reviewer:
DLA–IS

Preparing Activity:
Air Force – 84

Agent:
Air Force – 99

(Project 3930-2010-005)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.daps.dla.mil/online/ .

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.