(INCH-POUND)
A-A-58083
18 Oct 96

COMMERCIAL ITEM DESCRIPTION

TRUCK, LIFT, FORK, DIESEL-ENGINE-DRIVEN, PNEUMATIC-TIRED, 4-WHEEL DRIVE, ROUGH TERRAIN, 6,000 POUNDS CAPACITY AT 24 INCH LOAD CENTER

The General Services Administration has authorized the use of this commercial item description, for all Federal Agencies.

1. SCOPE. This commercial item description covers the general requirements for a 114 inch lift height, diesel engine driven, rough terrain, four wheel drive, pneumatic tired, 6,000 pound at 24 inch load-center capacity, forklift truck. It shall be used for handling cargo on paved, mud, or snow covered surfaces.

2. SALIENT CHARACTERISTICS:

2.1 Safety. The forklift shall comply with ANSI B56.6, and OSHA standards in effect at the time of manufacture. A seatbelt conforming to SAE J386, and restraint devices designed to ensure the operator's upper body remains entirely within the protection of the overhead guard in the event of tip-over shall be provided. Unless otherwise specified in the contract, the final color shall be forest green for safe operation in an outdoor environment.

2.2 Environmental requirements. The engine shall start without preheating within 5 minutes in any ambient temperature, and with the truck stabilized at ambient temperature, from 0 to 120 degrees F. The forklift shall be capable of continuous operation as specified herein at any ambient temperature up to 120 degrees F.

2.3 Engine. A diesel fueled engine shall be provided.

2.4 Fuel system. All necessary filters, water separators, and other components required for diesel fuel operation shall be provided. It shall have a fuel tank of sufficient capacity to allow at least 8 hours of continuous operation.

2.5 Starting system. The engine starter motor shall not be capable of energizing while the engine is running or while the transmission is in any forward or reverse gear.

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any data which may improve this document should be sent to: WR-ALC/LVR, 225 Ocmulgee Court, Robins AFB GA 31098-1647

AMSC N/A FSC 3930
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

2.6 Transmission. A torque converter and a powershift type of transmission shall be furnished. The transmission shall provide for positive inching control, or declutch control, that permits lifting of rated load at maximum lifting speed while the transmission control is in either forward or reverse direction, without vehicle movement. This inching/declutch control shall also apply the service brakes.

2.7 Drive system. The truck shall have all wheels driven (4-wheel drive).
.
2.8 Hydraulic system. Filter(s) and a pressure relief protection device is required, along with all other components necessary to make a complete hydraulic system.

2.9 Fork visibility. With no load on the forks, the seated operator shall be able to see at least one fork tip at all lift heights and fork positions.

2.10 Forks. Fork dimensions shall be 2.60 inches maximum thickness, 5.06 inch maximum width, and 42.0 (+ or - 0.5 inch) long. Fork thickness at the tip shall be not more than 0.5 inch, and there shall be a taper on the underside of the forks of not less than 14 inches.

2.11 Fork positioner. A hydraulically powered adjustable fork positioner shall be furnished. The forks shall have spacing of 20.0 inches (or less) when in most closed position, and 69.0 inches (or more) when in most spread position. These dimensions shall be measured to the outside edges of the forks.

2.12 Side shift. Hydraulically powered side shifting shall be furnished. It shall be controlled by seated operator, with at least 4.0 inches side shift each side of center (8.0 inches minimum total travel) with rated load on the forks.

2.13 Fork oscillation. Hydraulically powered oscillation of the forks shall be furnished. The oscillation shall be not less than 6.0 degrees clockwise and 6.0 degrees counterclockwise from horizontal, for a total oscillation of 12.0 degrees. This oscillation shall occur at all side shift positions that the forklift is capable of achieving. With rated load on the forks, the time to oscillate the total 12 degrees shall be not more than 7 seconds, with the engine operating at idle speed.

2.14 Load backrest. The load backrest, in conjunction with the forks and carriage, shall provide a vertical rear load guard of at least 48 inches high, measured from the load horizontal carrying surfaces of the forks.

2.15 Steering. Power steering shall be furnished. Emergency steering in accordance with SAE J53 shall be provided.

2.16 Service brakes. Power assisted service brakes shall be furnished. They shall conforming to the performance requirements of ANSI B56.6, except the maximum brake pedal force during stopping distance and drawbar drag tests shall be not more than 80 pounds.

2.17 Parking brake. The parking brake shall conform to ANSI B56.6.

2.18 Electrical system. All components necessary to make a complete electrical system, including the capability to charge the battery when the engine is operating, shall be furnished.

2.19 Instruments. The instruments, gauges or warning indicator lights that are on the manufacturer’s standard commercial model shall be furnished. In addition, an unlighted hourmeter capable of totaling at least 9999 hours shall be included..

2.20 External lights. Minimum of two floodlights shall be furnished. One in front, facing forward, and one mounted in the rear, facing rearward.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

2.21 Taillight. One combination stoplight and taillight shall be provided.

2.22 Horn. A horn shall be furnished, with the horn actuator located within reach of the seated operator.

2.23 Ground clearance. The ground clearance of the truck with rated load, as defined in SAE J1234, shall be not less than 12.0 inches. The truck both with and without rated load, shall be capable of traveling from a horizontal surface, up a 30 degree ramp, and unto another horizontal surface with no contact, except the tires.

2.24 Operator's overhead guard. An overhead guard shall be provided. The guard shall be a roll-over-protective structure (ROPS) and falling-object-protective-structure (FOPS) conforming to SAE J1040 and SAE J231. The clearance from operator's seat to underside of the guard shall be in accordance with ANSI B56.6.

2.25 Cab. When specified (see 2.37), a cab shall be furnished. It shall have ROPS and FOPS capability in accordance with paragraph 2.24 above. It shall have two opening doors, or one door and one window that meets the emergency exit requirements of SAE J185. and at least one fan for ventilation. The door(s) shall be capable of being securely retained when in the open position. There shall be sufficient window area to permit at least 250 degrees of horizontal visibility by the seated operator. The clearance from the operator's seat to the underside of the cab shall be in accordance with ANSI B56.6. The most heavy duty heater and defroster supplied on the manufacturer's standard forklift shall be provided.

2.26 Painting. The forklift shall be primed and painted using standard commercial practices. Unless otherwise specified (see 2.37), the final color shall be the color commonly called forest green.

2.27 Walkway coating. Step surfaces shall be made of, or covered with, a non-slip material.

2.28 Lifting and tie-down provisions. There shall be permanently installed lifting devices that enable the truck to be lifted in its normal travel position, and tie-down devices that that enable the truck to be tied down to the floor of the transportation media. All devices shall be capable of accepting a chain and hook with an outside diameter of 3.0 inches and shall have a structural safety factor of at least 2.0 to 1, based on static load. The notation "LIFT HERE" or "TIE DOWN" shall be stenciled, in black letters, near each lifting and tie-down device.

2.29 Marking. All stencils, decals, plates, etc. normally provided on the manufacturer's standard forklift shall be included. This shall include, as a minimum, the forklift's capacity in pounds, and all information, cautions and warnings normally provided.

2.30 Identification plate. A corrosion resistant identification plate shall be permanently installed at an easily accessible place on the truck. It shall contain the following information:

NOMENCLATURE:
MANUFACTURER'S NAME:
MANUFACTURER'S ADDRESS:
MANUFACTURER'S SERVICE PHONE NUMBER:
MANUFACTURER'S MODEL NUMBER:
MANUFACTURER'S SERIAL NUMBER:
DATE OF MANUFACTURE:
CONTRACT NUMBER:
NATIONAL STOCK NUMBER:
REGISTRATION NUMBER:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

2.31 Axle spacing. Axle spacing for the truck shall be not less than 96 inches.

2.32 Tires. The tires shall be pneumatic, off road type, and all tires shall be the same size, type and tread pattern. Tire loadings shall not exceed those specified in the Tire and Rim Association Yearbook.

2.33 Wheel guards. Wheel guards shall be provided on all wheels to prevent the operator from being hit with material thrown radially from the tires.

2.34 Width. The width of the truck, as defined in SAE J1234, including tire bulge at manufacturer's recommended tire pressure, shall be not more than 102 inches, even with the forks fully side shifted.

2.35 Towing devices. At least two devices to allow the truck to be towed from the rear shall be provided. The devices shall be capable of accepting common chains and hooks of 3 inches in diameter. The devices shall withstand a force of at least 3 times the gross vehicle weight. The forklift shall be capable of being towed at a speed of not less than 15 miles per hour, for a distance of at least three miles, with no damage to any components of the truck.

2.36 Performance. The truck shall be capable of meeting the following performance requirements:

(1) Capability to safely handle a 6,000 pound, 48 inch per side cube with the center of gravity at the center of the cube. This shall be defined, and referred to in this document, as the rated load. The forklift shall be able to safely handle this rated load at all lift heights and fork side shift positions that it is capable of attaining.

(2) Load lifting speed: Shall be capable of raising rated load at a speed of at least 55 feet per minute.

(3) Load lowering speed: Not more than 80 feet per minute with rated load of forks and not less than 30 feet per minute with no load on the forks.

(4) Curb circle clearance. The curb circle clearance, as defined in SAE J695 shall be 34.5 feet maximum.

(5) Travel speed: 12 miles per hour minimum, in both forward and reverse, while carrying rated load on the forks.

(6) Slope ascension: With the truck facing up the slope and with rated load on the forks it shall be able to accelerate up a 30 degree slope from a dead stop.

(7) Upright tilt: With no load on the truck the forks shall have at least 20.0 degrees forward tilt, and at least 20.0 degrees of rear tilt.

(8) Side slope operation. The truck shall be capable of being driven in a full circle on a 20 percent slope, both with and without rated load on the forks. This shall be accomplished at maximum steering angle, in both directions, without any tire leaving the ground.

(9) Maximum fork lift height. At least 114.0 inches with rated load on forks and forks horizontal, when measured from ground to top surfaces of the forks.

(10) Low engagement height: With no load on the forks and the forks horizontal, the upper surfaces of the forks shall be capable of lowering at least 6.0 inches below ground level.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

(11) Drift of load. With hydraulic fluid at ambient temperature, lift assembly shall hold rated load at maximum lift height for at least 10.0 minutes with not more than 1-3/4 inch of vertical drift, and not more than 1.0 degree of rotational drift.

(12) Stability. The forklift shall meet the ANSI B56.6 "forward stacking", "forward travel", "lateral stacking", and "lateral travel" stability requirements.

(13) Noise limits. The maximum allowable at the operator's ear is 95 db(A). If the noise level at the operator's ear exceeds 84 db(A) (85 to 95 db(A)), a warning sign stating that operator's hearing protection is required shall be installed at the operator's station. The sign shall be at least 4 inches square, with a yellow background.

(14) Electromagnetic radiation. The forklift shall not exceed the limits of electromagnetic radiation specified in SAE J551.

2.37 Options. When specified the following shall be furnished:
a. Cab (see 2.25).
b. Final color other than forest green (see 2.26).

3. REGULATORY REQUIREMENTS.

3.1 The offer/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR). However, used, rebuilt, or remanufactured components, pieces, and parts shall not be incorporated in the forklift.

4. QUALITY ASSURANCE PROVISIONS:

4.1 Product Conformance. The products provided shall conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial market. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

4.2 Market acceptability. The following market acceptability criteria are necessary to document the quality of the product to be provided under this CID.

4.2.1 Commercial. The vehicle furnished shall be, as of the date of award, the latest model (with minor modifications, as that term is defined in DoD FAR Supplement 252.211-7012, Paragraph K-85 of the solicitation) of an established product previously produced and sold in substantial commercial quantities (exceeding the criteria at FAR 15.804-3(f)(2)(ii)(A)) for at least three years. The vehicle furnished, or earlier models of it, absent minor modifications, shall have routinely been supported with spare/repair parts which were produced or sold in the normal course of business. At the time of delivery, the contractor shall furnish the Administrative Contracting Officer with verification of compliance with these requirements. Offers shall provide, as part of their proposals, the following information on the vehicle (or its earlier models) being offered as a commercial item:

(1) Total sales to the U.S. Government or to contractors for U.S. Government use during the three years.
(2) Total sales of the item to the general public during the three years.
(3) Length of time the item has been sold in the commercial market place.

5. PACKAGING. Preservation, packing, and marking for shipment shall be specified in the contract or order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

6. NOTES.

6.1 Source of Documents.

6.1.1 ANSI documents may be obtained from American National Standards Institute, 11 West 42nd Street, New York NY 10036.

6.1.2 SAE documents may be obtained from Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale PA 15096

MILITARY INTERESTS:

CIVIL AGENCY COORDINATING ACTIVITY:
GSA-FSS

CUSTODIANS:
Air Force - 99
Army-AT
Navy-SA

PREPARING ACTIVITY:
Air Force - 84

Project 3930-0689

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.