INCH-POUND

A-A-58090A
23 January 2004
SUPERSEDING
A-A-58090
1 May 1997

COMMERCIAL ITEM DESCRIPTION
GENERATOR, SIGNAL, VOR/ILS

The General Services Administration has authorized the use of this Commercial Item Description (CID) for all federal agencies.

1. SCOPE. This Commercial Item Description (CID), describes a VOR/ILS/MB signal generator. This CID is meant as a minimum requirement for the VOR/ILS/MB signal generator in which only those manufacturers that meet or surpass the following requirements are supplied per this CID. The signal generator shall produce both RF and audio signals for testing VHF Omnidirectional Radio range (VOR), localizer (LOC), glideslope (GS), and marker beacon (MB) receivers. The equipment shall test receivers in the benchtop environment and shall test receivers which are installed in an aircraft.

2. SALIENT CHARACTERISTICS. The equipment shall be capable of operation within the accuracies, limits, and specifications herein. Equipment covered by this CID shall be commercially available equipment and may modified to the extent necessary to meet this description. The equipment shall be Class 1 in accordance with MIL-PRF-28800, except as specified herein.

2.1 Safety and Environmental. The equipment shall meet all safety and environmental requirements as specified in MIL-PRF-28800 for the classification as stated herein except as specified herein.

2.1.1 Water Resistance. The equipment shall not be required to be watertight and splashproof. The equipment shall conform to the dripproof requirements of MIL-PRF-28800 Class 2, while the equipment is not operating and the equipment covers are closed.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data that may improve this document should be sent to: WR-ALC/LEEC, 295 Byron Street, Robins AFB, GA 31098-1611

AMSC N/A FSC 6625

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

2.1.2 Explosive Atmosphere. The equipment shall meet the explosive atmosphere requirements of MIL-PRF-28800 or the requirements of MIL-STD-810, METHOD 511.4, PROCEDURE I.

2.1.3 Dust Resistance. Dust resistance shall not be required.

2.1.4 Salt Exposure. Salt exposure verification testing shall not be required.

2.1.5 Operating Temperature. The equipment shall meet its performance and accuracy requirements in an operating environment of -20 degrees C to +50 degrees C.

2.1.6 Relative Humidity. The equipment shall meet its performance and accuracy requirements in an operating environment where the relative humidity is 5 to 75±5 percent in the temperature range of 10 to 30 degrees C and 5 to 45±5 percent in the temperature range of 30 to 50 degrees C.

2.1.7 Altitude Requirements. The equipment shall meet its performance and accuracy requirements operating and nonoperating as specified in MIL-PRF-28800, except the maximum required altitude shall be 13100 feet (4000 meters).

2.1.8 Random Vibration. The equipment shall conform to the random vibration requirements of MIL-PRF-28800 Class 2.

2.1.9 Transit Drop. The equipment shall conform to the transit drop requirements of MIL-PRF-28800 Class 2.

2.2 Electrical Power Sources and Connections. The equipment shall operate from nominal commercial, military, and shipboard power sources with a nominal voltage of 120 Vrms single-phase AC (±10%) at line frequencies of 50 Hz, 60 Hz, and 400 Hz (±5%) in accordance with MIL-PRF-28800, Section 3. Transient state conditions shall meet MIL-PRF-28800 requirements for the classification specified herein. AC input power shall be used to power the signal generator and recharge its internal batteries.

2.3 Internal DC Power. DC power shall be supplied by internal, rechargeable storage batteries. The signal generator shall be capable of operating away from an external AC power source. The rechargeable batteries shall have the capability of operating the unit with full performance for a period of not less than one hour for the operating temperature range specified herein. The batteries shall conform to MIL-PRF-28800.

2.4 Recharge Time. The charger circuitry shall be such that a condition of charge which shall permit at least one hour of continuous use of the unit, within all specification requirements, shall be reached in no more than eight hours following a low battery indication. Under no condition of discharge shall the charging rate applied to the battery exceed the battery manufacturer's recommended maximum rate, nor shall an indefinite charging period result in any damage to the battery or any other components.

2.6 Battery Conservation. The signal generator shall cycle to the off or standby mode after 15 minutes of switch inactivity to conserve internal battery power.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

2.7 Battery Charger. An internal battery charger shall be provided in accordance with MIL-PRF-28800, Section 3.

2.8 Pre-Conditioning Requirement. Each deliverable equipment shall be capable of being subjected to the environmental screening effects of burn in and thermal cycling, with thermal cycling being accomplished in the sample testing phase.

2.9 Calibration. The calibration interval shall be as specified in MIL-PRF-28800, Section 3. No special tools shall be required for alignment or adjustment except those furnished with the test set.

2.10 Performance Requirements. The instrument shall meet all requirements specified herein, after the warm-up period specified in MIL-PRF-28800, under all combinations of input power conditions, output signal conditions and operating service condition as specified in MIL-PRF-28800. Instrument Landing System (ILS), VHF Omnidirectional Radio range (VOR), and Marker Beacons (MB) are defined in ICAO Annex 10, Volume I (Radio Navigation Aids).

2.10.1 Marker Beacon Generator. A Marker Beacon (MB) generator shall be provided and selected by means of an ON/OFF control or function selector located on the front panel and labeled as such.

2.10.1.1 RF Frequency. The MB generator shall provide continuous sine waves at the fixed frequency of 75.0 MHz ±0.005%. This frequency referred as RF herein, shall be modulated as specified herein.

2.10.1.1.1 RF Frequency Stability. The variation in frequency of the RF output frequency shall not exceed ±0.005%.

2.10.1.1.2 RF Spectral Purity. At the frequency specified in 2.10.1.1, the following specifications shall be met:

2.10.1.1.2.1 Harmonics. The level of any harmonic on the desired RF signal shall be at least 30 dB below the output level of the desired fundamental RF signal.

2.10.1.1.2.2 Spurious Signals. The total of all spurious signals, including sub harmonics, accompanying the desired RF signal shall be at least 35 dB below the output level of the desired RF signal at ±15kHz and at least 40 dB below the carrier output level at ±25.0 kHz in a 300 Hz resolution bandwidth, as measured at the RF IN/OUT connector and into a 50 ohm load.

2.10.1.1.2.3 Broadband Noise. The level of any broadband noise on the desired RF signal shall be at least 90 dB below the carrier output level measured in a 1 Hz noise bandwidth at more than 50 kHz from the carrier frequency, as measured at the RF IN/OUT connector and into a 50 ohm load.

2.10.1.2 RF Output for MB, GS, LOC, and VOR.

2.10.1.2.1 RF Output Attenuator. The RF level shall be adjustable, in not greater than 1 dB increments, from 0 to -100 dB ±2.0 dB, when measured into a 50 ohm load at the RF IN/OUT connector.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

2.10.1.2.2 RF IN/OUT Connector/Antennas.

2.10.1.2.2.1 Connector. The RF IN/OUT connectors for detachable antennas are required by the test set's designs. The connectors shall be a stainless steel chassis mounting type and shall be labeled "RF IN/OUT."

2.10.1.2.2.2 Antennas. Antennas shall be provided, and the antennas shall be capable of radiating the MB, GS, LOC and VOR frequencies specified in this specification when they are modulated as specified in this specification. The antennas shall be either collapsible into the test set or detachable. The surface-mounted connector or remaining protrusion of the collapsed antenna shall not extend over 0.25 inches from the test set. If the antenna must be longer than 12.0 inches, it shall be telescoping. It shall be mechanically and electrically compatible with the connector specified in 2.10.1.2.2.1.

2.10.1.2.2.3 RF Output Level. The level of the unmodulated RF signal shall be not less than -20 dBm when measured into a 50 ohm load. The test set shall radiate sufficient RF output power from the antenna, at a 0 dB attenuation setting, to perform all testing functions while being operated from within the cockpit of the aircraft under test (AUT). The contractor shall submit certification that their test set has this one-man testing capability. No cabling or other physical connections from inside the AUT to outside AUT shall be required.

2.10.1.2.2.4 Output Impedance. The output impedance of the RF signal circuit shall be 50 ohms and shall be matched to the antennas.

2.10.1.3 Marker Beacon Tones. The MB carrier shall be amplitude modulated by the following audio frequency (AF) tones.

a. 400 Hz sine wave (outer marker beacon).

b. 1300 Hz sine wave (middle marker beacon).

c. 3000 Hz sine wave (inner marker beacon).

2.10.1.3.1 Audio Frequency Accuracy. The audio signals specified in 2.10.1.3 shall be accurate to within ±2.0%.

2.10.1.3.2 Audio Frequency Spectral Purity. For each of the audio signals specified in 2.10.1.3, the total distortion due to harmonics, noise, and spurious signals shall be less than 10.0%.

2.10.1.3.3 Modulation Depth. Each marker tone shall be capable of amplitude modulating the carrier with a modulation level range from 95.0 ± 5 %.

2.10.1.3.3.1 Envelope Distortion. The distortion of the modulation envelope on the RF carrier shall be less than 10%.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

2.10.1.3.4 Tone Selection. Each tone shall be selected by means of control(s) with each control or controls position properly labeled to indicate the marker beacon frequency or position (i.e., outer, middle, inner).

2.10.2 Glide Slope Generator.

2.10.2.1 Glide Slope Generator Selection. The Glide Slope (GS) generator shall be selected by means of an ON/OFF control or function selector located on the front panel and labeled as such.

2.10.2.2 RF Frequency Range. The GS generator shall provide continuous sine waves over the frequency range of 330.95 MHz ±0.002% to 334.7 MHz ±0.002%. These frequencies, referred to RF herein, shall be modulated as specified herein. The GS generator shall provide a minimum of two selectable fixed frequency outputs which shall be selected from and paired with the corresponding localizer frequencies specified in the table below.

LOC(MHz)	GS(MHz)		LOC(MHz)	GS(MHz)		LOC(MHz)	GS(MHz)
108.1	334.7		109.5	332.6		110.9	330.8
108.15	334.55		109.55	332.45		110.95	330.65
108.3	334.1		109.7	333.2		111.1	331.7
108.35	333.95		109.75	333.05		111.15	331.55
108.5	329.9		109.9	333.6		111.3	332.3
108.55	329.75		109.95	333.65		111.35	332.15
108.7	330.5		110.1	334.4		111.5	332.9
108.75	330.35		110.15	334.25		111.55	332.75
108.9	329.3		110.3	335.0		111.7	333.5
108.95	329.15		110.35	334.85		111.75	333.35
109.1	331.4		110.5	329.6		111.9	331.1
109.15	331.25		110.55	329.45		111.95	330.95
109.3	332.0		110.7	330.2			
109.35	331.85		110.75	330.05			

2.10.2.2.1 RF Frequency Selection. The output frequency shall be selected by means of a control located on the front panel. The positions of the control shall be labeled with the appropriate frequency pairs.

2.10.2.2.2 RF Frequency Stability. The variation in frequency of the RF output frequency shall not exceed ±0.002%.

2.10.2.2.3 RF Spectral Purity. At the frequencies specified in 2.10.2.2, the following specifications shall be met:

2.10.2.2.3.1 Harmonics. The level of any harmonic on the desired RF signal shall be at least 25 dB below the output level of the desired fundamental RF signal.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

2.10.2.2.3.2 Spurious Signals. The total of all spurious signals, including subharmonics, accompanying the desired RF signal shall be at least 35 dB below the output level of the desired RF signal at ±15 kHz and at least 40 dB below the carrier output level at ±25.0 kHz in a 300 Hz resolution bandwidth, as measured at the RF IN/OUT connector and into a 50 ohm load.

2.10.2.2.3.3 Broadband Noise. The level of any broadband noise on the desired RF signal shall be at least 90 dB below the carrier output level (measured in a 1 Hz noise bandwidth at less than 50 kHz from the carrier frequency), as measured at the RF IN/OUT connector and into a 50 ohm load.

2.10.2.3 Glide Slope Tones. The GS carriers shall be amplitude modulated by 90 and 150 Hz sine wave audio frequency (AF) tones.

2.10.2.3.1 Audio Frequency Accuracy. The audio signals specified in 2.10.2.3 shall be accurate to within ±0.01%.

2.10.2.3.2 Audio Frequency Spectral Purity. For each of the audio signals specified in 2.10.2.3, the total distortion due to harmonics, noise, and spurious signals shall be less than 5.0% for the 90 Hz and 150 Hz signals.

2.10.2.3.3 90 Hz/150 Hz Modulation Depth. The 90 Hz and 150 Hz signals shall be used to amplitude modulate the GS frequencies specified in 2.10.2.2. The 90 Hz and 150 Hz signals shall be supplied both separately and together. The 90 Hz and 150 Hz signals shall be of sufficient magnitude to modulate the carrier to a preset depth of 40% ± 2 %.

2.10.2.3.4 90 Hz/150 Hz Phase Error. The phase error of the 90 Hz and 150 Hz signals shall not exceed 10.0 degrees. Relative phase is defined as the difference in degrees of the points at which the 90 Hz and 150 Hz waveforms cross the zero axis in the same direction at the same time.

2.10.2.3.5 DDM Control. The output ratio of the 90 Hz signals shall have presets at 0.175 ±0.025 DDM, at both 90 Hz predominant and 150 Hz predominant, 0.000±0.10 DDM on course ("OC"). For purposes of determining DDM, the base shall be 0.40 for the GS function.

2.10.2.3.5.1 Variable DDM Control. A control shall be provided to continuously vary the DDM from 0.175 ±0.035 DDM, 90 Hz predominant to 0.175 ±0.035 DDM , 150 Hz predominant. This control shall have an off position in which the variable DDM circuitry is not operative.

2.10.2.3.6 90 Hz and 150 Hz Delete. Two front panel controls shall be provided to delete the 90 Hz and 150 Hz tones independently.

2.10.3 Localizer Generator.

2.10.3.1 Localizer Generator Selection. The LOC generator shall be selected by means of an ON/OFF control or function selector located on the front panel and labeled as such.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

2.10.3.2 RF Frequency Range. The LOC generator shall provide continuous sine waves over the frequency range from 108.10 MHz ± 0.002% to 111.95 MHz ±0.002%. These frequencies, referred to as RF herein, shall be modulated as specified herein. The LOC generator shall provide a minimum of two selectable fixed frequency outputs which shall be paired with the corresponding glide slope frequencies specified in paragraph 2.10.2.2.

2.10.3.2.1 RF Frequency Selection. The LOC RF output frequency shall be selected as specified in 2.10.2.2 with the respective paired GS frequency .

2.10.3.2.2 RF Frequency Stability. The variation in frequency of the RF output frequency shall not exceed ±0.002%.

2.10.3.2.3 RF Spectral Purity. At the frequencies specified in 2.10.3.2, the following specifications shall be met:

2.10.3.2.3.1 Harmonics. The level of any harmonic on the desired RF signal shall be at least 30 dB below the output level of the desired fundamental RF signal.

2.10.3.2.3.2 Spurious Signals. The total of all spurious signals, including subharmonics, accompanying the desired RF signal shall be at least 75 dB below the output level of the desired RF signal at ±15.0 kHz and at least 80dB below the carrier output level at ±25.0 kHz in a 300 Hz resolution bandwidth, as measured at the RF IN/OUT connector and into a 50 ohm load.

2.10.3.2.3.3 Broadband Noise. The level of any broadband noise on the desired RF signal shall be at least 90 dB below the carrier output level (measured in a 1 Hz noise bandwidth at more than 15kHz from the carrier frequency), as measured at the RF IN/OUT connector and into a 50 ohm load.

2.10.3.3 Localizer Tones. The LOC carriers shall be amplitude modulated by 90, 150, and 1020 Hz sine wave audio frequency (AF) tones.

2.10.3.3.1 Audio Frequency Accuracy. The 90 Hz and 150 Hz signals shall be accurate to within ±0.01%. The 1020 Hz signal shall be accurate to within ±2.0%.

2.10.3.3.2 Audio Frequency Spectral Purity. For each of the audio signals specified in 2.10.3.3, the total distortion due to harmonics, noise, and spurious signals shall be less than 5% for the 90 Hz and 150 Hz signals at preset 20% AM, less than 1.0% in the variable range from 5 to 40% AM, and less than 10% for the 1020 Hz signal at preset 30% AM.

2.10.3.3.3 90 Hz and 150 Hz Modulation Depth. The 90 Hz and 150 Hz signals shall be used to amplitude modulate the LOC frequencies specified in 2.10.3.3. The 90 Hz and 150 Hz signals shall be supplied both separately and together and be of sufficient magnitude to modulate the carrier to a preset depth of 20% ± 2%. The 90 Hz and 150 Hz signals shall also vary simultaneously and proportionately.

2.10.3.3.4 90 Hz and 150 Hz Phase Error. The phase error of the 90 Hz and 150 Hz signals shall be as specified in 2.10.2.3.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

2.10.3.3.5 DDM Control. The output ratio of the 90 Hz and 150 Hz signals shall have at least the following presets 0.155±0.020 DDM, for both 90 Hz dominant and 150 Hz predominant ; and 0.000 ± 0.100 DDM. For purposes of determining DDM, the base shall be 0.20 when the function selector is in the LOC (localizer) function.

2.10.3.3.5.1 Variable DDM Control. A control shall be provided to continuously vary the DDM from 0.155 ±0.030 DDM 90 Hz predominant to 0.155 ±0.020 DDM, 150 Hz predominant. This control shall have an off position in which the variable DDM circuitry is not operative.

2.10.3.3.6 90 Hz and 150 Hz Delete. Front panel controls shall be provided to delete the 90 Hz and 150 Hz tones independently.

2.10.3.3.7 ID Tone. The 1020 Hz signal shall amplitude modulate localizer frequencies, either separately or with the LOC modulation present and shall be selectable by a front panel ON/OFF control or function selector.

2.10.3.7.1 1020 Hz Modulation Depth. The depth of modulation of the localizer frequencies by the 1020 Hz signal shall be fixed at a modulation level of 20.0% ± 5.0% with less than 5.0% RF tone distortion.

2.10.4 VHF Omnidirectional Range Generator.

2.10.4.1 VOR Generator Selection. The VOR signal generator shall be selected by means of an ON/OFF control located on the front panel.

2.10.4.2 RF Frequency Range. The VOR signal generator shall provide continuous sine waves over the frequency range from 108.00 to 117.95 MHz ±0.002% with channels separated in increments of 50 KHz. These frequencies, referred to as RF herein, shall be modulated as specified herein.

2.10.4.2.1 RF Frequency Selection. The output frequency shall be selected by means of a front panel control.

2.10.4.2.2 RF Frequency Stability. The variation in frequency of the RF output frequency shall not exceed ±0.002%.

2.10.4.2.3 RF Spectral Purity. At the frequencies specified in 2.10.4.2, the following specifications shall be met:

2.10.4.2.3.1 Harmonics. The level of any harmonic on the desired RF signal shall be at least 30 dB below the output level of the desired fundamental RF signal.

2.10.4.2.3.2 Spurious Signals. The total of all spurious signals, including subharmonics, accompanying the desired RF signal shall be at least 35 dB below the output level of the desired RF signal at ±15 kHz and at least 40 dB below the carrier output level at ±25.0 kHz in a 300 Hz resolution bandwidth, as measured at the RF IN/OUT connector and into a 50 ohm load.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

2.10.4.2.3.3 Broadband Noise. The level of any broadband noise on the desired RF signal shall be at least 90 dB below the carrier output level (measured in a 1 Hz noise bandwidth at more than 15 kHz from the carrier frequency), as measured at the RF IN/OUT connector and into a 50 ohm load.

2.10.4.3 VOR Tones. The VOR carriers shall be amplitude modulated by the following AF tones:

a. 30 Hz sine wave (variable phase).

b. 9960 Hz sine wave (frequency modulated by a 30 Hz reference phase signal).

c. 1020 Hz sine wave.

2.10.4.3.1 Audio Frequency Accuracy. The 30 Hz variable phase, the 30 Hz reference phase, and the 9960 Hz shall be accurate to within ±0.01%. The 1020 Hz signal shall be accurate to within ±2.0%.

2.10.4.3.2 Audio Frequency Spectral Purity. For each of the audio signals specified in 2.10.4.3, the total distortion due to harmonics, noise, and spurious signals shall be less than 5.0% the level of the fundamental audio frequency in a bandwidth of twice the fundamental frequency.

2.10.4.3.2.1 Incidental AM Due to FM. With the 9960 Hz signal frequency modulated with a deviation ratio of 16 ±1 by a 30 Hz signal, the amplitude modulation of the 9960 Hz signal shall not exceed 1.0%.

2.10.4.3.3 9960 Hz FM Subcarrier. The 9960 Hz subcarrier shall be frequency modulated by a 30 Hz fixed reference phase signal, with a peak deviation ±480 ±30 Hz. The 9960 Hz FM signal shall amplitude modulate the RF carriers.

2.10.4.3.4 30 Hz Variable Phase Signal. A second 30 Hz signal shall be provided which is variable in phase with respect to the 30 Hz fixed phase reference signal from 0 degrees to 359.0 degrees in steps less than or equal to 1.0 degree.

2.10.4.3.5 30 Hz Frequency Equality. The 30 Hz reference signal and 30 Hz variable signal shall be coherent.

2.10.4.3.6 Bearing Signal. The 9960 Hz subcarrier (9960 FM signal), which is frequency modulated by the 30 Hz reference signal, and the 30 Hz variable phase signal shall amplitude the RF carriers simultaneously and proportionately.

2.10.4.3.6.1 Modulation Depth. The 9960 Hz FM signal and the 30 Hz variable signal shall each be of sufficient magnitude to amplitude modulate the RF carriers to the depth of preset 30% ± 2.0%.

2.10.4.3.6.2 Bearing Selector. A control shall be provided to vary the bearing from 000.0 to 359.00 degrees in steps less than or equal to 1.0 degree.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

2.10.4.3.6.2.1 Bearing Indicator. The bearing indicator shall have a resolution of 1.0 degrees or better and indicate directly in degrees.

2.10.4.3.6.2.2 Bearing Accuracy. The bearing of the VOR signal on the RF carrier shall be within ±0.33 degrees of the audio bearing as set by a VOR standard (Collins Radio Group Model 478A/2 or equal).

2.10.4.3.6.2.3 Bearing Stability. The VOR bearing shall not vary more than ±1.0 degree under all combinations of environmental conditions.

2.10.4.3.7 30 Hz Variable And 30 Hz Reference Delete. Front panel control shall be provided to delete the 30 Hz variable and 30 Hz reference signals independently and simultaneously.

2.10.4.3.8 ID Tone. The 1020 Hz signal shall amplitude modulate VOR frequencies both separately and with the VOR modulation present. A ON/OFF front panel control shall be provided for this signal.

2.10.4.3.8.1 Modulation. The depth of modulation of the VOR frequencies by the 1020 Hz signal shall be fixed at a modulation level of 20.0% ±5.0% with less than 5% RF distortion.

2.10.5 Physical Characteristics. The size and weight of the signal generator shall be consistent with current commercial practices. The equipment shall be portable with the following physical characteristics.

2.10.5.1 Dimensions. The maximum height of the signal generator shall not exceed eight inches.

2.10.5.2 Weight. The total weight of the equipment, excluding accessories and manuals, shall not exceed a one-person lift of 37 pounds (or 16.8 kilograms).

If the depth of the equipment is greater than 24 inches the maximum allowable weight shall be reduced by 33 percent. If the depth of the equipment is greater than 36 inches the maximum allowable weight shall be reduced by 50 percent. If the depth of the equipment is greater than 48 inches the maximum allowable weight shall be reduced by 66 percent .

2.10.5.3 Equipment Cover. The equipment enclosure shall have a cover.

2.10.6 Manuals. The equipment shall be delivered with operator, maintenance, and illustrated parts manuals. Format and quantity shall be as specified in the contract or order. Level of maintenance philosophy, as defined in MIL-PRF-28800, shall be as specified in the contract or order.

3. REGULATORY REQUIREMENTS

3.1 The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4. PRODUCT CONFORMANCE PROVISIONS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

4.1 Product Conformance. The products provided shall meet the salient characteristics of this CID, conform to the producer's own drawings, specifications, standards and quality assurance practices, and be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

4.2 Metric Products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within the specified tolerances using conversion tables contained in the latest revision of Federal Standard No. 376, and all other requirements of this CID are met. If a product manufactured to metric dimensions exceeds the tolerances specified in the inch/pound units, a request should be made to the contracting officer to determine if the product is acceptable.

4.3 The contracting officer has the option of accepting or rejecting the product.

5. PACKAGING.

5.1 Preservation, Packing, and Marking. Preservation, packing, and marking shall be as specified in the contract or order.

6. NOTES.

6.1 Sources of documents.

6.1.1 Military Specifications, Standards, and Handbooks referenced herein may be obtained from the Standardization Documents Order Desk, 700 Robbins Ave, Bldg 4, Section D, Philadelphia, PA 19111-5094, Phone 215-697-2179.

6.1.2 The Code of Federal Regulations (CFR) may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC, 20402.

6.1.3 International Civil Aviation Organization (ICAO) documents can be obtained from the Document Sales Unit, International Civil Aviation Organization, 999 University Street, Montreal, Quebec, Canada H3C 5H7, Tel.: (514) 954-8219, Fax: (514) 954-6077, Internet: www.icao.org

MILITARY INTEREST

Custodian:
Air Force – 99
DLA-CC
Navy – SH

Preparing activity:
Air Force - 84

Agent:
Air Force - 99

(Project 6625-F082)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.