NOTICE OF
CHANGE

DOD-STD-35-67A(MI)
NOTICE 2
18 SEPTEMBER 1992

MILITARY STANDARD

AUTOMATED ENGINEERING
DOCUMENT PREPARATION SYSTEM

CORD, ELECTRICAL

TO ALL HOLDERS OF DOD-STD-35-67A(MI):

1. THE FOLLOWING PAGES OF DOD-STD-35-67A(MI) HAVE BEEN REVISED AND SUPERSEDE THE PAGES LISTED.

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
v	18 SEPTEMBER 1992	v	15 JUNE 1978
1	15 JUNE 1978	(Reprinted without change)	
2	18 SEPTEMBER 1992	2	15 JUNE 1978
3	18 SEPTEMBER 1992	3	15 JUNE 1978
4	18 SEPTEMBER 1992	4	15 JUNE 1978
39	15 JUNE 1978	(Reprinted without change)	
40	18 SEPTEMBER 1992	40	15 JUNE 1978
41	18 SEPTEMBER 1992	41	15 JUNE 1978
42	18 SEPTEMBER 1992	42	15 JUNE 1978
43	18 SEPTEMBER 1992	43	15 JUNE 1978
44	15 JUNE 1978	(Reprinted without change)	
51	15 JUNE 1978	(Reprinted without change)	
52	18 SEPTEMBER 1992	52	15 JUNE 1978
53	18 SEPTEMBER 1992	53	15 JUNE 1978
54	15 JUNE 1978	(Reprinted without change)	
59	15 JUNE 1978	(Reprinted without change)	
60	18 SEPTEMBER 1992	60	15 JUNE 1978
61	18 SEPTEMBER 1992	61	15 JUNE 1978
62	15 JUNE 1978	(Reprinted without change)	
65	15 JUNE 1978	(Reprinted without change)	
66	18 SEPTEMBER 1992	66	15 JUNE 1978
67	18 SEPTEMBER 1992	67	15 JUNE 1978
68	15 JUNE 1978	(Reprinted without change)	
69	15 JUNE 1978	(Reprinted without change)	
70	18 SEPTEMBER 1992	70	15 JUNE 1978
71	18 SEPTEMBER 1992	71	15 JUNE 1978
72	15 JUNE 1978	(Reprinted without change)	

AMSC N/A AREA EGDS

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:57Z
Check the source to verify that this is the current version before use.

The MSE title may or may not be the same as the title used in DODISS, FIIG, or the base document. In general, the MSE title uses the basic federal item name listed in Cataloging Handbook H6. However, titles with additional modifying and identifying words are provided to assist in defining the scope of the MSE. Also, less restrictive titles are provided to prevent exclusion of items.

TABLE I. TITLE INDEX

MSE TITLE	TITLE CODE	BASE DOCUMENT	
		NUMBER	COVERAGE
CORD, ELECTRICAL	034001	MIL-C-915	CABLE AND CORD, SHIPBOARD
		MIL-C-3849	TINSEL
		MIL-C-3883	SHIELDED AUDIO
		MIL-C-3884	SHORT LAY
		MIL-C-5898	HEADSET AND MICROPHONE EXTENSIONS
		MIL-C-6166	HEADSET AND MICROPHONE
		MIL-C-10392	AUDIO, MINIATURE
		MIL-C-13273	RETRACTILE
		J-C-580	CORD, FLEXIBLE

Source: https://assist.dla.mil -- Downloaded: 202610-23T20:57Z
Check the source to verify that this is the current version before use.

CONTENTS

Paragraph	1.	SCOPE	1
	1.1	General	1
	1.2	Purpose	1
	1.3	Utilization	1
	1.4	Military Specification Exception Title Index	1
	2.	APPLICABLE DOCUMENTS	3
	2.1	Government documents	3
	2.2	Non-Government publications	4
	3.	DEFINITIONS	5
	4.	GENERAL REQUIREMENTS	7
	4.1	Introduction	7
	4.2	Specification Requirement Sheet (SRS)	7
	4.3	Configuration	7
	4.3.1	Dimensions	7
	4.3.2	Illustrations	7
	4.4	Units of measure	7
	5.	DETAILED REQUIREMENTS	9
	5.1	Introduction	9
	5.2	MSE Formats	9
	5.3	Referenced documents	9
	5.4	Tabulation	9
	5.5	Keyword Code Index (KCI) and Standard Paragraphs	11
	5.5.1	Interrelationship of Codes	11
	5.5.2	Automatic MSE Data	11
	5.5.3	DOD-STD-35 Tables	11

TABLES

Table	I.	Title Index	2
	II.	Tabulation candidates	10

APPENDICES

Appendix	A.	Illustrations	85
	B.	Characteristic Code Index	111
		Index	117

Source: https://assist.dla.mil -- Downloaded: 202640-23T20:57Z
Check the source to verify that this is the current version before use.

1. SCOPE

1.1 General. This dash-numbered part of the Automated Engineering Document Preparation System (AEDPS), provides detailed requirements for the preparation of Military Specification Exception (MSE) documentation for electrical cord.

1.2 Purpose. This military standard provides the necessary information to prepare a Specification Requirement Sheet (SRS) which will be used to generate an MSE by automated data processing.

1.3 Utilization. General instructions, quality assurance provisions, packaging, and notes, applicable to all AEDPS dash-numbered parts have been included in the basic document (DOD-STD-35) to avoid redundancy. Unless otherwise specified in this dash-numbered part, the following list contains additional subjects that are applicable to all AEDPS dash-numbered parts and are included in DOD-STD-35:

a. Writing Methodology
b. Document and Part Numbering
c. Applicable Documents
d. Single and Multi-item Specifications (Tabulation)
e. Keyword Code Index (KCI)
f. General Requirements of AEDPS

1.4 Military Specification Exception Title Index. The title code for an MSE shall be selected from one of the MSE titles listed in the Title Index (see table I). Data bases have been established for the generation of MSE's for the MSE titles indicated. If a suitable title code is not contained in the Title Index, leave the title code spaces on the SRS blank, and attach a request for the assignment of a title code. Include in the request the desired title and the base document identifier. A code will be assigned and the code, title, and base document will be made a part of the Title Index.

One of the six-digit codes listed in the Title Index, entered on an SRS, will specify that the title of the MSE will be the title shown in the Title Index.

Each MSE title listed in the Title Index is compatible with the document(s) listed with that title under base document. The list of base documents may or may not be a complete listing. The information shown under coverage is intended for the user's reference; when more than one document is listed for an MSE title, this information will be found useful in determining which of the documents is most suitable for use as the base document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:57Z
Check the source to verify that this is the current version before use.

2. RETAIN THIS NOTICE PAGE AND INSERT BEFORE THE TABLE OF CONTENTS.

3. Holders of DOD-STD-35-67A(MI) will verify that page changes and additions indicated above have been entered. The notice page will be retained as a check sheet. This issuance, together with appended pages is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or canceled.

Custodians:
Army-MI

Review activities:
Army-AT, AV, CR, ER
ME, MR, SC

User activity
Army - AR

Preparing activity:
Army - MI

(Project EGDS-A426)

Source: https://assist.dla.mil -- Downloaded: 202610-23T20:57Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-C-915	Cable and Cord Electrical, for Shipboard Use General Specification for
MIL-C-3849	Cord, Electrical (Tinsel)
MIL-C-3883	Cord, Electrical, Shielded (Audio Frequency)

STANDARDS

MILITARY

DOD-STD-35	Automated Engineering Document Preparation System
MIL-STD-104	Limit for Electrical Insulation Color
MIL-STD-130	Identification Marking of U.S. Military Property
MIL-STD-202	Electronic Component Parts Test Methods
MIL-STD-681	Identification Coding and Application of Hookup and Lead Wire
MIL-STD-810	Environmental Test Methods

FEDERAL

FED-STD-228	Cable and Wire, Insulated; Methods of Testing

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:57Z
Check the source to verify that this is the current version before use.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Bldg 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation.

ASTM B 33	Tinned Soft or Annealed Copper Wire for Electrical Purposes, Specification for
ASTM E 380	Metric Practice Guide

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race St., Philadelphia, PA 19103.)

Source: http://assist.dla.mil -- Downloaded: 202640-23T20:57Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2150	BENDING ENDURANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2150.
2148	BENDING ENDURANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH MIL-C-915.
2152	THE TENSION DURING TEST SHALL BE 2152 POUND(S) PER SQUARE INCH.
2158	THE TENSION DURING TEST SHALL BE 2158 KILOPASCAL(S).
2154	THE SPECIMEN LENGTH SHALL BE 2154 INCH(S).
2160	THE SPECIMEN LENGTH SHALL BE 2160 MILLIMETER(S).
2156	THE TEST TEMPERATURE SHALL BE 2156 DEGREE(S) CELSIUS.
2162	THE BENDING RATE SHALL BE 2162 CYCLES PER MINUTE.
2164	THE VOLTAGE WITHSTAND TEST SHALL BE PERFORMED.
2172	THE TEST VOLTAGE SHALL BE 2172 VOLTS AC.
2173	THE TEST VOLTAGE SHALL BE 2173 VOLTS DC.
2056	BREAKING LOAD. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2056.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:57Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
BREAKING LOAD (CONT)	
REQUIREMENTS (CONT)	
MINIMUM BREAKING LOAD (SELECT ONE)	
(POUNDS)	2048
(KILOGRAMS)	2054
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2050
PER (DOC DES)	2052
CAPACITANCE	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2020
MAXIMUM CAPACITANCE (SELECT ONE)	
(PICOFARADS PER FOOT)	2022
(PICOFARADS PER METER)	2018
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2014
PER MIL-C-3883.	2012
TEST FREQUENCY (HERTZ)	2016

Source: https://assist.dla.mil -- Downloaded: 202640-23T20:57Z
Check the source to verify that this is the currentversion before use.

CHAR CODE	STANDARD PARAGRAPH
2048	BREAKING LOAD. THE BREAKING LOAD SHALL BE NOT LESS THAN 2048 POUND(S).
2054	BREAKING LOAD. THE BREAKING LOAD SHALL BE NOT LESS THAN 2054 KILOGRAM(S).
2050	BREAKING LOAD. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2050.
2052	BREAKING LOAD. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2052.
2020	CAPACITANCE. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2020.
2022	CAPACITANCE. THE CAPACITANCE SHALL BE NOT GREATER THAN 2022 PICOFARAD(S) PER FOOT.
2018	CAPACITANCE. THE CAPACITANCE SHALL BE NOT GREATER THAN 2018 PICOFARAD(S) PER METER.
2014	CAPACITANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2014.
2012	CAPACITANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH MIL-C-3883.
2016	THE TEST FREQUENCY SHALL BE 2016 HERTZ.

Source: https://assist.dla.mil -- Downloaded: 202610-23T20:57Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
COLD BENDING	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2086
NO CRACKS, FLAWS OR DAMAGE.	2088
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2062
PER (DOC DES)	2060
SPECIMEN LENGTH (SELECT ONE)	
(INCHES)	2064
(MILLIMETERS)	2068
DIAMETER OF MANDREL (SELECT ONE)	
(INCHES)	2066
(MILLIMETERS)	2070
COLD CHAMBER TEMPERATURE (DEGREES CELSIUS)	2072
TEST DURATION (HOURS)	2078
NUMBER OF TURNS (NUMBER)	2080
RATE OF TURNS PER SECOND (NUMBER)	2082

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:57Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2086	COLD BENDING. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2086.
2088	COLD BENDING. THE JACKET OR INSULATION OF THE CORD SHALL EXHIBIT NO EVIDENCE OF CRACKS, FLAWS, OR OTHER DAMAGE.
2062	COLD BENDING. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2062.
2060	COLD BENDING. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2060.
2064	THE SPECIMEN LENGTH SHALL BE 2064 INCH(S).
2068	THE SPECIMEN LENGTH SHALL BE 2068 MILLIMETER(S).
2066	THE MANDREL DIAMETER SHALL BE 2066 INCH(S).
2070	THE MANDREL DIAMETER SHALL BE 2070 MILLIMETER(S).
2072	THE COLD CHAMBER TEMPERATURE SHALL BE 2072 DEGREES CELSIUS.
2078	THE TEST DURATION SHALL BE 2078 HOUR(S).
2080	THE NUMBER OF SPECIMEN TURNS AROUND THE MANDREL SHALL BE 2080.
2082	THE RATE SHALL BE 2082 TURNS PER SECOND.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:57Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
CONDUCTOR ELONGATION	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2432
MINIMUM ELONGATION (PERCENT)	2434
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2426
PER FED-STD-228	2427
*METHOD (SELECT ONE)	
3211, SOFT.	2428
3212, HARD.	2429
NUMBER OF SPECIMENS (NUMBER)	2430
CONDUCTOR RESISTANCE	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1946
MAXIMUM CONDUCTOR RESISTANCE (SELECT ONE)	
(OHMS PER 1000 FEET)	1948

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:57Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2446	CONDUCTOR TENSILE STRENGTH. THE TENSILE STRENGTH SHALL BE NOT LESS THAN 2446 POUND(S) PER SQUARE INCH.
2442	CONDUCTOR TENSILE STRENGTH. THE TENSILE STRENGTH SHALL BE NOT LESS THAN 2442 KILOPASCAL(S).
2438	CONDUCTOR TENSILE STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2438.
2439	CONDUCTOR TENSILE STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH FED-STD-228.
2440	TEST METHOD 3211 SHALL APPLY.
2441	TEST METHOD 3212 SHALL APPLY.
2436	THE NUMBER OF SPECIMENS SHALL BE 2436.
1934	CONTINUITY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1934.
1936	CONTINUITY. THERE SHALL BE NO OPEN CIRCUITS.

Source: https://assist.dla.mil -- Downloaded: 202610-23T20:57Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
CONTINUITY (CONT)	
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1926
PER (DOC DES)	1928
CORD RETRACTILITY	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2366
MAXIMUM RETRACTION (PERCENT OF ORIGINAL LENGTH)	2368
RETRACTION DURATION (SECONDS)	2370
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2358
PER (DOC DES)	2364
EXTENSION (TIMES RETRACTED LENGTH)	2360
CYCLES (NUMBER)	2362

Source: https://assist.dla.mil -- Downloaded: 202610-23T20:57Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1926	CONTINUITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1926.
1928	CONTINUITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 1928.
2366	CORD RETRACTILITY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2366.
2368	CORD RETRACTILITY. THE RETRACTED LENGTH SHALL BE NOT GREATER THAN 2368 PERCENT OF THE ORIGINAL LENGTH.
2370	THE RETRACTION DURATION SHALL BE 2370 SECOND(S).
2358	CORD RETRACTILITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2358.
2364	CORD RETRACTILITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2364.
2360	THE EXTENSION SHALL BE 2360 TIMES THE RETRACTED LENGTH.
2362	THE NUMBER OF EXTENSION CYCLES SHALL BE 2362.

Source: https://assist.dla.mil -- Downloaded: 202610-23T20:57Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
FLAMMABILITY	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2206
AS FOLLOWS:	2207
FLAME DISTANCE (SELECT ONE)	
(INCHES)	2208
(MILLIMETERS)	2204
MAXIMUM FLAME DURATION (SECONDS)	2210
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2198
PER FED-STD-228	2199
*METHOD (SELECT ONE)	
5211.	2200
5221.	2201
5231.	2203
HEATING DURATION (SECONDS)	2202

Source: https://assist.dla.mil -- Downloaded: 202610-23T20:57Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
4760	FUNGUS. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 4760.
4761	FUNGUS. ALL EXTERNAL MATERIALS SHALL BE NONNUTRIENT TO FUNGUS GROWTH OR SHALL BE SUITABLY TREATED TO RETARD FUNGUS GROWTH. THE MANUFACTURER SHALL VERIFY BY CERTIFICATION THAT ALL EXTERNAL MATERIALS ARE FUNGUS RESISTANT OR SHALL PERFORM THE FUNGUS TEST. WHEN THE FUNGUS TEST IS PERFORMED, THERE SHALL BE NO EVIDENCE OF FUNGUS GROWTH ON THE EXTERNAL SURFACES.
4762	FUNGUS. ALL EXTERNAL MATERIALS SHALL BE NONNUTRIENT TO FUNGUS GROWTH OR SHALL BE SUITABLY TREATED TO RETARD FUNGUS GROWTH. THERE SHALL BE NO EVIDENCE OF FUNGUS GROWTH ON THE EXTERNAL SURFACES.
4754	FUNGUS. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 4754.
4755	FUNGUS. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 508 OF MIL-STD-810.
4756	TEST PERIOD SHALL BE 4756 DAY(S).
2320	HIGH TEMPERATURE RETRACTION. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2320.
2322	HIGH TEMPERATURE RETRACTION. THE RETRACTED LENGTH SHALL BE NOT GREATER THAN 2322 PERCENT OF THE ORIGINAL LENGTH.
2324	THE RETRACTION DURATION SHALL BE 2324 SECOND(S).

Source: https://assist.dla.mil -- Downloaded: 202640-23T20:57Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
HIGH TEMPERATURE RETRACTION (CONT)	
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2306
PER (DOC DES)	2312
EXTENSION (TIMES RETRACTED LENGTH)	2308
CONDITIONING TEMPERATURE (DEGREES CELSIUS)	2310
CONDITIONING DURATION (HOURS)	2316
CYLES (NUMBER)	2314
INSULATION ELONGATION	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2122
ELONGATION (PERCENT)	2124
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2114
PER FED-STD-228, METHOD 3031 .	2661
NUMBER OF SPECIMENS (NUMBER)	2118

Source: https://assist.dla.mil/ Downloaded: 2026-10-23T20:57Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2306	HIGH TEMPERATURE RETRACTION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2306.
2312	HIGH TEMPERATURE RETRACTION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2312.
2308	THE EXTENSION SHALL BE 2308 TIMES THE RETRACTED LENGTH.
2310	THE CONDITIONING TEMPERATURE SHALL BE 2310 DEGREES CELSIUS.
2316	THE CONDITIONING DURATION SHALL BE 2316 HOUR(S).
2314	THE NUMBER OF EXTENSION CYCLES SHALL BE 2314.
2122	INSULATION ELONGATION. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2122.
2124	INSULATION ELONGATION. THE ELONGATION SHALL BE NOT LESS THAN 2124 PERCENT OF THE ORIGINAL LENGTH.
2114	INSULATION ELONGATION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2114.
2116	INSULATION ELONGATION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 3031 OF FED-STD-228.
2118	THE NUMBER OF SPECIMENS SHALL BE 2118.

Source: https://assist.dla.mil -- Downloaded: 202640-23T20:57Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
INSULATION RESISTANCE	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1960
MINIMUM INSULATION RESISTANCE (SELECT ONE)	
(MEGOHMS PER 1000 FEET)	1962
(MEGOHMS PER KILOMETER)	1958
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1952
PER FED-STD-228, METHOD 6031.	1951
TEST VOLTAGE (VOLTS DC)	1954
TEST TEMPERATURE (DEGREES CELSIUS)	1955
IMMERSION SOLUTION (TYPE)	1956
IMMERSION PERIOD (HOURS)	1950
MEASURED AFTER CIRCUIT CLOSED (MINUTES)	1957
INSULATION TENSILE STRENGTH	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2142

Source: https://assist.dla.mil -- Downloaded: 202610-23T20:57Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2144	INSULATION TENSILE STRENGTH. THE TENSILE STRENGTH SHALL BE NOT LESS THAN 2144 POUND(S) PER SQUARE INCH.
2140	INSULATION TENSILE STRENGTH. THE TENSILE STRENGTH SHALL BE NOT LESS THAN 2140 KILOPASCAL(S).
2134	INSULATION TENSILE STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2134.
2136	INSULATION TENSILE STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 3111 OF FED-STD-228.
2138	THE NUMBER OF SPECIMENS SHALL BE 2138.
2278	LOW TEMPERATURE EXTENSION AND RETRACTION. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2278.
2282	LOW TEMPERATURE EXTENSION AND RETRACTION. THE REQUIREMENT(S) SHALL BE AS FOLLOWS.
2280	THERE SHALL BE NO PHYSICAL DAMAGE OR DEGRADATION.

Source: https://assist.dla.mil -- Downloaded: 202610-23T20:57Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
LOW TEMPERATURE EXTENSION AND RETRACTION (CONT)	
AS FOLLOWS: (CONT)	
EXTENSION FORCE (SELECT ONE)	
(OUNCES)	2270
(NEWTONS)	2276
MAXIMUM RETRACTION (PERCENT OF ORIGINAL LENGTH)	2281
RETRACTION DURATION (SECONDS)	2284
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2272
PER (DOC DES)	2274
TEST TEMPERATURE (DEGREES CELSIUS)	2275
EXTENSION (TIMES RETRACTED LENGTH)	2286
MOISTURE RESISTANCE	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1400
NO EVIDENCE OF CORROSION OR PHYSICAL DAMAGE.	1396
NO DIELECTRIC OR INSULATION BREAKDOWN.	2488
REQUIREMENTS AFTER TEST SHALL BE ____	2490

Source: http://assist.dla.mil -- Downloaded: 202640-23T20:57Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2270	THE EXTENSION FORCE SHALL BE 2270 OUNCE(S).
2276	THE EXTENSION FORCE SHALL BE 2276 NEWTON(S).
2281	THE RETRACTED LENGTH SHALL BE NOT GREATER THAN 2281 PERCENT OF THE ORIGINAL LENGTH.
2284	THE RETRACTION DURATION SHALL BE 2284 SECOND(S).
2272	LOW TEMPERATURE EXTENSION AND RETRACTION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2272.
2274	LOW TEMPERATURE EXTENSION AND RETRACTION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2274.
2275	THE TEST TEMPERATURE SHALL BE 2275 DEGREES CELSIUS.
2286	THE EXTENSION SHALL BE 2286 TIMES THE RETRACTED LENGTH.
1400	MOISTURE RESISTANCE. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1400.
1396	MOISTURE RESISTANCE. THERE SHALL BE NO EVIDENCE OF CORROSION OR PHYSICAL DAMAGE.
2488	THERE SHALL BE NO DIELECTRIC OR INSULATION BREAKDOWN.
2490	THE REQUIREMENT(S) AFTER THE TEST SHALL BE 2490.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:57Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
MOISTURE RESISTANCE (CONT)	
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1391
PER MIL-STD-202, METHOD 106.	1397
POLARIZING VOLTAGE (VOLTS, DC)	1395
INITIAL MEASUREMENTS SHALL BE ____	2484
LOADING VOLTAGE (VOLTS)	2487
FINAL MEASUREMENTS SHALL BE ____	2486
STEP 7A NOT APPLICABLE.	4985
STEP 7B NOT APPLICABLE.	4986
MUTUAL INDUCTANCE	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1992
MAXIMUM INDUCTANCE (SELECT ONE)	
(MICROHENRIES PER FOOT)	1994
(MICROHENRIES PER METER)	1996

Source: https://assist.dla.mil -- Downloaded: 202610-23T20:57Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1391	MOISTURE RESISTANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1391.
1397	MOISTURE RESISTANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 106 OF MIL-STD-202.
1395	POLARIZING VOLTAGE SHALL BE 1395 VOLTS, DC.
2484	THE INITIAL MEASUREMENTS SHALL BE 2484.
2487	THE LOADING VOLTAGE SHALL BE 2487 VOLT(S).
2486	THE FINAL MEASUREMENTS SHALL BE 2486.
4985	STEP 7A OF METHOD 106 OF MIL-STD-202 IS NOT APPLICABLE.
4986	STEP 7B OF METHOD 106 OF MIL-STD-202 IS NOT APPLICABLE.
1992	MUTUAL INDUCTANCE. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1992.
1994	MUTUAL INDUCTANCE. THE MUTUAL INDUCTANCE SHALL BE NOT GREATER THAN 1994 MICROHENRY(S) PER FOOT.
1996	MUTUAL INDUCTANCE. THE MUTUAL INDUCTANCE SHALL BE NOT GREATER THAN 1996 MICROHENRY(S) PER METER.

Source: https://assist.dla.mil -- Downloaded: 202610-23T20:57Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
MUTUAL INDUCTANCE (CONT)	
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1982
PER MIL-C-915.	1986
FREQUENCY (HERTZ)	1988
RETRACTION AFTER STATIC LOADING	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2336
MAXIMUM RETRACTION (PERCENT OF ORIGINAL LENGTH)	2338
RETRACTION DURATION (MINUTES)	2340
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2328
PER (DOC DES)	2334
EXTENSION (PERCENT)	2330
EXTENSION PERIOD (HOURS)	2332

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:57Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1982	MUTUAL INDUCTANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1982.
1986	MUTUAL INDUCTANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH MIL-C-915.
1988	THE TEST FREQUENCY SHALL BE 1988 HERTZ.
2336	RETRACTION AFTER STATIC LOADING. THE REQUIREMENTS SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2336.
2338	RETRACTION AFTER STATIC LOADING. THE RETRACTED LENGTH SHALL BE NOT GREATER THAN 2338 PERCENT OF THE ORIGINAL LENGTH.
2340	THE RETRACTION DURATION SHALL BE 2340 MINUTE(S).
2328	RETRACTION AFTER STATIC LOADING. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2328.
2334	RETRACTION AFTER STATIC LOADING. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2334.
2330	THE EXTENSION SHALL BE 2330 PERCENT OF THE ORIGINAL LENGTH.
2332	THE EXTENSION PERIOD SHALL BE 2332 HOUR(S).

Source: https://assist.dla.mil -- Downloaded: 202610-23T20:57Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
SEA WATER RESISTANCE	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2108
MAXIMUM WEIGHT CHANGE (SELECT ONE)	
(MILLIGRAMS PER SQUARE INCH OF WETTED SURFACE)	2110
(MILLIGRAMS PER SQUARE MILLIMETER OF WETTED SURFACE)	2090
NO EVIDENCE OF CHEMICAL REACTION OR OTHER DELETERIOUS EFFECTS.	2091
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2092
PER MIL-C-3849.	2102
SPECIMEN LENGTH (SELECT ONE)	
(FEET)	2094
(METERS)	2104

Source: https://assist.dla.mil -- Downloaded: 202610-23T20:57Z
Check the source to verify that this is the current version before use.