MIL-C-52074C
30 March 1981
SUPERSEDING
MIL-C-52074B
22 December 1971

MILITARY SPECIFICATION

CLEANERS, VACUUM

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers two types of industrial vacuums cleaners (see 6.1).

1.2 Classification. The vacuum cleaners shall be of the following types as specified (see 6.2).

Type I - 120 volt, AC, 50 to 400-hertz with 120 volt AC power source (without casters)

Type II - 120 volt, AC, 60 hertz with 115 volt DC power source (with casters)

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATION

FEDERAL

CC-M-1807 - Motor, Alternating Current, Fractional and Integral Horsepower (500 Horsepower and Smaller)

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Natick Research and Development Laboratories, Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:06Z
Check the source to verify that this is the current version before use.

PPP-B-601 - Boxes, Wood, Cleated-Plywood
PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner
PPP-B-636 - Boxes, Shipping, Fiberboard

MILITARY

MIL-P-116 - Preservation-Packaging, Methods of
MIL-L-10547 - Liners, Case and Sheet, Overwrap; Water-Vaporproof or Waterproof, Flexible

STANDARDS

FEDERAL

FED-STD-595 - Colors

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-130 - Identification Marking of US Military Property
MIL-STD-461 - Electromagnetic Interference Characteristics, Requirements for Equipment
MIL-STD-462 - Electromagnetic Interference Characteristics, Measurement of
MIL-STD-1186 - Cushioning, Anchoring, Bracing, Blocking, and Waterproofing, with Appropriate Test Methods
MIL-STD-1188 - Commercial Packaging of Supplies and Equipment
MIL-STD-1474 - Noise Limits for Army Material
MIL-STD-1653 - Power Cable Assemblies

(Copies of specifications, standards, and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply:

UNDERWRITERS LABORATORIES INC. (UL)

UL 73 - Motor-Operated Appliances

(Application for copies should be addressed to the Underwriters Laboratories, Inc., 333 Pfingsten Road, Northbrook, IL 60062.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:06Z
Check the source to verify that this is the current version before use.

NATIONAL ELECTRICAL MANUFACTURER'S ASSOCIATION (NEMA)

ICS - Industrial Controls and Systems

(Application for copies should be addressed to the National Electrical Manufacturers' Association, 155 East 44th Street, New York, NY 10017.)

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)

NFPA No. 70 - National Electrical Code

(Application for copies should be addressed to the National Fire Protection Association, Batterymarch Park, Quincy, MA 02169.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Standard product. The cleaners furnished shall be the manufacturer's current standard product, except for changes necessary to comply with the requirements of this specification.

3.2 Codes and standards.

3.2.1 Compliance. The vacuum cleaner shall comply with the following:

(1) The electrical materials and components shall conform to standards of the Underwriters Laboratories, Inc., as applicable.

(2) The electrical control components shall conform to the National Electrical Manufacturer's Association Standards Publications for Industrial Controls and Systems ICS.

(3) The installation of the electrical components shall conform to the applicable requirements of the National Electrical Code No. 70.

3.2.2 Certification. Prior to approval of the first shipment, the contractor shall submit satisfactory evidence to the contracting officer or his authorized representative that the vacuum cleaner he proposes to furnish meets the requirements specified in 3.2.1.

3.2.2.1 NFPA and NEMA. Acceptable evidence of meeting the requirements of NFPA No. 70 and NEMA ICS shall be the manufacturer's certified statement that the vacuum cleaner conforms to the applicable requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:06Z
Check the source to verify that this is the current version before use.

3.2.2.2 UL. Acceptable evidence of meeting the requirements of Underwriters Laboratories Inc., shall be the UL Listing Mark or a certified test report from a recognized independent testing laboratory, acceptable to the Government, indicating that the electrical materials and components offered have been tested and conform to applicable UL standards.

3.3 Materials and components. Materials and components shall be as specified herein. Materials and components not definitely specified shall be of the quality normally used by the manufacturer provided the completed items comply with all the provisions of this specification (see 6.3).

3.4 Design and construction. The cleaners shall be the upright tank type capable of being operated as either blower or vacuum cleaners for wet or dry pickup. A cleaner shall consist of a cover containing the operation hand, a receptacle can and filter assembly. Unless otherwise specified (see 6.2), an air hose and attachments as specified in 3.4.9 and 3.4.10 shall be furnished with each cleaner. The cleaner shall operate as a vacuum cleaner when the hose is connected to the air inlet and as a blower cleaner when the hose is connected to the outlet.

3.4.1 Type I cleaner. The type I cleaner diameter shall be not greater than 14 inches excluding clamps and 23 inches in overall height. The weight of the cleaner, less hose and attachments, shall be not greater than 30 pounds. The cleaner shall have an automatic cutoff switch to insure against overfilling during wet pickup.

3.4.2 Type II cleaner. The type II cleaner diameter shall be not greater than 20 inches in diameter excluding clamps and hose adapter and 36 inches in overall height. The weight of the cleaner, less hose and attachments, shall be not greater than 55 pounds. The cleaner shall have an automatic cutoff switch to insure against overfilling during wet pickup. The cleaner shall be mounted on not less than three rubber tired swivel casters and the diameter shall not be less than 2 inches. Two of the casters shall be furnished with foot operated brakes.

3.4.3 Receptacle can. The receptacle can shall be cylinderical in shape. The cleaners shall have three locking clamps of chromium or zinc plated steel to provide an air tight attachment of the cover to the receptacle can. The filter assembly shall be mounted in the can. The air inlet hose adapter shall be attached to the receptacle can and shall be 1-1/2 inches inside diameter, chromium plated steel designed to engage a swivel type hose coupling.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:06Z
Check the source to verify that this is the current version before use.

3.4.4 Operating head. The operating head shall be contained within the cover and shall consist of a motor, a blower fan, an air exhaust chamber and an outlet with a hose adapter. The blower fan shall be dynamically balanced as to revolve smoothly during operation, with no audible thumping vibrations when tested as specified in 4.3.1. The hose adapter in the air outlet shall be nominal 1-1/2 inch inside diameter chromium plated steel. The hose adapter shall be capable of engaging a hose with a swivel type connector. The air outlet shall have a metal screen for the protection of the blower fan. The cover shall have a handle for lifting the cleaner.

3.4.5 Filter assembly. Each vacuum cleaner shall be provided with a filter assembly consisting of a replaceable filter bag mounted on a metal frame. The bag shall be made of heavy felt and cambric or moleskin or equivalent, for screening the dust and dirt and permitting desired air flow specified in 3.5. The filtered air shall bypass the motor and shall exhaust through the air outlet.

3.4.6 Motor. The motor for the type I cleaner shall be designed for operation on 120 volt, 50 to 400 hertz, AC power. The motor for the type II cleaner shall conform to universal type, AC/DC, fungus and moisture resistant, type I, class 2, style C, continuous duty of CC-M-1807. The power input shall not exceed 1000 watts for the type I cleaner and 1400 watts for the type II cleaner when tested as specified in 4.3.2. The motor shall be cooled by a separate fan-forced system. Electrical insulation of the motor shall not fail when tested in accordance with the dialectric test of UL-73.

3.4.7 Switch. The switch shall have two positions, ON and OFF, shall be of the double pole, single-throw type to break both the line in OFF position an shall have ample capacity for the intended use. The switch shall be mounted on the operating head.

3.4.8 Power cord. The power cord shall conform to the following requirements as specified (see 6.2).

3.4.8.1 Fifteen foot length. The power cord for types I and II cleaners shall be a 3 wire conductor (including ground) NEMA type, SJO or SJJ, No. 16 AWG. The cord length shall not be less than 15 feet and equipped with an approved three prong ground and attachment plug. A cord strain relief device shall be provided at point of entry of the cord into both the plug and unit. Provisions shall be made on the cleaner for conveniently storing the power cord.

3.4.8.2 Eight foot length. The power cord for types I and II cleaners shall conform to the requirements for power cable (permanently attached) 400 hertz, single phase, 115 volt and 60 hertz, single phase, 115 volts respectively as specified in MIL-STD-1653.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:06Z
Check the source to verify that this is the current version before use.

3.4.9 Hose and couplings. The hose length shall not be less than 8 feet and with a nominal 1-1/2 inches inside diameter flexible plastic hose reinforced with spirally coiled wire so that a weight of 150 pounds will not cause a rupture or deformation when tested as specified in 4.3.3 A nominal 1-1/2 inch inside diameter swivel coupling shall be provided on one end for attaching the hose to the cleaner. The other end shall have a fitting 1-1/2 inch nominal inside diameter to accommodate the attachments specified in 3.4.10.

3.4.10 Hose attachments. The hose attachments shall consist of the following:

1 - Flat crevice nozzle, 2 inch by 1/4 inch opening, mitred end.

1 - Round brush, nominal 3-1/2 inches in diameter with nominal 3-1/2 inches in length of nylon filament.

1 - Floor brush, 8-5/8 inches ± 1/2 inch long.

1 - Tapered nozzle, and adaptor, 8 inches ± 1/2 inch long for 1-1/2 inch hose.

1 - Switchboard brush, nominal 2 inches by 4 inches overall with brush bristles not less than 3/4 inch long.

1 - Straight tube with swivel coupling, 26 inches ± 1 inch long.

With the exception of the floor brush, all hose attachments shall be made of electrically nonconducting, fire and impact resistant, high strength, reinforced material in accordance with manufacturer's standard commercial practice. The hose and attachment fittings shall not separate under a tensile force of 25 pounds when tested as specified in 4.3.4.

3.5 Performance. The cleaner shall be capable of maintaining the following minimum vacuum values through the hose when tested as specified in 4.3.1.

TABLE I. Vacuum values

Vacuum-inches water		Orifices-inches diameter
Type I	Type II	
35	40	9/16
24	30	3/4
11	18	1
3	5-1/2	1-1/2 (wide open)

The noise level generated by the cleaner at normal operator ear positions shall be as low as practical but in no case shall exceed the limits of MIL-STD-1474, Category D (less than 85dBA).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:06Z
Check the source to verify that this is the current version before use.

3.6 Electromagnetic compatibility. When specified (see 6.2 and 6.4), the cleaner shall be designed and equipped for electromagnetic compatibility of Group I, class C3 of MIL-STD-461 and tested as specified in 4.3.6.

3.7 Contract data requirement. The contract data requirements shall be as specified (see 6.2 and 6.2.1).

3.8 Marking.

3.8.1 Identification. The vacuum cleaner shall be marked for identification in accordance with MIL-STD-130.

3.8.2 Warning. A warning plate shall be attached to the cleaner with the following:

(a) For TYPE I - WARNING-USE WITH 120 VOLT, 50 TO 400-HERTZ AC.

(b) For TYPE II - WARNING USE WITH 120 VOLT, 60-HERTZ AC OR 115 VOLT, DC ONLY.

3.9 Finish. All external surfaces of the cleaners shall have a baked enamel finish in accordance with the manufacturer's standard commercial practice. The color shall conform to Number 16187 of FED-STD-595. The inside of receptable cans constructed of carbon steel shall be baked epoxy enamel in accordance with manufacturer's standard commercial practice.

3.10 Acoustical noise limit. The noise level generated by the cleaner at normal operator ear positions shall be as low as practical but in no case shall exceed the limits of MIL-STD-1474, category D (less than 85dBA) (see 4.3.5).

3.11 Workmanship. The units shall be free from defects, such as fractures, splits, punctures, tears, dents, creases, deterioration or malformation. There shall be no sharp edges, slivers, burrs or projections. The finish shall be free of blisters, peel, chipped areas or areas of no film. The finish shall be free from smudges, poor touch-up, scale, scratches, stain, overspray, sag, imprint or embedded foreign matter. Threaded fasteners shall not be broken, stripped, fractured or loose. Rivets shall completely fill the holes, with full size heads neatly finished and in full contact with the surface of the riveted members and shall not be loose. Wiring shall not be cut, abraded or have insulation stripped, and shall be joined at the terminals. Wiring shall have adequate slack to provide strain relief.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:06Z
Check the source to verify that this is the current version before use.

4.2 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.2.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.2.2 End item inspection. The inspection lot shall be all vacuum cleaners of one type offered for inspection at one time. The sample unit shall be one complete vacuum cleaner.

4.2.2.1 Visual examination. Examination shall be made of the end item for defects listed in table II. The inspection level shall be level II and the acceptable quality level (AQL) shall be 2.5 major and 6.5 total (major and minor combined) defects per hundred units.

TABLE II. Visual defects

Examine	Defect	Classification Major	Minor
Finish	Color and finish not as specified		X
	Blistered, peeled, chipped, or area of no film		X
	Poor touch-up, scale, scratched, stained, overspray, sag, imprint, or foreign matter embedded		X
Design and construction and workmanship, general (applicable to all components and assemblies)	Any component or part missing or not specified type or size	X	
	Fractured, split, punctured, torn, dented, creased, deteriorated, or malformed (unless otherwise classified herein)	X	
	Not upright tank type	X	
	Receptacle can not cylindrical shape	X	
	Locking clamps do not provide tight fit	X	
	Filter not replaceable bag type	X	
	Filtered air does not bypass motor	X	
	Motor not cooled by a separate fan	X	
	Switch not two position or double pole single throw	X	
	Handle not securely attached	X	
	Component loose	X	
	Sharp burr, edge, or sliver	X	
	Any functioning component that is inoperative or will not operate as intended	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:06Z
Check the source to verify that this is the current version before use.

TABLE II. Visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Bolts, nuts, screws, studs, and other types of threaded fasteners	Broken, stripped, fractured, or not tight		X
Rivets	Broken, not peened or insufficiently peened, or loose		X
Electrical	Wiring cut, abraded, or not properly installed or joined	X	
	Adequate slack not provided for wiring to relieve strain	X	
Marking for identification and warning	Missing, incomplete, or not legible	X	

4.2.2.2 Dimensional and weight examination. Examination shall be made of the end item for compliance with dimensions and weight specified. Any deviation from specified requirements shall constitute a defect. The inspection level shall be S-2 and the AQL shall be 4.0 defects per hundred units.

4.2.2.3 End item testing. The end item shall be tested as specified in 4.3.1 through 4.3.4. The inspection level shall be S-2 and the AQL shall be 2.5 defects per hundred units. One end item shall be selected at random from the contract quantity and tested as specified in 4.3.5 and when electromagnetic compatibility is required one end item shall be selected at random and tested as specified in 4.3.6. Failure to pass either test shall be cause for rejection.

4.2.3 Code and standards compliance. Proof of compliance with the requirements of 3.2.1 and 3.2.2 shall be submitted to the Government representative.

4.2.4 Packaging inspection. An examination shall be made to determine that preservation, packing, and marking comply with section 5. Defects shall be scored as specified in table III. The lot shall be the number of shipping containers offered for inspection at one time. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL shall be 4.0 defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:06Z
Check the source to verify that this is the current version before use.

TABLE III. Packaging defects

Examine	Defect
Preservation	Missing or not performed as specified.
Markings (exterior and interior)	Missing; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Any component missing, damaged, or not as specified.
Weight	More than specified.

4.3 Methods of inspecion.

4.3.1 Performance tests. The type I cleaner shall be connected to a 120 volt, 50 to 400-hertz power source and tested by one continuous run (after temperatures have stabilized) at normal full load operating condition for wet and dry pickup. The type II cleaner shall be operated continuously until all temperatures are stabilized when connected to a 120 volt, 60-hertz AC source and also when connected to a 115 volt DC source. The degree of vacuum of type I or II cleaners, as applicable, shall be determined during the above run by connecting one end of the specified hose to the air inlet and the attachment end to a static pressure chamber containing orifices of 9/16, 3/4, 1 inch and 1-1/2 inches (wide open) and a manometer. The difference in water level in the two columns of the manometer shall be not less than the vacuum values specified in 3.5. The cleaner during this test shall be also examined for compliance with the vibration requirements in 3.4.4. The power input shall be as specified in 3.4.6. Any noncompliance with vibration or vacuum requirements of 3.4.4 and 3.5, as applicable, shall constitute a defect.

4.3.2 Power input test. The power input shall be measured after a constant motor temperature is reached during the test run specified in 4.3.1. Failure to conform to the power input requirements in 3.4.6 shall be considered as a defect.

4.3.3 Hose test. A compressive load of 150 pounds shall be applied to any portion of the hose, by means of force surfaces having a length of 3 inches and an area of 1 inch parallel to the axis of the hose, for not less than 2 minutes. The hose shall be examined to determine compliance with 3.4.9. Rupture or deformation of the hose shall constitute a defect.

4.3.4 Attachment test. A tensile force of 25 pounds shall be applied to the engaged cleaner hose and each attachment for not less than 2 minutes to determine compliance with 3.4.10. Separation of hose and attachments shall constitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:06Z
Check the source to verify that this is the current version before use.

4.3.5 Acoustical noise test. The procedures and instrumentation used in the noise tests shall be in accordance with MIL-STD-1474 (Section on steady-state noise, personnel occupied areas). The microphone shall be located so as to simulate the head position of a seated operator cleaning or drying electronic equipment. The microphone shall be simultaneously 18 inches from the nozzle and 36 inches from the center of the operating head of the cleaner. A measurement shall be made for each nozzle and for each normal operating mode (cleaning/drying) and any noise level or levels measured at this location that exceeds the limits of MIL-STD-1474, Category D shall constitute failure of this test.

4.3.6 Electromagnetic compatability test. When electromagnetic compatability is required, one item shall be tested by the contractor in accordance with Part 10, Method UMO-5 of MIL-STD-462. The Government reserves the right to witness tests performed by the contractor or an independent testing agency. The contractor shall furnish the contracting officer written certification that the EMI test plan, the electromagnetic test report and the end item meet MIL-STD-461 (see 3.6).

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Disassembly and lubrication. The casters shall be detached from the type II vacuum cleaner, and shall be lubricated to capacity with the manufacturer's recommended lubricant containing a rust-inhibitor.

5.1.1.2 Unit packing. The casters for type II vacuum cleaner shall be completely wrapped in kraft paper having a minimum basis weight of 60-pound and the wrap secured with tape. The hose with attached couplings and hose attachments for the type I or II vacuum cleaners shall be protected in accordance with method III of MIL-P-116. The power cord shall be stored in a convenient place provided for on each vacuum cleaner.

5.1.1.3 Intermediate packing. The hose with couplings, hose attachments and casters when required for each identical type vacuum cleaner, unit packed as specified in 5.1.1.2, shall be packed in a snug-fitting intermediate fiberboard box conforming to style RSC, type CF, variety SW, or type SF, class domestic, grade 200 of PPP-B-636. Closure shall be in accordance with the appendix of the box specification.

5.1.2 Commercial. Each complete vacuum cleaner shall be preserved in accordance with MIL-STD-1188.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:06Z
Check the source to verify that this is the current version before use.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

5.2.1 Level A packing. One or more complete vacuum cleaners of identical type, preserved and unit packed as specified in 5.1, shall be packed in a snug-fitting shipping container conforming to style RSC, grade V2s of PPP-B-636, or overseas type of PPP-B-601, or class 2, style 2 or 4 of PPP-B-621. The intermediate packed box as specified in 5.1.1.3, shall be placed in an unused portion of the shipping container. Contents of each shipping container shall be cushioned, blocked, and braced in accordance with MIL-STD-1186. Each fiberboard shipping container shall be waterproofed by means of tape in accordance with the appendix of the container specification. Cleated plywood or nailed wood containers shall be provided with a type I or II, grade C case liner conforming to MIL-L-10547. Each shipping container shall be closed and reinforced with strapping or tape banding in accordance with the appendix of the applicable container specification. The weight of contents for fiberboard shipping containers shall not exceed 65 pounds; cleated plywood and nailed wood shipping containers shall not exceed 150 pounds.

5.2.2 Level B packing. One or more complete vacuum cleaners of identical type, preserved as specified in 5.1, shall be packed in a snug-fitting shipping container conforming to style RSC, type CF, variety SW, or type SF, class domestic, grade 275 of PPP-B-636, or domestic type, style A or B of PPP-B-601, or class 1, style 2 or 4 of PPP-B-621. The intermediate packed box as specified in 5.1.1.3, shall be placed in an unused portion of the shipping container. Contents of each shipping container shall be cushioned, blocked and braced in accordance with MIL-STD-1186. Closure of the fiberboard shipping container shall be in accordance with method II of the appendix of the container specification. The weight of contents for fiberboard shipping containers shall not exceed 65 pounds; cleated plywood and nailed wood shipping containers shall not exceed 150 pounds.

5.2.2.1 Weather-resistant containers. When specified (see 6.2), the fiberboard shipping container shall be a grade V3c, V3s or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with the appendix of PPP-B-636.

5.2.3 Commercial packing. Complete vacuum cleaners, preserved as specified in 5.1, shall be packed in accordance with MIL-STD-1188.

5.3 Marking. In addition to any special marking required by the contract, unit packs, intermediate packs and shipping containers shall be marked in accordance with MIL-STD-129 or MIL-STD-1188, as applicable.

6. NOTES

6.1 Intended use. The type I vacuum cleaner is intended for cleaning and drying electronic equipment, where the only power source is 120 volt, 50 to 400-hertz alternating current. The type II cleaner is intended for cleaning and drying equipment where the power source may be either 120 volt, 60-hertz AC or 115 volt DC.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:06Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Type vacuum cleaner required (see 1.2).
(c) When no attachments are required (see 3.4).
(d) Selection of the power cord (see 3.4.8).
(e) When electromagnetic compatibility is required (see 3.6).
(f) Contract data requirements (see 3.7).
(g) Selection of applicable levels of preservation and packing (see 5.1 and 5.2).
(h) Whether weather-resistant grade fiberboard is required (see 5.2.2).

6.2.1 Contract data requirements. Any data item to be delivered under any contract for items covered by this specification should be specifically called for in the contract in accordance with the applicable regulation of the procuring activity (see 3.7 and 6.2).

6.3 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the specification (see 3.3).

6.4 Critical or non-critical areas.

6.4.1 Critical area. A location on a platform or installation containing equipments or subsystems which, if malfunctioning due to unwanted electromagnetic energy, could degrade the overall system performance and result in the failure or abortion of a primary mission. All locations on a submarine and surface ship are considered critical areas.

6.4.2 Non-critical area. A location in a ground installation where EMI will not result in failure or abortion of a mission or degradation of the overall system performance. Examples of areas which may be considered non-critical are: Office buildings, recreational areas, laundry areas, food servicing areas, drafting rooms and woodworking shops.

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodians:

Army - GL
Navy - YD

Review activity:

Army - MD

User activities:

Army - CE
Navy - MC
Air Force - 99

Preparing activity:

Army - GL

Project No. 7910-0062

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:06Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to *preparing activity*. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: *This form shall not* be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-C-52074C Cleaners, Vacuum

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:06Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
ENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and Development Command
ATTN: DRDNA-ES
Natick, MA 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:06Z
Check the source to verify that this is the current version before use.