MILITARY SPECIFICATION

DOCUMENT DESTROYER, EMERGENCY INCENDIARY: M4

This specification is approved for use by U.S. Army Armament Reasearch and Development Command and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This document covers requirements and quality assurance provisions for one type of incendiary device.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-F-18405 - Fuze, Firecracker, 30-second
MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1168 - Lot Numbering of Ammunition

DRAWINGS

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

D4-11-47 - Document Destroyer, Emergency Incendiary: XM4.

FSC: 1375

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. - Materials shall be in accordance with the applicable drawings and specifications.

3.2 Components and assemblies. - The components and assemblies shall comply with all requirements specified on drawings D4-11-47 and D4-11-46 and all associated drawings and with all requirements specified in applicable specifications and standards.

3.3 Functioning

3.3.1 Igniter. - The igniter, drawing C4-11-51, shall ignite and completely burn within 24 ± 8 seconds when tested as specified in 4.5.3.

3.3.2 Document destroyer. - The document destroyer shall ignite and completely burn a minimum of 98 percent by weight of 100 pounds of paper products to be reduced to ash within 20 minutes after ignition. The paper products shall be placed in the inner drum in accordance with the operational instruction card, drawing D4-11-52, and tested as specified in 4.5.4. The paper products shall consist of the type and quantity of paper in Table III.

3.4 Leakage. - The sealed document destroyer shall maintain a pressure of 15 PSIG for 3 minutes with leakage not to exceed 1 PSIG when tested as specified in 4.5.5.

3.5 Workmanship. - The parts and assemblies shall be free from chips, dirt, grease and other foreign matter that may impair proper functioning. The cleaning method used shall not be injurious to any of the parts, nor shall the parts be contaminated.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. - Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspection. - The following types of inspection shall be conducted on this item:

a. First Article Inspection
b. Quality Conformance Inspection

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.

TABLE III - PAPER PRODUCTS MIX

Item	Thickness Inches	Percent by Weight	Approx. Height Inches
A. Military technical manuals, pamphlets, and directives	1/8-1/2	50	16
B. Computer data runs	1-3	7.5	3
C. Military pamphlets and directives	3/4-1 1/2	7.5	2 1/2
D. Telephone books or Federal registers	1/2-2	7.5 max	2 1/2
E. Glossy magazines	1/4-1/2	5.0 max	1 1/2
F. Bond paper	loose in folders	15.0	5
G. Data process cards	loose in folders	7.5	2

Notes: 1. Place computer runs and glossy paper in bottom of drum.

2. Alternately layer approximately 2 inch thick stacks of A and F.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.

4.3 First article inspection

4.3.1 Submission. - The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part Description	Drawing	Quantity
Igniter	C4-11-51	6
Igniter Assembly	C4-11-53	6
Document Destroyer Emergency Incendiary	D4-11-47	5

4.3.2 Inspections to be performed. - See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. - See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
	Document Destroyer Emergency Incendiary, M4 and Components				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Igniter (Dwg. C4-11-51)				
	Examination for defects	6	100%	3.2	4.4.2.2
	Functioning	6	100%	3.3.1	4.5.3
	Igniter Assembly (Dwg. C4-11-53)				
	Examination for defects	6	100%	3.2	4.4.2.3
	Document Destroyer Emergency Incendiary (Dwg. D4-11-47)				
	Examination for defects	5(b)	100%	3.2	4.4.2.9
	Leakage	5	100%	3.4	4.5.5
	Functioning	1	100%	3.3.2	4.5.4
	Card, Instructional, Operational (Dwg. D4-11-52)				
	Examination for defects	1(a)	100%	3.2	4.4.2.6
	Card, Instruction, Preparation (Dwg. D4-11-49)				
	Examination for defects	1	100%	3.2	4.4.2.7
	Card, Instruction, Preparation (Dwg. D4-11-49)				
	Examination for defects	1	100%	3.2	4.4.2.7

NOTES: (a) This one item will be taken from the item tested for functioning.
(b) After functioning the one item, the remaining four items may be used as part of the deliverable quantity when approved by the contracting officer.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection

4.4.1 Inspection lot formation. - Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of Document Destroyers shall contain:

a. Not more than three batches (see 6.5) of Ignition Mixture Igniter Charge of one interfix number from one manufacturer. In addition any one interfix number of Igniters from one manufacturer shall not contain more than one interfix number of each chemical element.

b. Not more than one interfix number from one manufacturer of Oxidizing Agent NO_3- Charge I.

4.4.2 Examination. - See MIL-A-48078.

a. Sampling plans. - Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-63266(AR)

PARAGRAPH	TITLE		SHEET		DRAWING NUMBER
4.4.2.1	Ignition Mixture Igniter Charge		1 OF 1		B143-8-1
					NEXT HIGHER ASSEMBLY C4-1[1-51]
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Moisture content over max.	(a)	--	3.2	4.5.2
Minor	None defined				

NOTES:

(a) At the time and place of loading one sample shall be taken every shift for each batch (see 6.5) of material used during that shift.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER C4-11-51
4.4.2.2	Igniter				NEXT HIGHER ASSEMBLY C4-11-53
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Weight of igniter charge under min		0.40	3.2	Gage
102	Heat seal missing or incomplete		0.40	3.2	Visual
103	End not tied off properly		0.40	3.2	Visual
104	Function	(a)		3.3.1	4.5.3
105	Length incorrect		0.40	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.00	3.5	Visual

NOTES:
(a) Sample size per MIL-STD-105 inspection level S-3

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-63266(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER C4-11-53
4.4.2.3	Igniter Assembly				NEXT HIGHER ASSEMBLY E4-11-55
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Heat seal missing or incomplete		0.40	3.2	Visual
102	Igniter missing		0.40	3.2	Manual
Minor					
201	Marking missing, incorrect or illegible		0.65	3.2	Visual
202	Evidence of poor workmanship		1.00	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-63266(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER D4-11-48
4.4.2.4	Drum				NEXT HIGHER ASSEMBLY D4-11-47
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Component missing or incorrectly assembled		0.40	3.2	Visual
102	Inside height incorrect		0.40	3.2	Gage
Minor					
201	Paint missing or incomplete		0.65	3.2	Visual
202	Evidence of poor workmanship		1.00	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

MIL-D-63266(AR)

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER D4-11-46
4.4.2.5	Inner Drum				NEXT HIGHER ASSEMBLY D4-11-47
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside height incorrect		0.40	3.2	Gage
102	Drum damaged		0.40	3.2	Visual
103	Spacer missing or incorrectly assembled		0.40	3.2	Visual
Minor					
201	Evidence of poor workmanship		1.00	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-63266(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER D4-11-52
4.4.2.6	Card, Instructional, Operational				NEXT HIGHER ASSEMBLY D4-11-47
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Printed incorrectly	1	--	3.2	Visual
Minor					
201	Evidence of poor workmanship	1	--	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.7	Card, Instruction, Preparation	1 OF 1	D4-11-49
			NEXT HIGHER ASSEMBLY: D4-11-47

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Printed incorrectly	1		3.2	Visual
Minor					
201	Evidence of poor workmanship	1		3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER B143-13-3
4.4.2.8	Oxidizing Agent NO_3 - Charge I				NEXT HIGHER ASSEMBLY D4-11-47
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Moisture content over max	(a)	--	3.2	4.5.2
Minor	None defined				

NOTES: (a) At the time and place of loading one sample shall be taken every shift for each batch (see 6.5) of material used during that shift.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET OF		DRAWING NUMBER D4-11-47
4.4.2.9	Document Destroyer, Emergency Incendiary M4				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Weight of oxidizing agent NO_3 - Charge I under min		0.40	3.2	Gage
102	Fill level of Oxidizing Agent NO_3 - Charge I not correct		0.40	3.2	Gage
103	Component missing or incorrectly assembled		0.40	3.2	Visual
104	Function	(a)		3.3.2	4.5.4
105	Marking incorrect, illegible or missing		0.40	3.2	Visual
106	Seal missing or broken		0.40	3.2	Visual
107	Leakage		0.40	3.4	4.5.5
Minor					
201	Evidence of poor workmanship		1.00	3.5	Visual

NOTES:

(a) Sample size shall be one item for every 300 items in a lot or fraction thereof.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. - Testing is described in the First Article and Quality Conformance Inspection tables.

4.4.4 Inspection equipment. - The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6 herein.

4.5 Test methods and procedures. -

4.5.1 Materials, components and processes. - Compliance with all requirements of Section 3 of this specification shall be ascertained by current and continuing examination of inspection and test data to determine that all components (parts, subassemblies, and materials) have been inspected and tested and found to comply with their respective drawing and specification requirements, and that all specified manufacturing processes have been followed.

4.5.1.1 Visual and mechanical inspections. - The visual, manual and mechanical inspections and tests shall verify compliance with the requirements of Sections 3 and 5 of this specification in accordance with 4.4.2 herein and Table I.

4.5.2 Moisture content. - Place 5 grams of the material to be tested into a tared weighing dish. Place in an oven maintained at 100°C for 3 hours. Cool in a desicator and weigh. Calculate the loss in weight of contents as the percent moisture.

4.5.3 Igniter. - Place a screen conforming to drawing C4-11-50 spaced 2 ± ¼ inches above a flat horizontal noncombustible surface. Use a M72 fuzee to start the igniter charge burning by directing the fuzee at one end, with the fuzee parallel to the igniter axis. Start timing when the igniter charge starts burning. Record the time required to burn the igniter. Remove the hot ashes from the screen and cool the surface area before repeating the test.

4.5.4 Document destroyer. - Set up and operate the document destroyer in accordance with the preparation and operational instructions, drawings D4-11-49 and D4-11-52. Start timing when the igniter starts burning. At 19 minute, remove the lever lock ring and screen and at 20 minutes tip the drum on its side. Rake out and recover any paper products not reduced to ash and immediately extinguish by smothering. Weigh the unburned paper products.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.

4.5.5 Leakage. - Connect the document destroyer to a source of dry air (.75 percent maximum moisture content) by securing an adapter (containing a pressure gage with a shut-off valve in the line) to the threaded flange on the top head of the drum. Subject the document destroyer to the air pressure; when stabilized at the required pressure (15 PSIG), close valve, and observe for a drop on the pressure gage for a minimum of 3 minutes. Record any pressure drop observed.

5. PACKAGING

5.1 Packing. - Packing shall be as specified on drawings D4-11-46 and D4-11-47.

5.2 Marking. - Marking shall be as specified on drawing D4-11-47.

6. NOTES

6.1 Intended use. - The item covered by this specification is intended for the emergency destruction of documents.

6.2 Ordering data. - See MIL-A-48078.

6.3 Submission of inspection equipment designs for approval. - See MIL-A-48078. Submit equipment designs as required to Commander, U.S. Army Armament Research and Development Command, ATTN: DRDAR-QAA-I, Dover, New Jersey 07801.

6.4 Caution. - Suppliers are advised to take all necessary precautions to protect personnel while filling, assembling, and testing document destroyers due to the incendiary nature of the item and test pressure requirements.

6.5 Batch. - A batch is defined as that quantity of material which has been manufactured by some unit chemical process and subjected to some physical mixing operation intended to make the final product substantially uniform.

6.6 Drawings. - Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Command (ARRADCOM) may also include drawings prepared by, and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARRADCOM.

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project Number: 1375-A-215

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-D-63266 Document Destroyer, Emergency Incindiary; M4

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Armament R&D Command
ATTN: DRDAR-QAA
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.